# HERE'S A REAL ONE.



THE NEW H2. HUMMER<sup>®</sup> LIKE NOTHING ELSE."







#### **COMPONENTS & FEATURES**

ENGINE: Vortec 6000 6.0L V8 with cast iron block, cast aluminum cylinder heads and sequential fuel injection HORSEPOWER (SAE hp): (est.) 316 @ 5200 rpm TORQUE (lb.-ft/Nm): (est.) 360 @ 4000 rpm TRANSMISSION: 4L65-E 4-speed automatic DRIVETRAIN: 2-speed electronically controlled full-time 4WD TRACTION CONTROL SYSTEM (TCS): Brake controlled, single-wheel control capability with rear axle electronic locking differential STEERING: Variable ratio, integral power, recirculating ball BRAKES: 4-wheel disc, 4-wheel/4-channel ABS, dual piston calipers with Dynamic Rear Proportioning FRONT SUSPENSION: Independent with torsion bars, 46 mm monotube gas charged shocks and 35.9 mm stabilizer bar **REAR SUSPENSION:** 5-link variable-rate coil spring, 46 mm monotube gas charged shocks and 30 mm stabilizer bar FRAME: 3-piece fully welded ladder-type WHEELS & TIRES: 17 x 8.5 in. cast aluminum wheels, LT315/70R-17 all-terrain tires with full-sized spare

## SPECIFICATIONS & PERFORMANCE DATA

HEIGHT: 77.8 in. WIDTH (EXCLUDING MIRRORS): 81.2 in. LENGTH: 189.8 in. WHEELBASE: 122.8 in. TRACK WIDTH: 69.4 in. GROUND CLEARANCE: 10 in. APPROACH ANGLE: 40.4° DEPARTURE ANGLE: 39.6° MAXIMUM TOWED LOAD: 6,500 lb. (NOTE 1) WATER FORDING DEPTH: 20 in. FUEL CAPACITY: 32 gal. tank

#### STANDARD EXTERIOR EQUIPMENT

Front bumper with retrieval loops and access hole for hitch/winch receiver Rear bumper with recovery loops and access hole for class 3 hitch Full undercarriage/rocker panel protection Power-folding, heated outside rearview mirrors with curb assist feature Daytime Running Lamps

### STANDARD INTERIOR EQUIPMENT

Seating for 5 Dual front air bags (NOTE 2) Driver's seat with standard memory feature for 2 drivers Remote keyless entry with panic button Tan wheat cloth seats with 8-way power adjustment for front passengers Fold-down 60/40 split 2nd row seats Driver Information Center 6 power points (cigarette lighter, 2 front, 2 rear and 1 tailgate accessible) Dual zone heating, ventilation and A/C units with rear controls 9-speaker Bose® music system with in-dash CD/cassette and AudioPilot™ technology Rear seat audio controls Leather-wrapped steering wheel with secondary audio controls Triple sealed doors and enhanced acoustical insulation Electrochromic inside rearview mirror with compass and outside temperature display OnStar<sup>®</sup> system (NOTE 3) Content alarm anti-theft system PASSLock® anti-theft vehicle security system TheftLock for RDS radio Rear compartment cargo and tailgate tie-downs

#### **OPTIONAL EQUIPMENT**

Self-leveling rear air spring suspension with on-board air compressor Leather-trimmed, heated seats 3rd row seat 6-disc CD changer Sunroof Brush grille guard (flat or wrap-around) Off-road lamps – grille guard or roof-mounted Chrome accents Roof rack crossbars (bright or black) Hard cargo carrier Tubular tail lamp guards Tubular assist steps or removable "U" steps

For more information check out www.HUMMER.com or call us at 1 800 REAL 4WD.





NOTE 1: Trailer tongue weight should be 10-15% of trailer, 1.000 lbs. maximum. Do not exceed the maximum allowable tongue weight for your vehicle Grass Combination Weight Rating (GCWR), which is the total allowable weight of the completely loaded whicle and trailer including any passengers, cargo, equipment and conversions and is 14,000 lbs. If you'l be pulling a trailer that, when loaded, will weigh more than 4,000 lbs, be sure to use a property mounded, weight distributing hich and away control of the proper size. If your than 2,000 lbs, beaution, then no.2000 lbs, loaded, then it needs its own brakes, and the maximum trailer weight ratings are calculated assuming a base vehicle, except for any option(3) necessary to achieve the rating, plus driver. The weight of other optional equipment assessmers and cargo will reduce adarge will reduce weight weight your which is can brakes, and use after for additional details. NOTE 2: Always use safety belts and proper child ratinstits, even with a base. Children are safet when properly secured in a trans safe. Both Owners Manual for more safety information. NDTE 2: Always use safety belts and proper child ratinstits, even with a base. Children are safet when properly escured in a trans safe. Both Owners Manual for more safety information. NDTE 2: Always and Corporation. To Kostar Corporation. On Safe: A Sound plan is standard on the 1/2. Call 1: 800 OKS18. CP (2) for system limitations and details. ADDITONAL MOTES: Boxe and AudioPild are registered trademarks of Boc Corporation. To Softar Corporation PASSLock is a registered trademark of GM corporation. Pictured vehicles may vary from actual production models and myscording to local enviroe mark of corporation. Pictured vehicles may vary from actual production models and specifications at any time and without prior incide. Details adord specifications may vary according to local conditions. Like NOTHING LES less and and without prior incide. Details adord specifications may vary according to local conditions. Like NOTH