°6 RIDGELINE

When Honda does something, we do it right. And we do it better. Introducing the Ridgeline, a next-generation truck from Honda. It's tough, big and plenty powerful. And it's a Honda, so it's packing way more versatility, innovation and performance than your run-of-the-mill box on wheels. For starters, check out the huge In-Bed Trunk" and an interior just as comfortable as it is utilitarian. Then get out on a rough road, and feel all four wheels smoothly power you ahead like there's nothing to it. Make no mistake, the new Ridgeline is all truck—and then some.



3 5-Liter 24-Valve SOHC VTEC® V 6 Engine				
ENGINE 3.5-Liter, 24-Valve, SOHC VTEC* V-6 Engine		Drive-by-Wire Throttle System™		
247 hp @ 5750 rpm '		Fresh-Air Intake		
245 lbft. @ 4500 rpm '		Multi-Point Fuel Injecti	on	
		Direct Ignition System	vith Immobilizer	
Bore and Stroke (mm): 89 x 93		ULEV-2 Emissions Rating (CARB)		
Compression Ratio: 10.0:1		105,000-Mile Tune-Up	nterval*	
DRIVETRAIN				
-Speed Automatic Transmission		Variable Torque Manage	ment® /I-Wheel-Drive System	
Gear Ratios: 1st: 2.693, 2nd: 1.566, 3rd: 1.023		Variable Torque Management® 4-Wheel-Drive System (VTM-4®)		
4th: 0.729, 5th: 0.531		Locking Rear Differential		
Reverse: 1.889, Final Drive: 4.533		Heavy-Duty Automatic-Transmission Cooler		
•		Houry Buty Hutomatio	Transmission Seeds	
TOWING				
Fully Boxed High-Strength Steel (HSS) Frame Rails and Crossn	nembers with Internal Stiffeners	Pre-Wired for Trailer Brake Controller		
Heavy-Duty Radiator with Dual 160-Watt Fans		6050-lb. Gross Vehicle Weight Rating (GVWR)		
Heavy-Duty Power-Steering Cooler		10,085-lb. Gross Combined Weight Rating (GCWR)		
Pre-Wired for 4- and 7-Pin Connectors		5000-lb. Towing Capacity ²		
		1550-lb. Total Payload C	apacity	
BODY/SUSPENSION/CHASSIS				
tabilizer Bar (mm, front/rear): 23.0/25.4		All-Season Tires: P245	65 R17 105S	
teering Ratio: 18.5:1		Steel-Reinforced Composite (SRC) Cargo Bed		
teering Wheel Turns, Lock-to-Lock: 3.38		MacPherson Strut Front Suspension		
Turning Diameter, Curb-to-Curb (ft.): 42.6		Multi-Link Rear Suspension with Trailing Arms		
ower-Assisted Ventilated Front Disc/Solid Rear Disc Brakes (in.): 12.6/13.1		Variable-Assist Power Rack-and-Pinion Steering		
7" Styled Steel Wheels (RT) / 17" Alloy Wheels (RTS, RTL)	,	100101 1 01/01	and i mon occorning	
SAFETY			(4.00)	
3-Point Seat Belts at All Seating Positions		Anti-Lock Braking Syste		
ont 3-Point Seat Belts with Automatic Tensioning System		Electronic Brake Distribution (EBD)		
djustable Front Seat-Belt Anchors		Vehicle Stability Assist (VSA*)		
Oual-Stage, Dual-Threshold Front Airbags (SRS)		Brake Assist		
	nt Side Airbags with Passenger-Side Occupant Position Detection System (OPDS)		Tire Pressure Monitoring System (TPMS)	
Side Curtain Airbags with Rollover Sensor		Lower Anchors and Tethers for Children (LATCH)		
Side-Impact Door Beams		Child-Proof Rear Door L	ocks	
EXTERIOR MEASUREMENTS	RT	RTS	RTL	
Wheelbase (in.)	122.0	122.0	122.0	
ength (in.)	206.8	206.8	206.8	
Height (in.)	70.3	70.3	70.3/71.2 with Moonroof	
Width (in.)	77.8	77.8	77.8	
Frack (in., front/rear)	67.1/66.9	67.1/66.9	67.1/66.9	
Minimum Ground Clearance (in.)	8.2	8.2	8.2	
Approach/Departure Angles (degrees)	24.5/22.0	24.5/22.0	24.5/22.0	
Cargo Bed Length (in., tailgate up/down)	60.0/79.0	60.0/79.0	60.0/79.0	
Jargo Dea Length (III., tangate up/uowii)				
Cargo Bed Vidth (in., tangate up/down) Cargo Bed Width (in., between wheelwells)	49.5	49.5	49.5	
	49.5 350	49.5 350		
Cargo Bed Width (in., between wheelwells) Heavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat)	350	350	49.5 350	
Cargo Bed Width <i>(in., between wheelwells)</i> Heavy-Duty Tie-Down Cleats <i>(6)</i> Capacity <i>(lbs. per cleat)</i> n-Bed Trunk™ Capacity <i>(cu. ft.)</i>			49.5	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk* Capacity (cu. ft.) Curb Weight (lbs.)	350 8.5	350 8.5	49.5 350 8.5	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk "Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear)	350 8.5 4503	350 8.5 4494	49.5 350 8.5 4498	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk" Capacity (cu. ft.) Lurb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS	350 8.5 4503 58/42	350 8.5 4494 58/42	49.5 350 8.5 4498 58/42	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk" Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS Headroom (in., front/rear)	350 8.5 4503	350 8.5 4494	49.5 350 8.5 4498 58/42	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk* Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear)	350 8.5 4503 58/42 40.7/39.1	350 8.5 4494 58/42 40.7/39.1	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk "Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) egroom (in., front/rear)	350 8.5 4503 58/42 40.7/39.1	350 8.5 4494 58/42 40.7/39.1	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n.Bed Trunk" Capacity (cu. ft.) Lurb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) Leadroom (in., front/rear) Shoulder Room (in., front/rear)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk* Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) egroom (in., front/rear) Shoulder Room (in., front/rear)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk* Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) egroom (in., front/rear) houlder Room (in., front/rear) liproom (in., front/rear) liproom (in., front/rear) liproom (in., front/rear)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 576/57.2 112.0	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonroo	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk "Capacity (cu. ft.) lurb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) egroom (in., front/rear) liproom (in., front/rear)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 576/57.2 112.0/108.9 with Moonroo 2.6	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk "Capacity (cu. ft.) lurb Weight (lbs.) Veight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) leadroom with Moonroof (in., front/rear) liproom (in., front/rear) lassenger Volume (cu. ft.) nd-Row Underseat Storage (cu. ft.) leating Capacity	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 576/57.2 112.0	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonrool	
argo Bed Width (iin., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk "Capacity (cu. ft.) urb Weight (lbs.) Veight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (iin., front/rear) leadroom with Moonroof (iin., front/rear) egroom (iin., front/rear) liboulder Room (iin., front/rear) liproom (iin., front/rear) liproom (iin., front/rear) liproom (iin., front/rear) liproom (iin., front/rear) lassenger Volume (cu. ft.) nd-Row Underseat Storage (cu. ft.) leating Capacity	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonrool	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk "Capacity (cu. ft.) lurb Weight (lbs.) Veight Distribution (%, front/rear) INTERIOR IMEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) leadroom with Moonroof (in., front/rear) liproom (in., front/rear)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonrool	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk" Capacity (cu. ft.) curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) egroom (in., front/rear) houlder Room (in., front/rear) leasenger Volume (cu. ft.) nd-Row Underseat Storage (cu. ft.) leasting Capacity SEATING eather-Trimmed Seats	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonrool	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat)Bed Trunk** Capacity (cu. ft.)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonrool 2.6 5	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk "Capacity (cu. ft.) lurb Weight (lbs.) Veight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom with Moonroof (in., front/rear) leadroom with Moonroof (in., front/rear) leadroom with Moonroof (in., front/rear) liproom (in., front/rear) leasenger Volume (cu. ft.) nd-Row Underseat Storage (cu. ft.) leating Capacity SEATING eather-Trimmed Seats leated Front Seats briver's Seat Adjustment	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonrool 2.6 5	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk" Capacity (cu. ft.) curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) egroom (in., front/rear) liproom (in., front/rear) lipr	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonrool 2.6 5	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk* Capacity (cu. ft.) lurb Weight (lbs.) lveight Distribution (%, front/rear) leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) leadroom (in., front/rear) houlder Room (in., front/rear) lassenger Volume (cu. ft.) nd-Row Underseat Storage (cu. ft.) leating Capacity SEATING leather-Trimmed Seats leated Front Seats with Dweer Lumbar Support 0/40 Lift-Up Rear Seat with Underseat Storage	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonroo 2.6 5	
argo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) Bed Trunk** Capacity (cu. ft.) Bed Trunk** Capacity (cu. ft.) Bed Trunk** Capacity (cu. ft.) Weight Distribution (%, front/rear)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.65.7.2 112.0 2.6 5	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonrool 2.6 5	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk "Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) leadroo	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonrool 2.6 5 • • • 8-Way Power •	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk* Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) egroom (in., front/rear) Shoulder Room (in., front/rear) liproom (in., front/rear) Passenger Volume (cu. ft.) Ind-Row Underseat Storage (cu. ft.) Seating Capacity SEATING Leather-Trimmed Seats leated Front Seats Driver's Seat Adjustment Driver's Seat Seat with Power Lumbar Support Boy Adjustment Driver's Seat Seat with Power Lumbar Support Driver's Seat Seat with Power Lumbar Support Driver's Seat Seat With Underseat Storage Head Restraints at All Seating Positions EPA MILEAGE ESTIMATES/CAPACITIES Sepeed Automatic (City/Highway)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5 8-Way Power Manual	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonroof 2.6 5	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk* Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) leadroom (in., front/rear) Passenger Volume (cu. ft.) Passenger Volume (cu. ft.) Caeting Capacity SEATING Leather-Timmed Seats leated Front Seats Driver's Seat Adjustment Driver's Seat with Power Lumbar Support 50/40 Lift-Up Rear Seat with Underseat Storage lead Restraints at All Seating Positions EPA MILEAGE ESTIMATES/CAPACITIES 5-Speed Automatic (City/Highway) Trankcase (qt.)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	350 8.5 8.5 4494 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5 8-Way Power Manual • • 16/21 5.3	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 576/57.2 112.0/108.9 with Moonroof 2.6 5 • • • 8-Way Power • • 16/21 5.3	
Cargo Bed Width (in., between wheelwells) leavy-Duty Tie-Down Cleats (6) Capacity (lbs. per cleat) n-Bed Trunk** Capacity (cu. ft.) Curb Weight (lbs.) Weight Distribution (%, front/rear) INTERIOR MEASUREMENTS leadroom (in., front/rear) leadroom with Moonroof (in., front/rear) leadroom with Moonroof (in., front/rear) leadroom (in., front/rear)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5 6-Way Manual • • 16/21 5.3 8.5	350 8.5 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5 8-Way Power Manual • • 16/21 5.3 8.5	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 57.6/57.2 112.0/108.9 with Moonroof 2.6 5 • • • • 8-Way Power • • 16/21 5.3 8.5	
Cargo Bed Width (in., between wheelwells)	350 8.5 4503 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5	350 8.5 8.5 4494 4494 58/42 40.7/39.1 40.8/36.4 63.2/62.6 57.6/57.2 112.0 2.6 5 8-Way Power Manual • • 16/21 5.3	49.5 350 8.5 4498 58/42 40.7/39.1 38.7/39.0 40.8/36.4 63.2/62.6 576/57.2 112.0/108.9 with Moonroof 2.6 5 • • • 8-Way Power • • 16/21 5.3	

^{*}Does not apply to fluid and filter changes. See your owner's manual for details



reduces a vehicle's horsepower rating and torque due to more stringent testing procedures. Many manufacturers are still using the older standard

tion. ³Based on 2006 EPA mileage estimates. Use for comparison purposes only. Your mileage may vary. ⁴Based upon internal Honda testing for frontal and side impacts. 5The Honda Satellite-Linked Navigation System is available only in the 48 contiguous United States on select RTL models. ⁶HomeLink® is a registered trademark of Prince Corporation, a wholly owned subsidiary of Johnson Controls.™ ⁷XM® subscription sold separately. XM-ready audio systems are pre-wired to accept the dealer-installed accessory XM Satellite Radio hardware. XM Satellite Radio is available only in the contiguous United States. The XM name is a registered trademark of XM Satellite Radio, Inc. See your Honda dealer for subscription information. 83-Year/36.000-Mile Limited Warranty: Ordinary maintenance or adjustments. parts subject to normal wear and replacement, and certain items are excluded. See your Honda dealer for terms and conditions of this limited warranty. Always use seat belts and appropriate child seats. Children 12 and under are safest when properly restrained in the rear seat. Specifications, features, illustrations and equipment shown in this brochure are based upon the latest available information at the time of printing. Although descriptions are believed to be correct, accuracy cannot be guaranteed. American Honda Motor

Co., Inc., reserves the right to make changes at any time, without notice or obligation, in colors, specifications, accessories, materials and models. Some features mentioned herein are not available in all areas. See your Honda dealer for details. Some vehicles may be shown with optional equipment. Available = Optional. All images contained herein are either owned by American Honda Motor Co., Inc., or used under a valid license. It is a violation of federal law to reproduce these images without express written permission from American Honda Motor Co., Inc., or the individual copyright owner of such images. Honda Financial Services is a DBA of American Honda Finance Corporation. Honda, the H-mark symbol, Honda Care, Honda Satellite-Linked Navigation System, Drive-by-Wire Throttle System, In-Bed Trunk, Variable Torque Management, VSA, VTEC and VTM-4 are trademarks of Honda Motor Co., Ltd. @2005 American Honda Motor Co., Inc.