

NPR AND NPR-HD GAS POWERTRAIN

2016 Isuzu N-Series gas trucks are powered by a 6.0L V-8 Vortec engine coupled to a double overdrive 6-speed automatic transmission with a lockup torque converter, improving both vehicle performance and fuel economy.



With 297 hp and 372 ft.-lbs. of torque, the engine provides well-proven design features like a 100,000 mile maintenance-free ignition system, a long-life timing chain and cast stainless steel exhaust manifolds. The Isuzu N-Series gas trucks are also available with an optional CNG/LPG compatible engine.

NPR AND NPR-HD GAS LOW CAB FORWARD CHASSIS

Isuzu N-Series gas trucks are built with the same proven frame, front axles and brakes found on Isuzu N-Series diesel trucks.



NPR AND NPR-HD GAS TRUCK PRODUCTIVITY

N-Series Gas Regular Cab Models provide body applications up to 20 feet.
GVWR/GCWR for NPR: 12,000/18,000 lbs.
GVWR/GCWR for NPR-HD: 14,500/20,500 lbs.

N-Series Gas Crew Cab Models provide body applications up to 16 feet.
GVWR/GCWR for NPR: 12,000/18,000 lbs.
GVWR/GCWR for NPR-HD: 14,500/20,500 lbs.

THE #1 SELLING LOW CAB FORWARD TRUCK IN THE UNITED STATES SINCE 1986



**Available
24 / 7 / 365
(866) 441-9659**

If your new Isuzu N-Series truck experiences a breakdown anywhere in the United States, a tow truck will be dispatched to provide minor roadside repair or to take your truck to our nearest dealer for service.

For more information visit

www.isuzucv.com

All photographs, illustrations, equipment and technical data in this brochure are based on the latest information available at the time of publication. Isuzu Commercial Truck of America, Inc. reserves the right to make changes at any time, without notice, in prices, colors, materials, equipment, specifications and models, and to discontinue models or equipment. These vehicles are assembled from component parts manufactured by Isuzu Motors Limited and its affiliated companies and by independent suppliers who manufacture such components to Isuzu's exacting standards for quality, performance and safety. Some vehicles are shown with optional equipment. Some equipment is dealer installed. Visit your authorized Isuzu truck dealer for warranty and other details. NPR and NPR-HD are trademarks of Isuzu Motors Limited. Vortec is a trademark of General Motors. Facebook is a registered trademark of Facebook, Inc. Instagram is a registered trademark of Instagram, LLC. Twitter is a registered trademark of Twitter, Inc. LinkedIn is a registered trademark of LinkedIn Corporation. Google+ is a registered trademark of Google, Inc. Isuzu is not sponsored by or affiliated with these platforms.



**ISUZU
TRUCK**

NPR GAS



ISUZU LCF GAS TRUCKS OFFER CNG/LPG CAPABILITY



ISUZU LCF CAB

Isuzu LCF cab design provides ease of maintenance that cutaway and conventional trucks can't offer: Isuzu cabs tilt to allow complete access to the engine and transmission for fast and easy service.

This Hexapod-built cab design increases safety with a panoramic windshield and side windows that provide unsurpassed driver visibility. Standard features enhancing your productivity include: power windows and door locks, tilt/telescopic steering wheel, air conditioning, driver-friendly instrumentation, generous interior space for three-across seating, overhead storage and additional storage behind driver and passenger seats.

ISUZU LCF CREW CAB




Our crew cab, with seating for seven, will get your entire crew to the job site at the same time!


2016 Gas N-Series Truck Specifications

ISUZU MODEL	NPR GAS	NPR-HD GAS	NPR GAS CREW CAB	NPR-HD GAS CREW CAB
GVWR/GCWR	12,000/18,000 lbs.	14,500/20,500 lbs.	12,000/18,000 lbs.	14,500/20,500 lbs.
BODY/PAYLOAD ALLOWANCE	6,782-6,978 lbs.	8,977-9,174 lbs.	6,246-6,308 lbs.	8,442-8,503 lbs.
GAWR				
Front	4,860 lbs.	6,630 lbs.	4,860 lbs.	6,630 lbs.
Rear	8,840 lbs.	11,020 lbs.	8,840 lbs.	11,020 lbs.
FRONT AXLE CAPACITY	6,830 lbs.	6,830 lbs.	6,830 lbs.	6,830 lbs.
REAR AXLE CAPACITY	11,020 lbs.	11,020 lbs.	11,020 lbs.	11,020 lbs.
Ratio	5.125	5.375	5.125	5.375
SUSPENSION				
F/R SPRINGS	Tapered/Multi-Leaf	Tapered/Multi-Leaf	Tapered/Multi-Leaf	Tapered/Multi-Leaf
Capacity	8,440/12,900 lbs.	8,440/12,900 lbs.	8,440/12,900 lbs.	8,440/12,900 lbs.
FRAME				
Section Modulus	7.20 in. ³	7.20 in. ³	7.20 in. ³	7.20 in. ³
Resis. Bending Moment	316,800 lb.-ft./in.	316,800 lb.-ft./in.	316,800 lb.-ft./in.	316,800 lb.-ft./in.
SERVICE BRAKES	Vacuum/Hydraulic with 4-Channel ABS	Vacuum/Hydraulic with 4-Channel ABS	Vacuum/Hydraulic with 4-Channel ABS	Vacuum/Hydraulic with 4-Channel ABS
Front/Rear	Disc/Drum	Disc/Drum	Disc/Drum	Disc/Drum
TRANSMISSION				
Standard	6L90 6-speed auto. with double overdrive and lock-up converter	6L90 6-speed auto. with double overdrive and lock-up converter	6L90 6-speed auto. with double overdrive and lock-up converter	6L90 6-speed auto. with double overdrive and lock-up converter
ENGINE				
Standard	GMPT L96 (Gen IV) V8 Vortec 6000	GMPT L96 (Gen IV) V8 Vortec 6000	GMPT L96 (Gen IV) V8 Vortec 6000	GMPT L96 (Gen IV) V8 Vortec 6000
Optional	KL8 (Alternative Fuel Compatible Engine)	KL8 (Alternative Fuel Compatible Engine)	KL8 (Alternative Fuel Compatible Engine)	KL8 (Alternative Fuel Compatible Engine)
Displacement	6.0L (365 in. ³)	6.0L (365 in. ³)	6.0L (365 in. ³)	6.0L (365 in. ³)
Engine Power	297hp@4,300 rpm	297hp@4,300 rpm	297hp@4,300 rpm	297hp@4,300 rpm
Engine Torque	372 lb.-ft. @ 4,000 rpm	372 lb.-ft. @ 4,000 rpm	372 lb.-ft. @ 4,000 rpm	372 lb.-ft. @ 4,000 rpm
ALTERNATOR	145-amp	145-amp	145-amp	145-amp
BATTERIES	1 Maintenance-Free 750-CCA	1 Maintenance-Free 750-CCA	1 Maintenance-Free 750-CCA	1 Maintenance-Free 750-CCA
TIRES				
215/85R16E (10-ply)	225/70R19.5G (14-ply)	215/85R16E (10-ply)	225/70R19.5G (14-ply)	
Low Rolling Resistance	Standard	Standard	Standard	Standard
STEERING	Integral Hydraulic Power	Integral Hydraulic Power	Integral Hydraulic Power	Integral Hydraulic Power
STEERING COLUMN	Tilt and Telescopic	Tilt and Telescopic	Tilt and Telescopic	Tilt and Telescopic
FUEL TANK	30 Gal. in-frame	30 Gal. in-frame	30 Gal. in-frame	30 Gal. in-frame

NPR / NPR-HD Gas Dimensions



NPR / NPR-HD Gas Crew Cab Dimensions



NPR / NPR-HD GAS

Wheelbase (in.)	Cab to Axle (in.)	Cab to End of Frame (in.)	Back of Cab (in.)	Overall Length (in.)	Body Length (in.)	Overall Width (in.)	Front Axle Width (in.)	Overall Height (in.)
109.0	86.5	129.6	6.5	200.5	10-12	81.3	65.6	90.0/90.9
132.5	110.0	153.1	6.5	224.0	14	81.3	65.6	90.0/90.9
150.0	127.5	170.6	6.5	241.5	16-18	81.3	65.6	90.0/90.9
176.0	153.5	196.6	6.5	267.5	20	81.3	65.6	90.0/90.9

NPR / NPR-HD GAS CREW CAB

Wheelbase (in.)	Cab to Axle (in.)	Cab to End of Frame (in.)	Back of Cab (in.)	Overall Length (in.)	Body Length (in.)	Overall Width (in.)	Front Axle Width (in.)	Overall Height (in.)
150.0	88.5	131.6	5.0	241.5	12	81.3	65.6	90.0/91.1
176.0	114.5	157.6	5.0	267.5	16	81.3	65.6	90.0/91.1

2016 ISUZU N-SERIES GAS WARRANTY COVERAGE AT A GLANCE

Vehicle Coverage	Warranty Limitations (Time or Mileage, Whichever Comes First)*		Percentage Of Dealer's Normal Charge Paid By Owner	
	Time in months*	Vehicle miles*	Parts	Labor
Basic (See "What's covered")	0-36	0-36,000	No Charge	No Charge
Engine	0-60	0-75,000	No Charge	No Charge
• Transmission • Drive Axles • Propeller Shaft • Front Axle I-Beam • Crossmembers	0-60	0-75,000	No Charge	No Charge
Frame Rails	0-36 36-60	0-36,000 Unlimited	No Charge 50%	No Charge 50%
Federal Emissions	0-60	0-50,000	No Charge	No Charge
Engine Emissions Control System (NPR model) California	0-36	0-50,000	No Charge	No Charge
Engine Emissions Control System (NPR model) California	0-84	0-70,000	No Charge	No Charge
Corrosion (Rust Through)	0-48	Unlimited	No Charge	No Charge
Batteries	0-12	Unlimited	No Charge	No Charge

*The warranty coverages are determined by the mileage of the vehicle and the number of months from the delivery date. The warranty coverages are limited by whichever occurs first. See your authorized Isuzu dealer for warranty details.