
# TWIN STEER




# 4800

TS TWIN STEER		
	Α	BBC: 109"
<u> </u>	В	WB: Up to 448"
	C	BA: 33"(SF) / 50"(SB)
	D	TAS: 60"(SF) / 72"(SB)
	1	
® • • • • • • • • • • • • • • • • • • •		

## 4900



## 6900



## Construction sites. Oilfields. Mines. Heavy hauls.

Western Star Twin Steers are right at home on demanding job sites. Engineered for increased maneuverability and improved ride without compromising load rating, there is no better choice for tough jobs than the Twin Steer options you'll find right here.

## CAB TYPE

Severe Duty galvannealed steel with bonded windshield

## HOOD TYPE

4800TS Set Forward Axle

Fiberglass traditional non-sloping hood

4800TS Set Back Axle

Supervisibility fiberglass hood

4900TS Set Back Axle

Fiberglass traditional non-sloping hood

6900TS Set Back Axle

Fiberglass hood with LH and RH full-length butterfly openings

## **ENGINE**

Detroit™ DD13® 12.8L, 350-505HP, 1250-1850lb-ft.

4900TS

Detroit™ DD15®, 14.8L, 455-505HP, 1550-1750lb-ft.

Detroit™ DD16®, 15.6L, 500-600HP,

1850-2050lb-ft.

Cummins X15, 15.0L, 400-605HP, 1450-2050lb-ft.

Detroit™ DD15®, 14.8L, 455-505HP, 1550-1750lb-ft.

Detroit™ DD16®, 15.6L, 500-600HP, 1850-2050lb-ft.

## TRANSMISSION

4800TS Set Back Axle

Eaton Fuller Manual Eaton Fuller UltraShift Plus

Allison Automatic

4800TS Set Forward Axle

Eaton Fuller Manual

4900TS

Eaton Fuller Manual

Allison Automatic

6900TS

Eaton Fuller Manual Allison Automatic

## **EXHAUST**

4800TS Set Forward Axle

RH outboard frame-mounted vertical

4800TS Set Back Axle

RH outboard frame-mounted vertical RH mid-chassis-mounted horizontal

4900TS

RH outboard frame-mounted vertical

RH mid-chassis-mounted horizontal

RH outboard mid-chassis-mounted horizontal

## **STEERING**

4800TS Set Forward Axle

Single main gear with dual auxiliary gears

4800TS Set Back Axle

Dual main gears with dual ram assist

4900TS

Dual main gears with dual ram assist

6900TS

Dual main gears with dual auxiliary gears

## **FRONT AXLE**

4800TS Set Forward Axle

Tandem 40,000 lbs

4800TS Set Back Axle

Tandem 40,000 lbs

4900TS

Tandem 40,000-44,000 lbs

6900TS

Tandem 44,000 lbs

## **REAR AXLE**

Tandem 46,000-52,000 lbs

Tridem 69,000 lbs

4900TS

Tandem 46,000-70,000 lbs Tridem 69,000 lbs

6900TS

Tandem 70,000-110,000 lbs Tridem 69,000 lbs

## FRONT SUSPENSION

### 4800TS

Flatleaf 40,000 lbs

### 4900TS

Slippered 36,000, 40,000 and 44,000 lbs

Slippered 36,000 and 40,000 lbs

## **REAR SUSPENSION**

Tandem 46,000-52,000 lbs Tridem air ride 69,000 lbs

### 4900TS

Tandem 46,000-65,000 lbs Tridem air ride 69,000 lbs

Tandem 65,000-110,000 lbs Tridem air ride 69,000 lbs

## **FRAME**

4800TS Set Forward Axle Double-channel @ 3.2MM RBM and 4.5MM RBM

4800TS Set Back Axle Single-channel @ 2.5MM RBM Double-channel @ 3.2MM RBM and

4.5MM RBM

Double-channel @ 3.2MM RBM and 4.5MM RBM

### 6900TS

Double-channel @ 3.2MM RBM and 4.5MM RBM

Triple-channel @ 5.6MM RBM

## **FUEL TANK**

### 4800TS/4900TS

Aluminum 25" cylindrical 60-150 gallon (227-567 liter) RH or LH

#### 6900TS

100-150 gallon (378-567 liter) aluminum – RH 100-150 gallon (378-567) liter aluminum – LH 90-120 gallon (340-453 liter) steel - RH 90-120 gallon (340-453 liter) steel – LH

## **DEF TANK**

23 gallon (87 liter)



For the Western Star dealer nearest you, call 1-866-850-STAR | WESTERNSTAR.COM

