





WEIGHT (LBS.)

Max GVWR		13,500	
	Front	5,070	
	Rear	9,040	
Body/Payload		Up to 8,505	

DIMENSIONS (IN.)


Wheelbase	108.3/131.9/148.0	
Usable cab to rear axle	83.1/106.7/122.9	
Overall length (End of frame)	192.3/215.7/231.9	


ENGINE

Model	Mitsubishi 4D34-2AT3A
Туре	4-stroke cycle, watercooled, direct injection,
	turbocharged, intercooled diesel
No. of cylinders	Four in-line
Piston displacement	238.0 cu. in. (3.9 liters)
Max. output (SAE, gross)	135 hp/3,000 rpm
Max. torque (SAE, gross)	253 lb.ft./1,800 rpm
Air cleaner	Dry paper element with snorkel and rain cap
Starter	12-volt
Alternator	12-volt, 80 amp.

CHASSIS

	Hydraulic control, 11.8 in., single dry plate
	, , , , , , , , , , , , , , , , , , , ,
atic option)	5 forward and 1 reverse speed, 2nd to 5th synchromesh,
	1st and reverse constant mesh gears
Ratio: manual	5.380/3.028/1.700/1.009/0.722, reverse 5.380
Ratio: automatic	3.068/1.570/1.000/0.724, reverse 2.625
Front	Reverse Elliot, I-beam-type, 5,290 lbs. capacity
Rear	Full-floating-type, 9,480 lbs. capacity
•	Single-reduction hypoid gear
Ratio	5.714 (manual/automatic)
	Single front steer, dual rear traction
Size	LT215/85R16E (10 PR)
	Ball-nut-type with integral-type hydraulic power booster.
	Telescopic and tilt steering column with steering lock
Front	Heavy-Duty laminated leaf springs with shock
	absorbers and stabilizer bar
Rear	Heavy-Duty laminated leaf springs with shock
	absorbers and stabilizer bar
Service	Hydraulic with vacuum servo assist, front disc,
	self-adjusting rear drum
Parking	Internal expanding shoe-type
-	33 gallons
	Two 12-volt, maintenance-free batteries
	All-steel, tilt cab
	Ratio: automatic Front Rear Ratio Size Front Rear Service





- A. Wheelbase (in.) 108.3/131.9/148.0 B. Usable cab to rear axle (in.) 83.1/106.7/122.9
- C. Overall length (in.)
- 192.3/215.7/231.9



P.O. Box 464, 100 Center Square Road Bridgeport, NJ 08014

NOT AVAILABLE IN CALIFORNIA

Vehicle specifications are subject to change without notice.

Photos and descriptions may vary in comparison to actual vehicle models.



