


SPECIFICATIONS



1 9 9 9

Weight (lbs.)

| Max GVWR | | 32,900 | |
|--------------|-------|--------------|--|
| | Front | 11,700 | |
| | Rear | 21,200 | |
| Body/Payload | | Up to 22,890 | |

Dimensions (in.)

| Wheelbase | 181.9/200.0/218.5/239.4 | |
|-------------------------------|-------------------------|--|
| Usable cab to rear axle | 146.6/164.7/183.2/203.7 | |
| Overall length (End of frame) | 313.8/340.6/368.1/409.5 | |

Engine

| Model | Mitsubishi 6D16-2AT3 |
|--------------------------|--|
| Туре | 4-stroke cycle, watercooled, direct injection, turbocharged, intercooled diesel |
| No. of cylinders | Six in-line |
| Piston displacement | 460.3 cu. in. (7.5 liters) |
| Max. output (SAE, gross) | 200 hp/2,600 rpm |
| Max. torque (SAE, gross) | 434 lb.ft./1,600 rpm |
| Air cleaner | Dry paper element with snorkel and rain cap |
| Starter | 12-volt |
| Alternator | 12-volt, 80-amp |

Chassis

| Clutch | | Hydraulic control, coil spring 13.8 in., single cerametallic disc |
|----------------------|--------------------|--|
| Transmission | | 6 forward and 1 reverse speed, 2nd to 6th synchromesh, 1st and reverse constant mesh gears |
| | Ratio: 6-speed OID | 6.875/4.189/2.460/1.542/1.000/0.786, reverse 6.875 |
| Axle | Front | Reverse Elliot, I-beam-type, 11,905 lbs. capacity |
| | Rear | Full-floating-type, 22,485 lbs. capacity |
| Final reduction gear | | Single-reduction hypoid gear |
| | Ratio | 6.166 (6-speed) |
| Tires | | Single front, dual rear |
| | Size | Premium 11R22.5 (14PR) |
| Wheel | | 7.50x22.5-162-12t, 10-stud, 1-piece disc wheel |
| Steering | | Ball-nut-type with integral-type hydraulic power booster. Telescopic and tilt steering column with steering lock |
| Suspension | Front | Laminated leaf springs with shock absorbers |
| | Rear | Laminated leaf springs |
| Spring capacity | Front | 11,900 |
| | Rear | 23,810 |
| Brakes | Service | Full air, air dryer standard, auto slack adjusters with anti-lock (exhaust brake standard) |
| | Parking | Spring-loaded-type on rear wheels |
| Fuel tank | | 50-gallon tank and fuel/water separator (standard) |
| Electrical system | | Two 12-volt, maintenance-free batteries |
| Cab | | Tilt cab |



FM·SR


MITSUBISHI FUSO TRUCK OF AMERICA, Inc. P.O. Box 464 100 Center Square Road Bridgeport, NJ 08014

For the dealer nearest you, or for more information, write or call: 1 (800) 648-3876

Or visit our web site at http://www.mitfuso.com

Vehicle specifications are subject to change without notice. Photos and descriptions included in this brochure may vary in comparison to actual vehicle models.

☼ ₱ PRINTED IN THE U.S.A. ON RECYCLED AND RECYCLABLE PAPER 4/98. ©1998 MITSUBISHI FUSO TRUCK OF AMERICA, INC.



A. Wheelbase (in.) 181.9/200.0/218.5/239.4

B. Usable cab to rear axle (in.) 146.6/164.7/183.2/203.7

C. Overall length (in.) 313.8/340.6/368.1/409.5

