



SPECIFICATIONS

Weight (lbs.)

Max. GVWR	17,995
Front	6,660
Rear	12,700
Body/Payload	Up to 11,700

Dimensions (in.)

Wheelbase	114.6/130.3/150.0/169.7/181.5/191.7
Usable cab to rear axle	90.5/106.2/125.9/145.6/157.4/168.9
Overall length (End of frame)	206.9/222.6/257.3/285.4/302.6/318.3

Engine

Model	Mitsubishi 6D34-1AT2
Type	4-stroke cycle, watercooled, direct injection, turbocharged, intercooled diesel
No. of cylinders	Six in-line
Piston displacement	358 cu. in. (5.9 liters)
Max. output (SAE, gross)	175 hp@2,900 rpm
Max. torque (SAE, gross)	325 lb.ft.@2,000 rpm
Air cleaner	Dry paper element with snorkel and rain cap
Starter	12-volt
Alternator	12-volt, 100-amp

Chassis

Clutch	Hydraulic control, coil spring 12.8 in., single dry cerametallic plate
Transmission (Automatic option)	6 forward and 1 reverse speed, 2nd to 6th synchromesh, 1st and reverse constant mesh gears (except 114.6" wheelbase)*
Ratio: manual	6.523/3.975/2.193/1.336/1.000/0.803, reverse 6.523
Ratio: automatic	(Allison AT542)** 3.454/2.253/1.407/1.000, reverse 5.024
Axle	Front Reverse Elliot, I-beam-type 7,275 lbs. capacity
Rear	Full-floating-type 16,975 lbs. capacity
Final reduction gear	Single-reduction hypoid gear
Ratio	4.111 automatic and 5-speed MT, 4.625 6-speed MT
Tires	Single front highway, dual rear traction
Size	LT215/75 R17.5 (12PR)
Steering	Ball-nut-type with integral-type hydraulic power booster. Telescopic and tilt steering column with steering lock
Suspension	Front Heavy-duty laminated leaf springs with shock absorbers and stabilizer bar
Rear	Heavy-duty laminated leaf springs
Brakes	Service Hydraulically boosted, self-adjusting drum with ABS. Exhaust brake standard on MT only.
Parking	Internal expanding-type on propeller shaft
Fuel tank	33 gallons
Electrical system	Two 12-volt, maintenance-free batteries
Vehicle safety	Energy-absorbing steering wheel, crush bars in doors, daytime running lights and ABS standard

*114.6" wheelbase is 5-speed direct drive transmission.

**Allison does not approve the AT542 Transmission for use in refuse packers or one-way rental operations. Allison AT545 is an available option.

FH



2 0 0 1



FH


MITSUBISHI FUSO TRUCK
OF AMERICA, Inc.
P.O. Box 464
100 Center Square Road
Bridgeport, NJ 08014

For the dealer nearest you,
or for more information,
call: 877-202-9650

Or visit our web site at:
www.mitfuso.com

Vehicle specifications are subject to change
without notice. Photos and descriptions included
in this brochure may vary in comparison to
actual vehicle models.

♻️ PRINTED IN THE U.S.A. ON RECYCLED AND
RECYCLABLE PAPER 6/00. ©2000 MITSUBISHI FUSO
TRUCK OF AMERICA, Inc.



- A. Wheelbase (in.)
114.6/130.3/150.0/169.7/181.5/191.7
- B. Usable cab to rear axle (in.)
90.5/106.2/125.9/145.6/157.4/168.9
- C. Overall length (in.)
206.9/222.6/257.3/285.4/302.6/318.3

