## SPECIFICATIONS



Weight (Ibs.)	Model 639*	Model 649
Max. GVWR	13,500	14,050
Front	5,070	5,290
Rear	9,040	9,480
Body/Payload	Up to 8,375**	Up to 8,825**

#### Dimensions (in.)

Wheelbase	108.3/131.9/148.0			
Usable cab to rear axle	83.1/106.7/122.9			
Overall length (End of frame)	192.3/215.7/232.1			

#### Engine

Lighto		
Model	Mitsubishi 4D34-3AT3B	
уре	4-stroke cycle, watercooled, direct injection, turbocharged, intercooled diesel	
No. of cylinders	Four in-line	
Piston displacement	238.0 cu. in. (3.9 liters)	
Max. output (SAE, gross)	145 hp@2,900 rpm	
Max. torque (SAE, gross)	275 lb.ft.@1,600 rpm	
Air cleaner	Dry paper element with snorkel and rain cap	
Starter	12-volt	
Alternator	12-volt, 100-amp	

### Chassis

Chassis				
Clutch		Hydraulic control, 11.8 in., single dry plate		
Transmission		5-speed manual 4-speed automatic		
	Ratio:	5.380/3.028/1.700/1.009/ 0.722, reverse 5.380	3.018/1.548/1.000/0.703, reverse 2.678	
Axle	Front	Reverse Elliot, I-beam-type, 5,290 lbs. capacity		
	Rear	Full-floating-type, 9,480 lbs. capacity		
Final reduction gear		Single-reduction hypoid gear	Single-reduction hypoid gear	
	Ratio	5.714 (manual/automatic)		
Tires (Premium)		Single front highway, dual rea	Single front highway, dual rear traction	
Size		LT215/85R16E (10 PR)		
Steering		Ball-nut-type with integral-type hydraulic power booster. Telescopic and tilt steering column with steering lock		
Suspension	Front	Heavy-duty laminated leaf springs with shock absorbers and stabilizer bar		
	Rear	Heavy-duty laminated leaf springs with shock absorbers and stabilizer bar		
Brakes	Service	Hydraulic with vacuum servo assist, ABS dual-caliper four-wheel disc brakes with exhaust brake		
	Parking	Internal expanding shoe-type		
Fuel tank		33 gallons		
Electrical system		Two 12-volt, maintenance-free batteries		
Vehicle safety		Energy-absorbing steering wheel, crush bars in doors, daytime running lights and ABS standard		




\*\*Weight approximate. See dealer for complete details.



# 2002

### SPECIFICATIONS







**A. Wheelbase (in.)** 108.3/131.9/148.0

**B. Usable cab to rear axle (in.)** 83.1/106.7/122.9

- C. Overall length (in.)
- 192.3/215.7/232.1





#### MITSUBISHI FUSO TRUCK OF AMERICA, Inc. P.O. Box 464 100 Center Square Road Bridgeport, NJ 08014

FE-HD

2002

For the dealer nearest you, or for more information, call: **877-202-9650** 

Or visit our web site at: www.mitfuso.com

Vehicle specifications are subject to change without notice. Photos and descriptions included in this brochure may vary in comparison to actual vehicle models.

♥ PRINTED IN THE U.S.A. ON RECYCLED AND RECYCLABLE PAPER 8/01. ©2001 MITSUBISHI FUSO TRUCK OF AMERICA, Inc.