SALEEN



# THE SALEEN S351 SPEEDSTER

If your idea of the perfect car is a sedan, stop reading now. Because this is about as far from that as you can get. The S351 is about just one thing and only one thing - performance. Based on the Saleen Mustang that's won the SCCA Championship four out of the last five years, it features a supercharged 495 horsepower

351 CID V8

engine that puts common sense deep in your rear view

mirror. With forged pistons, Saleen-engineered aluminum heads, 65mm throttle and ceramiccoated headers, this intense powerplant makes the S351 the fastest vehicle sold in the U.S. For those statistically oriented, we're talking 122mph in a quarter mile. Have we gone a bit over the edge? Isn't that what you had in mind.

# \$281 Coupe, Convertible & Speedster

ENGINE 281 cid (4.6L) 2V SOHC V-8 engine Horsepower - 285 @ 5100 / Torque - 315 ft. lbs. @ 4100

> Compression ratio 8.2:1 / Bore and stroke - 3.60 x 3.60" Saleen 2.5" stainless steel 4-way catalytic high flow custom exhaust Premium fuel calibration

Optional: Saleen Roots style supercharger, water-to-water intercooler Horsepower - 350 hp @ 5000 / Torque - 410 ft. lbs. @ 3000. Calibrated Saleen engine management system, Saleen cast 356-T6 aluminum manifold, 24 lb./hr. fuel injectors

DRIVETRAIN Saleen Quick Ratio 5-speed manual transmission 8.8" differential, 3.27:1 ratio

> Optional: AOD 4-speed automatic transmission. 8.8" differential, 3.55:1 or 3.08:1 ratio

SUSPENSION Front: Hybrid MacPherson struts with Saleen's Racecraft system including (struts, variable rate springs mounted on lower control arms, 1.38" stabilizer bar with urethane pivot bushings, specially calibrated suspension settings.)

> Rear: Live axle four bar link with Saleen Racecraft variable rate coil-springs on lower trailing arms, stabilizer bar, Quadra shock system with Saleen Racecraft shocks

BRAKES Power 4-wheel ABS disc brakes Front: 10.8" dual-piston vented disc / Rear: 10.5" disc Optional: Saleen 13.0" grooved disc with 4-piston calipers

WREELS Saleen five spoke alloy wheels, Front / Rear: 18" x 9" Optional: Rear: 18" x 10"

TIRES High performance Pirelii P7000. Front: P255/35 ZR-18, Rear: P265/35 ZR-18 Optional: High performance Pirelli PZero. Front: P265/35 ZR-18, Rear: P295/35 ZR-18

### \$351 Coupe, Convertible & Speedster

351 cid (5.8L) Saleen Centrifugal Supercharged OHV 90 degree V-8 Horsepower - 495 @ 5400 / Torque - 490 ft, lbs. @ 3500 Compression ratio 8.2:1 / Bore and stoke - 4.00 x 3.50" Sequential electronic fuel-injection, 65 mm throttle body, Saleen upper/lower manifold, 80 mm mass-air sensor, 36 lb./hr. fuel injectors, hydraulic roller camshaft and lifters, forged aluminum pistons, aluminum heads, Saleen ceramic coated headers, Saleen 2.5" stainless steel 4-way catalytic high flow exhaust, high flow fuel pump, premium fuel calibration, Saleen high performance radiator

Saleen Quick Ratio 6-speed manual transmission, 8.8" differential, 3.27:1 ratio, Saleen posi-traction Balanced custom driveshaft Optional: 8.8" differential, 3.55:1 or 3.08:1 ratio

Front: Hybrid MacPherson struts with Saleen Racecraft system including (No struts, variable rate springs mounted on lower control arms. 1.38" stabilizer bar with urethane pivot bushings. specially calibrated suspension settings.)

Rear: Live axle four bar link with Saleen Racecraft variable rate coil-springs on boxed lower trailing arms, .94" stabilizer bar, Quadra shock system with Saleen No shocks and dampners

Power 4-wheel ABS disc brakes Front: Saleen 13.0" grooved disc with 4-piston calipers Rear: 10.5" disc

Saleen five spoke alloy wheels, Front / Rear: 18" x 9" Optional: Rear: 18" x 10"

High performance Pirelli P7000, Front: P255/35 ZR-18, Rear: P265/35 ZR-18 Optional: High performance Pirelli PZero. Front: P265/35 ZR-18, Rear: P295/35 ZR-18

SALEEN

# SR WIDEBODY (NOT PICTURED)

351 cid (5.8L) Saleen Centrifugal Supercharged OHV 90 degree V-8 Horsepower - 495 @ 5400 / Torque - 490 ft. lbs. @ 3500 Compression ratio 8.2:1 / Bore and stoke - 4.00 x 3.50" Sequential electronic fuel-injection, 65 mm throttle body, Saleen upper/lower manifold, 80 mm mass-air sensor, 36 lb./hr. fuel injectors, hydraulic roller camshaft and lifters, forged aluminum pistons, aluminum heads, Saleen ceramic coated headers, Saleen 2.5" stainless steel 4-way catalytic high flow exhaust, high flow fuel pump, premium fuel calibration. Saleen high performance radiator

Saleen Quick Ratio 6-speed manual transmission, Saleen Salisbury type IRS differential, 3.55:1 ratio, with Dana 60 ring and pinion, custom balanced driveshaft

Front: Saleen independent uneven length double wishbone with Saleen No triple adjustable shocks and adjustable sway bars Rear: Saleen independent uneven length double wishbone with Saleen No triple adjustable shocks and adjustable sway bars Performance Enhancements: Unibody construction with roll cage and suspension reinforcement, power assisted rack and pinion steering, quick release steering wheel

Power 4-wheel ABS disc brakes with integrated cooling ducts Front: Saleen 14.7" metallic disc, 6-piston calipers Rear: Saleen 14.0" metallic disc, 4-piston calipers

Saleen five spoke alloy wheels Front: 18" x 10" / Rear: 18" x 11"

High performance Pirelli PZero, Front: 285/30 ZR-18 / Rear: 335/30 ZR-18


RPM Stoco he race in the an inferiority complex since


#### DIMENSIONS / CAPACITIES

Wheelbase	101.3"	101.3"	101.3"
Track, F/R	59.7" / 61.5"	59.7" / 61.5"	65.24" / 63.84"
Width	73.1"	73.1"	78.5"
Length	185.2"	185.2"	187.0"
Height	52.0"	52.2"	50.0"
Distribution, F/R	56 / 44	58 / 42	54 / 46
Curb weight Unlaiden	3070 lbs.	3290 lbs.	2750 lbs.
281 Fuel tank	15.4 gallons	15.4 gallons	n/a
351 Fuel cell	22.0 gallons	22.0 gallons	22.0 gallons
Trunk volume	10.8 cubic feet	10.8 cubic feet	5.0 cubic feet

Coupe

Dimension for the SR Widebody not shown. For more information regarding the any Saleen product or the SR Widebody, please request a full-line brochure available from your local Saleen Certified Dealer or Saleen, Inc. 949 597 4900.





Convertible / Speedster SR Widebody

All product illustrations and specifications are based upon current information at the time of publication. Saleen, Inc., reserves the right to make changes from time to time, without notice or obligation, in prices specifications, colors and materials, and to change or discontinue models or optional equipment. Saleen, Inc., does not encourage or condone unsafe or illegal driving. Always wear your seat belt.

"Saleen" and other marks are registered trademarks of Saleen, Inc. © Saleen, 1999

BASF is the official paint supplier of Saleen. Pirelli is the official tire supplier of Saleen.

Two words put the entire ride into perspective. Hang On. Saleen Racecraft struts, a rear Quadra shock system and specially calibrated settings make for a suspension which is more than simply race-inspired. It was born and bred there. The \$351's No shocks and racecraft G-load brace push the envelope even further.







