

'05

Honda ▶ Civic Sedan/Hybrid



Why Civic.

Civic EX Special Edition Sedan shown in Shoreline Mist Metallic.



When you drive a Honda, you expect certain things. Things like really smart, innovative engineering. Clean, less-is-more simplicity of design. Uncommon reliability. And lots of car for the price. For 2005, we're happy to say that Civic Sedan and Civic Hybrid will give you all that—plus best-in-class resale value¹ and reassuring safety performance—wrapped in a fun-to-drive package. In other words, a whole lot more than you'd expect.

civic sedan ▶ specifications and features

Safety	DX/VP	LX	EX
Engine Type	In-Line 4-Cylinder	In-Line 4-Cylinder	In-Line 4-Cylinder
Engine Block/Cylinder Head	Aluminum-Alloy	Aluminum-Alloy	Aluminum-Alloy
Displacement (cc)	1668	1668	1668
Horsepower @ rpm (SAE net)	115 @ 6100	115 @ 6100	127 @ 6300
Torque (lb.-ft. @ rpm)	110 @ 4500	110 @ 4500	114 @ 4800
Compression Ratio	9.5:1	9.5:1	9.9:1
Valve Train	16-Valve SOHC	16-Valve SOHC	16-Valve SOHC VTEC®
Multi-Point Fuel Injection	•	•	•
CARB Emissions Rating	ULEV	ULEV	ULEV
Direct Ignition System with Immobilizer	•	•	•
110,000-Mile Tune-Up Interval*	•	•	•
Transmissions			
5-Speed Manual Transmission	DX Only	•	•
4-Speed Automatic Transmission	VP Only	Available	Available
Body/Suspension/Chassis			
Unit-Body Construction	•	•	•
Control-Link MacPherson Strut Front Suspension	•	•	•
Reactive-Link Double Wishbone Rear Suspension	•	•	•
Stabilizer Bar (mm, front/rear)		15.9/12.0	15.9/12.0
Power-Assisted Rack-and-Pinion Steering	•	•	•
Turning Diameter, Curb-to-Curb (ft.)	34.1	35.4	35.4
Power-Assisted Ventilated Front Disc/Rear Drum Brakes (in., front/rear)	10.3/7.8	10.3/7.8	10.3/7.8
Wheels	14" with Full Covers	15" with Full Covers	15" Alloy
All-Season Tires	P185/70 R14 87S	P195/60 R15 87H	P195/60 R15 87H
Compact Spare Tire	•	•	•
Interior Measurements			
Headroom (in., front/rear)	39.8/37.2	39.8/37.2	38.0/36.3
Legroom (in., front/rear)	42.2/36.0	42.2/36.0	42.2/36.0
Shoulder Room (in., front/rear)	52.6/52.0	52.6/52.0	52.6/52.0
Hiproom (in., front/rear)	51.2/49.8	51.2/49.8	51.2/49.8
Cargo Volume (cu. ft.)	12.9	12.9	12.9
Passenger Volume (cu. ft.)	91.4	91.4	88.1
Seating Capacity	5	5	5
Exterior Measurements			
Wheelbase (in.)	103.1	103.1	103.1
Length (in.)	175.4	175.4	175.4
Height (in.)	56.7	56.7	56.7
Width (in.)	67.5	67.5	67.5
Track (in., front/rear)	57.8/57.8	57.8/57.8	57.8/57.8
Curb Weight (lbs., MT/AT)	2449/NA (DX) NA/2544 (VP)	2560/2606	2612/2668
Exterior Features			
Power Moonroof with Tilt Feature			•
Integrated Rear-Window Antenna	•	•	•
Remote Entry System		•	•
Dual Manual Remote-Operated Mirrors	•		
Dual Power Mirrors		•	Body-Colored
2-Speed/Intermittent Windshield Wipers	•		
Variable Intermittent Windshield Wipers			•
Impact-Absorbing Body-Colored Bumpers	•	•	•
Body Side Molding	•	Body-Colored	Body-Colored
Multi-Reflector Halogen Headlights	•	•	•
Tinted Glass	•	•	•
Body-Colored Door Handles		•	•
Body-Colored Trunk Garnish	•	•	•

Safety	DX/VP	LX	EX
3-Point Seat Belts at All Seating Positions	•		•
Front 3-Point Seat Belts with Automatic Tensioning System	•	•	•
Adjustable Front Seat Belt Anchors	•	•	•
Dual-Stage, Dual-Threshold Front Airbags (SRS)	•	•	•
Front Side Airbags with Passenger-Side Occupant Position Detection System (OPDS)	Available	Available	Available
Side-Impact Door Beams	•	•	•
Lower Anchors and Tethers for Children (LATCH)	•	•	•
Child-Proof Rear Door Locks	•	•	•
Anti-Lock Braking System (ABS)			•
Immobilizer Theft-Deterrent System	•	•	•
Emergency Trunk Opener	•	•	•
Comfort & Convenience			
Air Conditioning with Air-Filtration System	VP Only	•	•
Power Windows with Illuminated Auto-Down Driver's Window Switch		•	•
Power Door Locks		•	•
Cruise Control		•	•
Adjustable Steering Column	•	•	•
Beverage Holders	Front with Lid	Front with Lid	Front and Rear
Center Console with Armrest and Storage Compartment	VP Only	•	•
Front Door-Pocket Storage Bins	•	•	•
Passenger-Side Seatback Pocket		•	•
Chrome Door-Handle Pulls		•	•
Remote Fuel Filler Door Release	•	•	•
Remote Trunk Release with Lock	•		•
Headlights-On Reminder	•	•	•
Driver's and Front Passenger's Vanity Mirrors	•	•	•
Map Lights		•	•
Rear-Seat Heater Ducts	•	•	•
12-Volt Power Outlet	•	•	•
Rear Window Defroster with Timer	•	•	•
Cargo Area Light	•	•	•
Seating			
Driver's Seat with Manual Height Adjustment		•	•
Reclining Front Seatbacks	•	•	•
Adjustable Outboard Head Restraints	•	•	•
60/40 Split Fold-Down Rear Seatback with Lock	•	•	•
Audio Systems			
AM/FM Audio System with 4 Speakers and Clock	DX Only		
AM/FM/CD Audio System with 4 Speakers and Clock	VP Only	•	•
Instrumentation			
Backlit Instrument Panel		•	•
Tachometer		•	•
Digital Odometer and Digital Trip Meters (2)	•	•	•
Fuel and Coolant Temperature Gauges	•	•	•
Trunk-Open Indicator Light	•	•	•
Low-Fuel and Low-Oil-Pressure Indicator Lights	•	•	•
Maintenance Interval Indicator	•	•	•
Illuminated Ignition Switch			•
EPA Mileage Estimates*/Fuel Capacity			
5-Speed Manual (City/Highway)	32/38	32/38	32/37
4-Speed Automatic (City/Highway)	29/38	29/38	31/38
Fuel (gal.)	13.2	13.2	13.2
Required Fuel	Regular Unleaded	Regular Unleaded	Regular Unleaded

*Does not apply to fluid and filter changes. See your owner's manual for details.
†AT-PZEV (Advanced Technology Partial Zero-Emission Vehicle) as certified by CARB.
AT-PZEV vehicles are SULEV-rated and have zero evaporative emissions.
AT-PZEV models available in California and some Northeastern states.

civic hybrid ▶ specifications and features

Engineering	Hybrid (CVT)	Hybrid (MT)
Engine Type	In-Line 4-Cylinder	In-Line 4-Cylinder
Engine Block/Cylinder Head	Aluminum-Alloy	Aluminum-Alloy
Displacement (cc)	1339	1339
Horsepower @ rpm (SAE net/with IMA ¹)	85 @ 5700/93 @ 5700	85 @ 5700/93 @ 5700
Torque (lb.-ft. @ rpm/with IMA)	87 @ 3300/105 @ 3000	87 @ 3300/116 @ 1500
Compression Ratio	10.8:1	10.8:1
Valve Train	8-Valve SOHC VTEC [®]	8-Valve SOHC VTEC
Multi-Point Fuel Injection	•	•
Idle-Stop Feature	•	•
CARB Emissions Rating	ULEV or AT-PZEV [†]	ULEV or AT-PZEV [†]
Dual-Point Sequential (i-DSI)		
Lean-Burn Ignition System	with Immobilizer	with Immobilizer
110,000-Mile Tune-Up Interval*	•	•
Electric Motor/Generator		
Permanent Magnet Motor	•	•
Power Output	13.4 hp @ 4000 rpm	13.4 hp @ 2500-4000 rpm
Motor Width (mm)	60	60
Electric Power Storage		
Nickel Metal Hydride (Ni-MH) Battery	•	•
Output	144V (120 cells @ 1.2V)	144V (120 cells @ 1.2V)
Rated Capacity	6.0 Ah	6.0 Ah
Transmissions		
5-Speed Manual Transmission		•
Continuously Variable Transmission (CVT)	•	
Body/Suspension/Chassis		
Unit-Body Construction	•	•
Control-Link MacPherson Strut Front Suspension	•	•
Reactive-Link Double Wishbone Rear Suspension	•	•
Stabilizer Bar (mm, front/rear)	25.4/13.0	25.4/13.0
Electric Power-Assisted Rack-and-Pinion Steering (EPS)	•	•
Turning Diameter, Curb-to-Curb (ft.)	34.8	34.8
Power-Assisted Ventilated Front Disc/ Rear Drum Brakes (in., front/rear)	10.3/8.6	10.3/8.6
Electronic Brake Distribution System (EBD)	•	•
Wheels	14" Lightweight Alloy	14" Lightweight Alloy
Low-Rolling-Resistance All-Season Tires	P185/70 R14 87S	P185/70 R14 87S
Interior Measurements		
Headroom (in., front/rear)	39.8/37.2	39.8/37.2
Legroom (in., front/rear)	42.2/36.0	42.2/36.0
Shoulder Room (in., front/rear)	52.6/52.0	52.6/52.0
Hiproom (in., front/rear)	51.2/49.8	51.2/49.8
Cargo Volume (cu. ft.)	10.1	10.1
Passenger Volume (cu. ft.)	91.4	91.4
Seating Capacity	5	5
Exterior Measurements		
Wheelbase (in.)	103.1	103.1
Length (in.)	175.4	175.4
Height (in.)	56.3	56.3
Width (in.)	67.5	67.5
Track (in., front/rear)	57.9/57.9	57.9/57.9
Curb Weight (lbs., ULEV/AT-PZEV)	2736/2749	2675/2684
EPA Mileage Estimates ² /Fuel Capacities		
5-Speed Manual (City/Highway) (ULEV)		46/51
CVT (City/Highway) (ULEV)	48/47	
5-Speed Manual (City/Highway) (AT-PZEV)		45/51
CVT (City/Highway) (AT-PZEV)	47/48	
Fuel (gal., ULEV/AT-PZEV)	13.2/11.9	13.2/11.9
Required Fuel	Regular Unleaded	Regular Unleaded

Safety	Hybrid (CVT)	Hybrid (MT)
3-Point Seat Belts at All Seating Positions	•	•
Front 3-Point Seat Belts with Automatic Tensioning System	•	•
Adjustable Front Seat Belt Anchors	•	•
Dual-Stage, Dual-Threshold Front Airbags (SRS)	•	•
Front Side Airbags with Passenger-Side Occupant Position Detection System (OPDS)	•	•
Side-Impact Door Beams	•	•
Lower Anchors and Tethers for Children (LATCH)	•	•
Child-Proof Rear Door Locks	•	•
Anti-Lock Braking System (ABS)	•	•
Immobilizer Theft-Deterrent System	•	•
Emergency Trunk Opener	•	•
Exterior Features		
Body-Colored Dual Power Mirrors	•	•
Integrated Grille and Front Bumper	•	•
Impact-Absorbing Body-Colored Bumpers	•	•
Variable Intermittent Windshield Wipers	•	•
Rear Decklid Spoiler	•	•
Heat-Rejecting Green-Tinted Glass	•	•
Remote Entry System	•	•
Roof-Mounted Antenna	•	•
Comfort and Convenience		
Automatic Climate Control with Air Filtration	•	•
Power Windows with Auto-Down Driver's Window	Illuminated Switch	Illuminated Switch
Power Door Locks	•	•
Cruise Control	•	•
Adjustable Steering Column	•	•
Headlights-On Reminder	•	•
Front Beverage Holders with Lid	•	•
Center Console with Armrest and Storage Compartment	•	•
Driver's and Front Passenger's Vanity Mirrors	•	•
Map Lights	•	•
Chrome Door-Handle Pulls	•	•
Front Door-Pocket Storage Bins	•	•
12-Volt Power Outlet	•	•
Remote Fuel Filler Door Release	•	•
Remote Trunk Release with Lock	•	•
Rear-Seat Heater Ducts	•	•
Seatback Pockets	•	•
Rear Window Defroster with Timer	•	•
Cargo Area Light	•	•
Seating		
Driver's Seat with Manual Height Adjustment	•	•
Reclining Front Seatbacks	•	•
Adjustable Outboard Head Restraints	•	•
Audio System		
AM/FM/CD Audio System w/4 Speakers and Clock	•	•
Instrumentation		
Blue-Lit Instrument Panel with Electronic IMA Display	•	•
Tachometer	•	•
Idle-Stop Indicator Light	•	•
Economy Shift Indicator		•
Maintenance Interval Indicator	•	•
Digital Odometer and Digital Trip Meters (2)	•	•
Digital Fuel-Mileage Indicators	•	•
IMA Charge and Assist Indicators	•	•
Battery Charge Indicator	•	•
Illuminated Ignition Switch	•	•

¹ © 2004 The Complete Car Cost Guide.™ IntelliChoice, Inc., www.intellichoice.com. ² Insurance Institute for Highway Safety frontal crash test: December 2002. ³ Based on 2005 EPA mileage estimates. Use for comparison purposes only. Actual mileage may vary. ⁴ Manual-transmission model only. ⁵ ULEV model only. AT-PZEV model mileage range will be lower. ⁶ Limited battery pack warranty may vary. Consult your warranty booklet. AT-PZEV model differs slightly due to emission standards. ⁷ ULEV model only; 47 mpg for AT-PZEV model. ⁸ Tier 2 Bin 2 EPA certification as of June 2004. ***3-Year/36,000-Mile Limited Warranty:** Ordinary maintenance or adjustments, parts subject to normal wear and replacement, and certain items are excluded. See your Honda dealer for terms and conditions of this limited warranty. **Always use seat belts and appropriate child seats. Children 12 and under are safest when properly restrained in the rear seat.** Specifications, features, illustrations and equipment shown in this brochure are based upon the latest available information at the time of printing. Although descriptions are believed to be correct, accuracy cannot be guaranteed. American Honda Motor Co., Inc., reserves the right to make changes at any time without notice or obligation, in colors, specifications, accessories, materials and models. Some features mentioned herein are not available in all areas. See your Honda dealer for details. Some vehicles may be shown with optional equipment. Available = Optional. All images contained herein are either owned by American Honda Motor Co., Inc., or used under a valid license. It is a violation of federal law to reproduce these images without express written permission from American Honda Motor Co., Inc., or the individual copyright owner of such images. Honda Financial Services is a DBA of American Honda Finance Corporation. Honda, the H-mark symbol, Honda Care, IMA and VTEC are trademarks of Honda Motor Co., Ltd. © 2004 American Honda Motor Co., Inc.