

PreRunner Xtracab V6 shown in Impulse Red Pearl with available Color-Keyed SR5 Package and TRD Off-Road Package

THE TOUGH CHOICES START HERE:

04 MODEL GRADES*

Cabs

• Regular Cab

Xtracab

• Double Cab

Engines

• 2.4-liter 4-cyl.

• 2.7-liter 4-cyl.

• 3.4-liter 6-cyl.

Option Packages

SR5 Chrome PackageSR5 Color-Keyed Package

Limited PackageTRD Off-Road Package

• Enhancement Package

• Convenience Package

^{*}Tacoma combinations vary with cab, engine and option packages. See Specifications for complete details.

MODEL GRADE FEATURES

	x2 Eg. Cab	4x2 Xtracab	4x2 S-Runner	PRERUNNER Reg. Cab	PRERUNNER Xtracab	PRERUNNER Double cab	4x4 Reg. Cab	4x4 Xtracab	4x4 Double
Exterior									
Front tow hook	_	_	_	S	S	S	S	S	S
Aerodynamic multi-reflector halogen headlamps	S	S	S	S	S	S	S	S	S
Color-keyed grille, bumpers, valance, door handles and power mirrors	_	_	S	_	_	_	_	_	_
Engine/front suspension and fuel tank skid plates		_	_	S	S	S	S	S	S
Mist-cycle windshield wipers	S	S	_	S	S	3	S	S	_
· ·	S	S	S	S	S	S	S	S	S
Tinted windshield glass	3	S	S	3	S	3	- -	S	3
Tilt-out rear quarter windows	_	ŭ	•	_	-	_			_
Black remote outside mirrors	S	S	S	S	S	S	S	S	S
Double-walled bed	S	S	S	S	S	S	S	S	S
Black-painted rear bumper	0	S	_	S	S	S	S	S	S
Front and rear mudguards	S	S	-	S	S	S ¹	S	S	S ¹
Fender flares	-	_	-	02	02	0^{2}	0^{2}	0^2	02
4WDemand 4-wheel drive with automatic disconnecting differential (4x4 models)	_	-	_	_	-	-	S	S	S
Locking rear differential	-	-	-	-	0 (V6)	0 (V6)	-	0 (V6)	0
Tuned exhaust with chrome-tipped tailpipe	_	_	S	_	_	_	_	_	_
Performance-tuned suspension with gas-filled Tokico shock absorbers and									
rear stabilizer bar	_	_	S	_	_	_	_	_	_
15" steel wheels with P205/75R15 tires	S	S	_	_	_	_	_	_	_
15" styled steel wheels with P225/75R15 tires	_	_	_	S	S	S	S	S	S
16" aluminum alloy wheels with P235/55R16 tires	0	0	S	_	_	_	_	_	_
Full-size spare tire	S	S	S	S	S	S	S	S	S
Interior									
Tilt-forward fabric-trimmed front bench seat with height-adjustable headrests	S	_	_	S		_	S		
Sculpted door trim with fabric insert	S	S	S	S	S	S	S	S	S
60/40 split front bench seat with height-adjustable headrests	_	S	S	_	S	_	_	S	_
Fabric-trimmed front bucket seats with adjustable headrests and center		Ü	Ü		Ü			Ü	
console with dual covered storage	0	0	_	0	0	S	0	0	S
Fabric-trimmed sport seats with driver-seat power-adjustable lumbar support	_	_	S	_	_	_	_	P (V6) ³	P^3
60/40 split fold-down rear bench seat with outboard height-adjustable headrests	_	_	_	_	_	S	_	_	S
Full carpeting	S	S	S	S	S	S	S	S	S
Leather-wrapped tilt steering wheel and shift knob	-	_	S	_	_	P^3	-	P (V6) ³	P^3
Orange-illuminated instrument panel with speedometer,									
coolant temperature/fuel-level meters and warning lights	S	S	-	S	S	S	S	S	S
Orange-illuminated instrument panel with white-faced gauges (speedometer,									
tachometer with LCD twin tripmeters, and coolant temperature and				-1	-1	-1	-1	-1	_ A
fuel-level meters)	_	-	S	P^4	P^4	P^4	P^4	P^4	P^4
AM/FM radio with four speakers	S	-	_	S	-	-	S	_	-
Deluxe 3-in-1 AM/FM Cassette/CD with six speakers	_P 4	_P 4	c	P ⁴	0	0	P ⁴	P ⁴	P^4
(four speakers on Regular Cab models)		S P	S		0	-			
Dual cup holders	S	ა P ⁵	S S	S	S P ⁵	S S	S	S P ⁵	S S
Front maplights Forward-facing rear jump seats with 3-point outboard seatbelts	_	S	S S	_	S	2	_	S	2
rorward-racing rear jump sears with 3-point outboard searbeits Rear-seat heater ducts	_	٥	ى -	_	ა _	S	_	3	_ S
	_	_	_	_	_	S	_	_	S
							_	_	J
near-sear nearer ucts Dual rear cup holders One-Touch Hi-4 electronically controlled 4WD transfer case selector switch5	_	_	_	_	_	_	_	0 (V6)	0



Available 15" styled steel wheel



Available 16" aluminum alloy wheel Standard on 4x2 S-Runner



Standard 15" styled steel wheel



Available 16" styled steel wheel



Available 16" chrome-clad styled steel wheel



Available 16" aluminum alloy wheel

¹Rear mudguards only when running boards are installed.

²Color-keyed fender flares with SR5 Color-Keyed Package or Limited Package; black when offered otherwise.

³Available as part of Limited Package.

⁴Available on SR5 Chrome, SR5 Color-Keyed or Limited Packages.

⁵Requires Power Package.

OPTIONS AND PACKAGES

	UPTIONS AND PACKAGES									
		4x2	4x2	4x2	PRERUNNER	PRERUNNER	PRERUNNER	4x4	4x4	4x4
		REG. CAB	XTRACAB	S-RUNNER	REG. CAB	XTRACAB	DOUBLE CAB	REG. CAB	XTRACAB	DOUBLE CA
Pack	age Availability									
visor digita	hrome Package — includes chrome bumpers an extensions, orange-illuminated white-faced gaug I clock, tilt steering wheel, washer-linked variablers (Xtracab and Double Cab)	es (speedometer, f e intermittent win	tachomete dshield wi	r with LCD t	win tripmete luxe AM/FM (ers, and cool Cassette/CD	ant tempera with four s	ature and f peakers (R	uel-level me egular Cab)	eters), or six
		0	0		0	0	0	0	0	0
	olor-Keyed Package ⁶ — includes all SR5 Chrome und; color-keyed door handles; color-keyed remote								umpers and O	grille O
bump tacho steeri	ed Package ⁷ — includes color-keyed front bumpe er; sliding rear window with privacy glass; dual-f meter with LCD twin tripmeters, and coolant tem ng wheel; leather-trimmed shift knob (manual tra ree air conditioning; fabric-trimmed sport seats v	abric sun visors w perature and fuel- ansmission only); v	vith mirror level mete washer-lin	and visor ex rs); power w ked variable	tensions; or indows, doo intermitten	ange-illumir r locks with t windshield	nated white- remote keylo wipers; cru	-faced gau ess entry; l iise control	ges (speedo eather-trim ; defroster-l	med tilt inked
	ff-Road Package — includes off-road-tuned sus 1 16" 5-spoke aluminum alloy wheels, locking rea					P265/70R16	BFGoodrich O	n tires with —	solid white O (V6)	letter-
	ncement Package — includes defroster-linked CF nclude P225/75R15 tires on 15" styled steel when				with four sp	peakers (on l —	Regular Cat —	o models of	nly); 4x2 mo –	dels _
	nience Package — includes power outside mirro	rs, windows and d	oor locks v	vith remote	keyless entry	y system; do	or-trimmed	tabric; cru	ise control;	and
SHain	g rear window with privacy glass	_	0	_	_	0	0	_	0	0
Power	Package — includes power windows and door lo	ocks with remote k O	eyless entr O	y (black pov S	ver mirrors i O	ncluded on F O	PreRunner a O	nd 4x4 mo O	dels) O	0
Additi	onal Options									
	tyled steel wheels with P205/75R15 tires	0	0	_	_	_	_	_	_	_
	tyled steel wheels and fender flares ² with P265/7 hrome-clad styled steel wheels and fender flares ²		-	_	0	0	0	0	0	0
	2265/70R16 tires	_	_	_	0	0	0	0	0	0
	luminum alloy wheels with P235/55R16 tires	0	0	S	_	_	_	_	_	_
	luminum alloy wheels and fender flares ² with 70R16 tires				0	0	0	0	0	0
	e control	0	0	0	0	0	0	0	0	0
	eering wheel with washer-linked variable intermi		Ü	Ü	Ü	Ü	Ü	Ü	Ü	Ü
	hield wipers	0	0	S	0	0	S	0	0	S
	e AM/FM Cassette with four speakers	0	_	_	0	_	_	0	_	_
	meter	P^4	P^4	S	0	0	S	0	0	S
Defro	ster-linked CFC-free air conditioning	0	0	S	0	0	0	0	0	0
	seatback cargo net	_	_	_	_	_	0	_	_	0
	ng boards	_	_	_	_	_	0	_	_	0
Slidin	g rear window ¹⁰	0	0	S	0	0	0	0	0	0
Lin ⁴ Ava ⁶ Ava Imi	or-keyed fender flares with SR5 Color-Keyed Package or ited Package; black when offered otherwise. ilable on SR5 Chrome, SR5 Color-Keyed or Limited Packages. ilable in Lunar Mist, Black Sand Pearl, Radiant Red and bulse Red only. ilable in Lunar Mist, Black Sand Pearl and Impulse Red only.	have, give us a call at 1-800-GO-TOYOTA and tell us your si toyota.com						you		



Super White 2, 3, 4 with Charcoal or Oak interior



Lunar Mist Metallic² with Charcoal interior



Mystic Gold Metallic^{2, 3, 4} with Charcoal or Oak interior



Radiant Red⁴ with Charcoal or Oak interior



Impulse Red Pearl² with Charcoal or Oak interior



Imperial Jade Mica $^{2,\,3,\,4}$ with Charcoal or Oak interior



Black Sand Pearl with Charcoal or Oak interior

Standard/Maximum	Regular Cab	Xtracab	S-Runner V6	Xtracab V6	Double Cab	Double Cab V6
trailer weight ⁶ Standard/Maximum	3,500/3,500	3,500/3,500	3,500/3,500	3,500/5,000 ⁷	3,500/3,500	3,500/5,000 ⁷
tongue load	350/350	350/350	350	350/500 ⁷	350/350	350/500 ⁷
Gross Combined Weight Rating (GCWR)						
4x2	6,700	6,700	6,800	NA	NA	NA
PreRunner	7,400	7,400	NA	9,000	7,400	9,000
4x4	7,400	7,400	NA	9,000	7,400	9,000
Payload ⁵ (man./auto.)	,	,		•	,	,
4x2	1,500/1,480	1,550/1,530	1,375	NA	NA	NA
PreRunner	NA/2,005	NA/1,830	NA	NA/1,745	NA/1,670	NA/1,625
4x4	1,810/1,780	1,630/1,600	NA	1,585/1,560	NA	NA/1,395

⁵Includes the weight of occupants, available equipment and cargo; limited by weight distribution.

Toyota Tacomas are designed to meet most off-road driving requirements. Abusive use may result in bodily harm or damage. Toyota encourages responsible operation to protect you, your vehicle and the

Some vehicles are shown with available equipment. Seatbelts should be worn at all times. Please do not allow passengers to ride in the cargo area. Towing hitch receivers/ball mount kits are not intended to provide crash protection.age. Toyota encourages responsible operation to protect you, your vehicle and the environment.

Some vehicles are shown with available equipment. Seatbelts should be worn at all times. Please do not allow passengers to ride in the cargo area. Towing hitch receivers/ball mount kits are not intended to provide crash protection.

For details on vehicle specifications, standard features and available equipment in your area, contact your Toyota dealer. A vehicle with particular equipment may not be available at the dealership. Ask your Toyota dealer to help locate a specifically equipped vehicle.

All information presented herein is based on data available at the time of printing, is subject to change without notice and pertains specifically to mainland U.S.A. vehicles only (may differ in the state of Hawaii, Puerto Rico, the U.S. Virgin Islands and in other regions).

²Not available on S-Runner.

³Not available with SR5 Color-Keyed Package.

⁴Not available with Limited Package.

⁶Before towing, confirm your vehicle and trailer are compatible, hooked up properly and you have all necessary additional equipment. Do not exceed any Weight Ratings and review all instructions and cautions from your trailer hitch manufacturer and Toyota vehicle Owner's Manual. Note that the maximum amount you can tow depends on the total weight of any cargo, occupants and available equipment in the vehicle.

⁷Requires available 5,000-lb. Tow Package with Class III tow hitch.

SPECIFICATIONS

31 2011 10	MIIUNO	J							
					PreRunner				
	S-Runner	Regular Cab	Xtracab	Double Cab	Regular Cab	Xtracab	Double Cab		
Mechanical/Performance Engine									
2.4-liter DOHC EFI 4-cylinder	S	S	NA	NA	NA	NA	NA	NA	NA
142 hp @ 5,000 rpm									
160 lbft. @ 4,000 rpm				•		•			
2.7-liter DOHC EFI 4-cylinder	NA	NA	NA	S	S	S	S	S	NA
150 hp @ 4,800 rpm 177 lbft. @ 4,000 rpm									
3.4-liter DOHC EFI V6	NA	NA	S	NA	Α	Α	NA	Α	S
190 hp @ 4,800 rpm									
220 lbft. @ 3,600 rpm Transmission									
5-speed manual with overdrive	S	S	S	NA	NA	NA	S	S	NA
4-speed automatic with overdrive	A	A	NA	NA	NA	NA	NA	NA	NA
4-speed electronically controlled automatic									
transmission with overdrive	NA Waldad ataal a	NA h and daubla wa	NA	S	S	S	A	A	S
Body construction Suspension			lled bed; ladder fram ependent front susp		zer har and gas sh	nck absorbers1 · leaf	snring rear susne	ension with stagg	ered gas shock
- Cusponision	absorbers		oponuone none ouop	onoron men ocabini	zor bar ana gao on	0011 0200120101, 1001	opinig rour ouop	onoron man otagg.	orou guo orroon
Steering		rack-and-pinion							
Turning circle diameter (ft.) Brakes	36.7	41.7 ck Brakes (ABS)	41.7 with power-assisted v	34.4	40.0	40.0	34.4	40.0	40.0
— standard on all models	4-MIICEI MIIII-II	on Dianes (ADS)	hower-assisted /	rominateu munt uis	ovicai uiuiii Willi l	מוועכווו שטטאנצו מווע	icai ivau-stiisilly	Proportioning Agi,	VC (LOI ¥)
Axle ratios					(4 cyl.)/(V6)	(4 cyl.)/(V6)		(4 cyl.)/(V6)	
Manual	3.58:1	3.58:1	3.15:1	NA 2.01.1	NA/NA	NA/NA	3.91:1	3.91:1/3.91:1	NA 2.01.1
Automatic with locking rear differential	3.73:1 NA	3.73:1 NA	NA NA	3.91:1 4.30:1	4.10:1/3.91:1 NA/4.10:1	3.91:1/3.91:1 NA/4.10:1	4.10:1 NA	4.10:1/3.91:1 NA/4.10:1	3.91:1 NA/4.10:1
Exterior Dimensions (IN.)	IVA	IVA	INA.	4.50.1	147/4.10.1	NA/4.10.1	INA	147/4.10.1	NAV4.10.1
Overall height/with available tires	64.1/63.7	63.5/63.1	62.5/NA	67.7/68.8	67.5/68.9	67.5/68.7	67.7/68.8	67.5/68.9	67.5/68.7
Overall width	66.5	66.5	66.5	66.5	66.5	70.3	66.5	66.5	70.3
Overall length with rear bumper Wheelbase	184.4 103.3	202.9 121.9	202.9 121.9	184.4 103.3	202.9 121.9	202.9 121.9	184.4 103.3	202.9 121.9	202.9 121.9
Track (front/rear)	57.1/57.3	57.1/57.3	57.1/57.3	57.5/57.3	57.5/57.3	57.5/57.3	57.5/57.3	57.5/57.3	57.5/57.3
with available tires	57.1/57.3	57.1/57.3	NA	59.1/58.9	59.1/58.9	59.1/58.9	59.1/58.9	59.1/58.9	59.1/58.9
Bed length/height	74.5/15.9 57.9/40.9	74.5/15.9 57.9/40.9	74.5/15.9 57.9/40.9	74.5/15.9 57.9/40.9	74.5/15.9 57.9/40.9	61.5/15.9 57.9/40.9	74.5/15.9 57.9/40.9	74.5/15.9 57.9/40.9	61.5/15.9 57.9/40.9
Bed width/between wheelwells Interior dimensions front/rear (IN.)	57.9/40.9	37.9/40.9	37.9/40.9	57.9/40.9	37.9/40.9	37.9/40.9	37.9/40.9	57.9/40.9	57.9/40.9
Head room	38.5/NA	38.7/34.8	38.7/34.8	38.5/NA	38.7/34.8	38.8/37.7	38.5/NA	38.7/34.8	38.8/37.7
Shoulder room	53.9/NA	53.9/52.3	53.9/52.3	53.9/NA	53.9/52.3	53.9/53.5	53.9/NA	53.9/52.3	53.9/53.5
Hip room Leg room	49.4/NA 41.7/NA	49.6/48.8 42.8/27.2	49.6/48.8 42.8/27.2	49.4/NA 41.7/NA	49.6/48.8 42.8/27.2	49.6/50.8 42.8/33.7	49.4/NA 41.7/NA	49.6/48.8 42.8/27.2	49.6/50.8 42.8/33.7
Seating capacity	3	5	5	3	5	5	3	5	5
Off-Highway									
Approach/departure angle	24°/28° 23°/20°	24°/26° 23°/19°	23°/19° NA	32°/24° 35°/26°	32°/24° 35°/26°	30°/23° 33°/25°	32°/24° 35°/26°	32°/24° 35°/26°	30°/23° 33°/25°
with available tires Minimum running	23 /20	23 /19	INA	33 /20	30 /20	33 /23	30 /20	33 /20	33 /23
ground clearance (in.)	8.5	8.5	7.6	11.0	10.8	10.0	11.0	10.8	10.0
with available tires (in.)	8.1	8.1	NA	12.0	12.0	11.2	12.0	12.0	11.2
4x4 transfer case ratios (high/low) Weights and Capacities	NA	NA	NA	NA	NA	NA	1.00:1/2.57:1	1.00:1/2.57:1	1.00:1/2.57:1
Curb weight (lbs.) man./auto.									
4-cylinder	2,750/2,770	2,950/2,970	NA	NA/3,095	NA/3,270	NA/3,430	3,290/3,320	3,470/3,500	NA
V6		NA	NA	3,125/NA	NA	NA/3,355	NA/3,475	NA	3,515/3,540
NA/3,705 Gross Vehicle Weight									
Rating — GVWR (Ibs.)	4,250	4,500	4,500	5,100	5,100	5,100	5,100	5,100	5,100
Payload2 man./auto. (lbs.)									
4-cylinder V6	1,500/1,480	1,550/1,530 NA	NA NA	NA/2,005 1.375/NA	NA/1,830	NA/1,670	1,810/1,780 NA/1 625	1,630/1,600 NA	NA 1 585/1 560
NA/1,395		INA	NA	1,375/NA	NA	NA/1,745	NA/1,625	INA	1,585/1,560
Fuel tank (gal.)	15.8	15.8	15.8	18.5	18.5	18.5	18.5	18.5	18.5
Tires	D205/75D15	D20E/7FD1F	D22E/EED10	D205/75D15	D22E/75D15	D22E/7FD1F	D00E/7FD1F	D00E/7FD1F	D22E/7FD1F
Size — Standard — Available	P205/75R15 P235/55R16	P205/75R15 P235/55R16	P235/55R16 NA	P225/75R15 P265/70R16	P225/75R15 P265/70R16	P225/75R15 P265/70R16	P225/75R15 P265/70R16	P225/75R15 P265/70R16	P225/75R15 P265/70R16
Type	All-Season	All-Season	Mud-and	Mud-and-	Mud-and-	Mud-and-	Mud-and-	Mud-and-	Mud-and-
			Snow-rated	Snow-rated	Snow-rated	Snow-rated	Snow-rated	Snow-rated	Snow-rate
Mileage Estimates (MPG City/Highway) ³									
5-speed manual 4-cylinder	22/25	22/25	NA	NA	NA	NA	18/21	18/21	NA
V6	NA NA	NA	18/22	NA	NA	NA	NA NA	17/19	NA
4-speed automatic	00/05	00/05	N/A	10/00	10/00	10/00	10/01	10/01	N/A
4-cylinder V6	22/25 NA	22/25 NA	NA NA	19/22 NA	19/22 17/19	19/22 17/19	18/21 NA	18/21 17/19	NA 17/19
	1101								
S = Standard A = Available NA = Not Available Hydraulic shock absorbers on 4-cylinder models.			weight of occupants, av	ailable equipment an	d cargo; limited by	³ 2004 preliminary mi			
nyaraunc shock absorbers on 4-cyllilder illodels.		weight distri	DUTION.			mates not available	at time of printing. I	Actual mileage may v	ary