

THE UNBREAKABLE



TOYOTA HILUX 4X2

HILUX 4 X 2 TECHNICAL SPECIFICATIONS.

CAR	SINGLE						DOUBLE		KTRA		SINGLE		DOUBLE			
	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis		
Grade	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis		
Body	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis	Utility	Col. Chassis		
Model Code	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G			
	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G	YH55G			
ENGINE																
Type	Petrol						Diesel									
Valve	2V						22V						3V			
Configuration	Carburettor						Injection						Indirect Injection			
Cylinder	4						4						4			
Displacement (cc)	2567						2567						2778			
Bore x Stroke (mm)	86 x 78						82 x 89						96 x 96			
Compression Ratio	8.8:1						9.2:1						9.2:1			
Max. Power (kW/hp) - DIN	56/80@0						75/100@0						62/80@0			
Max. Torque (Nm/kgm) - DIN	140/3000						185/2000						183/2400			
TRANSMISSION																
Type - Manual	2 speed, Single Shift (5-speed, 5-speed, 5-speed)															
Type - Automatic	4 speed automatic															
Gear Ratio	MANUAL	AUTO	MANUAL	AUTO	MANUAL	AUTO	MANUAL	AUTO	MANUAL	AUTO	MANUAL	AUTO	MANUAL	AUTO		
1st	4.452	3.828	2.452	3.876	2.452	3.876	2.452	3.876	2.452	3.876	2.452	3.876	2.452	3.876		
2nd	2.296	2.233	1.492	2.233	1.492	2.233	1.492	2.233	1.492	2.233	1.492	2.233	1.492	2.233		
3rd	1.414	1.451	1.000	1.451	1.000	1.451	1.000	1.451	1.000	1.451	1.000	1.451	1.000	1.451		
4th	1.000	1.000	0.698	1.000	0.698	1.000	0.698	1.000	0.698	1.000	0.698	1.000	0.698	1.000		
5th	0.801	0.851	-	0.851	-	0.851	-	0.851	-	0.851	-	0.851	-	0.851		
Reverse	4.477	4.743	2.212	4.743	2.212	4.743	2.212	4.743	2.212	4.743	2.212	4.743	2.212	4.743		
Final Drive Ratio	4.555	4.100	4.300	4.100	4.300	4.100	4.300	4.100	4.300	4.100	4.300	4.100	4.300	4.100		
STEERING																
System	Recirculating Ball						Power assisted recirculating ball									
Power Assistance	N/A						Engine Speed Sensitive									
Turning Circle (left to right - m)	11.8						12.2						11.8			
BRAKES																
System	Vacuum boosted disc/ drum hydraulic with lead sensing proportioning and by pass valve															
Front	Ventilated disc with single piston floating caliper															
Rear	Drum with self adjusting duo servo						Drum with self adjusting leading and trailing shoes						Drum with self adjusting duo servo			
SUSPENSION																
Front Type	Independent double wishbone, torsion bar spring with double acting damper (stabilizer bar - petrol models only)															
Rear Type	Leaf spring with double acting gas filled damper															
WHEELS																
Type	16" H14.8 Ply Dunlop SP 14 x 6.5J Steel				16" H14C 8 Ply Dunlop SP 14 x 6.5J Steel				16" H14 Dunlop SP 14 x 6.5J Steel				16" H14.8 Ply Dunlop SP 14 x 6.5J Steel			
Dimensions																
Wheelbase (mm)	2650				2650				2650				2650			
Overall Length (mm)	4726				4470				4726				4470			
Overall Width (mm)	1658				1658				1658				1658			
Overall Height (mm)	1568				1568				1568				1568			
Front Track (mm)	1365				1365				1365				1365			
Rear Track (mm)	1370				1370				1370				1370			
Tray Length (mm)	2160				N/A				1405				1405			
Tray Depth (mm)	1405				N/A				1405				1405			
Overall Height (mm)	435				455				N/A				455			
Ground Clearance (mm)	199				195				N/A				195			
WEIGHTS/CAPACITIES																
Normal Kerb Weight (kg)	1190				1190				1225				1275			
Gross Vehicle Weight (kg)	2740				2730				2690				2540			
Front Axle Capacity (kg)	1590				1590				1590				1590			
Rear Axle Capacity (kg)	1590				1590				1590				1590			
Seating Capacity	3				3				3				3			
Fuel Capacity (litres)	56				56				56				56			
TOWING CAPACITY (MAXIMUM)																
with Trailer Brakes	3500 kg*															
without Trailer Brakes	600 kg*															

* Subject to State regulations and low bar design.

Toyota Motor Corporation Australia Limited - A.C.N. 004 384 338 ("Toyota") reserve the right to alter any detail of specifications and equipment without notice. Details of specifications and equipment are also subject to change to suit local conditions and requirements. Please inquire at your local Toyota dealer for details of any change that might be required for your area.
Note: Vehicle colours may vary from the printed photo on this leaflet. Part number HILUX2WD 0895SV.



FEATURES	SINGLE CAR	DOUBLE CAR	KTRA CAR
MECHANICAL			
Halogen Headlamps	•	•	•
Power Steering (Engine Speed Sensitive)	•	•	•
Fuel Tank Protector	•	•	•
Hand Throttle (Diesel Only)	•	•	•
EXTERIOR			
Tinted Windows	•	•	•
Quarter Vent Windows	•	•	•
Rear Mullaps	Utility	•	•
Locking Fuel Cap	•	•	Deluxe
Tinted Laminated Windscreen with Top Shade	•	•	•
Tinted Laminated Windscreen with Top Shade Chrome Package**	•	•	•
Side Protection Moulding	•	•	•
Wheel Arch Moulding	•	•	•
Remote Fuel Lid Release	•	•	•
Full Wheel Covers	•	•	•
Rear Step Bumper	•	•	•
Sidekick Tray	•	•	•
INTERIOR			
Side Door Invention Beams	•	•	•
Soft Foot 3 Spoke Racing Wheel	•	•	•
Day/Night Mirror	•	•	•
Digital Clock	•	•	•
*Speaker	•	•	•
Instrument Illumination Control	•	•	•
Tachometer	Deluxe	Deluxe & SR5	•
Child Restraint Anchorage**	•	•	•
Cloth Seat Facings	SR5 Grade	•	•
Intermitt Wipers	•	•	Deluxe
Front Bench Seat	Greener	•	•
Driver's Bucket Seat + Front Two Seat Bench	SR5 Grade	•	•
Vinyl Seat Facings	Greener	•	•
Electronic Trip/AMM Radio with 2 Speakers and 4 Light Clocks	•	•	•
Rear Bench Seat	•	•	•
18 adjustable Steering Column	•	•	SR5
Driver's Side Fashrest	SR5	•	•
Assist Grip	•	•	•
Centre Console	•	•	•
Lockable Glove Box	SR5	•	•
Cup Holder	SR5	•	•
Front Bucket Seats	•	•	•
Variable Intermittent Wiper	•	•	SR5
Auto Reverse Cassette Paper with Noise Reduction	•	•	SR5
Cloth Hook	•	•	•
Anti-Lock Cigarette Lighter Illumination	•	•	•
Oil Pressure Gauge	•	•	•
Voltsmeter	•	•	•
Front Door Pockets	•	•	•
Cup Holder - 2 Cup	•	•	•
2-Door Door Trim	•	•	•
Beer Dispenser	•	•	SR5
Rear Folding Jump Seats	•	•	•

** Chrome radiator grille, door outside handle, weather strip moulding.

** Meets the load and location requirements of ADR 34/01 (Single and Double Cab).

OH WHAT A FEELING!

TOYOTA HILUX