



















## >>> PERSONALISATION



SupaShock suspension\*



Load rack



18" X 10" FORGED ALLOY WHEEL (MATTE BLACK) SPORTSCAT



Eye-bolt



Tub liner & Loadmaster



18" X 10" FORGED ALLOY WHEEL (MATTE BLACK/MACHINED-FACE) SPORTSCAT+

# >>> COLOURS



Summit White



Satin Steel Grey ^

Mineral Black^



**Absolute Red** 

# >>> TECHNICAL DATA

## 2.8L DURAMAX 2 DIESEL

| Engine                    | 2.8L double overhead cam 4-cylinder common rail injection Duramax 2 Diesel with 4 valves per cylinder |                              |  |  |  |
|---------------------------|---|------------------------------|--|--|--|
| Capacity (cc)             | 2776  |                              |  |  |  |
| Compression ratio         | 1   | 6.5:1                        |  |  |  |
| Bore × stroke (mm)        | 94 × 100  |                              |  |  |  |
| Maximum power (ECE, kW)*  | 147 @ 3600rpm   |                              |  |  |  |
| Maximum torque (ECE, Nm)* | 440 @ 2000rpm<br>(manual)   | 500 @ 2000rpm<br>(automatic) |  |  |  |
| Gearratios                | 6-speed manual  | 6-speed automatic            |  |  |  |
| 1st                       | 4.02  | 4.06                         |  |  |  |
| 2nd                       | 2.21  | 2.37                         |  |  |  |
| 3rd                       | 1.46  | 1.55                         |  |  |  |
| 4th                       | 1.00  | 1.16                         |  |  |  |
| 5th                       | 0.76  | 0.85                         |  |  |  |
| 6th                       | 0.59  | 0.67                         |  |  |  |
| Reverse                   | 3.63  | 3.20                         |  |  |  |
| Final drive ratio         | 4.10  | 3.42                         |  |  |  |

## TRANSFER CASE RATIO

| Low range                             | 2.62 : 1   |
|---------------------------------------|--|
| High range                            | 1:1  |
| Fuel tank capacity (L)                | 76   |
| Fuel                                  | Diesel   |
| Electronic Stability Control<br>(ESC) | Incorporating: Anti-lock Braking System (ABS),<br>Electronic Brakeforce Distribution (EBD), Traction<br>Control System (TCS), Hill Descent Control (HDC), Hill<br>Start Assist (HSA), Trailer Sway Control (TSC) and Roll<br>Over Mitigation (ROM) |

#### **BRAKES**

| Brakes (SportsCat)  | Front discs with 25.4mm master cylinder; rear drum                       |
|---------------------|--|
| Brakes (SportsCat+) | Front discs with 4-piston calipers and 25.4mm master cylinder; rear drum |

| Front disc diameter (mm)         | 300 (SportsCat); 362 (SportsCat+)  |                      |                         |  |  |  |  |  |
|----------------------------------|--|----------------------|-------------------------|--|--|--|--|--|
| Rear disc diameter (mm)          | 295  |                      |                         |  |  |  |  |  |
| Track: Front and rear (mm)       | 1600   |                      |                         |  |  |  |  |  |
| Turning circle (kerb to kerb, m) | 13.6   |                      |                         |  |  |  |  |  |
| 4x4 system                       | Electronic select shift on the fly 4x4, 2-speed transfer case  |                      |                         |  |  |  |  |  |
| Suspension                       | Independent double wishbone, coil spring front suspension; leaf spring rear suspension   |                      |                         |  |  |  |  |  |
|                                  | Rear de-coupling ar  | nti-roll bar (Sports | Cat+)                   |  |  |  |  |  |
| Steering                         | Electric Power Steering (EPS)  |                      |                         |  |  |  |  |  |
| Service                          | The complimentary inspection is due at 1 month of owning your new vehicle. The first service is due at 15,000km or 9 months (whichever occurs first) and then every 15,000km or 9 months (whichever occurs first) since the last service. Additional services may be required under certain driving conditions such as when towing (refer to Owner's Handbook) |                      |                         |  |  |  |  |  |
| Angles^                          | Approach<br>angle  | Departure<br>angle   | Ramp breakover<br>angle |  |  |  |  |  |
| Both models                      | 32° 24°  |                      | 27°                     |  |  |  |  |  |
| Gross Vehicle Mass (GVM) (kg)    |  | 3150                 |                         |  |  |  |  |  |
| Gross Combined Mass (GCM) (kg)   |  | 6300                 |                         |  |  |  |  |  |
| Wade Depth (mm)                  |  | 600                  |                         |  |  |  |  |  |
| Tow ball load (kg)†              |  | 350                  |                         |  |  |  |  |  |
| TOWING MASS                      |  |                      |                         |  |  |  |  |  |
| Braked (kg)                      | 3500   |                      |                         |  |  |  |  |  |
| Unbraked (kg)                    | 750  |                      |                         |  |  |  |  |  |
| KERB MASS                        | Manual   | Auto                 |                         |  |  |  |  |  |
| SportsCat (kg)                   | 2257   |                      | 2250                    |  |  |  |  |  |
| SportsCat+ (kg)                  | 2281 2274  |                      |                         |  |  |  |  |  |
| AXLE LOAD LIMITS                 |  | 1450                 |                         |  |  |  |  |  |
| Front (kg)                       | 1450   |                      |                         |  |  |  |  |  |

## Exterior dimensions (mm)

| Model                  | Body Width | Height | Ground<br>Clearance | Wheelbase | Length | Tray Height | Tray Length | Tray Width<br>btw. Arches | Tray Width |
|------------------------|------------|--------|---------------------|-----------|--------|-------------|-------------|---------------------------|------------|
| SportsCat & SportsCat+ | 1933       | 1826   | 251                 | 3095      | 5345   | 466         | 1484        | 1122                      | 1534       |

Rear (kg)

## Interior dimensions (mm)

| Model                  | Front Headroom | Rear Headroom | Front Legroom | Rear Legroom | Front Shoulder Room | Rear Shoulder Room |
|------------------------|----------------|---------------|---------------|--------------|---------------------|--------------------|
| SportsCat & SportsCat+ | 1005           | 973           | 1045          | 856          | 1488                | 1472               |

1850

# >> FULL SPECIFICATIONS

LIGHTING ENGINE AND TRANSMISSION 2.8L 4-cylinder Duramax 2 Diesel LED daytime running lamps\_ 6-speed manual transmission Automatic on/off headlights 6-speed automatic transmission with Active Select Halogen reflector headlights Shift on the fly 4WD Manual levelling headlights \_ Limited Slip Differential (LSD) \_ Chrome headlamp bezel Engine sump guard \_ LED tail lights \_ Front LED fog lamps \_\_ **SAFETY AND HANDLING EXTERIOR** Forward Collision Alert (FCA) Lane Departure Warning (LDW) HSV recovery hooks (2) - front \_ Front airbags for driver and front passenger \_ Front and rear mudflaps \_ Front seat side impact airbags \_ Bonnet bulge. Full length side curtain airbags \_ Black exterior door handles \_ Driver knee airbag . Black exterior mirrors Front disc brakes HSV designed front fascia with lower integrated splash tray \_ AP Racing forged 4-piston brake calipers (362mm discs) - front \_ Black rear bumper 25.4mm brake master cylinder\_ HSV upper grille finished in Satin Black \_ Tyre pressure monitoring / indicator\_\_\_ HSV '3D' upper grille finished in Satin Black \_ High ride height\_ HSV wheel arch flares in Satin Black HSV Sports suspension (independent double wishbone, HSV '3D' wheel arch flares in Satin Black coil spring - front; leaf spring - rear) \_ Soft-open tail gate strut SupaShock suspension COLORADO tail gate applique \_ Rear de-coupling anti-roll bar \_ HSV hard tonneau with load rail provision \_ Electronic Stability Control (ESC) incorporating: HSV alloy sports bar \_\_\_ • Anti-lock Braking System (ABS) • Electronic Brakeforce Distribution (EBD)\_ HSV sailplane • Traction Control System (TCS)\_ Tubular side steps \_\_\_\_ • Hill Descent Control (HDC)\_ Roof rails Hill Start Assist (HSA) **DRIVER** • Trailer Sway Control (TSC) • Roll Over Mitigation (ROM) Electric Power Steering (EPS) Remote start (auto only) Front seatbelt sash height adjust \_ Bluetooth® connectivity Rear 3-point lap sash seatbelts Electronic cruise control Automatic Locking Retractor (ALR) - Rear Seat Driver's foot rest\_ Driver and front passenger seatbelt warning lamp and tone\_ Rear-view camera Rear seat seatbelt warning reminder\_ Rear Park Assist Rear seat child restraint anchor points (3) \_\_\_ Front Park Assist ISOFIX child restraint anchor point \_ Enhanced multi-function display: vehicle information menu, trip information menu, fuel economy menu, warning/messages **SECURITY** Power adjustable exterior mirrors \_\_\_\_ Power folding exterior mirrors \_\_\_ Remote keyless entry \_\_\_\_ Electrochromatic (light sensitive) rear view mirror \_ Tailgate lock\_ Steering wheel height adjust\_ Multifunction steering wheel controls featuring: Engine immobiliser \_\_\_\_\_ Bluetooth®, cruise control, audio controls \_\_ Flip keys (2) \_ Leather wrap steering wheel\_ WHEELS/TYRES Premium gear selector (manual) Chrome gear selector (automatic) 18" x 10" 6-spoke forged alloy wheels (Matte Black) Variable intermittent wipers\_\_\_ 18" x 10" 6-spoke forged alloy wheels (Matte Black with machined-face) Rain sensing wipers\_ 285/60 R18 Cooper Zeon LTZ Sports All-Terrain tyres Rear window demister\_

#### **ENTERTAINMENT**

Phone projection featuring Apple CarPlay® and Android® Auto\_ MyLink infotainment system with 8" colour touchscreen\_ Digital Audio Broadcast (DAB+) multimedia\_ Embedded satellite navigation\_\_\_\_ 7-speaker audio \_ Steering wheel mounted audio controls\_ USB input with iPod® connectivity\_\_\_ Auxiliary input\_ Roof mounted antenna\_\_\_\_

#### SEATING

SV Sports seats (Jasmine leather / Windsor suede) Front heated seats\_ Front bucket seats 6-way electric adjustable driver's seat\_ 6-way adjustable front passenger seat\_ Head restraints - driver and front passenger \_\_\_ Head restraints - three rear passengers\_ Rear seat centre armrest\_\_

#### CABIN COMFORT

Air conditioning with pollen filter Electronic climate control\_ Power windows, with express driver and passenger up and down Power windows, with express rear passenger up and down \_ Remote window activation via key fob\_ Dual front reading lamps \_\_\_\_ Centre dome lamp\_ Two 12 volt power outlets in centre dash. 12 volt power outlet in rear of centre console Vanity mirror on front passenger sunvisor with cover\_ Chrome interior door handles\_\_\_\_ Aluminium door insert\_ Driver and front passenger pillar assist handle\_ Front passenger overhead assist handle . Rear passenger overhead assist handles with coat hooks \_ Floor covering - carpet\_\_\_\_\_ Floor mats \_\_\_\_

#### STORAGE AND CARGO

Tub liner Front dual cup holders in centre console\_ Door pockets with integrated bottle storage Driver and front passenger seat cushion pocket. Driver and front passenger seat back pocket\_ Rear seats with 60/40 split fold base and under seat storage. Roof console - sunglass holder & dual reading lamps\_

Standard Optional

Visit hsv.com.au for more details. Follow us on















A word about this catalogue. Images shown are for illustration purposes only. We have tried to make this catalogue as comprehensive and factual as possible however, since the time of printing, some of the information you'll find here may have been updated. Also, some of the equipment shown or described throughout this catalogue may have been changed and/or is available at extra cost. Further, HSV reserves the right to make changes at any time, without notice, in prices, colours, materials, equipment and models. Your HSV Dealer has details and, before ordering, you should ask them to bring you up to date. No HSV Dealer or other person, is authorised, or permitted, to give, or make any purpose, of HSV product which is at variance with any written statement, assertion or undertaking on any of these subjects given, or made, by HSV in its published sales literature, and HSV does not accept any liability for such unauthorised action. HSV has authorised Dealers in many parts of Australia for the sale of service parts and the provision of service to owners of HSV's products. Every endeavour is made to ensure that such Dealers carry adequate stocks of service parts but neither HSV, nor GM Holden Ltd, make any promise other than that contained in the New Vehicle Warranty given by GM Holden Ltd, and HSV, that such parts or service facilities will be available at any specific location, or at any particular time. Express warranties offered for GM Holden Ltd and HSV products are subject to the conditions set out in all vehicle handbooks. Details are also available from GM Holden Ltd. and HSV on request. Copyright Premoso Pty. Ltd. (HSV) A.B.N. 84 006 802 053. Colours are for illustration purposes only. Printed January 2018.