JAGUAR XF SALOON AND XF SPORTBRAKE

TECHNICAL SPECIFICATION - JANUARY 2019







You can select from a choice of 2.0 or 3.0 litre diesel or petrol engines. These engines are designed for clean and efficient combustion and are all equipped with Stop/Start technology.

ENGINES			4-CYL	ITRE INDER RGED DIESEL		TU	20d 2.C 4-CYL RBOCHAF	INDER	5EL	
Capacity		СС	1,9	99			1,9	99		
Maximum power		EEC-PS (kW)	163	(120)			180 (132)		
@rev/min		rpm	4,0	000			4,0	00		
Maximum torque		EEC-Nm (lb.ft.)	380	(280)			430	(317)		
@rev/min		rpm	1,750-	2,500			1,750-	2,500		
No. of cylinders/Valves per o	cylinder		4	/4			4/	′ 4		
Cylinder layout			Turbocha	arge Inline			Turbocha	rge Inline		
Bore/stroke		(mm)	83.0/	92.35	83.0/92.35					
Compression ratio		(:1)	15.5 +	-/-0.5	15.5 +/-0.5					
FUEL ECONOMY			Manual RWD	Automatic RWD	Manua	I RWD	Automa	tic RWD	Automa	tic AWD
Fuel tank capacity - useable	el tank capacity - useable litres		55	55	66 66		6	6	66	
Diesel Exhaust Fluid (DEF) -	useable litres		16	16	16 16 16			6		
Diesel/Gasoline Particulate F	Filter (DPF/GPF)		•	•)	(•
FUEL ECONOMY -	NEDC EQUIVALEN	NT (NEDCeq*)	Class A	Class A	Class A	Class B	Class A	Class B	Class A	Class B
NEDCeq CO ₂ Emissions	Combined	(g/km)	124	135	126	131	135	139	144	148
FUEL ECONOMY -	WLTP**		TEL - TEH†	TEL - TEH†	TEL -	TEH [†]	TEL -	TEH [†]	TEL -	· TEH†
	Low	mpg (l/100km)	37.0 - 35.0 (7.6 - 8.1)	34.7 - 32.7 (8.1 - 8.6)	38.1 - 35.2	(7.4 - 8.0)	31.6 - 29.6	(8.9 - 9.6)	31.3 - 29.1	(9.0 - 9.7)
	Medium	mpg (l/100km)	49.1 - 45.7 (5.8 - 6.2)	48.6 - 45.3 (5.8 - 6.2)	49.3 - 44.0	(5.7 - 6.4)	49.4 - 44.1	(5.7 - 6.4)	42.8 - 39.0	0 (6.6 - 7.2)
WLTP Consumption	High	mpg (l/100km)	58.0 - 53.0 (4.9 - 5.3)	59.3 - 53.8 (4.8 - 5.2)	59.2 - 53.0	(4.8 - 5.3)	60.8 - 54.3	(4.6 - 5.2)	52.3 - 47.3	(5.4 - 6.0)
Consumption	Extra High	mpg (l/100km)	52.5 - 48.4 (5.4 - 5.8)	52.1 - 47.9 (5.4 - 5.9)	51.9 - 45.5	(5.4 - 6.2)	53.3 - 47.3	(5.3 - 6.0)	46.5 - 41.7	7 (6.1 - 6.8)
	Combined	mpg (l/100km)	50.4 - 46.7 (5.6 - 6.1)	49.9 - 46.1 (5.7 - 6.1)	50.9 - 45.4	(5.6 - 6.2)	49.9 - 44.8	(5.7 - 6.3)	44.4 - 40.2	2 (6.4 - 7.0)

● Standard — Not Available

Class A (17" wheels on the 163PS engine and 18" wheels) Class B (17", 19", 20" wheels and 18" wheels on the TDV6 engine)

*The figures provided are NEDCeq calculated from official manufacturer's WLTP tests in accordance with EU legislation. For comparison purposes only. Real world figures may differ. CO₂ and fuel economy figures may vary according to wheel fitment and optional extras fitted. NEDCeq are figures calculated using a Government formula from WLTP figures equivalent to what they would have been under the old NEDC test. The correct tax treatment can then be applied.


20d 2.0 4-CYLIND TURBOCHAR	ER TWIN	30d 3.0 LITRE V6 6-CYLINDER TWIN TURBOCHARGED DIESEL	CYLINDER TWIN 4-CYLINDER		30t 2.0 LITRE 4-CYLINDER TURBOCHARGED PETI		
1,99	99	2,993	1,9	97	1,9	97	
240 ((177)	300 (221)	250 ((184)	300	(221)	
4,00	00	4,000	5,5	00	5,5	00	
500 ((369)	700 (516)	365 (269)	400 ((295)	
1,500-2	2,500	1,500-1,750	1,300-	4,500	1,500-	4,500	
4/	/4	6/4	4,	4	4/	' 4	
Turbochar	rge Inline	Vee	Turbocha	rge Inline	Turbocharge Inline		
83.0/9	92.35	84/90	83.0/	83.0/92.29		83.0/92.29	
15.5 +,	/-0.5	16.1	10.5 +/-0.5		9.5 +/-0.5		
Automat	tic AWD	Automatic RWD	Automa	tic RWD	Automatic AWD		
6	66	66	7-	74		74	
1	16	16	-	-	_		
	•	•			•	•	
Class A	Class B	Class B	Class A	Class B	Class A	Class B	
151	155	157	165	166	171	172	
TEL -	TEH†	TEL - TEH†	TEL - TEH ⁺		TEL - TEH†		
27.9 - 26.8 (10.1 - 10.6)		30.9 - 29.6 (9.2 - 9.5)	23.6 - 22.9 (11.9 - 12.3)		23.2 - 21.9 (12.2 - 12.9)		
42.4 - 38.5	(6.7 - 7.3)	42.1 - 40.1 (6.7 - 7.0)	33.8 - 31.4 (8.3 - 9.0)		32.1 - 30.2	(8.8 - 9.4)	
	50.4 - 45.1 (5.6 - 6.3) 51.0 - 48.0 (5.5 - 5.9)		40.4 - 36.8 (7.0 - 7.7)		37.9 - 34.7	(7.4 - 8.1)	
50.4 - 45.1	(5.6 - 6.5)	0.10 10.0 (0.0 0.0)	36.1 - 32.1 (7.8 - 8.8)		34.0 - 30.1 (8.3 - 9.4)		
50.4 - 45.1 45.9 - 40.1	· · · · · · · · · · · · · · · · · · ·	44.6 - 41.8 (6.3 - 6.8)	36.1 - 32.1	(7.8 - 8.8)	34.0 - 30.1	(8.3 - 9.4)	

^{**}WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars. It measures fuel, energy consumption, range and emissions. This is designed to provide figures closer to real-world driving behaviour. It tests vehicles with optional equipment and with a more demanding test procedure and driving profile.

**TEL (Test Energy Low) and TEH (Test Energy High) figures are shown as a range under WLTP testing measures. TEL refers to the lowest/most economical figures (with the lightest set of options).

**TEH refers to the highest/least economical figures (with the heaviest set of options). WLTP legislation dictates that where there is <5g CO₂ variance between TEL and TEH, only the TEH is declared.

XF SALOON TECHNICAL SPECIFICATION



	4-CYL	2.0 LITRE 4-CYLINDER TURBOCHARGED DIESEL		20d 2.0 LITRE 4-CYLINDER TURBOCHARGED DIESEL		
PERFORMANCE	Manual RWD	Automatic RWD	Manual RWD	Automatic RWD	Automatic AWD	
Acceleration (secs) 0-60mph (0-100 km/h)	9.3 (9.8)	8.6 (9.1)	8.7 (9.2)	7.9 (8.4)	8.0 (8.5)	
Maximum speed mph (km/h)	132 (212)	132 (212)	136 (219)	136 (219)	136 (219)	
BRAKES						
Front type		Single Piston Slidi	ng Caliper, Vented Disc			
Front diameter (mm)	325	325	325	325	325	
Rear type	Single Piston Slic	ling Caliper, Solid Disc	Single I	Piston Sliding Caliper, Ven	ed Disc	
Rear diameter (mm)	300	300	325	325	325	
Park Brake		iEPB, mo	otor on caliper			
WEIGHTS (kg)*						
Unladen weight (EU)**	1,699	1,720	1,719	1,734	1,771	
Unladen weight (DIN)†	1,624	1,645	1,644	1,659	1,696	
Gross Vehicle Weight (GVW)	2,190	2,230	2,270	2,295	2,340	
TOWING (kg)						
Unbraked trailer	_	750	750	750	750	
Maximum towing	_	1,600	1,800	2,000	2,000	
Maximum coupling point (nose weight)	_	100	100	100	100	
Maximum vehicle and trailer combination	-	3,830	4,070	4,295	4,340	
ROOF CARRYING (kg)						
Maximum roof load (including cross bars)	75	75	75	75	75	

⁻ Not Available

^{*}Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel.

20d 2.0 LITRE 4-CYLINDER TWIN TURBOCHARGED DIESEL	30d 3.0 LITRE V6 6-CYLINDER TWIN TURBOCHARGED DIESEL	25t 2.0 LITRE 4-CYLINDER TURBOCHARGED PETROL	30t 2.0 LITRE 4-CYLINDER TURBOCHARGED PETROL
Automatic AWD	Automatic RWD	Automatic RWD	Automatic AWD
6.5 (6.9)	6.0 (6.4)	6.4 (6.7)	5.6 (5.9)
153 (246)	155 (250)	152 (244)	155 (250)
	Single Piston Sliding	Calinar Vantad Disc	
325	350	325	350
	Single Piston Sliding		330
325	325	325	325
	iEPB, motor		
1,808	1,878	1,704	1,786
1,733	1,803	1,629	1,711
2,370	2,390	2,260	2,330
750	750		750
2,000	2,000	1,900	1,900
100	100	100	100
4,370	4,390	4,160	4,230
, , , , , , , , , , , , , , , , , , ,	, .		,
75	75	75	75

XF SPORTBRAKE TECHNICAL SPECIFICATION

You can select from a choice of 2.0 or 3.0 litre diesel or petrol engines. These engines are designed for clean and efficient combustion and are all equipped with Stop/Start technology.

ENGINES				.ITRE .INDER RGED DIESEL	т		D LITRE LINDER RGED DIES	EL	
Capacity		сс	1,9	99		1,9	999		
Maximum power		EEC-PS (kW)	163 ((120)		180	(132)		
@rev/min		rpm	4,0	000		4,0	000		
Maximum torque		EEC-Nm (lb.ft.)	380 ((280)		430	(317)		
@rev/min		rpm	1,750-	-2,500		1,750	-2,500		
No. of cylinders/Valves per cyl	linder		4,	/4		4	/4		
Cylinder layout			Turbocha	arge Inline		Turboch	arge Inline		
Bore/stroke		(mm)	83.0/	92.35	83.0/92.35				
Compression ratio		(:1)	15.5 +	-	15.5 +/-0		+/-0.5	-0.5	
FUEL ECONOMY			Manual RWD	Automatic RWD	Automa	atic RWD	Automa	atic AWD	
Fuel tank capacity - useable li	tres		55	55	6	66	(56	
Diesel Exhaust Fluid (DEF) - u	seable litres		16	16	16 16		16		
Diesel/Gasoline Particulate Filt	ter (DPF/GPF)		•	•	•		•		
FUEL ECONOMY - N	NEDC EQUIVALE	NT [NEDCeq]*	Class A	Class A	Class A	Class B	Class A	Class B	
NEDCeq CO ₂ Emissions	Combined	(g/km)	135	139	139	143	147	151	
FUEL ECONOMY - V	VLTP**		TEL - TEH†	TEL - TEH†	TEL - TEH†		TEL - TEH†		
	Low	mpg (l/100km)	33.5 - 33.8 (8.4 - 8.4)	34.3 - 33.1 (8.2 - 8.5)	31.2 - 29.3	3 (9.1 - 9.6)	30.7 - 28.	7 (9.2 - 9.8)	
	Medium	mpg (I/100km)	45.4 - 43.8 (6.2 - 6.5)	47.7 - 45.9 (5.9 - 6.2)	48.1 - 43.4	1 (5.9 - 6.5)	41.7 - 38.3	3 (6.8 - 7.4)	
WLTP Consumption	High	mpg (I/100km)	55.3 - 53.6 (5.1 - 5.3)	57.0 - 54.3 (5.0 - 5.2)	59.0 - 53.3	3 (4.8 - 5.3)	50.8 - 46.	3 (5.6 - 6.1)	
Consumption	Extra High	mpg (I/100km)	49.9 - 47.2 (5.7 - 6.0)	49.5 - 47.2 (5.7 - 6.0)	51.3 - 46.	1 (5.5 - 6.1)	44.8 - 40.	6 (6.3 - 7.0)	
	Combined	mpg (I/100km)	47.3 - 45.8 (6.0 - 6.2)	48.2 - 46.1 (5.9 - 6.1)	48.4 - 44.0	0 (5.8 - 6.4)	43.1 - 39.4	4 (6.6 - 7.2)	
		13 (7 ,						, ,	

● Standard — Not Available

Class A (17" wheels on the 163PS engine and 18" wheels) Class B (17", 19", 20" wheels and 18" wheels on the TDV6 engine)

*The figures provided are NEDCeq calculated from official manufacturer's WLTP tests in accordance with EU legislation. For comparison purposes only. Real world figures may differ. CO₂ and fuel economy figures may vary according to wheel fitment and optional extras fitted. NEDCeq are figures calculated using a Government formula from WLTP figures equivalent to what they would have been under the old NEDC test. The correct tax treatment can then be applied.

20d 2.0 4-CYLIND TURBOCHAR	ER TWIN	30d 3.0 LITRE V6 6-CYLINDER TWIN TURBOCHARGED DIESEL	25t 2.0 4-CYLI TURBOCHAR	INDER	30t 2.C 4-CYL TURBOCHAR	INDER	
1,99	9	2,993	1,9	97	1,9	97	
240 (*	177)	300 (221)	250 ((184)	300	(221)	
4,00	00	4,000	5,5	00	5,5	00	
500 (3	369)	700 (516)	365 (269)	400 ((295)	
1,500-2	2,500	1,500-1,750	1,300-	4,500	1,500-	4,500	
4/4	4	6/4	4/	/4	4/	/4	
Turbochar	ge Inline	Vee	Turbocha	rge Inline	Turbocharge Inline		
83.0/9	2.35	84/90	83.0/92.29		83.0/92.29		
15.5 +/	[′] -0.5	16.1	10.5 +/-0.5		9.5		
Automati	ic RWD	Automatic RWD	Automat	tic RWD	Automatic AWD		
6	6	66	7-	4	7-	74	
16	6	16	_	-	_		
		•	•	•	•		
Class A	Class B	Class B	Class A	Class B	Class A	Class B	
157	161	160	171	172	175	176	
TEL - 1	ΓEH [†]	TEL - TEH [†]	TEL - TEH ⁺		TEL - TEH†		
27.7 - 26.6 (1	10.2 - 10.6)	30.4 - 29.3 (9.3 - 9.7)	23.4 - 22.7 (23.4 - 22.7 (12.0 - 12.4)		22.7 - 21.6 (12.5 - 13.1)	
41.4 - 38.0 ((6.8 - 7.4)	41.3 - 39.5 (6.8 - 7.1)	33.1 - 31.0 (8.5 - 9.1)		31.2 - 29.6 (9.0 - 9.5)		
48.9 - 44.3	(5.8 - 6.4)	49.6 - 47.1 (5.7 - 6.0)	39.1 - 35.9	39.1 - 35.9 (7.2 - 7.9)		(7.8 - 8.4)	
43.9 - 39.0) (6.4 - 7.3)		471 400 (00 00)	34.3 - 31.0 (8.2 - 9.1)		31.4 - 28.7 (9.0 - 9.8)		
43.9 - 39.0)	(6.4 - 7.5)	43.1 - 40.8 (6.6 - 6.9)	34.3 31.0	(0.2 0.1)		(3.0 3.0)	

^{**}WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars. It measures fuel, energy consumption, range and emissions. This is designed to provide figures closer to real-world driving behaviour. It tests vehicles with optional equipment and with a more demanding test procedure and driving profile.

**TEL (Test Energy Low) and TEH (Test Energy High) figures are shown as a range under WLTP testing measures. TEL refers to the lowest/most economical figures (with the lightest set of options).

**TEH refers to the highest/least economical figures (with the heaviest set of options). WLTP legislation dictates that where there is <5g CO₂ variance between TEL and TEH, only the TEH is declared.

XF SPORTBRAKE TECHNICAL SPECIFICATION

Configure your vehicle at jaguar.co.uk

	2.0 LITRE 4-CYLINDER TURBOCHARGED DIESEL		20d 2.C 4-CYLI TURBOCHAR	NDER
PERFORMANCE	Manual RWD	Automatic RWD	Automatic RWD	Automatic AWD
Acceleration (secs) 0-60mph (0-100 km/h)	9.5 (10.0)	8.8 (9.3)	8.0 (8.5)	8.1 (8.6)
Maximum speed mph (km/h)	132 (212)	132 (212)	136 (219)	136 (219)
BRAKES				
Front type		Single Piston Sliding	Caliper, Vented Disc	
Front diameter (mm)	325	325	325	325
Rear type		Single Piston Sliding	Caliper, Vented Disc	
Rear diameter (mm)	325	325	325	325
Park Brake		iEPB, moto	or on caliper	
WEIGHTS (kg)*				
Unladen weight (EU)**	1,727	1,753	1,789	1,842
Unladen weight (DIN)†	1,652	1,678	1,714	1,767
Gross Vehicle Weight (GVW)	2,260	2,260	2,320	2,375
TOWING (kg)				
Unbraked trailer	750	750	750	750
Maximum towing	2,000	2,000	2,000	2,000
Maximum coupling point (nose weight)	100	100	100	100
Maximum vehicle and trailer combination	4,260	4,260	4,320	4,375
ROOF CARRYING (kg)				
Maximum roof load (including cross bars)	100	100	100	100

20d 2.0 LITRE 4-CYLINDER TWIN TURBOCHARGED DIESEL	30d 3.0 LITRE V6 6-CYLINDER TWIN TURBOCHARGED DIESEL	25t 2.0 LITRE 4-CYLINDER TURBOCHARGED PETROL	30t 2.0 LITRE 4-CYLINDER TURBOCHARGED PETROL
Automatic RWD	Automatic RWD	Automatic RWD	Automatic AWD
6.7 (7.0)	6.1 (6.6)	6.5 (6.9)	5.7 (6.0)
150 (241)	155 (250)	150 (241)	155 (250)
	Cinale Distancellisting	Calina an Manta d Diag	
	Single Piston Sliding		
325	350	325	350
	Single Piston Sliding	Caliper, Vented Disc	
325	325	325	325
	iEPB, motor	on caliper	
1,875	1,924	1,775	1,838
1,800	1,849	1,700	1,763
2,395	2,430	2,290	2,400
	_		
750	750	750	750
2,000	2,000	1,900	1,900
100	100	100	100
4,395	4,430	4,190	4,300
100	100	100	100

XF SALOON DIMENSIONS

Configure your vehicle at jaguar.co.uk



Vehicle Height

With roof antenna 1,457mm

Headroom

Maximum front/rear headroom with Panoramic roof fitted 953/970mm Rear headroom 970mm

Legroom

Maximum front legroom 1,055mm Maximum rear legroom 957mm

Loadspace Capacity Height 686mm, Width 1,257mm Loadspace width between arches 850mm Maximum loadspace volume behind first row Dry* 680 litres, Wet** 885 litres Maximum loadspace volume behind second row Dry* 415 litres, Wet** 540 litres


Turning Circle

Kerb-to-kerb 11.61m Wall-to-wall 11.94m Turns lock-to-lock 2.6





Dimensions were measured with vehicle at unladen weight.



XF SPORTBRAKE DIMENSIONS



Vehicle Height

With roof antenna 1,494mm

Headroom

Maximum front/rear headroom with Panoramic roof fitted 989mm/991mm Rear headroom 995mm

Legroom

Maximum front legroom 1,055mm Maximum rear legroom 957mm

Loadspace Capacity Height 635mm, Width 1,057mm Loadspace width between arches 1,058mm Maximum loadspace volume behind first row Dry* 860 litres, Wet** 1,035 litres Maximum loadspace volume behind second row Dry* 490 litres, Wet** 565 litres

Turning Circle

Kerb-to-kerb 11.61m Wall-to-wall 11.94m Turns lock-to-lock 2.6







