



Adaptive Cruise Control^{1.}



Autonomous Emergency Braking with Pedestrian Detection^{1.}



Lane Keeping Aid^{1.}



Active Park Assist^{1.}



Leather-Accented Interior



Tow Bar 2.



FordPass Connect - Embedded Modem^{3.}



18" Black Alloy Wheels



SYNC®3 with Apple CarPlay $^{\text{TM}}$ & Android Auto $^{\text{TM}}$ 4.

Available in:

*Prestige Paint Incurs Additional Cost



Alabaster White*



Aluminium Silver*



Arctic White



Blue Lightning*



Meteor Grey*



Shadow Black*



True Red

Ranger XLT Fully Loaded Specifications Visit ford.com.au for full details.

Decide Policitary Policit	5.1.5		1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.		
Divertinins 3nd Brow Legroum 902 6x4 2.2 IT DCI Disest Engine 7 2nd Brow Shoulder Room 1032 Avoidability 5 Front Handdroom 1032 Front Religion Infants Sport Handdroom 1038 Front Religion 1058 Front Handdroom 1038 Religion 1740 395 Front Handdroom 1038 Maximum Prove 1740 396 Front Handdroom 1040 1440 Walkingman Torque 1750 396 Read Walking Front May 1 2230 2170 Fuel Management System Turbobriaged direct Read Walking Front May 2 960 970 Fuel Type Deserted 274 65 Seed Auto Maximum Alloude Read Priorit 1490 490 Fuel Type Deserted 1400 Maximum Alloude Florin 1490 490 Fuel Type Deserted 1400 Maximum Alloude Florin 1490 490 Fuel Type Intel Sype 1500 490 490 <	Body Type		Interior Dimensions (mm)		006
Availability					
			<u>~</u>		
Maniform Provide Indiana Souther Souther Maniform Ma					
Engine Size (Cm) 3108					
Pages Page					
Maximum Prover M7KW @ 30.00 prover Engline 8.2 TOCID Gives 81 Touto Dives 81 Touto Dives 81 Touto Dives 82 Dougles					1110
Maximum Torque A70Nm (a) 1780 – 2800 mg/m Karb Weight - Torat 4 2250 (27) (27) (27) (27) (27) (27) (27) (27)	Maximum Power	147kW @ 3000rpm		3.2L TDCi Diesel	Bi-Turbo Die
Type Management System	Maximum Torquo	470Nm @		2230	2197
Part Management system Commonat Injection Payloads			Kerb Weight - Front Axle ^{6.}	1250	1218
Combined Fuel Economy (L/100km)² (Auto)	Fuel Management System		Kerb Weight - Rear Axle ^{6.}	980	979
COPE missions (g/km) * (Auto)			Payload ^{7.}	970	1003
Fuel Type			Gross Vehicle Mass	3200	3200
Diese Diese Maximum Axle Load - Front 1480 148			Gross Combined Mass	6000	6000
Transmission					
Maximum Nate Dates - Free Proper Service					
Availability		O Speed Auto		1850	1850
Engine Type Inline 4 Cylinder Centre Ingine Type Centre Ingine Type Centre Ingine Type Setterior Day 13198 Setterior Day 17 Tallgate Handles - Chrome S Engine Size (cm²) 3198 Exterior Day 7 Tallgate Handles - Chrome S Maximum Torque 1570-2000rpm Setterior Mirrors - Chrome S Fluel Management System Turbocharged direct common rall injection Transmission 74 CO2 Emissions (g/km)³ (Auto) 74 Fill Type Diesel Height - Indicator Front Flouring & Heated with Tindicator Transmission 10 Speed Auto Fill Chrome S Fluel Type Diesel Height - Box Dimensions (mm) Exterior Lighting - Front Folicing & Heated with Tindicator Transmission 10 Speed Auto Fill Chrome S Fluel Type Diesel Height - Box Dimensions (mm) Mud Flaps - Front and Rear S Fleight - 16 floor height to ground 840 Rear Sports Bar - Chrome Steel S Height - act floor of height to ground 840 Back Wheels - 18° Alloy S Unight - between wheelhouses 1139 Belloack Wheels - 18° Alloy		0			
Section Size (cm²) Size Section Size Section Size Section Size (cm²) Size					
Maximum Power					
Maximum Torque		157kW @ 3750rpm		Cnrome	
Puel Management System	M .				
Fuel Management System Turbocharged direct common relilinjections Turb Indicator Security Combined Fuel Economy (L/100km)*(Auto) 7.4 Front Burmer - Body Colour Security COZ Emissions (g/km)*(Auto) 195 Exterior Lighting - Front Fog Lamps (Halogen) Security Fuel Taype Diesel Exterior Lighting - Front Fog Lamps (Halogen) Security Fuel Taype Diesel Exterior Lighting - Front Fog Lamps (Halogen) Security Fuel Taype Diesel Exterior Lighting - Front Fog Lamps (Halogen) Security Fuel Taype Diesel Exterior Lighting - Front Fog Lamps (Halogen) Security Fuel Taype Diesel Exterior Lighting - Front Fog Lamps (Halogen) Security Fuel Taype Diesel Exterior Lighting - Front Fog Lamps (Halogen) Security Fuel Taype Diesel Exterior Lighting - Front Fog Lamps (Halogen) Security Fuel Taype Diesel Exterior Lighting - High Performance Bi-LED Exterior Lighting - High Performance Bi-LED Height - At Converlience 511 Privacy Class Security Lieght - At Converlience 151	Maximum Torque	1750-2000rpm			<u> </u>
Combined Fuel Economy (L/100km)* (Auto) 7.4 Effort Bumper - Body Colour \$ CO2 Emissions (g/km)* (Auto) 195 Exterior Lighting - Front Fog Lamps (Halogen) \$ Fuel Tank Capacity (L) 80 Exterior Lighting - Front Fog Lamps (Halogen) \$ Fuel Type Diesel Exterior Lighting - Front Fog Lamps (Halogen) \$ Fuel Type Diesel Exterior Lighting - Front Fog Lamps (Halogen) \$ Fuel Type Diesel Exterior Lighting - Front Fog Lamps (Halogen) \$ Fuel Type Diesel Exterior Lighting - Front Fog Lamps (Halogen) \$ Fuel Type Diesel Exterior Lighting - Front Fog Lamps (Halogen) \$ Fuel Type Diesel Exterior Lighting - Front and Rear \$ Fuel Type Bead Rear Bumper - Chrome Steel \$ Fleight - at centreline of axle \$1 \$ Height - floor height to ground 840 Rear Bumper - Chrome Steel \$ Length - top of box 1485 Black Bear - Black \$ Width - between wheelhouses 1139 Bealiner with 12V Socket \$	Fuel Management System	Turbocharged direct		Ticated With	S
Combined Fuel Economy (L/Tolokm)* (Auto) 7.4 Exterior Lighting - Front Fog Lamps (Halogen) S CO2 Emissions (gr/km)* (Auto) 195 Grille - Chrome S Fuel Tank Capacity (L) 80 Exterior Lighting - High Performance Bi-LED S Fuel Type Diesel Mud Flaps - Front and Rear S Pick-up Box Dimensions (mm) Privacy Glass S Height - at centreline of axle 511 Rear Bumper - Chrome Steel S Height - at floor 1549 Black Wheels - Black (Meels - Black) S Length - top of box 1485 Black Wheels - 18" Alloy S Length - top of box 1485 Bedliner with 12V Socket S Width - between wheelhouses 1139 Bedliner with 12V Socket S Width - petropening 1530 Inner Tie Downs S Exterior Dimensions (mm) Lead Box Illumination S Length - with rear bumper (where fitted) 5446 Taligate Lock - Manual S Width - exterior mirrors extended 2163 Taligate Lock - Manual S Width - exterio					S
COZ Emissions (g/km)*(Auto) 195 Grille - Chrome 5 Fuel Tank Capacity (L) BO Exterior Lighting - High Performance Bi-LED 5 Fuel Type Diesel Headlamps 5 Transmission 10 Speed Auto Mud Flaps - Front and Rear 5 Pick-up Box Dimensions (mm) Privacy Glass 5 Height - at centreline of askle 511 Rear Bumper - Chrome Steel 5 Height - at centreline of askle 511 Rear Bumper - Chrome Steel 5 Height - floor height to ground 840 Side Steps - Black 5 Length - toff floor or bight to ground 840 Rear Sports Bar - Chrome Tubular 5 Length - top of box 1485 Black Wheels - 18" Alloy 5 Length - top of box 1485 Bedliner with 12V Socket 5 Width - between wheelhouses 1139 Bedliner with 12V Socket 5 Width - pick-up box 1550 Tough Bed Spray-In Bedliner 0 Width - pick-up box 1550 Tough Bed Spray-In Bedliner 5 Exterior Dimensions (mm)				os (Halogen)	
Fuel Type Diesel Headlamps S Transmission 10 Speed Auto Mud Flaps - Front and Rear \$ Pick-up Box Dimensions (mm) Privacy Glass \$ Height - at centreline of axle 511 Rear Bumper - Chrome Steel \$ Height - at centreline of axle 840 Rear Sports Bar - Chrome Tubular \$ Length - at floor 1549 Back Wheels - 18 "Alloy \$ Length - top of box 1485 Load Box Elements Back Wheels - 18" Alloy \$ Width - between wheelhouses 1139 Bedliner with 12V Socket \$ Width - pick-up box 1560 Tough Bed Spray-In Bedliner O Width - pick-up box 1560 Tough Bed Spray-In Bedliner O Width - pick-up box 1560 Tough Bed Spray-In Bedliner O Width - pick-up box 1560 Tough Bed Spray-In Bedliner O Width - pick-up box 1560 Tough Bed Spray-In Bedliner O Width - exterior Dimensions (mm) Load Box Illumination S Length - with rear bumper (where fitted)					
Pediatrips				nce Bi-LED	
Pick-up Box Dimensions (mm) Privacy Glass S Height - at centreline of axle 511 Rear Bumper - Chrome Steel S Height - floor height to ground 840 Side Steps - Black S Length - at floor 1549 Rear Sports Bar - Chrome Tubular S Length - top of box 1485 Load Box Elements S Width - between wheelhouses 1139 Bedliner with 12V Socket S Width - pick-up box 1560 Tough Bed Spray-In Bedliner O Width - pick-up box 1560 Inner Tie Downs S Exterior Dimensions (mm) Load Box Illumination S Length - with rear bumper (where fitted) 5446 Tailgate Lock - Manual S Width - exterior mirors extended 1963 Tall gate with Lift Assistance S Width - exterior mirors extended 1977 Seating Width - exterior mirors folded 1977 Seating Width - exterior mirors folded 1977 Seating Width - excluding mirrors 1867 Churror Seat Adjustment (plus Lumbar Support) S					
Height - at centrelline of axle 511 Rear Bumper - Chrome Steel S		10 Speed Auto			
Height - floor height to ground					
Rear Sports Bar - Chrome Tubular S S Elack Wheels - 18" Alloy S Elack					
Length - at 1600r 1549 Black Wheels - 18" Alloy S Length - top of box 1485 Load Box Elements S Width - between wheelhouses 1139 Bedliner with 12V Socket S Width - pick-up box 1560 Tough Bed Spray-In Bedliner O Width - rear opening 1530 Inner Tie Downs S Exterior Dimensions (mm) Load Box Illumination S Length - with rear bumper (where fitted) 5446 Tallgate Lock - Manual S Width - exterior mirrors extended 2163 Seating S Width - exterior mirrors folded 1977 Seating S Width - excluding mirrors 1867 Cevery Manual Driver Seat Adjustment (plus Lumbar Support) S Width - excluding mirrors 1820 XLT Leather Accented Seats (Black) S Weight XLT Leather Accented Seats (Black) S Overhang - Front 928 Comfort and Convenience S Overhang - Rear 1226 230V Inverter - Rear of Centre Console S Track - Front and Rear 1560				 r	
Width - between wheelhouses 1139 Width - pick-up box 1560 Width - rear opening 1530 Exterior Dimensions (mm) Length - with rear bumper(where fitted) 5446 Width - exterior mirrors extended 2163 Width - exterior mirrors folded 1977 William - exterior mirror folded 1977 William - exterior mirror folded 1977 William - exterior mirror folded 1977 William Language Lock - Manual 1978 Seating - wall all sufficient folded 1977 William - exterior mirror folded 1977 William Language Lock - Manual 1978 Bedliner with 12t Sopkun 1981 Faligate Lock - Manual 1978 Faligate Lock - Manual 1978 F					
Width - pick-up box 1560 Tough Bed Spray-In Bedliner Width 2 Vocket S Exterior Dimensions (mm) Load Box Illumination S Length - with rear bumper (where fitted) 5446 Tailgate Lock - Manual S Width - exterior mirrors extended 2163 Tailgate Lock - Manual S Width - exterior mirrors folded 1977 Seating Width - excluding mirrors 1867 (plus Lumbar Support) S Height 1821 XLT Leather Accented Seats (Black) S Overhang - Front 928 Comfort and Convenience Overhang - Rear 1560 Accoustic Windshield S Wheelbase 3220 Auxillary 12V Power Outlet - Lower Dashboard S Ground Clearance (unladen, mm) 237 Auxillary 12V Power Outlet - Rear of Centre Console S Approach Angle (unladen, degrees): 29 Departure Angle (unladen, degrees): 21 a) measured to tow bar Ramp Breakover Angle (degrees) 25 Floor Coverings - Carpet S	Length - top of box		Load Box Elements		
Width - rear opening 1530 Insert Tie Downs S Exterior Dimensions (mm) Load Box Illumination S Length - with rear bumper (where fitted) 5446 Tailgate Lock - Manual S Width - exterior mirrors extended 2163 Tailgate with Lift Assistance S Width - exterior mirrors folded 1977 Seating Width - excluding mirrors 1867 (plus Lumbar Support) S Height 1821 XLT Leather Accented Seats (Black) S Overhang - Front 928 Comfort and Convenience Overhang - Rear 1226 230V Inverter - Rear of Centre Console S Track - Front and Rear 1560 Acoustic Windshield S Wheelbase 3220 Auxillary 12V Power Outlet - Lower Dashboard S Ground Clearance (unladen, mm) 237 Auxillary 12V Power Outlet - Rear of Centre Console S Wading Depth (mm) 800 Centre Console S Approach Angle (unladen, degrees): 29 Departure Angle (unladen, degrees): 21 a) measured to tow bar Ramp Breakover Angle (degrees) 25 Floor Coverings - Carpet S	Width - between wheelhouses	1139	Bedliner with 12V Socket		S
Exterior Dimensions (mm) Length - with rear bumper (where fitted) Width - exterior mirors extended 2163 Width - exterior mirors folded 1977 Width - excluding mirrors 1867 Width - exterior mirrors extended 1867 Comfort and Convenience Comfort and Convenience 230V Inverter - Rear of Centre Console S Acoustic Windshield S Auxillary 12V Power Outlet - Lower Dashboard S Auxillary 12V Power Outlet - Rear of Centre Console Centre Console - Single Lid with 2 Cup Holders S Child Seat Upper Anchorage Points (x 2) S Child Seat Upper Anchorage Points (x 2) S Child Seat ISOFIX Anchorage Points (x 2) S Climate Control - Dual Zone Automatic S Dual Colour 4.2" Instrumentation Screens S Floor Coverings - Carpet S	Width - pick-up box	1560	Tough Bed Spray-In Bedliner		0
Length - with rear bumper (where fitted) 5446 Width - exterior mirrors extended 2163 Width - exterior mirrors folded 1977 Width - excluding mirrors 1867 Width - excluding mirrors 1867 Width - excluding mirrors 18867 Width - exterior mirrors folded 1977 Seating 6-way Manual Driver Seat Adjustment (plus Lumbar Support) XLT Leather Accented Seats (Black) 5 Comfort and Convenience Coverhang - Rear 1226 230V Inverter - Rear of Centre Console 5 Track - Front and Rear 1560 Acoustic Windshield 5 Windlary 12V Power Outlet - Lower Dashboard 5 Auxillary 12V Power Outlet - Rear of Centre Console 5 Centre Console - Single Lid with 2 Cup Holders 5 Child Seat Upper Anchorage Points (x 2) 5 Child Seat Upper Anchorage Points (x 2) 5 Climate Control - Dual Zone Automatic 5 Dual Colour 4.2" Instrumentation Screens 5 Floor Coverings - Carpet 5	Width - rear opening	1530	Inner Tie Downs		S
Width - exterior mirors extended 2163 Width - exterior mirrors folded 1977 Width - excluding mirrors 1867 Width - exterior mirrors extended 1977 Width - exterior mirrors olded 1977 Width - excluding mirrors 1867 Width - exc	Exterior Dimensions (mm)				
Width - exterior mirrors folded 1977 Width - excluding mirrors 1867 Wight 1821 XLT Leather Accented Seats (Black) S Comfort and Convenience Overhang - Front Overhang - Rear 1226 230V Inverter - Rear of Centre Console S Track - Front and Rear 1560 Acoustic Windshield S Wheelbase Ground Clearance (unladen, mm) 237 Auxillary 12V Power Outlet - Lower Dashboard S Wading Depth (mm) 800 Centre Console - Single Lid with 2 Cup Holders S Approach Angle (unladen, degrees): 29 Departure Angle (unladen, degrees): 21 Child Seat Upper Anchorage Points (x 2) S Climate Control - Dual Zone Automatic S Dual Colour 4.2" Instrumentation Screens S Floor Coverings - Carpet S Seating 6-way Manual Driver Seat Adjustment (plus Lumbar Support) S Auxillary Support) S Comfort and Convenience S Comfort and Convenience S Control Console S Child Seat Upper Anchorage Points (x 2) S Climate Control - Dual Zone Automatic S Dual Colour 4.2" Instrumentation Screens S Floor Coverings - Carpet	Length - with rear bumper(where fitted)	5446			
Width - excluding mirrors 1867 Height 1821 XLT Leather Accented Seats (Black) S Overhang - Front Overhang - Rear 1226 Track - Front and Rear 1560 Wheelbase 3220 Ground Clearance (unladen, mm) 237 Auxillary 12V Power Outlet - Lower Dashboard S Wading Depth (mm) Approach Angle (unladen, degrees): a) measured to tow bar Ramp Breakover Angle (degrees) 256 Poverhang - Rear 1867 S-way Manual Driver Seat Adjustment (plus Lumbar Support) S XLT Leather Accented Seats (Black) S Comfort and Convenience 230V Inverter - Rear of Centre Console S Acoustic Windshield S Auxillary 12V Power Outlet - Lower Dashboard S Centre Console - Single Lid with 2 Cup Holders S Child Seat Upper Anchorage Points (x 2) S Climate Control - Dual Zone Automatic S Dual Colour 4.2" Instrumentation Screens S Floor Coverings - Carpet S	Width - exterior mirors extended	2163			S
Width - excluding mirrors1867(plus Lumbar Support)3Height1821XLT Leather Accented Seats (Black)SOverhang - Front928Comfort and ConvenienceOverhang - Rear1226230V Inverter - Rear of Centre ConsoleSTrack - Front and Rear1560Acoustic WindshieldSWheelbase3220Auxillary 12V Power Outlet - Lower DashboardSGround Clearance (unladen, mm)237Auxillary 12V Power Outlet - Rear of Centre ConsoleSWading Depth (mm)800Centre Console - Single Lid with 2 Cup HoldersSApproach Angle (unladen, degrees):29Child Seat Upper Anchorage Points (x 2)SDeparture Angle (unladen, degrees):21Climate Control - Dual Zone AutomaticSa) measured to tow barDual Colour 4.2" Instrumentation ScreensSRamp Breakover Angle (degrees)25Floor Coverings - CarpetS	Width - exterior mirrors folded	1977			
Height1821XLT Leather Accented Seats (Black)SOverhang - Front928Comfort and ConvenienceOverhang - Rear1226230V Inverter - Rear of Centre ConsoleSTrack - Front and Rear1560Acoustic WindshieldSWheelbase3220Auxillary 12V Power Outlet - Lower DashboardSGround Clearance (unladen, mm)237Auxillary 12V Power Outlet - Rear of Centre ConsoleSWading Depth (mm)800Centre Console - Single Lid with 2 Cup HoldersSApproach Angle (unladen, degrees):29Child Seat Upper Anchorage Points (x 2)SDeparture Angle (unladen, degrees):21Climate Control - Dual Zone AutomaticSa) measured to tow barDual Colour 4.2" Instrumentation ScreensSRamp Breakover Angle (degrees)25Floor Coverings - CarpetS	Width - excluding mirrors	1867	(plus Lumbar Support)	ment	S
Overhang - Rear 1226 230V Inverter - Rear of Centre Console S Track - Front and Rear 1560 Acoustic Windshield S Wheelbase 3220 Auxillary 12V Power Outlet - Lower Dashboard S Ground Clearance (unladen, mm) 237 Auxillary 12V Power Outlet - Rear of Centre Console S Wading Depth (mm) 800 Centre Console - Single Lid with 2 Cup Holders S Approach Angle (unladen, degrees): 29 Child Seat Upper Anchorage Points (x 2) S Departure Angle (unladen, degrees): 21 Climate Control - Dual Zone Automatic S Ramp Breakover Angle (degrees) 25 Floor Coverings - Carpet S	Height	1821		ck)	S
Track - Front and Rear 1560 Acoustic Windshield S Wheelbase 3220 Auxillary 12V Power Outlet - Lower Dashboard S Ground Clearance (unladen, mm) 237 Auxillary 12V Power Outlet - Rear of Centre Console S Wading Depth (mm) 800 Centre Console - Single Lid with 2 Cup Holders S Approach Angle (unladen, degrees): 29 Child Seat Upper Anchorage Points (x 2) S Departure Angle (unladen, degrees): 21 Climate Control - Dual Zone Automatic S Ramp Breakover Angle (degrees) 25 Floor Coverings - Carpet S	Overhang - Front	928	Comfort and Convenience		
Wheelbase3220Auxillary 12V Power Outlet - Lower DashboardSGround Clearance (unladen, mm)237Auxillary 12V Power Outlet - Rear of Centre ConsoleSWading Depth (mm)800Centre Console - Single Lid with 2 Cup HoldersSApproach Angle (unladen, degrees):29Child Seat Upper Anchorage Points (x 2)SDeparture Angle (unladen, degrees):21Climate Control - Dual Zone AutomaticSa) measured to tow barDual Colour 4.2" Instrumentation ScreensSRamp Breakover Angle (degrees)25Floor Coverings - CarpetS	Overhang - Rear	1226	230V Inverter - Rear of Centre Co	nsole	S
Wheelbase3220Auxillary 12V Power Outlet - Lower DashboardSGround Clearance (unladen, mm)237Auxillary 12V Power Outlet - Rear of Centre ConsoleSWading Depth (mm)800Centre Console - Single Lid with 2 Cup HoldersSApproach Angle (unladen, degrees):29Child Seat Upper Anchorage Points (x 2)SDeparture Angle (unladen, degrees):21Child Seat ISOFIX Anchorage Points (x 2)Sa) measured to tow barClimate Control - Dual Zone AutomaticSRamp Breakover Angle (degrees)25Floor Coverings - CarpetS	Track - Front and Rear	1560	Acoustic Windshield		S
Wading Depth (mm) 800 Centre Console - Single Lid with 2 Cup Holders S Approach Angle (unladen, degrees): Departure Angle (unladen, degrees): a) measured to tow bar Ramp Breakover Angle (degrees) 25 Centre Console - Single Lid with 2 Cup Holders S Child Seat Upper Anchorage Points (x 2) S Climate Control - Dual Zone Automatic S Dual Colour 4.2" Instrumentation Screens S Floor Coverings - Carpet S	Wheelbase	3220	Auxillary 12V Power Outlet - Lowe	er Dashboard	S
Wading Depth (mm)800Centre Console - Single Lid with 2 Cup HoldersSApproach Angle (unladen, degrees):29Child Seat Upper Anchorage Points (x 2)SDeparture Angle (unladen, degrees):21Child Seat ISOFIX Anchorage Points (x 2)Sa) measured to tow barClimate Control - Dual Zone AutomaticSRamp Breakover Angle (degrees)25Floor Coverings - CarpetS	Ground Clearance (unladen, mm)				S
Approach Angle (unladen, degrees): Departure Angle (unladen, degrees): a) measured to tow bar Ramp Breakover Angle (degrees) 29 Child Seat ISOFIX Anchorage Points (x 2) Climate Control - Dual Zone Automatic Dual Colour 4.2" Instrumentation Screens S Floor Coverings - Carpet S			Centre Console - Single Lid with 2	2 Cup Holders	S
Departure Angle (unladen, degrees): a) measured to tow bar Ramp Breakover Angle (degrees) 21 Child Seat ISOFIX Anchorage Points (x 2) Climate Control - Dual Zone Automatic S Dual Colour 4.2" Instrumentation Screens S Floor Coverings - Carpet S			Child Seat Upper Anchorage Poin	ts (x 2)	S
a) measured to tow bar Ramp Breakover Angle (degrees) Climate Control - Dual Zone Automatic Dual Colour 4.2" Instrumentation Screens S Floor Coverings - Carpet S			Child Seat ISOFIX Anchorage Poir	nts (x 2)	
Ramp Breakover Angle (degrees) 25 Floor Coverings - Carpet S					
i tool Coverings - Calpet				Screens	
Turning Circle - Kerb to Kerb (m) 12.7 Floor Mats - Driver Only S					
	Turning Circle - Kerb to Kerb (m)	12.7	Floor Mats - Driver Only		S

Ranger XLT Fully Loaded Specifications (continued) Visit ford.com.au for full details.

Comfort and Convenience (continued)		Safety, Security and Driver Assistance (continued	Safety, Security and Driver Assistance (continued)		
Headlamps - Auto On/Off Function	S	Anti-Lock Braking System (ABS) ^{1.}	S		
Leather Wrapped Steering Wheel & Gear Knob	S	Auto High Beam ^{1.}	S		
Power Front Windows (Auto Driver)	S	Beltminder™ - All Positions	S		
Power Rear Windows	S	Cruise Control	S		
Rain Sensing Windscreen Wipers	S	Driver Impairment Monitor ^{1.}	S		
Rear Window Defrost	S	Dynamic Stability Control (DSC) ^{1.}	S		
Rear View Mirror - Electrochromatic	S	Emergency Assistance ^{11.}	S		
WindScreen Mounted USB Port	S	Emergency Brake Assist	S		
Audio And Communication		Emergency Brake Light	S		
FordPass Connect - Embedded Modem ^{3.}	S	Hill Descent Control ^{1.}	S		
8" Colour Touch Screen	S	Hill Launch Assist ^{1.}	S		
6 Speakers (2 Tweeters, 4 Woofers)	S	Lane Keeping Aid ^{1.}	S		
AM/FM Stereo Radio	S	Load Adaptive Control ^{1.}	S		
Apple CarPlay & Android Auto ^{8.}	S	MyKey®	S		
Bluetooth® with Phone/Audio Streaming ^{9.}	S	Parking Sensors - Front	S		
CD Player (MP3 compatible)	S	Parking Sensors - Rear	S		
DAB+ Digital Radio	S	Pre-Collision Assist - AEB with Pedestrian	S		
Satellite Navigation with Traffic Message Channel ^{10.}	S	Detection ^{1.} Rear Differential - eLocking	S		
SYNC®3 with Voice-Activated Controls ^{4.}	S	Rear View Camera	S		
USB Ports x 2	S	Roll Over Mitigation ^{1.}	S		
Safety, Security and Driver Assistance		Semi-Auto Active Park Assist ^{1.}	S		
3 Point Lap Sash Seat Belt - All Positions	S	Smart Keyless Entry with Push Button Start -	S		
Adaptive Cruise Control ^{1.}	S	2 Fobs Provided			
Adjustable Speed Limiter	S	 Traction Control System^{1.} Traffic Sign Recognition^{1.} 	S S		
Airbags - Driver and Front Passenger	S	Trailer Sway Control ^{1.}	S		
Airbags - Front Seat Side	S	Tyre Pressure Monitoring System	S		
Airbags - Side Curtain (Full Length)	S	Regular Production Options			
Alarm with Perimeter, Interior Motion &		Tough Bed Spray-In Bedliner	0		
Vehicle Inclination Sensors	S	Prestige Paint	0		

S = Standard O = Factory Option that can be ordered before a vehicle is manufactured P = Part of a Pack A - Accessory fitted at Ford Dealer

1. Driver-assist features are supplemental and do not replace the driver's attention, judgment and need to control the vehicle. May not operate in some driving and road conditions (including at certain speeds) or adverse weather.

2. Maximum braked towing capacity when fitted with a genuine Ford Tow Pack. Subject to 5state and Territory regulations. Further weight restrictions apply, please consult your authorised Ford Dealer and/or refer to the Owner's Manual for guidance.

3. Use of FordPass is subject to the FordPass Terms and Privacy Policy available on ford.com.au/fordpass and requires a compatible mobile device, internet access, and software (including software updates from time to time). You are responsible for internet access, mobile network data and voice call services required for your use of the FordPass App on your mobile device, including associated fees. The FordPass Connect Modemand FordPass App can only work when connected to the telecommunications network or of your mobile device.

4. SYNC®3 features may not be compatible with all phones. For compatibility, see ford.com.au/sync.

5. Fuel consumption and emissions as per ADR BI/O2 (combined cycle) and to be used for vehicle comparison purposes only. It is unlikely that these fuel consumption and emissions figures will be achieved in real world driving conditions.

4. Actual fuel consumption and emissions will depend on many factors including the driver's habits, prevailing conditions and the vehicle's equipment, condition and use.

5. Breat Consumption and emissions will depend on many factors including the driver's habits, prevailing conditions and the vehicle's equipment, condition and use.

5. Breat Consumption and emissions will depend on many factors including the driver's habits, prevailing conditions and the vehicle's equipment, condition and use.

6. Breat Weight includes the vehicle with a full tank of fuel, without occupants, luggage or cargo and with all standard equipment. Additional weight of optional features must be taken into ac