



**TRUST A TRITON  
TO LOOK THIS GOOD.**

**NEW TRITON GLX-R 4x4 WITH SPORTY FEATURES:**

- NUDGE BAR • REAR SPORTS BAR • 16" ALLOYS • SIDE STEPS • SPORTS GRILLE
- TONNEAU COVER • POWER WINDOWS • DUAL AIRBAGS • ABS • 'EASY SELECT' 2WD-4WD

With features like this, the new Triton GLX-R 4x4 is the best looking Triton to ever hit the streets. Backed with Mitsubishi's 5\* 10<sup>+</sup> year warranty, you can always trust a Triton to get the job done.



**MITSUBISHI  
MOTORS**  
engineered to excite

# Triton GLX-R

ENGINE			
<b>PETROL</b>			
Type	3.0 litre V6 SOHC 24 valve		
Bore x stroke	91.1mm x 76mm		
Capacity	2972cc		
Compression ratio	9.0:1		
Fuel system	ECI multi fuel inject		
Maximum Power	133kW @ 5250rpm		
Maximum Torque	255Nm @ 4500rpm		
<b>DIESEL</b>			
Type	2.8 litre 4 cyl SOHC Diesel with Intercooled Turbocharger		
Bore x stroke	95mm x 100mm		
Capacity	2835cc		
Compression ratio	21.0:1		
Fuel system	Fuel injection		
Maximum Power	92kW @ 4000rpm		
Maximum Torque	294Nm @ 2000rpm		
<b>ELECTRICAL SYSTEM</b>			
	<b>3.0L V6 Petrol</b>	<b>2.8L Turbo Diesel</b>	
Battery	12V-52 AH	12V-64 AH	
Alternator	12V-85A	12V-90A	
<b>TRANSMISSION</b>			
	5 speed manual transmission		
	4 speed automatic transmission (petrol only)		
	<b>3.0L V6 Petrol Manual</b>	<b>2.8L Turbo Diesel Manual</b>	
<b>RATIOS</b>			
First	3.918	2.842	3.952
Second	2.261	1.495	2.238
Third	1.395	1.000	1.398
Fourth	1.000	0.731	1.000
Fifth	0.829	-	0.760
Reverse	3.952	2.720	3.553
<b>TRANSFER RATIO</b>			
High	1.000	1.000	1.000
Low	1.925	1.900	1.900
<b>FINAL DRIVE</b>			
Final Gear Ratio	4.900	4.900	4.900
<b>CLUTCH</b>			
Manual	Single dry plate with diaphragm spring		
Automatic	3 element torque converter with lock-up		
<b>DRIVE TRANSFER-SYSTEM</b>			
Type	'Easy Select' Part Time 4WD Auto front free-wheel differential with synchromesh		
<b>BRAKES</b>			
Anti-lock Braking System (ABS) with Electronic Brakeforce Distribution (EBD)			
Front	Ventilated discs, twin-piston calipers		
Rear	Drums, leading and trailing shoes		
<b>SUSPENSION</b>			
Front	Independent - Wishbone, torsion bar		
Rear	Rigid - elliptic leaf spring		

STEERING			
Type	Power assisted re-circulating ball and nut		
<b>WHEELS</b>			
	16" x 7" alloy - 6 spoke		
<b>TYRES*</b>			
	265/70R-16 112S		
* The tyres fitted to Triton as standard equipment are designed primarily for use on sealed roads. If your Triton is to be driven mainly on unsealed roads, please consult your Mitsubishi dealer for advice on appropriate tyre selection.			
<b>GROUND CLEARANCE</b>			
	<b>3.0L V6 Petrol (unladen)</b>	<b>2.8L Turbo Diesel (unladen)</b>	
Ground clearance	235mm	235mm	
Fording depth	500mm	500mm	
Approach angle	30.7°	30.7°	
Ramp breakover angle	21.7°	21.7°	
Departure angle	28.3°	28.3°	
<b>CAPACITIES</b>			
	<b>3.0L V6 Petrol Manual</b>	<b>Auto</b>	<b>2.8L Turbo Diesel Manual</b>
Gross vehicle mass (kg)	2705	2715	2830
Kerb mass (kg)	1739	1744	1739
Payload** (kg)	966	971	1091
Gross combination mass (kg)	4205	4915	5030
Maximum Front Axle Load (kg)	1200	1200	1200
Maximum Rear Axle Load (kg)	1650	1650	1650
Seating Capacity			
	Front	2	
	2 <sup>nd</sup> Row	3	
	Total	5	
** Payload includes occupants, fuel and fitted options (if any). The weight of these must be deducted from Payload to determine actual load carrying capacity. Front and / or Rear Axle Loads must not be exceeded.			
<b>FUEL CONSUMPTION</b>			
	<b>3.0L V6 Petrol Manual</b>	<b>Auto</b>	<b>2.8L Turbo Diesel Manual</b>
Combined <sup>^</sup> (ADR81/01) (Litres per 100km)	12.5	12.8	10.5
<sup>^</sup> These figures are obtained from controlled laboratory tests conducted by Mitsubishi Motors to Australian Standard ADR81/01 and are provided to assist you in comparing the fuel consumption of Triton with other vehicles. The actual fuel consumption you achieve will depend, however, on many factors, including your driving habits, the prevailing conditions and your vehicles equipment, condition and use.			
<b>MECHANICAL</b>			
Power steering	Standard		
Engine immobiliser (Petrol only)	Standard		
Auto free wheeling hubs	Standard		
Limited slip differential (rear)	Standard		
Hand throttle (diesel only)	Standard		
<b>PAINT COMBINATIONS</b>			
	White		
	Black Mica*		
	Gunmetal*		
	Cool Silver*		
* Metallic and pearlescent paints are optional extra.			



Mitsubishi Motors Australia Ltd. offers a 5 year/130,000km\* (whichever comes first) New Vehicle Warranty, a 10 year/160,000km\* (whichever comes first) Powertrain Warranty<sup>1</sup> (non transferable) and a 5 year Perforation Corrosion Warranty on Mitsubishi Triton. Always consult your authorised Mitsubishi Dealer for the latest details on specifications, options, prices, availability and conditions on New Vehicle Warranty. All product illustrations and specifications referred to herein are correct at the time of publication approval. Subject to any applicable Federal, State or Territory Laws or ordinances, which may apply from time to time, Mitsubishi Motors Australia Ltd. reserves the right, without notice, or obligation, to discontinue or make changes to designs, specifications, colours and materials of the options and products referred to herein at any time without incurring any liability to any purchaser thereof. Tonneau cover does not provide total protection from external conditions such as water and dust. Goods able to be damaged by water and dust should be protected by appropriate means before carriage. ©Mitsubishi Motors Australia Limited. ABN 53 007 870 395. TRIGLXR0504F

