
A New Direction HD45

Dimensions



| | Standard Cab-Short | Standard Cab-Medium | Super Cab-Medium |
|----------------------------------|--------------------|---------------------|------------------|
| DIMENSIONS (mm) | | | |
| Wheel Base | 2,820 | 3,415 | 3,610 |
| Overall length | 5,300 | 6,170 | 6,380 |
| Overall width | 2,010 | 2,010 | 2,010 |
| Overall height | 2,250 | 2,250 | 2,250 |
| Front overhang | 1,120 | 1,120 | 1,120 |
| Rear overhang | 1,360 | 1,635 | 1,650 |
| Front track | 1,680 | 1,680 | 1,680 |
| Rear track | 1,495 | 1,495 | 1,495 |
| Rear frame width | 753 | 753 | 753 |
| Chassis height at rear axle | 750 | 750 | 750 |
| CA | 2,125 | 2,720 | 2,690 |
| CE | 3,415 | 4,295 | 4,265 |
| WEIGHTS (kg) | | | |
| GVM | 4,500 | 4,500 | 4,500 |
| GCM | 8,000 | 8,000 | 8,000 |
| Front loading limit | 2,600 | 2,600 | 2,600 |
| Rear loading limit | 4,400 | 4,400 | 4,400 |
| Total cab chassis mass | 2,305 | 2,430 | 2,475 |
| Front cab chassis mass | 1,585 | 1,640 | 1,665 |
| Rear cab chassis mass | 720 | 790 | 810 |
| PERFORMANCE (CALCULATION) | ΓED) | | |
| Speed at max. engine speed | 121KPH | 121KPH | 121KPH |
| Gradeability at rated GVM | 50.7% | 50.7% | 50.7% |
| Gradeability at rated GCM | 28.1% | 28.1% | 28.1% |
| Turning circle (Kerb to Kerb, m) | 10.2 | 12.4 | 13.0 |

WARRANTY

3 YEARS / 200,000 KM : Standard Vehicle Warranty* * For exceptions & exclusions, refer to the Hyundai service passport.

Truck Assist

National Truck Roadside Assistance for 3 years / 200,000 km



Hyundai Motor Company Australia Pty Ltd Corner of 394 Lane Cove Road & Hyundai Drive, Macquarie Park NSW 2113 T. 02 8873 6005

Hyundai Motor Company (HMC) and the Hyundai Motor Company Australia (HMCA) each reserve the right to alter vehicle specifications and equipment levels without notice. Some equipment featured on the vehicles in this spec sheet may not be available in Australia or may be optional. To the extent permitted by the law, neither HMC nor HMCA shall be liable to any person as result of reliance on the content of this spec sheet. Please consult your Hyundai dealer for the latest specifications, equipment levels, options, prices and vehicle availability.

Note: Information in this spec sheet is current as at 16/6/2010. Part No. HCV0901HD45





Photo of HD45 Super Cab

KEY FEATURES

- > Driver's suspension seat with lumbar support
- > Remote keyless entry
- > Computerised battery saver
- > ABS brake with EBD (Electronic Brakeforce Distribution)
- > Fog Lamps
- > Optional super cab

AT A GLANCE

GVM 4,500kg **GCM** 8,000kg

Wheelbase 2,820mm / 3,415mm / 3,610mm

Engine 3.9L, Electronic common rail, 16 Valve SOHC

ADR 80/02 (Euro 4) Compliant

 Max. power
 103kw / 2,700rpm

 Max. torque
 372Nm / 1,400rpm



HD45 A New Direction

Driveline & Chassis Specifications

ENGINE (HYUNDAI F140)

3.9L, Electronic common rail, Engine


16 Valve SOHC

ADR 80/02 (Euro 4) Compliant

Displacement Compression ratio 17.0 Bore x Stroke 103 x 118 103kw / 2,700rpm Max. power

372Nm / 1,400rpm Max. torque WGT, air-to-air intercooler Turbocharger Injection system Common rail system

Emission Control System Cooled EGR, PMC



CLUTCH

Type Auto adjusting hydraulic

control with vacuum assistance Disc diameter

Facing lining area 847cm²

TRANSMISSION (M035S5)

| Type | 5 Speed Manual, | | |
|------------|---------------------------|-------|--|
| | Synchromesh on gear 1 ~ 5 | | |
| Gear ratio | 1st | 5.380 | |
| | 2nd | 3.028 | |
| | 3rd | 1.70 | |
| | 4th | 1.00 | |
| | 5th | 0.722 | |
| | Reverse | 5.380 | |

PTO Opening PTO provision on LHS of transmission case

AXLES

Front axle Reversed Elliot I-beam Capacity 2,600 kg

Full floating type Rear axle Capacity 4,400 kg Final drive ratio 4.625:1

PROPELLER SHAFT

Type Tubular, Forged steel ends

BRAKES

Service brake Auto adjusting front drum and rear drum

brakes with dual circuit hydraulic control.

vacuum assistance

ABS/ASR ABS and ASR traction control with electronic brake force distribution(EBD)

Exhaust brake Vacuum controlled exhaust brake Parking brake 190mm diameter drum park brake mounted on rear of transmission

304mm

Front disc diameter Rear drum diameter 320mm

STEERING

Type Power assisted ball & nut type gear Tilt & Telescopic Steering Column

Maximum angle: inside wheel: 44.3° Maximum angle: outside wheel: 33.5°

SUSPENSION

Front Suspension

Multi-leaf spring Type Size x leaves 1.200 x 70 x 11t-1.10t-4

Shock absorber Double acting hydraulic shock absorber Stabiliser bar Equipped (diameter: 30mm)

Rear Suspension

Type

Multi-Leaf main spring, multi-leaf

helper spring

Size(main/Auxiliary) Main: 1,250 x 70 x10t-6 Helper: 990 x 70 x 13t-3

Shock absorber Double acting hydraulic shock absorber Stabiliser bar Equipped (diameter: 25mm)

WHEELS AND TYRES

Wheel type 5.25 x 17.5, five stud Rim size 205/75R17.5-10PR, Tubeless Tyre size Steer 1450kg X 2 Tyre rating Drive 1400kg X 4

FUEL TANK

Frame mounted steel fuel tank Type

lockable fuel cap

100 L Fuel capacity

CHASSIS FRAME

Cold riveted ladder type high-tensile frame Type Side rail (mm) 193 x 60 x 6.0

ELECTRICAL

24V electrical system Type Batteries Maintenance-free Batteries

2 x CMF90H(720CCA) batteries connected

Battery Auto/Off Device - turns off activated Battery saver power sources when the vehicle is not in use.

Alternator 55 ampere

5.5kW starter motor Starter capacity

Cab Equipment



*Optional Super Cab

CAB EXTERIOR

Design Slant windscreen by 32 degree to reduce aerodynamic drag

Liquid filled rubber type front and rear Cab mounting

> cab mounts Tinted & Laminated windshield with

Windscreen upper partial shade band

Solar type of side glass to reduce heat Side glass

and UV rays

Built-in washer nozzle type of dual wipers, Windscreen wipers intermittent and two speed mode

Electrically heated exterior main mirrors Rear vision mirror Multi focus reflector type headlamps Head lamps

with turn signals Fog lamps Built-in type fog lamps Side Reflector and turn signals on doors

Reverse alarm Built-in type reverse alarm 12V power outlet 3 A Nominal, 5 A Peak load

CAB INTERIOR

Steering wheel

Driver's Seat

wheel column, power assisted steering with urethane steering wheel for soft grip Contoured adjustable driver's bucket seat with coil suspension and lumbar support 2 seats capacity, foldable centre seat

with seat back storage & cup holders

Tilt & telescopic adjustable steering

Passenger's Seats

Seat covering Seat headrest

Height adjustable headrest Seatbelts 3 point type ELR seat belts for driver's

and Passenger's seat, 2-point centre seat lap belt

Overhead console Driver and Passenger overhead storage

shelf with safety net

Door and side pillar entry assist grips Interior finish Fully finished interior trim, padded roof

lining and PVC floor mat

High quality fabric cover

Driver and Passenger sun visors Sun visors Electric power windows Windows Remote keyless entry and Keyless entry

Interior lamp Air Conditioning

Interior lamp with on/door/off switch **Inside rearview mirror** Day and night type rearview mirror Fully integrated air conditioning with

central door locking

Door map Audio Lighter

heater and defrost Door mounted storage pockets CD / MP3 / Audio & Radio 24V cigarette lighter











