



BIG REPUTATION

Rodeo's rock solid heritage has been carved from decades of serious hard work. For over 20 years, Holden Rodeo has been delivering the goods. And the knowledge we've gained from creating light commercial vehicles for some of the world's most demanding jobs can be seen in every Rodeo we build.





V6 Engine:

This class leading all-alloy 3.5 litre V6 cranks out an impressive 147kW of power and 280Nm of torque.



Remote Key:

Standard on LX and LT models, this handy feature allows you easy access. The door lock is activated by a strengthened cable for improved security.



Limited Slip Diff:

The Limited Slip Diff provides greater traction on slippery roads, tracks and building sites. (Available on all LX V6 and 4x4 models.)




Rear Space in Space Cab:


New Rodeo provides extra storage room behind the seats in the Space Cab models. (LT model shown featuring rear jump seats.)



V6 PETROL ENGINE RANGE:



LX 4x2 Single Cab Chassis Manual, 8DH02-225 C Manual, 8DH02-225 E[#] Auto. 8DH02-224 C




LX 4x2 Space Cab Chassis Manual, 8DH85-225 C Manual, 8DH85-225 E#



LX 4x4 Single Cab Chassis Manual. 8DR02-225 C




LX 4x4 Crew Cab Chassis Manual, 8DR63-225 C



LX 4x2 Single Pickup Manual, 8DH80-225 C



LX 4x2 Space Pickup Manual, 8DH04-225 C Manual, 8DH04-225 E[#] Auto, 8DH04-224 C Auto, 8DH04-224 E[#]




LX 4x2 Crew Pickup, Manual, 8DH62-225 C Manual, 8DH62-225 E[#] Auto, 8DH62-224 C Auto, 8DH62-224 E[#]




LT 4x2 Crew Pickup, Manual, 8DL62-325 F#



LX 4x4 Space Pickup Manual, 8DR04-225 C



LT 4x4 Space Pickup Manual, 8DS04-325 F#



LX 4x4 Crew Pickup Manual, 8DR62-225 C Manual, 8DR62-225 E# Auto, 8DR62-224 C Auto, 8DR62-224 E#



LT 4x4 Crew Pickup Manual, 8DS62-325 F# Auto, 8DS62-324 F#





3.0 litre Intercooled Turbo Diesel Engine:

Powerful 96kW @ 3,800rpm, with torque of 280Nm @ 2,400rpm for the manual and 294Nm @ 2,400rpm for the automatic.



Over Fender Flares:

These flare guards ensure your Rodeo looks as tough as it truly is!



'Shift-on-the-Fly' Button:


This button eliminates the need for locking the front hubs when switching from two wheel to four wheel drive. You can do it, while driving, from the comfort of the driver's seat.

High Ride Suspension:

Offers greater ground clearance and improved road visibility.



3.0 LITRE INTERCOOLED TURBO DIESEL ENGINE RANGE:




LX 4x2 Single Cab Chassis Manual, 8DH02-265 C



DX 4x4 Single Cab Chassis Manual, 8DQ02-165 C




LX 4x4 Single Cab Chassis Manual, 8DR02-265 C Manual, 8DR02-265 E#



LX 4x4 Space Cab Chassis Manual, 8DR85-265 C



LX 4x4 Crew Cab Chassis Manual, 8DR63-265 C



LX 4x2 Crew Pickup Manual. 8DH62-265 B



LX 4x4 Space Pickup Manual, 8DR04-265 C



LT 4x4 Space Pickup Manual, 8DS04-365 F#



LX 4x4 Crew PickupManual, 8DR62-265 C
Manual, 8DR62-265 E[#]
Auto, 8DR62-264 C
Auto, 8DR62-264 E[#]



LT 4x4 Crew Pickup Manual, 8DS62-365 F# Auto, 8DS62-364 F#



2.4 litre Petrol Engine:

The new Single Overhead Cam 2.4 litre engine offers fuel efficiency while still providing 94kW of power and 207Nm of torque.



Coil Springs:

This suspension system offers significantly better handling and passenger car-like ride, while still maintaining a great load capacity.



Manual Transmission:

The new Rodeo comes with a five speed manual transmission.

The overdrive gives you a quieter ride at high speeds.




Vinyl Floor and Seats:


The floors of the new Rodeo are easy to clean, just get out the hose.



2.4 LITRE PETROL ENGINE RANGE:



DX 4x2 Single Cab Chassis Manual, 8DK02-115 A (non Power Steering & no radio) Manual, 8DK02-115 B



DX 4x2 Crew Pickup Manual, 8DK62-115 B



Front Seating:

New Rodeo has bigger seats and a longer seat slide, which means more room and more comfort.



Storage Pocket:

New Space and Crew Cab Rodeo has more storage pockets than ever before. So you can stow just about anything.



Adjustable Steering Wheel:

Different drivers prefer different wheel positions. Find the one that's right for you on your new LX or LT Rodeo.



Wider Opening Rear Door:

An increased opening for easy access.





Air Bags:

Safety protection for the front passenger and driver in severe frontal collisions.



Alloy Wheels: 16" alloy wheels offering

sports styling.



Electric Windows:

With power windows, an open window is just a button away.




6 Stack CD:

With room for your favourite 6 CD's, this stacker is ideal for long distance driving and switching between your favourites.




LT RANGE:



LT 4x2 Crew Pickup Manual, 3.5 litre V6, 8DL62-325 F Auto, 3.5 litre V6, 8DL62-324 F



LT 4x4 Space Pickup Manual, 3.5 litre V6, 8DS04-325 F Manual, 3.0 litre Diesel, 8DS04-365 F



LT 4x4 Crew Pickup Manual, 3.5 litre V6, 8DS62-325 F Auto, 3.5 litre V6, 8DS62-324 F Manual, 3.0 litre Diesel, 8DS62-365 F Auto, 3.0 litre Diesel, 8DS62-364 F

BIG ON SAFETY

TOUGHER CHASSIS.

The new Rodeo is big on size and strength, thanks largely to the new chassis. The middle section of the frame has been significantly increased in sectional areas, increasing resistance to bend by as much as 60% in longitudinal direction and 50% in traverse direction. The new chassis also means a longer wheel base in all cab chassis models, which maximises payload length and makes for a more comfortable ride. The unique Rear Cross Member is designed to increase the torsional rigidity of the chassis, more evenly spreading the forces placed upon the rear of the chassis by the weight of the load.

COIL SPRINGS.

The 2.4 litre Petrol Rodeo may be the most comfortable workhorse in its class. Coil springs, while still providing great load carrying capacity, significantly improve ride and handling.

NOISE VIBRATION HARSHNESS REDUCTION.

Vehicle noise has been reduced through increases in chassis rigidity and large one-piece side panels. Wind noise has been reduced. Engine mounts have been modified. Seals have been improved. And noise-dampening materials have been placed in the floor wells. Electrical looming is secured. And dampeners have been placed behind panels to minimise vibration.

GALVANIZED INTO ACTION.

Floor panels, and other areas subject to rust, have been treated with a highly resistant double-sided galvanization. Undercoating and wax injection also add to the process. This not only reduces the risk of corrosion, it increases the durability of the new Rodeo and helps reduce vehicle noise.

STRONGER TUBS.

Tub strength and durability has been improved thanks to a three-piece construction method. The rear tailgate sports a practical three-piece hinge, and steel rods have replaced the tailgate cables, which means the tailgate is even more robust than before.

RACK AND PINION STEERING.

All new Rodeos have rack and pinion steering. The good news? It's easier to steer. It's more comfortable. It provides more precise handling, so it's easier for you to get the truck to go where you want it to go. The bad news? You'll have to go back to the gym if you want to keep your chiselled biceps.

Workplace safety is a big issue. And big issues need a big truck.

3 POINT SEAT BELTS.

Every 5 seat Rodeo has three point seat belts in all positions, all bar the centre seat of course, have a height adjustable shoulder anchorage point.

AIRBAGS.

Driver and passenger airbags designed to deploy in severe frontal collisions are standard on the LT. and optional on other selected models.

LET'S TALK BRAKES.

ABS is standard on the LT. These brakes come with a new Electronic Brake Distribution system designed for the sort of control you'd find on a luxury sedan. And braking force has been further increased with 2 pot pistons, to increase the frictional area on the pads, on the front brake callipers.

LESS EFFORT.

Brake pedal effort is reduced through a tandem brake master vacuum and a vacuum tank has been introduced to ensure reliable braking when the brakes have to be applied repeatedly.

SOMETIMES, IT'S GOOD TO BEND.

New Rodeo has a new close-section collapsible body structure and a newly designed chassis to absorb impact in the cabin, improving crash protection in front and rear collisions.

SIDE INTRUSION BARS.


This extra reinforcement has been added specifically to provide greater protection in side collisions.

SEE THE LIGHT.

The high, rear centre-mounted stoplight makes you more visible when braking.




Tougher chassis.



Coil springs.



Stronger tubs.





Rack and pinion steering.




Height adjustable anchorage point.

Airbags.

Anti-Lock braking system.

Reduced pedal effort.





BIG ON PERSONALITY

Make your new Rodeo as individual as you are.
With these enhancements and factory fitted extras available on selected models (refer to the feature details at the rear of this brochure).
Each carrying Holden's comprehensive
New Vehicle Warranty. All designed to meet your individual needs.





Nudge bar. Carpet floor mats. Rubber floor mats. Bonnet protector. Soft tonneau. Insect screen.












BIG ON CAPACITY

CALCULATE YOUR LOAD AND DRIVE SAFER ON THE ROADS.


Safe operation of a light commercial vehicle demands careful attention to two vital aspects of loading: balance and safe operating limits. You should read this section carefully, as the concepts explained here could have a significant impact on your choice of model. **Remember:**

A vehicle that is loaded to excess, or carrying a load that's unbalanced, is going to experience reduced life through excess loads being placed on the frame, transmission, axles, hubs and tyres.



Space Cab Pickup

Single Cab Pickup



Crew Cab Pickup

Cab Chassis recommended body lengths.

When fitting a custom built body, we recommend you follow the length figures shown in the specification details at the rear of this brochure.

It is important to ensure that your rear axle capacity is not exceeded. Excessive overhang can affect vehicle balance and road holding. On 4x4 models, excess overhang will also affect departure angles.

When fitting a body or tray to a Cab Chassis model, refer

to your Holden Sales Consultant to ensure the proposed rear tray fitment is compliant with vehicle and transport regulations in your state.

It is important your new Holden Rodeo is correctly specified for its intended application. Inappropriate modifications to the standard vehicle specification may affect vehicle performance and safety through overloading of the vehicle. Such modifications may also affect your New Vehicle Warranty to the extent that Holden considers that it affects the specifications and quality of your vehicle. Please refer to your Holden Sales Consultant.

Front & Rear Axle Loads.

The maximum allowable front axle load for all Rodeo 2WD vehicles is 1200kg and for 4WD 1300kg. The maximum allowable rear axle load for both types is 1680kg.

This ensures that your Rodeo's axles have sufficient strength to carry the total weight of body and mechanicals, plus cargo and passengers, and still retain a considerable capacity safety margin to cope with weight transfer as the vehicle brakes, accelerates, rolls in corners and goes over bumps.

Carrying Capacity and Payload.

It is important that you understand the difference between Carrying Capacity and Payload.

'Carrying Capacity' is the maximum capacity of the vehicle for the carriage of all non-standard items including cargo carrying devices (ie tray or body), the cargo itself, occupants, optional equipment and accessories. Light commercial vehicles, depending on their body style, all have different carrying capacities. Carrying Capacity can be calculated by subtracting the figure for the vehicle's Kerb Mass from the vehicle's Gross Vehicle Mass (see the next two sections).

'Payload' is the mass of cargo that the finished vehicle is permitted to carry having regard to the aggregate mass of the vehicle's Kerb Mass, optional equipment, accessories, cargo carrying device and occupants. It is important that you calculate the intended 'Payload' accurately, and this section will assist you to understand how to do so.

GVM (Gross Vehicle Mass).

GVM is the accepted safe, maximum all-up weight rating of a fully loaded vehicle and is based on design factors and strength of the frame, spring fitment, tyre rates and axle capacities. (Refer to specifications for GVM.)

Kerb Mass.

'Kerb Mass' is the mass of the vehicle in running order, unoccupied and unladen with all fluid reservoirs filled to nominal capacity including fuel, and with all standard equipment. (Refer to specifications for Kerb Mass.)

Calculating Payload.

To calculate the maximum 'Payload', you simply subtract from the GVM, the Kerb Mass, the weight of the occupants, plus the weight of any fitted options (air conditioning, tow bar and tongue, bull bar etc.), and in the case of Cab Chassis models, the weight of the fitted tray. It is important to note that the combined weight of all additional items needs to be added to the published 'Kerb Mass' weight before being deducted form the vehicle's GVM to arrive at the final maximum 'Payload'. So before choosing your Rodeo model, first think seriously about the weight of your likely load. Ask your Sales Consultant to explain in detail how to complete the following calculation to ensure the selected vehicle is capable of performing the proposed work.

Payload Calculations.

RODEO MODEL:

= Carrying Capacity:	k
Kerb Mass:	k
less	
GVM:	k

Less weights for the following items

(if applicable)

applicable)	
ccupants:	kg
ull tank of fuel:	kg
ir conditioning:	kg
ow bar and tongue:	kg
ullbar:	kg
argo liner:	kg
tted body / tray:	kg
ther:	kg
ther:	kg
Total of Extras:	kg
arrying Capacity:	kg
ess	
otal of Extras:	kg
Payload: [*]	kg

*This figure is the maximum permissible load your Holden Rodeo can carry without exceeding its GVM rating. You also need to ensure that your load is balanced and is within the front and rear axle capacities.

BIG ON CHOICE

BIG ON SERVICE









The new Rodeo gives you a huge range of colours to choose from.













Light Quartz



Chamonix

	DX	LX	LT
Alpine	•	•	•
Sandalwood*		•	•
Glacier*	•	•	
Chamonix*		•	
Astral*	•	•	
Foxfire*		•	•
Light Quartz*			•

SMARTCHOICES. A smart way to get into a new Holden is by talking to Holden Financial Services. A wide range of finance options is on offer and you can select the product, term and payment structure to best suit your lifestyle. The SmartChoices range offers you flexibility to select from a choice of monthly repayments¹ and the option of the security of a guaranteed minimum buy back price.2 For more information contact your Holden Retailer or call Holden Customer Assistance on 1800 033 349. SMARTCARE. Holden offers a range of competitively priced insurance products that provide tailor-made protection. The SmartCare comprehensive motor vehicle policy offers new car replacement, agreed value and a genuine Holden Approved parts guarantee plus a range of additional premium benefits.3 For more information see your local Holden Retailer or call the Holden SmartCare hotline on 1800 060 094. **HOLDEN LEASING.** Holden Leasing is a vehicle fleet leasing specialist, offering a wide range of leasing and management products and services. Whatever your fleet size, Holden Leasing can provide the best in flexible, value driven and specialist fleet leasing products and services to

suit your needs. Our Holden focus means we can provide the very best fleet leasing and management solutions for any business running, or wanting to run, a predominantly Holden fleet. For more

information about your leasing options, please call Holden Leasing on 03 9696 7400. THE HOLDEN MASTERCARD. With the Holden

MasterCard, 5% of every dollar you spend on credit purchases goes toward your rebate on a new Holden.4 You can redeem a maximum core rebate of \$3000 on any new Holden.⁴ Use your Holden MasterCard at exclusive Holden MasterCard Bonus Partners and you'll receive an extra 1% bonus rebate. Holden Retailers are Bonus Partners. When you make a Holden MasterCard purchase at a Holden Retailer you'll earn a 2% bonus rebate.5 You'll also pay no annual card fee in the first year, get up to 45 days interest free on credit card purchases, and a competitive rate of interest.⁶ To apply, visit any Westpac/Challenge Bank/Bank of Melbourne branch, your local Holden Retailer or call the Holden MasterCard 24-hour customer line on 1300 650 696.

THE PACKAGE WOULDN'T BE COMPLETE WITHOUT EXTRA PEACE OF MIND.

WE'RE WITH YOU ALL THE WAY. Holden drivers are backed by one of the most comprehensive customer care packages on the road. With over 300 retailers and 900 Roadside Assistance centres nationwide, few other cars in Australia are supported with the level of customer care offered to Holden owners.

3 YEAR OR 100,000KM NEW VEHICLE

WARRANTY. Your peace of mind, guaranteed. Every Holden comes with a 3 year or 100,000km New Vehicle Warranty. Whichever comes first. This factory backed warranty covers items including the engine, transmission, interior and exterior components. A Holden Extended Warranty is able to be purchased. For more details contact Holden Customer Assistance on 1800 033 349 or your Holden Retailer. 3 YEAR/24 HOUR ROADSIDE ASSISTANCE. Go

If you want to know more about the extensive benefits of Holden ownership, contact anywhere, anytime, with complete confidence. Holden Customer Assistance on 1800 033 349, Holden Roadside Assistance, one of Australia's Monday - Friday, 8am - 7pm, Saturday 9am - 1pm most comprehensive assistance packages, EST. or visit www.holden.com.au

the latest technology.

is complimentary for 3 years.8 In the event

and accident advice, you can get in touch

your keys being locked in the car to mechanical

with our 24 hour hotline, 365 days of the year,

by calling the toll-free number 1800 817 100.

and the combined resources of the Australian

A DECIDEDLY DIFFERENT LEVEL OF SERVICE.

located nationwide, the Holden Service Network

technicians who have access to regular factory

Retailer support when you need it, where

you need it. With retailers strategically

Our service centres are staffed by trained

training, bringing them up to speed on

is one of the largest in the country.

This service is delivered by Assist Australia

motoring organisations.

of the unexpected happening, from

1. Fees and charges apply. For the annual percentage rate applicable to you contact your local Holden Retailer. 2. Conditions apply. A disposal fee of \$385 (inc'l GST) applies plus charges for excess wear and tear or excess kilometres may also apply. 3. Refer to the policy wording for specific terms, conditions and exclusions. 4. Earning and redemption of rebate is subject to the Holden MasterCard Rebate Program Rules. A maximum of \$3000 in the form of Holden MasterCard 'core' rebate (plus any additional 'bonus' rebate accumulated via the partner program) accrued over a maximum of 5 years may be applied per eligible vehicle purchased. Vehicle sales for which a fleet allowance is paid are not eligible for Holden MasterCard rebate. 5. At participating Retailers only, Credit card purchases of new or used vehicles are not eligible for the 2% Bonus Rebate at Holden Retailers, 6. The interest-free period applies where the card account is fully paid by the due date each month. 7. Refer to your owner's handbook or see your Holden Retailer for full terms, conditions and exclusions. 8. In remote or sparsely populated areas you may experience delays in obtaining Roadside Assistance. Refer to your Holden Roadside Assistance booklet or see your Holden Retailer for terms and conditions.

Variations between the colours shown and actual paint colours may occur due to the printing process. Actual vehicle colours may appear different under certain light conditions. *Metallic or Mica paints are available at an additional cost.

BIG ON SPECIFICATIONS

Engine	2.4 Litre SOHC Petrol	3.5 Litre	V6 Petrol	3.0 Litre Tur	bo Diesel
Code	C24SE	6V	E1	4JH1	TC
DESCRIPTION	4-cylinder,		inder,	4 cylir	
	SOHC multi-point fuel injection.		e, DOHC,	Intercooled tu	
	2 valves per cylinder.	electronic fo	uel injection.	electronic fue	el injection.
BORE X STROKE (mm)	87.5 x 100	93.4	x 85	95.5 x 1	104.9
CAPACITY (cc)	2405 cc	349	4 cc	2999	СС
COMPRESSION RATIO (:1)	9.6: 1		5: 1	18.3	
FUEL	91 RON unlead	ded petrol (ULP)		Distill	ate
POWER (DIN, kW)	94 @ 4800 rpm		400 rpm	96 @ 380	
TORQUE (DIN, Nm)	207 @ 3200 rpm		1000 rpm	280 @ 2000 r	
				294 @ 2000 rpi	
ALTERNATOR (amps)	100	9	0	80	
FUEL TANK (L)	. 30		s: 76 litres	, 00	
GEAR RATIOS (:1)	Manual	Manual	Auto	Manual	Auto
1st	4.357	4.008	2.804	4.008	2.785
2nd	2.502	2.301	1.532	2.301	1.545
3rd	1.501	1.427	1.000	1.427	1.000
4th	1.000	1.000	0.705	1.000	0.694
5th	0.809	0.828	-	0.828	-
Reverse	3.970	3.651	2.394:1	3.651	2.272
Final drive ratio 4x2 / 4x4	4.555 -	4.100 4.300	4.555 4.777	4.100 4.300	- 4.300
4x4 transfer gear ratio, low	-	2.482	2.482	2,482	2.482
4x4 transfer gear ratio, high	-	1.000	1.000	1.000	1.000
CLUTCH / CONVERTER					
Manual clutch	All engines: Diaphragm spring	pressure plate. Dry s	ingle clutch pressure	plate with cushioning	springs.
Size (mm) Capacity (kg)	240 / 560		/ 735	250 /	
Automatic	-	Toro	ue converter clutch,	lock up on overdrive t	op.
4WD SYSTEM	N/A		Push button 'Shift-	On-Fly' 4WD select,	'
		2-	speed transfer case,	limited slip differential	l.
AXLES					
Rear Type	Rigid semi-floating Banjo with hy			n all 4x4 and selected	4x2 models.
Capacity		1680kg (a	all models)		
Front Type	4x2: Independent. 4x4: Full floating,	independent with ou	iter constant velocity	joints and inner doub	le offset joints.
Capacity		1200 kg (4x2)	1300 kg (4x4)		
SUSPENSION					
Rear		elliptical leaf springs			
		avy duty springs for 4			
Front	Independent wishbone arms. Tors	ion bar springs. (DX -	4X2 & LX 4x2 3.0L [Diesel models feature of	coil springs).
	Stabiliser bar. Gas pressurised shock	absorbers. 'High rise'	front suspension ge	ometry offering increa	sed ride height
	on all V6 4x	2 models, increased		4x4 models.	
HUBS		6 stud wh	neel hubs.		
GROSS VEHICLE MASS	2800		4x2: 2800	/ 4x4: 2900	
RATING (GVM kg)					
STEERING		nion steering. Engine s			
		Single Cab Chassis (8D			
BRAKES				acting on rear wheels.	
2.4L Petrol DX &		m ventilated front dis			
3.0L Turbo Diesel 4X2		mm rear drum's with			
3.5L V6 Petrol 4X2 & all 4X4	280 mm ventilated front discs w	rith dual piston calipe	ers. 295 mm rear dru	ım's with leading / trai	ling shoes.
MAX. ALLOWABLE					
GTM (kg)					
Without trailer brakes			50		
With trailer brakes			00		
GCM-BRAKED 4X2			750 750		
TRAILER (kg) 4X4					

Wheels / Tyres / Track / Turning Circle

VEHICLE	Wheels	Tyres	Track Front / Rear (mm)	Turning Circle Kerb to kerb (m)
2.4L Petrol DX 4x2	14 x 5.5JJ Steel	195R 14C(613)	1460 / 1460	12.1
3.5L V6 Petrol 4x2	15 x 6.5JJ Steel	225/70R 15C(623)	1515 / 1520	12.1
3.0L Turbo Diesel 4x2	15 x 6.5JJ Steel	215/70R 15C Dueler	1460 / 1460	12.1
DX & LX 4X4 models	16 x 7.0JJ Steel	245/70R16(693)	1520 / 1525	12.6
LT 4x2 & 4x4 models	16 x 7.0JJ Alloy	245/70R16(693)	1520 / 1525	12.6

VEHICLE	Length (mm)	Body Wid	th (mm)*	Height	(mm)	Ground Cle	arance (mm)
		4x2	4x4	4x2	4x4	4x2	4x4
Single Cab Chassis DX	5000	1720	1800	1630	1725	190	225
Single Cab Chassis LX	5000	1800	1800	1710	1725	210	225
Single Cab Chassis LX 3.0L Turbo Diesel 4x2	5000	1800	-	1635	-	195	-
Space Cab Chassis LX	5000	1800	1800	1715	1730	210	225
Single Cab Pickup LX	5015	1800	-	1720	-	210	-
Space Cab Pickup LX	5020	1800	1800	1730	1745	210	225
Space Cab Pickup LT	5115	-	1800	-	1745	-	225
Crew Cab Chassis LX	4880	-	1800	-	1735	-	225
Crew Cab Pickup DX	4900	1720	-	1640	-	190	-
Crew Cab Pickup LX 3.0L Turbo Diesel 4x2	4900	1800	-	1660	-	195	-
Crew Cab Pickup LX	4900	1800	1800	1735	1750	210	225
Crew Cab Pickup LT	4995	1800	1800	1750	1750	225	225
WHEELBASE (mm)			ups: 3050/ All	Cab Chassis: 3	200		

*Body width excludes exterior mirrors

Length	Wi	dth	Wall Height	Area (m2)
	Max.	Btw. Arches	(Double Wall Const.)	
2306*	1553	1082	470	3.58
1836*	1553	1082	470	2.85
1419*	1553	1082	470	2.20
2710#	18	42	-	_
2250#	18	42	_	_
1795#	18	42	-	-
	2306* 1836* 1419* 2710# 2250# 1795#	Max. 2306* 1553 1836* 1553 1419* 1553 2710# 18 2250# 18	Max. Btw. Arches 2306* 1553 1082 1836* 1553 1082 1419* 1553 1082 2710# 1842 2250# 1842 1795# 1842	Max. Btw. Arches (Double Wall Const.) 2306* 1553 1082 470 1836* 1553 1082 470 1419* 1553 1082 470 2710# 1842 - 2250# 1842 - 1795# 1842 -

*Length - at Pickup floor level. #Exterior tray measurements (Max recommended length.)

VEHICLE	Leg F	Room	Shoulder Room	Head Room
	Front	Rear		Front
Single Cab Chassis	1085	-	1450	1004
Space Cab Chassis	1085	-	1450	1004
Single Cab Pickup	1085	-	1450	1004
Space Cab Pickup	1085	-	1450	1004
Crew Cab Chassis	1085	890	1450	1004
Crew Cab Pickup	1085	890	1450	1004

Initial service at 5,000 km, regular service every 10,000 km or six months, whichever occurs first.
Diesel oil change intervals: 10,000 km using prescribed oil.

BIG ON FEATURES

Cabin				Singl	e Cab			S	igle Cab	Space	Cab			Space	e Cab			Crew	Cab							Crew	v Cab						
Body				Cha	ssis				Pickup	Chas	ssis			Pick	kup			Chas	ssis							Picl	kup						
Drive			4x2		I		4x4			4x2	4x4	4>	(2		4)	(4		4X	4			4x	2						4:	x4			
Trim Level	DX	DX	LX	LX	LX		DX		LX			LX	_	LX	LX		LT	LX		DX	LX		LX	LT	LT	LX	LX	LX	LX		LT	LT	LT
Engine Transmission	2.4 Man	2.4 Man			3.0 TD	3.5V6		3.0TD	3.5V6	3.5V6							3.0TD	3.5V6			3.5V6			3.5V6 Man						3.5V6	3.5V6	3.0TD Man	3.0T
Retailer Ordering Code	١.		*				, ,	#		#		*	#			#	#				#	#		311-	211-	#	#	#	#	#	**	#	#
	15 A	15 B	25 C	24.0	65 0	25 C	165 C	65 C 65 E# 65 E#	25 C	25 C	65 C	25 C 25 E	24 C 24 E	25 C	92 C	25 Fi	55 F;	25 C	65 C	15 B	25 C	24 C 24 E	65 B	25 F4	24 F#	25 C 25 E#	24 C 24 E#	65 C 65 E#	264 C 264 E#	25 F#	24 F;	35 Fi	54 F
)2-1)2-1)2-2)2-2	25-2	25-2)2-2	02-1)2-2	30-2	85-2	35-2	34-2 34-2	34-2 34-2)4-2	04-2	94-3	94-3	53-2	53-2	52-1	52-2 52-2	52-2 52-2	52-2	52-37	52-37	52-2	52-2	52-2	52-2	52-3	52-3	52-3	52-3
	8DK02-115 A	8DK02-115 B	8DH02-225 C 8DH02-225 E#	8DH02-224 C	8DH02-265 C	8DR02-225 C	8DQ02-	8DR02-265 (8DH80-225 C	8DH85-225 C 8DH85-225 E#	8DR85-265 C	8DH04-225 C 8DH04-225 E#	80H(8	8DR04-225 C	8DR04-265 C	8DS04-325 F#	8DS04-365 F#	8DR63-225 C	8DR63-265 C	8DK62-115 B	8 8 8 8 8	8DH62-224 C 8DH62-224 E#	8DH62-265 B	8DL62-325 F#	8DL62-324	8DR6 8DR6	8DR62-224 (8DR62-224 E	8DR6 8DR6	8DR62-264 8DR62-264	8DS62-325 F	8DS62-324 F#	8DS62-365 F#	8DS62-364 F#
	_																																
WEIGHTS	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	200
Gross Vehicle Mass Rating (kg): Kerb Weight (kg)* (Est. inc A/C and fluids):					2800 1468																												
POWERTRAIN	1321	1332	1437	1447	1408	1540	103/	1037	1592	1492	100/	1592	1012	1/10	1/9/	1/21	1802	1706	1/8/	1559	10//	1087	1/02	1083	1093	1/91	1001	18/2	1002	1/90	1800	18//	100
94 kW, 2.4 litre 4-cyl, SOHC petrol engine.	S	S																		ς													
147 kW, 3.5 litre V6 DOHC petrol engine.	-		S	S		S			S	S		S	S	S		S		S			S	S		S	S	S	S			S	S		_
96 kW, 3.0 litre 4-cyl, OHV Intercooled Turbo-Diesel engine.					S		S	S			S				S		S		S			-	S			-		S	S			S	S
Alternator amps.	100	100	90	90	80	90	80	80	90	90	80	90	90	90	80	90	80	90	80	100	90	90	80	90	90	90	90	80	80	90	90	80	
Air snorkel - Diesel engine.					Α		Α	Α			Α				Α		Α		Α				Α					Α	Α			Α	Α
5-speed manual transmission.	S	S	S		S	S	S	S	S	S	S	S		S	S	S	S	S	S	S	S		S	S		S		S		S		S	
4-speed automatic transmission, overdrive top, lock-up torque converter clutch.				S									S									S			S		S		S		S		S
Transmission Control Module (TCM) 'Gradient Logic'.				S									S									S			S		S		S		S		S
4WD selection (Push Button): Shift-On-The-Fly.						S	S	S			S			S	S	S	S	S	S							S	S	S	S	S	S	S	S
Limited slip differential.			S	S		S	S	S	S	S	S	S	S	S	S	S	S	S	S		S	S		S	S	S	S	S	S	S	S	S	S
MECHANICAL	_																																
Steering: Rack and pinion (power assisted).		S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	- (/	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	S(P)	- '
Independent double wishbone front suspension.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
High Rise front suspension with added ground clearance.			S	S		S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S		S	S	S	S	S	S	S	S	S	S
Semi-elliptical leaf spring rear suspension.	S	S	5	5	5	5	5	2	5	5	5	S	5	S	5	5	S	5	5	S	5	S	5	5	5	5	5	5	5	5	5	S	S
Gas pressurised shock absorbers.	S	S	2	S	2	2	2	2	2	2	2	S	2	S	2	S	S	2	2	S	2	S	5	2	2	2	2	2	2	2	2	S	S
Front stabiliser bar. Power brakes - ventilated disc front / drum rear.	S	S	2	S	S	2	5	2	2	S	2	5	2	2	2	5	S	2	5	5	5	S	2	2	2	S	5	2	2	2	2	S	S
ABS anti-lock brakes.	3	3	S	3	3	3	3	3	3	3	3	3	3	3	3	S	5	3	3	3	3	3	3	5	2	3	3	3	3	2	5	S	S
	5	S	5	S	c	c	c	c	c	ς	5	ς	5	ς	ς	5	5	S	S	S	5	5	S	ς ς	5	ς	5	c	c	2	ς ς	5	5
Load sensing proportioning valve. Underbody impact protection: Radiator.	S	S	<u>S</u>		5	5	5	5	5	5	5	S	5	5	5	5	5	5	5	S	<u>S</u>	S	<u>S</u>	5	<u>S</u>	<u>S</u>	5	2	2	2	5	5	S
Additional protection: Transfer case & fuel tank.	3	3	3	3	3	2	5	5	3	3	5	3	3	ς	5	2	5	2	2	3	3	3	3	3	3	ς	2	3	2	2	ς ,	S	S
WHEELS.						3	3	3			3			3	J	3	J	3	3)	3	3	3	J	3	
14 x 5.5JJ steel wheels. Black caps. 195R14C (613) tyres.	S	S																		ς													
15 x 6.5JJ steel wheels. Black caps. 215/70R15C (623) tyres.	1				S			_		_										3			S										
15 x 6.5JJ steel wheels. Styled caps. 225/70R15C (Dueler) tyres.			S	S	3				S	ς		S	S								S	S											_
16 x 7.0JJ steel wheels. Styled caps. 245/70R16(693) tyres.						S	S	S		-	S			S	S			S	S							S	S	S	S				
16 x 7.0JJ alloy wheels. Styled caps. 245/70R16(693) tyres.																S	S							S	S			_		S	S	S	S
Steel spare wheel (alloy on LT models).	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
EXTERIOR																																	
One-piece resin bumper with air dam - grey finish.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S			S	S	S	S	S	S			S	S	S	S		_		
One-piece resin bumper with air dam - body colour.																S	S							S	S					S	S	S	S
Body colour grille surround.			S	S	S	S		S	S	S	S	S	S	S	S	S	S	S	S		S	S	S	S	S	S	S	S	S	S	S	S	S
Clear multi-reflector headlamps - flush mounted plastic lens.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
Combination tail lamps and high mount stop lamp.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S		S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
Fog lamps.																S	S							S	S					S	S	S	S
Grey body side moulding.			S	S	S	S		S	S	S	S	S	S	S	S			S	S		S	S	S			S	S	S	S				
Body colour side moulding.																S	S							S	S					S	S	S	S
Manual dual exterior mirrors - black (convex LHS).	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S			S	S	S	S	S	S			S	S	S	S				
Power dual exterior mirrors - chrome (convex LHS).	-		_													S	S							S	S		-	_		S	S	S	S
Black door handles.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S			S	S	S	S	S	S			S	S	S	S	_	-	_	
Chrome door handles with body colour surround.	-	-				_		_		_						S	5	_		-				S	S					S	S	S	S
Mudflaps - front (flat).	S	S	_	_	S	_		_	_	_	S	_	_		_			_	_	S	_	_	S			_	_	_					
Overfender flares with formed mudflaps - grey.			S	S		S	S	S	S	S		S	S	S	S			S	S		S	S				2	S	S	S				

Key: S = Standard fitment A = Accessory O = Optional fitment # Rodeo models fitted with dual airbags.

*Vehicle weights based on pre-production data. All fluid levels at their nominated capacity. Add 8kgs to stated Kerb Weight figure for models fitted with dual airbags (Kerb Weight excludes the mass of occupants, options, accessories and cargo carrying devices e.g. Tray body for Cab Chassis models).

BIG ON FEATURES

Cabin				Sing	le Cab				S'gle Cab	Space	e Cab			Spac	e Cab			Crew	Cab							Crev	v Cab					
Body				Ch	assis				Pickup	Cha	ssis			Pic	kup			Chas	ssis							Pic	kup					
Drive			4x2			T	4x4		4x2		1×1	1	x2			x4		4X				45	(2						4)	·Λ		
Trim Level	DX	DX			LX	LX		LX	LX	LX	LX		LX	IV	LX		LT		LX	DX	IV	LX		LT	LT	LX	LX	LX	LX		LT	LT I
irim Levei Engine Transmission	2.4 Man	2.4	3.5V6	3.5V6	3.0 TD	3.5V6	3.0TD	3.0TD				3.5V6	3.5V6	3.5V6		3.5V6		3.5V6			3.5V6					3.5V6	3.5V6			3.5V6	3.5V6	3.0TD 3.0
Retailer Ordering Code	8DK02-115 A	8DK02-115 B	8DH02-225 C 8DH02-225 E#	8DH02-224 C	8DH02-265 C	8DR02-225 C	8DQ02-165 C	8DR02-265 C 8DR02-265 E#	8DH80-225 C	8DH85-225 C 8DH85-225 E#	8DR85-265 C	8DH04-225 C 8DH04-225 E#	8DH04-224 C 8DH04-224 E#	8DR04-225 C	8DR04-265 C	8DS04-325 F#	8DS04-365 F#	8DR63-225 C	8DR63-265 C	8DK62-115 B	8DH62-225 C 8DH62-225 E#	8DH62-224 C 8DH62-224 E#	8DH62-265 B	8DL62-325 F#	8DL62-324 F#	8DR62-225 C 8DR62-225 E#	8DR62-224 C 8DR62-224 E#	8DR62-265 C 8DR62-265 E#	8DR62-264 C 8DR62-264 E#	8DS62-325 F#	8DS62-324 F#	8DS62-365 F#
Overfender flare in body colour with formed mudflaps - black.																_	S							S	S						S	5 5
Bonnet protector.	Α			Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	A A
Aluminium bull bar.	Α	Α		Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	A A
Aluminium nudge bar.	Α	Α		Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	A A
Driving lamps and harness - suitable if bull bar / nudge bar fitted.	Α			Α	Α	A	Α	Α	Α	Α	Α	Α	Α	A	Α	Α	Α	A	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	A	Α	Α Α
Headlamp guards.	A			A	Α	A	Α	Α	Α	Α	A	Α	Α	A	Α	Α	Α	A	Α	A	A	Α	Α	A	A	Α	Α	A	Α	A	Α	A A
Insect screen - radiator grille (upper section).	Α	Α	Α	Α	Α	Α	Α	Α	Α	A	A	A	Α	A	A	Α	A	A	A	A	A	Α	A	Α	A	Α	Α	Α	Α	Α	A	A A
Side step package.										Α	Α	Α	A	A	A	A	A	Α	Α	A	A	A	A	A	A	A	A	A	A	A	A	A A
Rear step package.		_	_		_					_	_	Α	A	A	A	S	S			Α	A	A	Α	S	S	A	A	A	A	S	S	S 5
Corrosion protection.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	5	S	S	S	S	5	S	5	S	S	5	5	5	S	S S
DRIVER		_				_	_			_	_	_	_	_	_		_	-	_	_		_		_		_	_	_	_	_		
Day/Night rear view mirror.	S			S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	<u>S</u>	S	5	S	S	S	S	5	S	S	S	S S
Four spoke soft feel steering wheel.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	-	-	S	S	S	S	S	S	_		S	S	S	S	_		-
Leather wrap steering wheel.						_				_	_	_		_		S	S	_				_	_	S	S	_	_	_	_	S	S	S S
Steering wheel height adjust.			S	S	S	S		S	S	S	S	S	S	S	S		S	S	S	_	S	S	S	S	S	S	S	S	S	5	S	S S
Remote fuel filler door release.			_						S	_	_	S	S	S	S	S	S	_	_	S	S	S	5	S	5	S	S	5	5	5	5	S S
Floor mounted parkbrake.			S	S		S			S	S	S	S	S	S	S	S	S	S	S		S	S	S	S	S	S	S	S	S	5	S	S S
Leather wrap transmission shift knob.		_										-				S	S	_				_		S	S			_		S	S	S 5
Wipers intermittent setting.			S	S	S	S		S	S	S	S	S	S	S	S		_	S	5		S	S	S	_	_	S	S	S	S	_		
Wipers variable intermittent setting.										_	_	_	_		_	S	S	_	_				_	S	S	_	-	_		5	S	S S
Electric rear window demist.			_		_		_			S	S	S	S	S	S	S	S	S	S	_	S	S	S	S	S	S	S	S	S	5	S	S S
Speedometer with odometer and trip meter.	S	S		S	S	S	S	S	S	S	5	S	5	2	2	2	S	5	S	S	S	S	5	2	- 5	3	2	2	2	2	5	S S
Tachometer.		6/ 1	S	S	S	S	S	S	S	S	5	S	5	5	5	5	S	S	5	6/ 8)	S	S	5	5	5	S	5	5	5	5	5	S S
Digital clock - in dash. (DX models in radio where fitted).		S (radio		S	5	S	S (radio	_	5	5	5	S	5	S	S	S	5	S	S	S (radio)	S	S	5	5	5	S	5	5	5	5	5	S S
Variable instrument dimming.	S	S	S	S	5	S	S	S	5	5	5	S	5	S	5	S	S	S	5	S	S	S	5	5	S	S	5	5	5	5	5	S S
Warning lamps include: Oil pressure, alternator and parking brake on.	S	S	S	S	S	S	S	S	5	S	5	S	5	S	5	S	S	5	S	S	S	S	5	5	5	S	5	5	5	5	5	S S
Low fuel warning lamp.	S	S	S	S	5	5	2	5		5	5	S	5	5	5	5	S	5	5	5	S	S	5	5	5	5	5	5	5	5	5	S S
Headlights left on warning buzzer.		_	S	S	S	5		S	S	S	5	S	5	S	5	S	S	S	5		S	5	5	5	5	S	5	5	5	5	5	5 5
Cruise control - engine specific system.			Α	Α	A	A	A	Α	Α	Α	Α	Α	A	Α	Α	S	Α	Α	Α		Α	Α	A	S	5	Α	Α	Α	A	5	5	A A
Mobile phone power connector.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S S
Lockable fuel gooseneck cap.	S	_		S	S	S	S	S		S	S							S	S			_						_				
Tool kit.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S S
SOUND SYSTEM																																
AM/FM radio - electronic tune / Antenna.		S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
Compact Disc player (single disc) / (6 stack).		S(1D	, , ,) S(1D)						• ,							S(1D)							. ,	. ,				S(6S) S(6
Security PIN code.			S	S	S	S		S		S	S	S	S	S	S	S	S	S	S		S	S	S	S	S	S	S	S	S	S	S	S 5
2 speaker elements.		S	S	S	S	S	S	S	S											S												
4 speaker elements.										S	S	S	S	S	S			S	S		S	S	S			S	S	S	S			
6 speaker elements. SEATING & RESTRAINTS																S	S							S	S					S	S	S
Bench front seat - vinyl trim.	S	S					S													S												
Bench front seat - cloth trim.					S			S																								
Reclining front bucket seats & adjustable head restraints - cloth.			S	S		S			S	S	S	S	S	S	S			S	S		S	S	S			S	S	S	S			
Reclining front bucket seats & adjustable head restraints - moquette.						Ť						_				S	S							S	S					S	S	S S
Rear jump seat.																	S							Ť								
Driver's left foot rest.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	_	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	5 5
Bench rear seat - vinyl trim.		,	,	,	3	,	3	J	,	,	,	,	,	,	,	,	,	J	,	S	,	J	,	J	3		,	J	,	J		,
Denier rear seat viriyi umi.																				J												

Key: S = Standard fitment A = Accessory O = Optional fitment # Rodeo models fitted with dual airbags.

Cabin				c. 1					c/ c	-	6 I			_	C I				.							_	<u> </u>						
				Singl	e Cab				Sigle Cab	Space	Cab			Space	e Cab			Crew	Cab							Crew	Cab						
Body				Cha	assis				Pickup	Cha	ssis			Pick	cup			Chas	ssis							Pick	up						
Drive			4x2				4x4		4x2	4x2	4x4	4x	(2		4x	4		4X	4			4x2	,						4)	x4			
Trim Level	DX	DX			LX	ΙX	DX	ΙX	LX		LX		LX	ΙX			LT			DX	LX			LT	LT	LX	ΙX	LX	LX		LT	LT L	IT
Fngine	2.4																	3.5V6														3.0TD 3.0	
Engine Transmission	Mai				Man		Man		Man		Man		Auto								Man						Auto	Man	Auto		Auto		
Retailer Ordering Code	⋖	ω	∪ #	U	U	U	U	# ن	U	し 豊	U	し 豊	し 豊	U	U	ŧ	#	U	U	8	し 豊 (歩	ω	走	进	し 豊	し 豊	し 豊	し 豊	走	誰	走 ;	#
	15	15	225	224	265	225	165	965	225	225	597	225	224 224	225	597	125	99	525	597	15	225	224	265	52	24	225	224	265	264	25	124	92	9
	05-	05-	02-	02-	02-	05-	02-	02-7	80-	85-	85-7	40	04-	04.	.40	5-40	5-4	63-	63-7	29	62-	62-	62-	52-3	52-3	62-7	62-7	62-7 62-7	62-7	52-3	52-3	52-3	52-:
	8DK02-115 A	8DK02-115 B	8DH02-225 C 8DH02-225 E#	8DH02-224 C	8DH02-265 C	8DR02-225	8DQ02-165 (8DR02-265 (8DR02-265 R	8DH80-225 C	8DH85-225 8DH85-225	8DR85-265	8DH04-225 C 8DH04-225 E#	80H	8DR04-225	8DR04-265 C	8DS04-325 F#	8DS04-365 F#	8DR63-225 C	8DR63-265 C	8DK62-115	8DH62-225 (8DH62-225 (8DH62-225) (8DH62-225 (8DH62-225 (8DH62-22) (8DH62-225 (8DH62-22) (8DH62-225 (8DH62-22)	8 H	8DH62-265	8DL62-325 F#	8DL62-324	8DR62-225 8DR62-225	8DR62-224 (8DR62-224 E	8DR62-265 8DR62-265	8DR62-264 8DR62-264	8DS62-325	8DS62-324 F#	8DS62-365 F#	8DS62-364 F#
Bench rear seat - cloth trim.																		S	S		S	S	S			S	S	S	S				
Bench rear seat - moquette trim.																								S	S					S	S	S S	5
Rear seat head restraints - adjustable.																		S	S	S	S	S	S	S	S	S	S	S	S	S	S	S S	5
Seat covers cloth - bench or bucket type.	А	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α Α	Ā
Driver and front passenger airbag #.			#					#		#		#	#			#	#				#	#		#	#	#	#	#	#	#	#	# #	#
Seat belts lap/sash, retracting - front seat(s).	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	
Seat belts lap/sash, retracting x 3 - rear seat.																		S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	
CHILDREN																																	
Rear seat child restraint anchor points.																		S	S	S	S	S	S	S	S	S	S	S	S	S	S	S S	5
Childproof rear door locks.																		S	5	S	S	S	S	S	5	S	5	S	S	S	5	S	
CABIN COMFORT																		-				-	-		-	-		,			-		_
Air conditioning - engine specific system.	A	A	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Δ	Δ	Α	Δ	Δ	Δ	Α	Δ	Α	Δ	A A	Δ
Power windows.										А	А					5	ς							S	ς					S	5	5	
Ashtray & cigarette lighter - front (illuminated lighter).	S	S	S(I)	S(I)	S(I)	S(I)	ς	S(I)	S(I)	S(I)	S(I)	S(I)	S(I)	S(I)	S(I)	S(I)	S(I)	S(I)	S(I)	S	S(I)	S(I)	S(I)		S(I)	S(I)	S(I)	S(I)	S(I)	S(I)	S(I)	S(I) S	_
Roof dome lamp - door activated.	S		- ()	S	S S	S	S	S	S S	S	S S	- ' '	S S	S S	S S	S S	S(1)	S	S S	S	S .	,	5	S	S(1)	ς ,	2(1)	2(1)	S S	2(1)	5(1)	S :	
Map reading lamp.	,		3	,	3	J	3	3	J	J	3	3	3	J	J	S	S	J	3	3	3	3	3	S	5	J	J	3	3	S	ς	S :	
Vinyl floor covering.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	J	J	c	S	S	S	S	C	3	3	c	S	S	S				_
Carpet with driver heel mat.	3	3	3	3	3	3	3	3	3	3	3	3	3	J	3	S	S	3	3	3	3	3	3	S	S	3		3	3	S	S	S S	_
Rubber floor mats.	A	A	Α	А	Α	Λ	۸	Α	Α	Α	Α	۸	Α	Α	Α	A	A	Α	Α	Α	۸	Α	Α	A	A	Α	A	Α	Α	A	Α	A A	
Carpet mats, tailored - front & rear (Crew Cab).	A	_		A	Α .	A	Α	A	Α	A	Α	Α	Α	A	Α	A	Α	A	Α	A	Α .	A	Α	A	Α	Α	A	A	Α	Α Λ	A		A
) S(-			C/C\	٠.	C/ \		C/C\	S(S)	C/C)	S(S)	S(S)		C/C\		C/C\		C/C\	C/ \	A C/C\	A C/C)	C/C)		A C/C\	A C/C)	C/C)	C/C)	C/C)	A C(C)	C/C)		
Full front door trim (cloth insert) - front cup holder and pockets.	3(-) 3(-	3(3)	3(3)	3(3)	3(3)	3(-)	3(3)	3(3)	3(3)	3(3)	3(3)	3(3)	3(3)	S(S)	3(3)	3(3)	S(S)					S(S)				S(S)		S(S)			. ,	· /
Full rear door trim (cloth insert) - ashtray .			C/1\	C/1\	C/1\	C/1\		C/1\	C/1\	C/1\	C/1\	C/1\	C/1\	C/1\	C/1\	C/1\	C/1\				. ,					S(S)	S(S)	S(S)	S(S)	. ,	. ,	S(S) S(· /
Passenger overhead assist handles.		-		S(1)					S(1)		S(1)		S(1)		S(1)			S(3)									S(3)	S(3)	S(3)			S(3) S(
Laminated windscreen - green tinted glass.	S	_		S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S S	
Weathershields - driver and front passenger windows.	A	A	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	А	Α	Α	Α	Α	Α	Α	Α	Α	А	Α	Α	Α	Α	A A	A
STORAGE, CARGO & TOWING	C/	C/ 1	C/C)	C/C)	C/C)	C/C\	c/ \	C/C\	C/C\	C/C\	C/C\	C/C)	C/C)	C/C\	C/C\	C/C\	C/C\	C/C\	C/C\	C/ \	C/C\	C/C)	C/C\	C/C)	c/c\	C/C)	C/C)	C/C\	C/C\	C/C)	C/C\	C/C) C	(C)
Glovebox - lockable (illuminated).) S(-)		S(S)	. ,	- ' '	. ,		S(S)	- ' '	S(S)	- ' '	. ,		S(S)		. ,		. ,	. ,	. ,	. ,	• •	. ,	. ,	. ,	S(S)					S(S) S(
Front floor shift console with cup holders.	S	S		S	S	S	S	S	S	S	S	S	S	S	2	S	S	S	S	S	S		S	S	S	S	S	S	S	S	S	S :	2
Rear console extension.			S	S		S			S	S	S	S	S	S	S	-		S	S		S	S	S	-	c	S	S	S	S	_			_
Rear console extension with lidded compartment.																_	S							S	S					2	S	S :	2
Storage containers x 2.		_		_		_		_				_		_		S	S	_		_		_		_	-	_				-			_
Tool and jack cover.	S	S	S	S	S	S	S	S	S	S	S	2	S	S	S	S	S	_	S	S	S	S	S	S	5	5	S	2	S	2	S	S S	
Rear coat hook x 2.	C/ 1	· · · · · ·	C()	C()	C/ \	C/C)	C/C)	C/C\	C()	2	2	2	5	2	2	2	2	S	2	5	5	5	5	S	5	2	2	2	2	2	5	S 5	
Tow hook front (& rear).	S(-)		. ,	S(-)	S(-)	S(S)	5(5)	S(S)	S(-)	S(-)	S(S)	S(-)	S(-)	S(S)	S(S)	S(S)	S(S)	. ,	S(S)	S(-)	S(-)	S(-)	S(-)	. ,	S(-)	S(S)	S(S)	S(S)	S(S)	S(S)	S(S)	S(S) S(` '
Trailer wiring - 7 lead.	A			A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A		A
Tow bar (2000 kg rated) - tongue and harness package .	A			Α	A	A	A	Α	A	A	A	A	A	A	A	A	A	A	Α	A	A	A	A	A	A	A	A	A	A	A	A		Α
Equaliser Hitch (2000 kg).	A	A	А	Α	Α	Α	Α	Α	Α	Α	Α	A	Α	Α	A	Α	A	Α	Α	Α	Α	A	A	Α	A	Α	Α_	Α	Α	A	A		<u>A</u>
Dual wall construction cargo tray.									S			S	S	S	S	S	S			S	S		S	S	S	S	S	S	S	S	S	S S	
Cargo tray tonneau cover.									Α			Α	Α	Α	Α	Α	Α			Α	Α			Α	Α	Α	Α	Α	Α	Α	Α		Α
Aluminium sports bar.									Α			Α		Α		Α	Α			Α	Α			Α	Α	Α	Α	Α			Α		Α
Cargo tray tonneau cover for sports bar.													Α																			Α Α	
Cargo tray mat - heavy duty rubber.													Α																			A A	
Cargo tray liner & tailgate liner.												Α	Α	Α	Α	Α	Α			Α	Α	А	Α	А	Α	Α	Α	Α	Α	Α	Α	A A	Α
SECURITY / SAFETY																																	
Engine immobiliser.	S	S	S	S	S	_	S	_		_		_								S												S S	
Power door locks with remote keyless entry.			S		S													S					S							S			S
Side impact door beams - all doors.			S				S		S		S							S					S							S			S
Collapsible steering column.	S		S				S	_		S								S					S							S			
Roadside Assistance.	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S S	S

Key: S = Standard fitment A = Accessory O = Optional fitment # Rodeo models fitted with dual airbags.