



## features

		exterior/interior		exterior/interior (continued)		safety/security	
	×		×		×		
	X X X		X X X		× × ×		× × ×
engine and transmission		wheels		driver		occupant safety	
3.2 litre High Performance Alloytec V6 petrol engine with 5-speed automatic transmission with Active Select	• • • •	17" x 7" 5 spoke alloy wheels. 235/60 R17 (road biased) tyres (4)	•	Steering wheel height and reach adjust	• • • •	Driver and front passenger airbags (full size)	• • •
Active All Wheel Drive (AWD)		17" x 7" 6 spoke alloy wheels. 235/60 R17 (road biased) tyres (4)	•	Leather wrap steering wheel	• •	Side Curtain airbags	0 • •
Active All Wiledi Dilive (AWD)		18" x 7" 7 spoke alloy wheels. 235/55 R18 (road biased) tyres (4)	•	Cruise control	• • • •	Front seat belt sash height adjust	• • •
ontrol and handling		18" x 7" 5 spoke alloy wheels. 235/55 R18 (road biased) tyres (4)	•	Power mirrors	• • • •	All seat belts retracting lap/sash	• • •
Hydraulic rack and pinion power steering	• • • •	16" x 6.5" steel spare wheel 215/70 R16		Heated mirrors with auto off function and side turn signal	•	Pyrotechnic front seat belt pretensioners	• • •
wheel disc brakes, front and rear ventilated	• • • •	Alloy wheel lock nuts	A A A A	Variable intermittent road speed sensitive wipers  Rear window wiper/washer	• • • •	Front seat belt force limiter, controls maximum force on chest  Child restraint anchor fittings (3) fixed to 2nd row seatback	• • •
Electronic Brakeforce Distribution (EBD)	• • • •	exterior		Variable instrument dimming	• • • •	Child-proof rear door locks	• • •
our-link Independent Rear Suspension (IRS)	• • • •	Wheel arch mouldings		Rear Parking Sensors	A A A A	enia proorteal door locks	
evel Ride Suspension	• •	Side fender vents	• •	Audible warning if headlamps left on	• • • •	security	
-channel Anti-lock Braking System (ABS)	• • • •	Front fog lamps	• •	Driver Information Centre	• •	Radio frequency remote key operates:	
Hydraulic Brake Assist (BA)	• • • •	Rear reflectors		Digital clock		Interior lighting	-
raction Control System (TCS)	• • • •	Centre high-mount stop light		Bluetooth mobile phone kit	A A A A	Central locking for keyless entry	_
lectronic Stability Program (ESP®)	• • • •	Anti-corrosion protection		Portable satellite navigation (Global positioning system)	A A A A	Tailgate	_
lescent Control System (DCS) .ctive Rollover Protection (ARP)	• • • •	Side steps	A A A A	Trip Computer	•	Key has security code	
ttive kollover Flotection (AKF)		Headlamp protectors	A A A A			Engine immobilised automatically when key removed from ignition	
		Bonnet protector	A A A A	sound system		Audible warning if key left in ignition and	• • •
		Metallic paint	0 0 0 •	AM/FM stereo electronic tune radio. Four speakers	•	driver's door opened to exit	
		Towing mirrors	A A A A	AM/FM stereo electronic tune radio. Six speakers	•	Radio security PIN coding	• • •
		Chrome exhaust tips	A A • A	AM/FM stereo electronic tune radio. Eight speakers	•		
		Licence plate frames, standard height or slimline	A A A A	AM/FM stereo electronic tune radio. Seven speakers	•	road safety	
		Nudge bar	A A A A	Sound system remote controls on steering wheel	• • • •	Warning triangle for roadway	A A
		Insect screen	A A A A	Single disc in-dash CD player. MP3 compatible	•	First aid kit  Jumper lead – anti zap cable	A A A
		Rubber mudflaps, front and rear	A A A A	6 disc in-dash CD player. MP3 compatible	• • •	- Tumper lead – anti zap cable	A A
		Silver decorative skid plates, front and rear	• •	Radio antenna in rear side window glass	• • •		
				Roof mounted radio antenna	•		
		cabin comfort					
		Air conditioning with air particle filter	• • • •	storage and cargo			
		Electronic climate control. Auto/manual mode. Air quality sensor	• •	Hot/cold cup holder	A A A A		
		Power windows, front and rear	A A A A	Glovebox cooling	• •		
		Overhead DVD player		Dashtop storage compartment	• •		
		Cigarette lighter and ashtray  Vanity mirror, driver and passenger side with cover	A A A A	Dashtop storage compartment with lid  Centre console compartment with lid	•		
		N. 11. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	•				
		Vanity mirror, driver and passenger side. Illuminated, with cover Vanity mirror, driver side. Illuminated with cover	•	Front and rear door storage bins	• • •		
		Centre dome lamp	• • • •	Sunglasses holder	• • • •		
		Front reading lamps	• • • •	Coat hooks			
		Cargo area lamp		60/40 split fold 2nd row rear seat back			
		Tinted windows		Wet/dry storage compartment	•		
		Front passenger and 2nd row overhead folding assist handles		12 Volt power outlet, front, 2nd row and cargo compartment			
		Black sill plates	• • •	Car fridge – 31 litres	A A A A		
		Stainless steel sill plates	•	Rear cargo organiser	A A A A		
		Carpeted floor mats, front and rear	A A A A	Cargo safety barrier	A A A A		
		Carpeted floor mats, third row rear	A A	Flexible cargo tie-down net	A A A A		
		Rubber floor mats, front and rear	A A A A	Load tie-down strap kit	A A A A		
		Slimline front and rear weathershields	A A A A	Cargo liner	A A A A		
				Cargo entry protector	A A A A		
		seating		Roof rails	• •		
		Seating capacity	5 7 7 5	Roof cross bars	A A A A		
		Seat trim in full cloth	• •	Roof mounted tray with spare wheel carrier	A A A A		
		Leather faced seat trim	• •	Roof mounted bike carrier	A A A A		
		Seat inserts, lambswool	A A A A	Roof mounted ski carrier. Scissor-type or universal	A A A A		
		Seat inserts, protective fabric	A A A A	Roof pod	A A A A		
		Electric 8-way adjustment of driver's seat Slide. Cushion tilt. Height. Recline	• •	Rear cargo tray	A A A A		
		Singe, Custifor the Fieldle Neclife		Tailgate window opens for quick access, using remote Power Key or button on driver's door	• • •		
		Fold-flat 2nd row seat	• •		Δ Δ Δ Δ		
		Fold-flat 2nd row seat Fold-flat 3rd row seat	• •	Cargo blind	A A A A		
standard		Fold-flat 2nd row seat Fold-flat 3rd row seat Fold-down 2nd row seats allowing access to 3rd row seats	• •	Cargo blind Tow ball cover	A A A A		
standard o optional		Fold-flat 2nd row seat Fold-flat 3rd row seat	• •	Cargo blind			

technical specifications vehicle dimensions


	3.2 litre high performance Alloytec V6 engine										
Engine	3.2L 60-degree Double Overhead Cam V6 with 4 valves per cylinder. Sequential fuel injection. High energy, distributorless ignition.  Twin knock control sensors with individual cylinder adaptive control. On-board diagnostics. Electric cooling fan. Stainless steel exhaust.  Low restriction air intake with acoustic dampening chambers. Continuously variable camshaft phasing for inlet and exhaust cams.  Variable intake manifold. Coil-on-plug										
Capacity (cc)	3195										
Compression ratio (:1)	10.3:1										
Maximum power (ECE, kW)*	SX, CX, LX: 169 @ 6600rpm	MaXX: 167 @ 6600rpm									
Maximum torque (ECE, Nm)*	SX, CX, LX: 297 @ 3200rpm	· · · · · · · · · · · · · · · · · · ·									
Gear ratios	1st 4.575	2nd 2.979	3rd 1.947	4th 1.318	5th 1.00						
	Final drive ratio 2.700										
Fuel economy (L/100km) <sup>^</sup>	SX, CX, LX: 11.5	MaXX: 11.6									
Recommended petrol octane rating	91 (ULP) 95 (PULP for sligh	tly higher performance)									
Petrol tank (L)	65										
Emission Class	Euro IV										
All Wheel Drive (AWD)	The All Wheel Drive system is 'Active Torque On Demand'. An electronically controlled electro-hydraulic differential ensures optimal torque distribution between the front and rear axles in all situations. As driving conditions dictate, the rear axle is instantly employed via an electronically controlled electro-magnetic coupling to give maximum traction. The torque split ratio between front and rear wheels is variable in real time depending on the driving conditions										
Brakes	Four wheel disc. Ventilated discs – front and rear										
Anti-lock Braking System (ABS)	4-channel, 4 sensor										
Traction Control System (TCS)	When sensors detect imminent wheel spin, engine torque is reduced. If one wheel is about to spin, braking is applied to transfer torque to the wheel with better traction										
Hydraulic Brake Assist (BA)	Provides additional braking assistance by allowing the driver to reach the ABS threshold sooner and therefore help to reduce stopping distances										
Electronic Stability Program (ESP®)	Assists the driver in emergency situations by providing correction to the intended vehicle path, which may help the driver to avoid obstacles and reduce slides. This is accomplished via individual brake application and engine torque management control. ESP is a registered trademark of Daimler Chrysler AG										
Descent Control System (DCS)	Utilises the active braking capability of the ESP® to maintain a controlled speed when travelling down hill										
Active Rollover Protection (ARP)	ARP is designed to reduce the risk of rollover when lane changing and cornering; working in conjunction with the ESP® system										
Suspension	Front: MacPherson Strut, gas pressurised dampers, stabiliser bar Rear: Independent Four-link, gas pressurised dampers, stabiliser bar										
Level Ride Suspension	Self contained load-sensiti	ve rear shock absorbers that	t automatically adjust to loa	ad and road conditions	s. (standard on CX and LX)						
Steering	Rack and pinion hydraulic	power steering									
Brakes	Front Diameter: 296mm Rear Diameter: 303mm										
Track (mm)	Front: 1562 Rear: 1572										
Turn circle (kerb to kerb, m)	SX, CX, LX: 11.5		MaXX: n/a								
Wheelbase (mm)	SX, CX, LX: 2707		MaXX: 2707								
Exterior dimensions (mm)	Length	Width (excluding mirrors)		Height							
SX, CX, LX	4637	1849	2110	1720							
MaXX	4570	1850	2085	1700							
Ground Clearance (mm)	SX, CX, LX: 200	MaXX: 200									
Off road (degrees)	Approach angle	Departure angle	Breakover angle								
SX, CX, LX MaXX	24.4 24.2	22.2 23.3	17.8 17.8								
				110							
Interior dimensions (mm) SX, CX, LX Front	Leg 1036	Shoulder 1454	Head 1026	Hip 1349							
SX, CX, LX Rear	939	1455	1017	1357							
MaXX Front	1036	1424	1026	1338							
MaXX Rear	939	1422	1003	1344							
Roof Load (kg)	100										
Cargo volume seats up/folded (L)  all seats up right	SX (5 seats) 465	CX, LX (7 seats) 85	MaXX (5 seats) 430								
3rd row seats folded	-	465	-								
all rear seats folded	930	930	865								
front passenger, all rear seats folded	1565	1565	n/a								
Towing (kg)	750kg unbraked	2000kg braked									
Service	V6 – 3,000km (at no cost) inspection, 15,000km then every 15,000km or 12 months, whichever comes first.  Holden Dealer 'Tech 2' computerised analysis available for engine management system										
			Tor engine management sy	Stelli							
	*Figures as per ECE regulat		hasa fauras are consider la	a aggist view in	ing the fuel						
	consumption of Captiva w	ption figures based on ADR 81/01 tests. These figures are provided to assist you in comparing the fuel of Captiva with other vehicles. The actual fuel consumption will depend, however, on many factors, r driving habits, the prevailing conditions and your vehicle's equipment, condition and use									

			ext	erior	colou	rs					seating	AND GENERAL AND ADDRESS OF THE PARTY OF THE	trim C			leather trim Charcoal
1	model		Arctic White	Mercury Silver*	Granada Black *	Merlot *	Midnight Blue *	Zest*	Chino *	Silverstone Grey *		n n n	= ; n :		0 0 0 0	
		SX	•	•	•	•	•	•	•		cloth	_				
		CX	•	•	•	•	•	•	•		cloth	=	= :	= =	=	
		LX	•	•	•	•	•	•	•		leather	=	3	= =	=	
	1	MaXX		•	•	•	•		•	•	leather				着立	
			dır	nensi	ons (r	nm)										
SX, CX, LX							6_	4637			1720	\$\frac{1}{2}\$	2111			1572
MaXX								4570			1700		208			1572
			5 s s	seats \$	SX, Ma	axx						7 s	seats CX,	LX		



## exterior colours







Mercury Silver\*



Granada Black\*



Merlot\*







Zest\*



Chino\*



Silverstone Grey\*

Variations between colours shown and actual paint colours/interior trim colours may occur due to the printing process. Actual vehicle colours may appear different under certain light conditions. Trim patterns are not to scale. Indicative only.

A word about this catalogue. We have tried to make this catalogue as comprehensive and factual as possible. However, since the time of printing some of the information you'll find here may have been updated. Also, some of the equipment shown or described through this catalogue may have been changed and / or is available at extra cost. Further, GM Holden Ltd, reserves the right to make changes at any time without notice, in prices, colours, materials, equipment and models. Your Holden Dealer has details, and before ordering, you should ask them to bring you up to date. No Holden Dealer or other person is authorised or permitted to give or make any statement, assertion or undertaking in relation to the quality, performance characteristics, descriptions or fitness for any purpose of any Holden product which is at variance with any written statement, assertion or undertaking on any of these subjects given or made by GM Holden Ltd ABN 84 006 893 232 in its published sales literature, and GM Holden Ltd does not accept any liability for any such unauthorised action. GM Holden Ltd has authorised dealers in many parts of Australia for the sale of service parts and the provision of service to owners of Holden's products. Every endeavour is made to ensure that such dealers carry adequate stocks of service parts, but GM Holden Ltd doesn't make any promise other than that contained in the New Vehicle Warranty given by GM Holden Ltd that such parts or service facilities will be available at any specific location or at any particular time. Express warranties offered for Holden products are subject to the conditions set out in all vehicle handbooks. Details also available from GM Holden Ltd on request. Copyright GM Holden Ltd. July 2006. emerystudio CAPTFL0706 AD12099

<sup>\*</sup> Metallic or Mica paints are available at an additional cost