

Features	LI	L2
BODYSTYLE		
Standard length van (L1)	•	
Extended length van (L2)		•
SAFETY		
Driver airbag	•	•
Passenger airbag	0	0
ABS with Electronic Brake Force Distribution (EBFD)	•	•
Emergency Brake Assist (EBA)	•	•
Electronic Stability Program (ESP)	0	0
Retractable steering column	•	•
Pretensioning and force limiting outer front seatbelts	•	•
Height adjustable front seatbelts	•	•
Driver seat belt warning alarm	•	•
Automatic door unlocking in accident	•	•
Automatic activation of hazard lights under emergency braking	•	•
Driver ladder frame protector	•	•
Half height steel bulkhead with removable mesh grille	0	0
SECURITY		
3 button remote for separate cab and cargo area locking	•	
Internal central locking of cab and cargo area		
Rolling code transponder immobiliser		
Visible VIN		
Automatic locking doors (activated by vehicle moving)		
Security coded audio system		
Locking fuel filler cap		
-		
Door ajar warning Very in ignition leads warning alarm		
Key in ignition lock warning alarm		
COMFORT AND CONVENIENCE		
Cruise control + speed limiter	•	•
Speed sensitive power steering	•	
Remote control central locking	•	•
Electronic parking assistance (rear)	0	0
Location of car via plip	•	•
Electric windows	•	
Height and reach adjustable steering wheel	•	•
Driver foot rest	•	
Electrically operated and heated door mirrors	•	•
Tinted glass	•	•
IN-CAR ENTERTAINMENT AND COMMUNICATION		
RD4 radio / CD player	•	•
Speed related volume controls	•	•
Digital 'head up' display separate from stereo unit	•	•
Remote audio controls on steering column	•	•



Features	LI	L2
IN-CAR ENTERTAINMENT AND COMMUNICATION (cont)		
Bluetooth capability	0	0
HEATING AND VENTILATION		
Air conditioning	•	•
INSTRUMENTS		
Speedometer with digital odometer and digital trip recorder	•	•
Rev counter	•	•
Water temperature and fuel gauges	•	•
Oil level gauge	•	•
Distance to next service indicator	•	•
Trip computer	•	•
External temperature gauge	•	•
INTERIOR FEATURES		
Front door stowage bins	•	•
Overhead driver and passenger storage compartments	•	•
Storage drawer under driver's seat	•	•
Courtesy light with delay	•	•
Rear cargo area light	•	•
Driver's armrest	•	•
Centre console storage bin	•	•
Driver's side glove box	•	•
Driver and passenger sunvisors with ticket holders	•	•
12V accessory power point in centre console	•	•
Dash mounted gear stick	•	•
6 tie down hooks in cargo area	•	•
Lower side protection in cargo area	•	•
EXTERIOR FEATURES		
15" steel wheels	•	•
Black bumpers and side rubbing strips	•	•
Panel sides, rear section		•
Left side sliding door	0	•
Right side sliding door	Oı	•
Twin glazed rear barn doors	•	•
Metallic paint	0	0
EXTERIOR LIGHTING AND VISIBILITY		
Double optic halogen headlights	•	•
Rear fog light	•	•
Remote headlight beam adjustment from fascia		•
Lights on warning alarm	•	•
High level third brake light	•	•
Intermittent rear wiper	•	•
Intermittent windscreen wipers	•	•



Features	LI	L2
SEATING		
Reclining front seats		•
Height adjustment of driver's seat	•	•
Height adjustable front head restraints	•	•
Passenger seat with fold down backrest with integrated cup holders	•	•
Multi Flex modular dual passenger seat	0	0
Cloth trim	•	•

O = optional

● = standard

1. Only available in conjunction with left side sliding door option



Technical Data	L1 1.6	LI 1.6 HDi (55)	LI 1.6 HDi (66)	L2 1.6 HDi (66)
ENGINE				
Туре	1.6-litre petrol	1.6-litre turbo diesel	1.6-litre turbo diesel	1.6-litre turbo diesel
Cylinders	4	4	4	4
Cubic capacity (cc)	1587	1560	1560	1560
Bore x Stroke (mm)	78.5 x 82	75 x 88.3	75 x 88.3	75 x 88.3
No. of valves	16	16	16	16
Max power (kW @ rpm)	66 @ 5800	55 @ 4000	66 @ 4000	66 @ 4000
Max torque (Nm @ rpm)	132 @ 2500	185 @ 1750	215 @ 1750	215 @ 1750
Induction	Electronic	Turbo diesel	Turbo diesel	Turbo diesel
Emission standard	Euro 4	Euro 4	Euro 4	Euro 4
TRANSMISSION				
Transmission type	5 man	5 man	5 man	5 man
PERFORMANCE				
Maximum speed (km/h)	160	150	160	160
Acceleration 0-100km/h (sec)	17.5	19.6	16.3	16.3
0-1000m (sec)	38.3	39.5	37.3	37.3
WHEELS AND TYRES				
Size	195/65 R15	195/65 R15	195/65 R15	195/65 R15
Wheel type	15" steel	15" steel	15" steel	15" steel
Full size spare wheel	•	•	•	•
FUEL TANK				
Capacity (1)	60	60	60	60
BRAKES				
Ventilated front discs	•	•	•	•
Rear discs	•	•	•	•
ABS with Electronic Brake Force Distribution	•	•	•	•
Emergency Brake Assist	•	•	•	•
STEERING				
Speed sensitive power steering	•	•	•	•
Turns lock to lock	2.89	2.89	2.89	2.89
Turning circle between kerbs (m)	11.0	11.0	11.0	11.0
SUSPENSION				
Front		Pseudo Macpershon type with lower wishbone struts, coil springs, telescopic hydraulic dampers and anti roll bar		
Rear	Deformable axle	Deformable axle with coil springs, telescopic hydraulic dampers and anti roll bar		



Technical Data	LI 1.6	LI 1.6 HDi (55)	LI 1.6 HDi (66)	L2 I.6 HDi (66)
WEIGHTS				
Gross train weight (kg)	2935	2935	3135	3130
Gross vehicle weight (kg)	2185	2185	2185	2130
Kerb weight (kg)	1413	1411	1411	1459
Maximum braked trailer towing weight (kg)	750	750	950	1000
Payload (kg)	850	850	850	750
DIMENSIONS				
Length (mm)	4380	4380	4380	4628
Width excluding mirrors (mm)	1810	1810	1810	1810
Width including mirrors (mm)	2112	2112	2112	2112
Height (mm)	1834	1834	1834	1834
Wheelbase (mm)	2728	2728	2728	2728
CARGO AREA				
Volume (m³)	3.3	3.3	3.3	3.7
Volume with optional Multi Flex seat (m³)	3.7	3.7	3.7	4.1
Maximum load height (mm)	1250	1250	1250	1250
Maximum load width no sliding doors (mm)	1620	1620	1620	
Maximum load width two sliding doors (mm)	1500	1500	1500	1500
Width between wheel arches (mm)	1229	1229	1229	1229
Load floor length (mm)	1800	1800	1800	2050
Load floor length with Multi Flex seat, folded, to 10cm height (mm)	3000	3000	3000	3250
Rear door loading height (mm)	1148	1148	1148	1148
Rear door loading width maximum (mm)	1250	1250	1250	1250
Rear door loading width at floor (mm)	1230	1230	1230	1230
Rear door loading width at roof (mm)	1100	1100	1100	1100
Side door loading width min / max (mm)	640 / 737	640 / 737	640 / 737	640 / 737
Side door loading height min / max (mm)	1100 / 1192	1100 / 1192	1100 / 1192	1100 / 1192
Height of load sill (mm)	609	609	609	612
CONSUMPTION AND EMISSIONS				
City cycle (1 / 100km)	10.8	7.0	7.0	7.0
II: -l				
Highway cycle (1 / 100km)	6.8	5.1	5.1	5.1
Combined cycle (1 / 100km)	6.8 8.2	5.1 5.8	5.1 5.8	5.1 5.8

= standard O = optional

Peugeot Automobiles Australia offers this information as a general guide to product specifications. All data is believed to be correct as at May 2009, however, as development is an ongoing process, changes may occur from time to time which will not necessarily reflected herein. Therefore, Peugeot Automobiles Australia reserves the right to change specifications without notice. Accordingly, this information should not be regarded as an infallible guide to correct specifications, nor does it constitute an offer for sale of any particular vehicle. Dealers are not agents of Peugeot Automobiles Australia and have absolutely no authority to bind Peugeot Automobiles Australia by an express or implied undertaking or representation. Peugeot Automobiles Australia is the trading name of Sime Darby Automobiles Pty. Ltd. (ACN 000 426 282).