

HiLux 4x2. Action Utility Vehicle.





4x2 Single Cab SR model shown.

Power and presence.

The Toyota HiLux is bigger, better and stronger than ever before. It's the versatile ute that is an Action Utility Vehicle (AUV). It's unbreakable workhorse meets off-road action lifestyle! Boasting impressive power across the range, inspiring performance and handling, comfort, and fabled HiLux reliability and dependability, it's got the performance you want and the toughness you've come to expect. Available in three versatile model variations (WorkMate, SR, & SR5), it's the ute of choice for drivers who want it all. So, when the weekend comes, it can trade wheelbarrows for trail bikes and take your weekend into high gear.

Work safe in HiLux.

Hilux is thankfully big on safety as well. It has been designed for outstanding crash performance to the toughest Australian and European standards. You'll breathe easier with dual SRS airbags and pretensioning seatbelts. In addition, ABS brakes are optional on SR and WorkMate models. The Hilux also has an energy absorbing front body/chassis structure and a strong Safe-T-Cell, to help keep the cabin intact during a collision. It's just another way that Hilux will further strengthen its 'unbreakable' reputation.



TECHNICAL SPECIFICATIONS			SING	LE CAB		XTR	A CAB		DOUBLE CAB						
HILUX 4x2		WorkMate		SR		SR	SR5	WorkMate	S	R	SR5				
		Cab Chassis	Cab (Chassis	Pickup	Pickup	Pickup	Pickup	Pic		Pickup				
		Petrol	Petrol	Turbo Diesel	Petrol	Petrol	Petrol	Petrol	Petrol	Turbo Diesel	Petrol				
/ECHANICAL									A/T M/T						
.7L Twin Cam VVT–i 4 cylii	linder Petrol engine	S	-	-	-	-	-	S	-	-	-				
ı.OL V6 Twin Cam VVT–i Pe	Petrol engine	-	S	-	S	S	S	-	S	-	S				
OL EDI Twin Cam Turbo D	Diesel engine	-	-	S	-	-	-	-	-	S	-				
5–Speed Manual Transmis	ission	S	S	S	S	-	-	S	S	S	S				
5-Speed Auto Transmissio	ion with AI Shift Control	-	0	-	0	S	S	-	0	-	0				
DIMENSIONS (*1)															
Overall Length (mm)			4975		5130	5130	5255		5130		5255				
verall Width (mm)						17	60								
verall Height (mm)			16	580		16	80		16	95					
Vheelbase (mm)			30	085		30	85		30	185					
rack – Front / Rear (mm)	1)		15	510		15	10		15	10					
Ground Clearance (mm)	,					1	77								
lverhang – Front			8	385		8	85		81	85					
verhang – Rear			1005		1160	1160	1160	1160	1160 1285	1160	1160				
ngle of approach			2	21°		2	10			1°					
ngle of departure				20°		20°	18°		20°		18°				
ray Length (mm)			-		2315		05		15	20					
ray Width (mm)			_		1520		15			i15					
ay Height (mm)			_		450		50			50					
EHICLE WEIGHTS & CAP	APACITIES														
erb Weight – Manual (kg		1450 ~	1480 ~	1560 ~	1490 ~	_	_	1535 ~	1565 ~	1665 ~	1570 ~				
-10 Treignt manual (Kg	15/1.4/	1520	1525	1620	1530			1580	1605	1680	1605				
Cerb Weight – Automatic (c (kg) (*2)	-	1510 ~	-	1520 ~	1550 ~	1550 ~	-	1595 ~	-	1595 ~				
	. 0/ . /		1550		1560	1585	1600		1630		1635				
ross Vehicle Mass (kg)		28	320	2875	2820	27	40		27	10					
lax. front axle capacity (k	(kg)		25	1125	1125		00		12						
lax. rear axle capacity (kg	1 0/	17	50	1750	1750	16	95		15	50					
ross Combined Mass (kg)						46	00								
owing capacity – with tra	27.1					22	50								
	ut trailer brakes (kg) (*4)					7	50								
		3	3	3	3	-	-	6	5	5	5				
eating capacity – including driver – Manual trans		_	2	_	2	4	4	_	5	_	5				
	ling driver – Auto trans	_													
eating capacity – includir uel tank capacity (litres) TEERING ype urning Circle		_				Power Assisted	Rack and Pinion								
eating capacity — including eating capacity — including eating capacity (litres) ITEERING TYPE TYPE TYPE TYPE TYPE TYPE TYPE TYPE		_				Power Assisted 1 Vacuum boosted	Rack and Pinion								
eating capacity — includir uel tank capacity (litres) TEERING ype urning Circle IRAKES ystem ront		_				Power Assisted To Vacuum boosted Ventilated	Rack and Pinion .8 hydraulic system								
eating capacity — includir uel tank capacity (litres) TEERING ype urning Circle RAKES ystem ront ear nti-skid Braking System	5)	_		Option		Power Assisted To Vacuum boosted Ventilated	Rack and Pinion .8 hydraulic system disc brakes	Option (*12)	Opi	tion	Standar				
eating capacity — including uel tank capacity (litres) TEERING Type Type Type Type Type Type Type Type	5)			Option		Power Assisted To Vacuum boosted Ventilated	Rack and Pinion .8 hydraulic system disc brakes ting drum	Option (*12)	Opt	tion	Standar				
eating capacity — includir uel tank capacity (litres) TEERING ype urning Circle RAKES ystem ront ear nti-skid Braking System	5)				Double wishbone type	Power Assisted 1 Vacuum boosted Ventilated Self adjus	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard			tion	Standar				
eating capacity — including the capacity (litres) TEERING TEERING TO THE CITCLE THE CAPACITY (litres) TEERING TO THE CITCLE THE CAPACITY (litres) TEERING TO THE CAPACITY (litres) THE CAPACITY (litre	5)					Power Assisted 1 Vacuum boosted Ventilated Self adjus	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard	ers and stabiliser		tion	Standar				
eating capacity — including the lank capacity (litres) TEERING TEERING TEERING TO THE LANG TO THE	5)					Power Assisted 1 Vacuum boosted Ventilated Self adjus	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort	ers and stabiliser		tion	Standar				
eating capacity — including the lank capacity (litres) TEERING TEERING TO THE LANG THE LA	5)		205/TORTSC			Power Assisted 1 Vacuum boosted Ventilated Self adjus	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort	ers and stabiliser		tion 205/70R/ISC					
eating capacity — including lating capacity — including latink capacity (litres) rEERING rpe graming Circle RAKES sstem ont ear atti-skid Braking System i ISPENSION rpe Front Rear HEELS	5)		205/TORTSC 6.0JJx15		Leaf sprii	Power Assisted 1 Vacuum boosted Ventilated Self adjuster e with coll springs, gong type rigid axle w	Rack and Pinion 8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock al	ers and stabiliser Isorbers	bar		205/70R1				
ating capacity — including el tank capacity (litres) EERING pe ming Circle **RAKES** stem ont ar **tir-skid Braking System** ISPENSION pe Front Rear HEELS res heels	5)	195R14C 5-5JJx14 steel	6.0JJx15 steel	205/70R15C	Leaf sprii 205/70R15C	Power Assisted 1 Vacuum boosted Ventilated Self adjusted with coil springs, going type rigid axle was a specific axle was	Rack and Pinion 8 hydraulic system disc brakes ting drum Standard as filled shock absorb ith gas filled shock at 205/70R15C	ers and stabiliser sorbers 195R14C	205/70R15C 6.0JJx15 steel	205/70R15C 6.0JJx15 steel	205/70R1 6.0JJx1				
ating capacity — including lel tank capacity (litres) FEERING pe Imming Circle RAKES Stem Ont ara It-skid Braking System ISPENSION pe Front Rear HEELS FEES heels	5)	195R14C 5.5JJx14	6.0JJx15 steel	205/70R15C 6.0JJx15	Leaf sprii 205/70R15C 6.0JJx15	Power Assisted Vacuum boosted Ventilated Self adjuste with coll springs, go the good of the self adjusted to t	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70R15C 6.0JJX15	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel	205/70R15C 6.0JJx15	205/70R1 6.0JJx1				
rating capacity — including lating capacity — including lating capacity (litres) rEERING repe	5)	195R14C 5-5JJx14 steel	6.0JJx15 steel PETROL	205/70R15C 6.0JJx15	Leaf sprii 205/70R15C 6.0JJx15	Power Assisted 1 Vacuum boosted Ventilated Self adjust e with coil springs, song type rigid axle w 205/TORTSC 6.0JJX15 Steel	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70R15C 6.0JJX15	ers and stabiliser isorbers 195R14C 5.5JJX14	bar 205/70R15C 6.0JJx15 steel TUR	205/70R15C 6.0JJx15 steel	205/70R1 6.0JJx1				
eating capacity — including let tank capacity (litres) FEERING IPPE I	n (ABS)	195R14C 5.5JJx14 steel 4 CYLINDER I	6.0JJx15 steel PETROL valves per cylinder	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v	Power Assisted Vacuum boosted Ventilated Self adjust with coil springs, go the good of the self adjust 205/T0R15C 6.0JJX15 steel V6 PETROL	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70R15C 6.0JJX15 alloy (4)*	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70RI5C 6.0JJx15 steel TUR 1 4 Cylinder in-li per cylinder, int	205/70R15C 6.0JJx15 steel IBO DIESEL	205/70R1 6.0JJx1! alloy (4				
ating capacity — including capacity — including lateral per	n (ABS)	195RI4C 55JIxI4 steel 4 CYLINDER I 2TR-FE	6.0JJX15 steel PETROL valves per cylinder i intelligence (WT-	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valve	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0RISC 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JJXI5 alloy (4)* inder with gence (WT-i)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in-lin per cylinder, int- direc	205/70R15C 6.0JJx15 steel 4BO DIESEL KD-FTV ne DOHC with 4 valvercooler and electro	205/70R1 6.0JJx1 alloy (4				
ating capacity — including lating capacity — including lating capacity (litres) FERING pe Imming Circle RAKES Steem John RAKES Steem John SPENSION PE Front Rear HEELS Tres Theels MGINE John J	n (ABS)	195R14C 55JJx14 steel 4 CYLINDER IF n-line DOHC with 4 e Valve Timing with	6.0JJX15 steel PETROL valves per cylinder i intelligence (WT-	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi	Power Assisted Vacuum boosted Ventilated Self adjust with coil springs, g ng type rigid axle w 205/70R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy Timing with intell	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JIXI5 alloy (4)* inder with gence (VVT-i)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, int- dire- Electronic Direct	205/70R15C 6.0JJx15 steel IBO DIESEL KD-FTV Her DOHC with 4 valv ercooler and electro	205/70R1 6.0JJx1 alloy (4				
ating capacity — includirel tank capacity (litres) rEERING pe Iming Circle RAKES stem John This stand Braking System ISPENSION Pe Front Rear HEELS res heels HEELS res HEELS res HEELS HEELS Front Rear HEELS Res HEELS Front Rear HEELS Front HEELS Fron	n (ABS)	195R14C 55JIx14 steel 4 CYLINDER I 0-line DOHC with 4 e Valve Timing with	6.0JJX15 steel PETROL valves per cylinder i intelligence (WT-	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi	Power Assisted 1 Vacuum boosted Ventilated Self adjust with coil springs, g ng type rigid axle w 205/70R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JIXI5 alloy (4)* inder with gence (VVT-i)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, int- dire- Electronic Direct	205/70R15C 6.0JJx15 steel BO DIESEL KD-FTV ne DOHC with 4 valv ercooler and electro ct injection, Common	205/70R 6.0JJx1 alloy (4				
aating capacity — including lating capacity — including lating capacity (litres) FEERING TEERING TE	n (ABS)	195R14C 5.5JJx14 steel 4 CYLINDER I 7 = Telline DOHC with 4 e Valve Timing with Electronic Fuel Unleaded P 2694 95.0 x 99	6.0JJx15 steel PETROL valves per cylinder i intelligence (WT-	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi	Power Assisted Vacuum boosted Ventilated Self adjust e with coil springs, g ng type rigid axle w 205/70R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JIXI5 alloy (4)* inder with gence (VVT-i)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in-li per cylinder, int dire Electronic Direct	205/TOR15C 6.0JJx15 steel BOD DIESEL KD-FTV ne DOHC with 4 vale recrooler and electric ct injection Injection, Common Diesel 2982 5.0 x 103.0	205/70R 6.0JJx1 alloy (4				
ating capacity — including capacity — including let tank capacity (litres) FERRING PERRING PERRING PERRING FORT FORT FORT HEELS THEELS THEEL	n (ABS)	195R14C 5.5JJx14 steel 4 CYLINDER I 7 Teline DOHC with 4 e Valve Timing with Electronic Fuel Unleaded P 2694 95.0 x 99 9.6:1	6.0JJx15 steel PETROL valves per cylinder intelligence (WT- Injection etrol	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, goog type rigid axle w 205/70R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cye Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1" 3956 94.0 x 95.0 10.0:1	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JIXI5 alloy (4)* inder with gence (VVT-i)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in–li per cylinder, int diret Electronic Direct	205/TOR15C 6.0JJx15 steel BIO DIESEL KD-FTV ne DOHC with 4 valve injection, Common Diesel 2982 5.0 x 103.0 17.9.1	205/70R 6.0JJx1 alloy (4				
ating capacity — including capacity — including lateral capacity — including lateral capacity (litres) FERING pe Imministrate FRAKES Stem Including Circle FRAKES FROTE Rear HEELS FROTE FR	n (ABS) 4 Cylinder i Variabl	195RI4C 55JJx14 steel 4 CYLINDER I — Inne DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 95 9.6:1 118 / 520	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT- Injection Petrol	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi	Power Assisted Vacuum boosted Ventilated Self adju: with coil springs, g ng type rigid axle w 205/T0R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell unleaded Petrol (*1" 3956 94.0 x 95.0 10.0:1 175 / 5200	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JIXI5 alloy (4)* inder with gence (VVT-i)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in–li per cylinder, int diret Electronic Direct	205/TOR15C 6.0JJx15 steel BOD DIESEL KD-FTV ne DOHC with 4 vale recrooler and electric ct injection Injection, Common Diesel 2982 5.0 x 103.0	205/70R1 6.0JJx1 alloy (4				
ating capacity — includir el tank capacity — includir el tank capacity (litres) EERING pe ming Circle **TAKES** **Sterm ont ar tti-skid Braking System i SPENSION pe Front Rear HEELS **Tees neels GINE me pe el System el Type splacement (cc) re and Stroke (mm) mpression Ratio ax. Power (kWirpm) (*5) **Tees **Tees	1 (ABS) 4 Cylinder i Variabl	195R14C 5.5JJx14 steel 4 CYLINDER I 7 Teline DOHC with 4 e Valve Timing with Electronic Fuel Unleaded P 2694 95.0 x 99 9.6:1	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT- Injection Petrol	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi	Power Assisted Vacuum boosted Ventilated Self adju: with coil springs, g ng type rigid axle w 205/70R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1" 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto)	hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70R15C 6.0JJX15 alloy (4)* inder with gence (VVT-i) on)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in–li per cylinder, int diret Electronic Direct	205/TOR15C 6.0JJx15 steel BIO DIESEL KD-FTV ne DOHC with 4 valve injection, Common Diesel 2982 5.0 x 103.0 17.9.1	205/70R1 6.0JJx1 alloy (4				
ating capacity — includir el tank capacity — includir el tank capacity (litres) EERING pe ming Circle **TAKES** **Sterm ont ar tti-skid Braking System i SPENSION pe Front Rear HEELS **Tees neels GINE me pe el System el Type splacement (cc) re and Stroke (mm) mpression Ratio ax. Power (kWirpm) (*5) **Tees **Tees	1 (ABS) 4 Cylinder i Variabl	195RI4C 55JJx14 steel 4 CYLINDER I — Inne DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 95 9.6:1 118 / 520	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT- Injection Petrol	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi	Power Assisted Vacuum boosted Ventilated Self adju: with coil springs, g ng type rigid axle w 205/T0R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell unleaded Petrol (*1" 3956 94.0 x 95.0 10.0:1 175 / 5200	hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70R15C 6.0JJX15 alloy (4)* inder with gence (VVT-i) on)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in–li per cylinder, int diret Electronic Direct	205/TORISC 6.0JJx15 steel BOD DIESEL KD-FTV ne DOHC with 4 value rect injection, Common Diesel 2982 6.0 x 103.0 17.9:1 166 / 3600	205/70R 6.0JJx1 alloy (4				
ating capacity — includir el tank capacity (litres) EERING pe rming Circle **TAKES** stem ont ar ti-skid Braking System SPENSION pe Front Rear HEELS res seels dGINE me el Type splacement (cc) re and Stroke (mm) mpression Ratio ax. Torque (Nm/rpm) (*5) ax. Torque (Nm/rpm) (*5) ax. Torque (Nm/rpm) (*5)	1 (ABS) 4 Cylinder i Variabl 5)	195RI4C 55JJx14 steel 4 CYLINDER I — Inne DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 95 9.6:1 118 / 520	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT- Injection 6.0 00 00	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto) 8 / 2400—4800 (man	hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70R15C 6.0JJX15 alloy (4)* inder with gence (VVT-i) on)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, into direct Electronic Direct 12 343 /	205/TORISC 6.0JJx15 steel BOD DIESEL KD-FTV ne DOHC with 4 value rect injection, Common Diesel 2982 6.0 x 103.0 17.9:1 166 / 3600	205/70Ri 6.0JJx1 alloy (4 ves pnic Rail				
ating capacity — includir el tank capacity — includir el tank capacity (litres) EERING pe ming Circle **AKES** stem ont ar ar tit-skid Braking System I SSPENSION pe Front Rear HEELS res sheels IGINE ume el Type splacement (cc) rer and Stroke (mm) mpression Ratio ax. Torque (Nm/rpm) (*5) ax. Torque (Nm/rpm) (*5) RIVETRAIN	1 (ABS) 4 Cylinder in Variable (Variable (Var	195RI4C 55JJx14 steel 4 CYLINDER 2TR-FI n-line DOHC with 4 e Valve Timing with Electronic Fuel Unleaded P 2694 95.0 x 9 9.6.1 118 / 52C 241 / 380	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT- Injection Petrol 5.0 00 7 ransmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valve El	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto) 8 / 2400—4800 (man	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70R15C 6.0JJX15 alloy (4)* inder with gence (VVT-i) on)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, into direct Electronic Direct 12 343 /	205/TOR15C 6.0JJx15 steel BO DIESEL KD-FTV ne DOHC with 4 valvercooler and electroct injection Injection, Common Diesel 2982 10 x 103.0 17.9:1 16 / 3600	205/70R 6.03Jx1 alloy (4 ves pric Rail				
ating capacity — including lating capacity — including lating capacity — including lating capacity (litres) FERING PERING PERING PERING PRAKES Stem Ont TITISH STATE — INCLUDING SYSTEM I	1 (ABS) 4 Cylinder i Variabl 5)	195RI4C 5-5JJx14 steel 4 CYLINDER I 2TR-FE n-line DOHC with 4 e Valve Timing with Unleaded F 2694 95.0 x 95 9.6:1 118 / 52C 241 / 380	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT- Injection Petrol 5.0 00 7 ransmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi El	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto) 8 / 2400—4800 (man	hydraulic system disc brakes ting drum Standard Standard Standard Standard Standard Standard Standard Sold Shock absorb tith gas filled shock absorb tith gas filled shock at 205/70R15C 6.0JJX15 alloy (4)* inder with gence (WT-i) on)	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, into direct Electronic Direct 12 343 /	205/TORISC 6.0JJx15 steel BO DIESEL KD-FTV ne DOHC with 4 valvercooler and electroct injection Injection, Common Diesel 2982 6.0 x 103.0 17.9.1 126 / 3600 11.1400—3400 nual Transmission	205/70Ri 6.0JJx1 alloy (4 ves pnic Rail				
ating capacity — including lating capacity — including latink capacity (litres) FERING pe Imming Circle FARKES Satem Including System in its skid Braking System in its skid Brak	1 (ABS) 4 Cylinder i Variabl 5) 5)	195RI4C 55JIx14 steel 4 CYLINDER I 2IR-FE n-line DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 9 9.6.1 118 / 52(241 / 380	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT- Injection Petrol 5.0 00 7 ransmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJX15 steel V6 DOHC v Variable Valve Eli 5-Speed Manua 3.830	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto) 8 / 2400—4800 (man	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JJXI5 alloy (4)* inder with gence (VVT-i) on) Speed Automatic 3.520	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, into direct Electronic Direct 12 343 /	205/TORISC 6.0JJx15 steel BO DIESEL KD-FTV ne DOHC with 4 valvercooler and electroctroin Injection, Common Diesel 2982 6.0 x 103.0 17.9:1 16/13600 11400–3400 nual Transmission 4.313	205/70Ri 6.0JJx1 alloy (4 ves pnic Rail				
eating capacity — including let tank capacity (litres) ITEERING	4 Cylinder i Variabl	195RI4C 55JIx14 steel 4 CYLINDER I 2TR-FE n-line DOHK with 4 e Valve Timing with Electronic Fuel Unleaded P 269 49 95.0 x 9 9.6.1 118 / 52C 241 / 380	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT- Injection Petrol 5.0 00 7 ransmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJX15 steel V6 DOHC v Variable Valve El. 343 5-Speed Manua 3.830 2.062	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto) 8 / 2400—4800 (man	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JJX15 alloy (4)* inder with gence (VVT-i) on) Speed Automatic 3.520 2.042	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, into direct Electronic Direct 12 343 /	205/70R15C 6.0JJx15 steel BO DIESEL KD-FTV me DOHC with 4 valvercooler and electro ct injection, Common Diesel 2982 6.0 x 103.0 117.9:1 16/ 3600 1400-3400 nual Transmission 4.313 2.330	205/70Ri 6.0JJx1 alloy (4 ves pnic Rail				
eating capacity — including let tank capacity (litres) ITEERING	to (ABS) 4 Cylinder in Variable (Variable in Variable	195R14C 55JJx14 steel 4 CYLINDER I n-line DOHC with 4 e Valve Timing with Electronic Fuel Unleaded P 2694 95.0 x 99 9.6.1 118 / 52C 241 / 380 5-Speed Manual T 3.830 2.062 1436	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT- Injection Petrol 5.0 00 00 Transmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi Eli 5-Speed Manua 3.830 2.062 1.436	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto) 8 / 2400—4800 (man	hydraulic system disc brakes ting drum Standard Standard Standard 205/70RI5C 6.0JJX15 alloy (4)* inder with gence (VVT-i) on) Speed Automatic 3.520 2.042 1.400	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, into direct Electronic Direct 12 343 /	205/70R15C 6.0JJx15 steel BO DIESEL KD-FTV nen DOHC with 4 valvercooler and electro ct injection, Common Diesel 2982 6.0 x 103.0 17.9:1 166 / 3600 17400-3400 nual Transmission 4.313 2.330 1.436	205/70Ri 6.0JJx1 alloy (4 ves pnic Rail				
ating capacity — including lating capacity — including latink capacity (litres) FERING PERING PERING PERING FORT FORT REAR HEELS FES HEELS	1 (ABS) 4 Cylinder i Variabl 5) 5) r ar ar ar	195RI4C 55JJx14 steel 4 CYLINDER IF n-line DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 99 9.6:1 118 / 520 241 / 380 2.062 1436 1.000	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT-i Injection Petrol 5.0 00 00 Transmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJX15 steel V6 DOHC v Variable Valvi Eli 5-Speed Manua 3.830 2.062 1.436 1.000	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto) 8 / 2400—4800 (man	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JJX15 alloy (4)* inder with gence (WT-i) on) Speed Automatic 3.520 2.042 1.400 1.000	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, into direct Electronic Direct 12 343 /	205/70R15C 6.0JJx15 steel BO DIESEL KD-FTV nee DOHC with 4 valvercooler and electro ct injection, Common Diesel 2982 6.0 x 103.0 17.9:1 166 / 3600 17400—3400 nual Transmission 4.313 2.330 1.436 1.000	205/70Ri 6.0JJx1 alloy (4 ves pnic Rail				
ating capacity — including lating capacity — including latink capacity (litres) FERING PERING PERING PERING FORT FORT FORT HEELS Tes Tes Tes Tes Tes Tes Tes Te	1 (ABS) 4 Cylinder i Variabl 5) 5) r ar ar ar	195R14C 55JJx14 steel 4 CYLINDER I — line DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 99 9.6:1 118 / 520 241 / 380 3.830 2.062 1.436 1.000 0.838	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT-i Injection Petrol 5.0 00 00 Transmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi Eli 343 5-Speed Manua 3.830 2.062 1.436 1.000 0.838	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0RI5C 6.0JJx15 steel V6 PEIROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto) 8 / 2400—4800 (man	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard 205/70RI5C 6.0JJXI5 alloy (4)* inder with gence (WT-i) on) Speed Automatic 3.520 2.042 1.400 1.000 0.716	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 4 Cylinder in-lin per cylinder, into direct Electronic Direct 12 343 /	205/70R15C 6.0JJx15 steel BO DIESEL KD-FTV ne DOHC with 4 valvercooler and electro ct injection, Common Diesel 2982 .00 x 103.0 17.9:1 166 / 3600 11400–3400 nual Transmission 4.313 2.330 1.436 1.000 0.838	205/70Ri 6.0JJx1 alloy (4 ves pnic Rail				
eating capacity — including let tank capacity (litres) ITERING I	1 (ABS) 4 Cylinder i Variabl 5) 5) r ar ar ar	195R14C 55JJx14 steel 4 CYLINDER I 2TR-FE n-line DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 99 9.6:1 118 / 520 241 / 38(5-Speed Manual T 3.830 2.062 14:36 1.000 0.838 4.220 4.100	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT— Injection betrol 5.0 00 7ransmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valva Eli 5-Speed Manua 3.830 2.062 1.436 1.000 0.838 4.220	Power Assisted Vacuum boosted Ventilated Self adjus with coil springs, g ng type rigid axle w 205/T0RI5C 6.0JJx15 steel V6 PEIROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.0:1 175 / 5200 376 / 3800 (auto) 8 / 2400—4800 (man	Rack and Pinion 8 hydraulic system disc brakes ting drum Standard 205/70RI5C 6.0JIXI5 alloy (4)* inder with gence (WVT-i) on) Speed Automatic 3.520 2.042 1.400 1.000 0.716 3.224	ers and stabiliser isorbers 195R14C 5.5JJX14	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in-li per cylinder, int dire Electronic Direct 12 343 / 5-Speed Ma	205/70R15C 6.0JJx15 steel 80 DIESEL KD-FTV ne DOHC with 4 vale recooler and electro ct injection, Common Diesel 2982 .10 x 103.0 17.91 166 / 3600 1/1400–3400 nual Transmission 4.313 2.330 1.436 1.000 0.838 4.220	205/70Ri 6.0JJx1 alloy (4 ves pnic Rail				
eating capacity — including let tank capacity (litres) TEERING //pe Jaming Circle RAKES //stem Front Rear //HEELS //res //heels NGINE Jame //pe Juel System Juel System Juel Type Juel	4 Cylinder i Variabl 5) 1 r ar	195R14C 55JJX14 steel 4 CYLINDER I —Inne DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 99 9.61 118 / 520 241 / 380 2.062 1436 1.000 0.838 4.220 4.100 4 CYLINDER	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT-i Injection Petrol 5.0 00 Transmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valvi Eli 5-Speed Manua 3.830 2.062 1.436 1.000 0.838 4.220 3.583	Power Assisted Vacuum boosted Ventilated Self adjust e with coil springs, g ng type rigid axle w 205/70R15C 6.0JJx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Injecti Unleaded Petrol (*1' 3956 94.0 x 95.0 10.01 175 / 5200 376 / 3800 (auto) 37 / 2400-4800 (man 1 5-	Rack and Pinion 8 hydraulic system disc brakes ting drum Standard 205/70RI5C 6.0JJXI5 alloy (4)* inder with gence (WVT-i) on) Speed Automatic 3.520 2.042 1.400 1.000 0.716 3.224 3.583	ers and stabiliser sorbers 195R14C 5.5JJx14 steel	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in-lii per cylinder, int dire Electronic Direct 12 343 / 5-Speed Ma	205/70R15C 6.0JJx15 steel BO DIESEL KD-FTV ne DOHC with 4 vale recrooler and electro ct injection, Common Diesel 2982 .10 x 103.0 17.91 166 / 3600 1/1400–3400 nual Transmission 4.313 2.330 1.436 1.000 0.838 4.220 3.583 BO DIESEL	205/70R1 6.0JJx1 alloy (4) ves onic Rail				
eating capacity — including the lank capacity (litres) TEERING TEERING TEERING TOTAL TOT	(ABS) 4 Cylinder i Variabl 5) 7 ar ar ar ar ar ar Single (195R14C 55JJX14 steel 4 CYLINDER I —Inine DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 99 9.661 118 / 520 241 / 380 2.062 1436 1.000 0.838 4.220 4.100 4 CYLINDER I Cab	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT-i Injection Petrol 5.0 00 Transmission	205/70R15C 6.0JJx15 steel	Leaf sprii 205/70R15C 6.0JJx15 steel V6 DOHC v Variable Valva Eli 5-Speed Manua 3.830 2.062 1436 1.000 0.838 4.220 3.583 Single Cab	Power Assisted Vacuum boosted Ventilated Self adjust with coil springs, good springs, good steel volume to the steel vith 4 valves per cye Timing with intell ectronic Fuel Injecti Unleaded Petrol (*17 3956 94.0 x 95.0 10.01 175 / 5200 376 / 3800 (auto) 37 / 2400 - 4800 (man I) 5- V6 PETROL Extra	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock at 205/70RI5C 6.0JJXI5 alloy (4)* inder with gence (WVT-i) on) Speed Automatic 3.520 2.042 1.400 1.000 0.716 3.224 3.583	ers and stabiliser sorbers 195R14C 5.5JJx14 steel	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in-lii per cylinder, int dire Electronic Direct 12 343 / 5-Speed Ma	205/70R15C 6.0JJx15 steel BO DIESEL KD-FTV ne DOHC with 4 vale recrooler and electro ct injection, Common Diesel 2982 .10 x 103.0 17.91 16/ 3600 1/1400-3400 nual Transmission 4.313 2.2330 1.436 1.000 0.838 4.220 3.583 BO DIESEL Dou	205/70R1 6.0JJx!! alloy (4) ves onic Rail				
eating capacity — including uel tank capacity (litres) TEERING type urning Circle IRAKES system ront ear uspension USPENSION Teer WHEELS Wheels Wheels Wheels Wheels Wheels Wheels Wheels Wheels INTERING WHEELS Wheels Wheels Wheels Wheels Wheels INTERING WHEELS Wheels INTERING WHEELS Wheels INTERING WHEELS WH	an (ABS) 4 Cylinder i Variabl 5) 5) r ar ar ar ar e gear Single (Cab Cha	195R14C 55JJX14 steel 4 CYLINDER I —Inine DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 99 9.661 118 / 520 241 / 380 2.062 1436 1.000 0.838 4.220 4.100 4 CYLINDER I Cab	6.0JJX15 steel PETROL E valves per cylinder intelligence (WT-i linjection Petrol 00 00 Transmission PETROL Double Ca Pickup	205/70R15C 6.0JJx15 steel	Leaf sprii	Power Assisted Vacuum boosted Ventilated Self adjus e with coil springs, g ng type rigid axle w 205/70R15C 6.0Jx15 steel V6 PETROL 1GR-FE with 4 valves per cy e Timing with intell ectronic Fuel Inject Unleaded Petrol (*1 3956 94.0 x 95.0 1175 / 5200 376 / 3800 (auto) 376 / 3800 (auto) 37 / 2400 - 4800 (man I 5- V6 PETROL Extra kup Pickt	hydraulic system disc brakes ting drum Standard Standard Standard Standard Standard Standard Standard 205/70RI5C 6.0JJX15 alloy (4)* sinder with gence (VVT-i) on) Speed Automatic 3.520 2.042 1.400 1.000 0.716 3.224 3.583 Cab Double Calpp Pickup	ers and stabiliser sorbers 195R14C 5.5JJx14 steel	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in-lin per cylinder, int dire: Electronic Direct 343 / 5-Speed Ma TUR TUR 1 TUR	205/70R15C 6.0JJx15 steel BO DIESEL KD-FTV ne DOHC with 4 valvercooler and electro ct injection, Common Diesel 2982 50 x 103.0 17.9:1 16/3600 11400-3400 nual Transmission 4.313 2.330 1.436 1.000 0.838 4.220 3.583 BO DIESEL Doul	Rail n ble Cab				
eating capacity — including the lank capacity (litres) TEERING TEERING TEERING TOTAL TOT	ar ar ar e gear Single (Cab Cha al 11.2	195R14C 55JJX14 steel 4 CYLINDER I —Inine DOHC with 4 e Valve Timing with Electronic Fuel Unleaded F 2694 95.0 x 99 9.661 118 / 520 241 / 380 2.062 1436 1.000 0.838 4.220 4.100 4 CYLINDER I Cab	6.0JJx15 steel PETROL E valves per cylinder intelligence (WT-i Injection Petrol 5.0 00 Transmission	205/70R15C 6.0JJx15 steel	Leaf sprii	Power Assisted Vacuum boosted Ventilated Self adjust with coil springs, good springs, good steel volume to the steel vith 4 valves per cye Timing with intell ectronic Fuel Injecti Unleaded Petrol (*17 3956 94.0 x 95.0 10.01 175 / 5200 376 / 3800 (auto) 37 / 2400 - 4800 (man I) 5- V6 PETROL Extra	Rack and Pinion .8 hydraulic system disc brakes ting drum Standard as filled shock absort ith gas filled shock al 205/70RI5C 6.0JJXI5 alloy (4)* inder with gence (WT-i) on) Speed Automatic 3.520 2.042 1.400 1.000 0.716 3.224 3.583 Cab Double Ca up Pickup 12.6	ers and stabiliser sorbers 195R14C 5.5JJx14 steel	205/70R15C 6.0JJx15 steel TUR 1 4 Cylinder in-lii per cylinder, int dire Electronic Direct 12 343 / 5-Speed Ma	205/70R15C 6.0JJx15 steel BO DIESEL KD-FTV ne DOHC with 4 vale recooler and electro ct injection, Common Diesel 2982 .0 x 103.0 17.91 166 / 3600 17.9400 1838 4.220 3.583 180 DIESEL Dou Pi	205/70R1 6.0JJxI! alloy (4) ves onic Rail				

IMPORTANT NOTICE - PLEASE READ

Toyota Australia uses its best endeavours to ensure brochure information is correct when published. You must check with your authorised Toyota Dealer when ordering to ensure the vehicle with your chosen specifications, equipment and colour is available and that the vehicle can be delivered within a timeframe suitable to you. When ordering accessories, you must check with your authorised Toyota Dealer to ensure the accessory's design, features and colours are available and will fit your vehicle. Colours displayed in this brochure in a guide only and may vary from actual colours due to printing/display process. Toyota Australia respectively only a dustralia vehicle for any damage, loss or expense incurred as a result of reliance on this brochure in any way, "All Toyota Genuine Accessories purchased and fitted to a Toyota are warranted for the remainder of the New Vehicle Warranty or 12 months, whichever is greater. Toyota Genuine Accessories purchased from an authorised Toyota Dealer over the counter are warranted from the date of purchase for one year (unlimited kilometres). Conditions apply. All warranties are additional to the implied warranties under the Trade Practices Act 1974. Distributed nationally by Toyota Motor Corporation Australia Limited. ABN 64 009 686 097. Crr Gannons Rd & Captain Cook Drive, Caringbah, NSW 2229. Part No. TYHILUXZWD0508SV. Printed May 2008.

Work Wide Mark Sal Sal Sal Sal Water Work Work Water Sal Sal Sal Water Sal Sal Sal Water Sal	ATURES		SINGLE CAB		XTF CA			DOUBLE (:AB	
speciment hamper			WorkMate			SR5 V				SR5
youther bord bumper	(TERIOR	Mate	ABS option				Mate	ABS optio	n	
Type match impror	ck polypropelene front bumper	S	S	-	-	-	S	S	-	-
The final proper	dy Colour front bumper	-	-	S	S	S	-	-		
Marked M	rome step type rear bumper	-	_	_		S	-			
to headigified	p type rear bumper dy Colour radiator grille	_	_		_	5	_	2		
indicates S	lti-reflector headlights	S	S	S	S	S	S	S	S	
windows	nt fog lamps	-	-	-	-	S	-	-		
els with control comments S	ninated windscreen			-	-	-				
sets with control comments — \$\frac{1}{2}\tag{1}\triangle sets of the center of control	ted side windows Steel wheels with centre ornaments	9		2	2	2			_	
eeth (s)	Steel wheels with centre ornaments	-	S(*13)	S	S	-	-	S(*13)	S	-
Transe with Support Pickup S S S - Front draws from a minimum of the support of the supp	Alloy wheels (4)	-		-	-	S	-			
bar	are steel wheel	S		-		S				
Thankelle se immost	ck guard frame with stopper by Sports bar	_		PICKUP —	2	- c	2		_	
Section Sect	rome door handles & mirrors	_	_	_	_	S	_	_	_	
pt PTY	nt only mudflaps	S	S	C/C	-	-	-	-	-	-
int	nt & Rear mudflaps	-				S	-			
im	nnet Scoop (*7) tallic paint	-			-	2				
	h-up paint									
seat time	ERIOR									
at thim	eat trim	S	S			-	S			
Int coor trins	facing seat trim	-	-	S	S	-	-			
int door trins with doth inserts	th seat trim	- (2				
If filton covering	d front door trims with cloth inserts	_	S(*13)	S	S	S			S	
set steat	e vinyl floor covering	S	S	S	S(*13)		S	S	S	
set seat	carpet	-	-	-	-	S	-	-	-	S
passenger seat	ng 's bucket seat	c	C	c	c	c	c	C	c	c
Segret bucker seart	t bench passenger seat			-	-	_		-		
Packet P	passenger bucket seat	-	-	. ,	S	S	-	-	S	S
inig – single type O O O S O O S O O S Pickup Donly — hard Tonneau Cover – Rickup Donly — hard Tonneau Cover – Rickup Donly — and rear windows — S S S S S S S S S S S S S S S S S S S	rson capacity rear jump seat	-	-	-		-	-	-		
Integrating by type		_	-	_	_	_	S	S	S	S
Neater controls S S S S S S S S S	TURES	0	0	Λ	0	ς	0	Λ	0	ς
and fear windows	ary type heater controls					-	-			
Series S	er front windows	-	S(*13)	S	S	S	-			
sing s	er front and rear windows	-		-	-	-				
Second column	er's auto down window	-	S(*13)	S	S	S	-	S(*13)	S	S
	ruments and controls er steering	ς	ς	ς	ς	ς	ς	ς	ς	ς
	ual tilt steering column	-		-	-	-		-		
Section Sect	Control (*8)	-	-	S(*13)	S(*13)	S	-	-	S(*13)	
Additional companishing Companis	tron combination meter	-	-	-	-	S	-	-	-	
terior mirror S S S S S S S S S S S S S S S S S S	ti Information Display including trip compute er mirrors	r –	_	- C/*13\	- C/*13\	2	_	_	- C/*13\	
Sory socket	night interior mirror	ς	ς	. ,	. ,	ς	ς	ς		
w demister S S S S S S S S S S S S S S S S	er accessory socket	-	-	-	-	S	-	-		
National Programs State	able intermittent windscreen wipers	-	-	S	-	S	-	-		
rangmission infit interlock (*8)	vindow demister	-	-	-	S	S	S	S		
an - audible warning		_	_	ς	5	S	_	_		
S S S S S S S S S S	lights on – audible warning	S	S	S		S	S	S		
In dashboard S S S S S S S S S S S S S S S S S S S	ter			S	-	S	S			
S = Standard, - = Not available, 0 = Option available at extra cost, 0/P = Option switch S S S S S S S S S S Pickup = Standard on Pickup models, C/C = Standard on Cab Chassis model all lamp S S S S S S S S S S S S S S S S	el warning light	-		S						
ded dome lamp S S S S S S S S S S S S S S S S S S	ock in dashboard	2	2)	2	3	3	2	2	2
ignition switch al lamp S S S S S S Pickup = Standard on Pickup models, C/C = Standard on Cab Chassis mode nal lamp S S S S S S S S S S S S S S S S	rated dome lamp	S	S	S	S	S	S	S	S	S
Options - Available at extra cost If a some vehicle dimension figures are approximate and may vary due diders - in centre console S(*8)	ted ignition switch	-	-	S		S	-	-		
S S S S S S S S S S S S S S S S S S S	personal lamp	-	-	-	- !	5(*13)	-	-	-	S(*13)
Ider/s - in dash S S S S S S S S S	<u>e</u> Iovehov	c	c	С	c	ς	ς	C	ç	c
Ider/s - in centre console	glovebox Cupholder/s – in dash					S	-			
ders – in centre console holders – in front doors S S S S S S	upholder/s – in centre console	-	-			S	_	-		
holders – in rear doors – – – – – S S S S S * 6 = Fuel economy varies with driving conditions and style, vehicle conditions an	upholders – in centre console	-	-	-	-	-	-		S	S
sockets S S S S S S S S S S S S S S S S S S S	bottle holders – in front doors	S	S	S	S	S	-			
obacid storage S S S S S S S S S S S S S S S S S S S	bottle holders – in rear doors door pockets	- (- (- (- (- (-			
sole box with lidd S(*8) S S S S **8 = Automatic transmission model only. y and cigarette lighter S S S S S S S S S S S S S S S S S S S	dashboard storage	-				S				
y and cigarette lighter 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	console box with lid	-	-		S	S	-	-	S	S
#11 = RON 91 or higher. For improved vehicle performance, the use of premiu. With MP3 compatible single disc S S S S S S S S S S S S S S S S S S S	shtray and cigarette lighter			S		S				
S S S S S S S S S S S S S S S S S S S	t (small)	5	2	5	5	7	5	5	S	5
S S S S S S S S S S S S S S S S S S S	radio with MP3 compatible single disc									
with MP3 compatible 6 disc in-dash S S S - S S S S S S S S S S	er	S	S	S	S	-	S	S	S	-
compatible with iPod em or other 3 players S S S S S S S S S S S S S S S S S S S	M radio with MP3 compatible 6 disc in-dash	1				c				
3 players SSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSS	nanger o Input compatible with iPod®# or other	-	_	-	-	2	-	-	-	2
^hands-free telephone capability S S \langle = Optional FollowMe iPod* kit available. iPod* is a registered trademark of App	ble MP3 players	S	S	S	S	S	S	S	S	S
peakers 2 2 2 4 2 2 4 ## = iPod is a registered trademark of Apple Inc.	th™†^hands-free telephone capability	-	_	-	-	S	-	-		
	of speakers	2	2	2	2	4	2	2	2	4



The HiLux Range.

With more spacious cabins than ever before in a HiLux, you can step in and stretch out in the WorkMate. It's also got more power than ever to haul heavy loads, carry all your gear to the worksite or tow jetskis to the beachside.

SR

This HiLux is a real trooper. With a big V6 or powerful turbo diesel it's a tireless worker. With even more creature comforts it's also easier to live in and feel completely at ease while behind the wheel. But deep down, the SR is a hard worker that never grumbles and is always kind to the boss.

This one's got many of the comfort features of a car, with the work ethics of HiLux. Live life to the full with the power of a big 4.0 litre V6. The interior features an MP3 compatible 6 disc audio with Bluetooth™†, leather steering wheel and remote central locking. So you can pick up clients by day, then impress the girlfriend on weekends - the SR5 is the ultimate weekday workhorse and weekend escape vehicle.

† The Bluetooth word mark is owned by Bluetooth SIG, Inc. Bluetooth™ will only operate with telephones enabled with compatible Bluetooth™ wireless technology (HFP [Hands Free Profile] v1.0 and OPP [Object Push Profile] v1.1 international standards). Available from January 2007 Production.

Colour guide.















(653)



TOYOTA SERVICE ADVANTAGE CUTS NEW CAR RUNNING COSTS

Toyota Service Advantage makes owning your HiLux# even more economical because you are now entitled to low cost scheduled servicing capped for up to 6 standard services during the first three years or 60,000km, whichever occurs first. Terms and conditions apply. See your Toyota Dealer or advantage.toyota.com.au for eligibility, pricing and more information. Toyota Service Advantage pricing represents the maximum amount payable for standard scheduled servicing which is as per 'maintenance for normal operating conditions' outlined in the Warranty & Service Handbook's service schedule. Service plan eligibility excludes Government and rental vehicles and certain other exclusions apply.



Note: Toyota Australia reserves the right to vary and discontinue from time to time the interior and exterior colours, trims and colour/trim/model combinations currently available. Colours and trims displayed here are a guide only and may vary from actual colours due to printing/display process. See your Toyota Dealer to confirm colour/trim/model availability when ordering your vehicle. *Indicates mica, metallic or pearlescent paint which is available at extra cost. ^Available from August 2007 Production.

HiLux. Toyota Genuine Accessories





Get it on and go your own way.

4x2 Xtra Cab SR5 Utility shown is accessorised with Alloy Nudge Bar, Hard Tonneau Cover, All Weather Rubber Ute Mat, Weathershields, Fabric Seat Covers, Headlamp Covers, Bonnet Protector and Tailored All Weather Rubber Floor Mats.

THESE ARE JUST SOME OF THE ACCESSORIES AVAILABLE FOR YOUR HILLY. FOR A COMPLETE LIST AND FURTHER DETAILS, PLEASE SEE YOUR TOYOTA DEALER OR REFER TO OUR WEBSITE.



ALLOY TRAY BODY WITH OPTIONAL REAR RACK AND



CANOPY (HIGH ROOF)



LITE LINER AND TAILGATE LINES





ANVAS SEAT COVERS





ALL WEATHER RUBBER FLOOR MATS FRONT AND REAR AVAILABLE (SOLD SEPARATELY)



STEEL BULL BAR – OVERBUMPER STYLE AIRBAG COMPATIBLE



HARD TONNEAU COVER





FOLLOWME SOUND AND NAVIGATION SYSTEM* – INCLUDES SINGLE IN-DASH MP3 CD CHANGER AND RADIO WITH BLUETOOTH™† HANDSERFF COMMUNICATIONS LISB IN AND (OPTIONAL) IPOD® CONTROL®



SATELLITE NAVIGATION AUDIO SYSTEM* - INCLUDES 4 IN-DASH MP3 CD CHANGER AND RADIO WITH BLUETOOTH™† HANDSFREE COMMUNICATIONS



6 IN-DASH MP3 COMPATIBLE CD CHANGER & RADIO WITH BLUETOOTH™† HANDSFREE COMMUNICATIONS & AUXILIARY AUDIO INPUT



TOYOTA GENUINE ACCESSORIES ARE COVERED BY OUR TOYOTA WARRANTY[‡]

Some Toyota Genuine Accessories are not applicable to all Hilux models. See your Toyota Dealer for advice regarding Toyota Genuine Accessories. Pictured Accessories are all sold separately. For a comprehensive guide on the entire range of Toyota Genuine Accessories, visit our website at accessories.toyota.com.au.

‡All Toyota Genuine Accessories purchased and fitted to a Toyota are warranted for the remainder of the New Vehicle Warranty or 12 months, whichever is greater. Toyota Genuine Accessories purchased from an authorised Toyota Dealer over the counter are warranted from the date of purchase for one year (unlimited kilometres). Conditions apply. All warranties are additional to the implied warranties under the Trade Practices Act 1974.

#Towbar capacity subject to regulatory requirements, towbar design, vehicle design and towing equipment limitations. †The Bluetooth word mark is owned by Bluetooth SIG, Inc. Bluetooth* will only operate with telephones enabled with compatible Bluetooth* wireless technology HFP (Hands Free Profile) v1.0 and OPP (Object Push Profile) v1.1 international standards. *Current Navigation mapping database encompasses major capital and primary national road networks, as well as offering some coverage of regional areas. "Available on selected models where AUX-In option is part of audio unit. Suits IPod® models that have a dock connector. Refer to your Apple iPod® Instruction Manual. iPod® is a registered trademark of Apple Inc. This accessory is not a Toyota Genuine Accessory (supplier branded) and is warranted for 12 months from the date of purchase. This warranty is additional to the implied warranties under the Trade Practices Act 1974. Optional FollowMe iPod® kit available. iPod® is a registered trademark of Apple Inc.