



# Atego

<b>Model</b>	1224 - 1229 L, 1624 - 1629 L, 1629 LF, AF	2329 L
<b>Configuration</b>	4x2 / 4x4	6x2
<b>Engine</b>	7.2 litre in-line 6 turbocharged with intercooling (Euro5 with EEV)*	
<b>Power</b>	238 - 286 hp (175 - 240 kW) @ 2,200 rpm	
<b>Torque</b>	810 - 1100 Nm (598 - 812 lbft) @ 1,200 - 1,600 rpm	
<b>GVM kg</b>	11,990 - 16,000	23,000
<b>Tare kg (+/-3%)</b>	From 4,675	From 5,930
<b>GCM kg</b>	Up to 34,000	
<b>Transmission</b>	6-speed synchromesh manual, 6-speed automated manual (2-pedal with 240 hp), 9-speed synchromesh manual	
<b>Rear Axle</b>	H4 hypoid 11,000 kg	H4 hypoid 11,000 kg Tag axle TZ 10,500 kg
<b>Rear Suspension</b>	2 bag air, 8,100 - 10,500 kg, 4 leaf parabolic (4x4), 10,500 kg	4 bag air 2 x 10,500 kg
<b>Front Axle</b>	AL3/VL3 5,300 - 6,100 kg	
<b>Front Suspension</b>	Parabolic 4,400 - 6,100 kg	

\*6.4 litre in line turbocharged with intercooling used in some variants.

## Structure of the Model Code

2644 LS

<b>26</b>	Gross Vehicle Mass	tonnes
<b>44</b>	Horsepower Rating	(x 10) 44 = 440 hp
<b>L</b>	Suspension Type	L = air
<b>S</b>	Vehicle Configuration	S = prime-mover


"blank" = rigid vehicle (steel suspension)      LF = fire fighting vehicle with rear air suspension  
 L = rigid with air (luft) suspension              A = all-wheel drive rigid  
 LS = tractor/prime-mover with air suspension      AS = all-wheel drive tractor/prime-mover  
 S = tractor/prime-mover with steel suspension      AK = all-wheel drive tipper  
 K = tipper chassis                                      AF = all-wheel drive fire fighting vehicle  
 B = concrete mixer/pumper

For full Warranty details and limitations contact your authorised Mercedes-Benz Truck Dealer.

**IMPORTANT!** This brochure has been compiled by Mercedes-Benz Australia/Pacific Pty Ltd to provide a general indication of the range of models available in Australia. Some of the models, features, optional extras and/or colours shown may not be available in Australia or may only be available in a different specification. Additionally, some models, features, optional extras and/or colours may only be available in combination with others. Some equipment depicted either on vehicle illustrations or separately may be non standard or options and may, where applicable, be available at an additional cost.

For current information on the availability, design features and prices of all models, features, optional extras and/or colours available in Australia, you should contact your authorised Mercedes-Benz Truck Dealer on 1300 66 22 30 or go to [www.mercedes-benz.com.au/trucks](http://www.mercedes-benz.com.au/trucks)

All of the information contained in this brochure was correct as at April 2011. However, the manufacturer reserves the right to discontinue, make changes to design and specifications to vehicles or optional equipment without notice.

The  and the words Mercedes-Benz, Telligent® and BlueTec® are registered trademarks of Daimler AG, Stuttgart, Germany.

Your authorised Mercedes-Benz Dealer is:

Mercedes-Benz Australia/Pacific Pty Ltd. ABN 23 004 411 410. Lexia Place, Mulgrave, Victoria 3170. Ph: (03) 9566 9266. Facsimile: (03) 9562 0397.



# Model Range 2011

125! years of innovation



**Mercedes-Benz**  
Trucks you can trust



# Axor

Model	1833 L, LS, A	2533 L	2633
Configuration	4x2 / 4x4	6x2	6x4
Engine	7.2 litre in-line 6 turbocharged with intercooling		
Power	326 hp (240 kW) @ 2,200 rpm		
Torque	1300 Nm (960 lbf) @ 1,200 – 1,600 rpm		
GVM kg	16,000 - 18,000	25,500	26,000 - 27,500
Tare kg (+/-3%)	From 5,505	From 7,235	From 7,695
GCM kg	Up to 39,000		
Transmission	9-speed synchromesh manual, 16-speed automated manual (3-pedal)		
Rear Axle	H6 hypoid, 13,000 kg, H7 planetary, 13,000 kg	H6 hypoid, 13,000 kg, Tag axle TZ5, 10,000 kg	H7 planetary, 13,000 kg
Rear Suspension	2-4 bag air, 11,500 kg, 4 leaf parabolic, 11,500 kg	8 bag air, 2 x 10,000 kg	6-rod, parabolic* 2 x 9,500 kg
Front Axle	AL7/ VL4 7,500 kg		
Front Suspension	2 - 3 leaf parabolic 7,100 – 7,500 kg		

+ 6-rod mechanical 'Road Friendly' version available 2 x 10,000 kg.



# Actros

Model	1836 - 1844 LS	2636 - 2644, L, LS & S, 2648 - 2660 LS & S	3341 - 3348 A	3241 - 3248, L, 4141 - 4144 B	4141 - 4148 AK
Configuration	4x2	6x4	6x6	8x4	8x8
Engine	11.9 litre V6 turbocharged with intercooling, 15.9 litre V8 turbocharged with intercooling (not available with all models)				
Power	360 - 598 hp (265 - 440 kW) @ 1,800 rpm				
Torque	1,850 - 2,800 Nm (1,365 - 2,065 lbf) @ 1,080 rpm				
GVM kg	16,000 - 18,000	26,000	33,000 - 40,000	32,000 - 48,000	41,000 - 48,000
Tare kg (+/-3%)	From 6,250	From 7,860	From 10,095	From 9,750	From 11,670
GCM kg	55,000	55,000 - 90,000 <sup>‡</sup>	70,000 <sup>‡</sup>	55,000 - 70,000 <sup>‡</sup>	70,000 <sup>‡</sup>
Transmission	12 or 16-speed automated manual (2 pedal), 16-speed semi-automated manual (3 pedal)				
Rear Axle	H6 hypoid 13,000 kg	H7 planetary 2 x 13,000 - 16,000 kg			
Rear Suspension	2 bag air 11,500 kg	8 bag air, 2 x 10,000 kg, 6-rod parabolic*, 2 x 9,500 kg	8 bag air 2 x 10,000 kg, 6-rod parabolic 2 x 9,500 - 18,000 kg		
Front Axle	VL4 7,500 kg	VL4 7,500 kg	AL7 7,500 - 9,000 kg	VL4 2 x 7,500 - 9,000 kg	AL7 9,000 kg
Front Suspension	parabolic 7,100 - 9,000 kg			parabolic 2 x 7,500 - 9,000 kg	

+ 6-rod mechanical 'Road Friendly' version available 2 x 10,000 kg.

‡ GCM to 130,000 kg with application approval (TAD).