

EXPLORE
THE
ONLY
COUNTRY



TOYOTA
4-WHEEL DRIVE

LAND CRUISER

HARDTOP, VINYLTOP,
STATION WAGON





Instrument panel and front seat of the Hard Top



Instrument panel and front seat of the Station Wagon



Vinyl Top



Hard Top



Station Wagon

EXPLORE
THE
BACK
COUNTRY

TOYOTA
LAND CRUISER

HARDTOP, VINYLTOP,
STATION WAGON

On highways, on byways or out in the backwoods where there's no roads at all, it's great to go-go in a Toyota Land Cruiser. Climb high mountains, cross dry deserts, take it through sand, rocks, mud—its big tough 6-cylinder, 155 HP engine, and 4-wheel drive with nine forward/three reverse

gear combinations just love roughing it. And this is one utility vehicle that's as much at home running errands, shopping, taking the family hither and yon, all in sedan type riding comfort. The Toyota Land Cruiser's a vehicle combining great engineering and meticulous craftsmanship. It'll soak up punishment and keep coming back for more. And it lasts and lasts and lasts—troublefree.

SPECIFICATIONS

Engine: 6-cylinder in line, OHV, 236.7 cu. in. Bore, 3.54 in. Stroke, 4.00 in. Compression ratio, 7.8 to 1. Maximum horsepower, 155hp at 4,000rpm. Maximum torque, 225ft.-lb. at 2,200rpm. 12-volt 50-amp. hr. battery. 12-volt 480-watt alternator. Down draft 2-barrel carburetor with automatic choke. Fuel tank capacity: Vinyl Top and Hard Top, 18.5 gal. Station Wagon, 23.8 gal. Cooling system: Forced circulation by centrifugal pump. Lubrication system: Forced lubrication by gear pump. Water capacity, 16.1 quarts. Crankcase capacity, 9.0 quarts. **Clutch:** Single dry plate with torsion rubbers. Facing diameter, 10.8 in. Facing area, 111 sq. in. **Transfer case:** 2-speed helical gear sliding type. Ratios: Low: 2.31, High: 1.00.

Dimensions and weight:

	HARD TOP	VINYL TOP	STATION WAGON
Overall Length (in.)	152.4	152.4	184.1
Overall Width (in.)	65.6	65.6	68.3
Overall Height (in.)	76.0	76.8	73.4
Wheelbase (in.)	90.0	90.0	106.3
Headroom (Front seat to Headliner) (in.)	40.2	40.6	38.6
Curb Weight (lb.)	3,680	3,470	4,120
Track (in.)	Front: 55.3/Rear: 55.1		

Transmission: 3-speed synchro-mesh 2nd and 3rd. Ratios: 1st: 2.757, 2nd: 1.672, 3rd: 1.000, Reverse: 3.678.

Axle: Front: Full-floating hypoid. Rear: Semi-floating hypoid.

Gear ratio, 4.111 to 1.

Suspension: Semi-elliptic leaf springs and double-acting hydraulic shock absorbers.

Brakes: Hydraulic drum brakes operate on 4 wheels. Drum diameter, 11.4 in. Lining area,

183 sq. in. Parking brake:

Mechanical brake operates on propeller shaft.

Steering: Worm and sector roller type. Gear ratio, 21 to 1.

Minimum turning circle: Vinyl Top and Hard Top, 34.8 feet.

Station Wagon, 40.8 feet.

Tires: 7.60 x 15, 4 PR.

Performance: Maximum speed;

Vinyl Top and Hard Top...85 mph

Station Wagon.....85 mph

TOYOTA

Wire quality oriented Toyota Motor Sales, U.S.A., Inc. 2055 West 190th Street, Torrance, California 90501

FJ4K () PRINTED IN JAPAN. NO. 88910