

2024 FORD RV & TRAILER TOWING GUIDE

EQUIPMENT • WEIGHTS • TECHNOLOGY • CAPABILITY





POWERFUL. PRODUCTIVE. BUILT FORD TOUGH.®

The 2024 F-Series® have an advanced, torque-rich powertrain lineup, delivering impressive payload and trailer tow ratings, no matter which model you choose. Whether carrying a serious payload or towing the heaviest of trailers, F-Series trucks are designed to help conquer the roughest of jobs.

F-150 Platinum Plus SuperCrew® in Darkened Bronze Metallic

F-Series – America’s best-selling truck for 47 consecutive years*, brings decades of impressive RV and towing experience for every configuration!

*Based on CY 1977–2023 total sales through Nov. 2023 and Ford internal projections.

2024 TOWING GUIDE CONTENTS

- 3 F-150® Pickup
- 4 Super Duty® Pickup
- 6 Slide-In Camper
- 7 Super Duty Chassis Cab
- 8 Class A Motorhome Chassis and Commercial Stripped Chassis
- 9 E-Series® Class C Motorhome Chassis
- 10 Transit® Class C Motorhome Chassis
- 11 Four-Wheel-Down Towing
- 12 Tow-Dolly Flexibility
- 13 Towing Equipment and Frontal Area Limitations
- 14 Towing Equipment/Packages and Maximum Trailer Weights

TRAILER TOWING SELECTOR

- 18 F-150 Pickup
- 23 F-250® SRW Super Duty Pickup
- 25 F-350® SRW Super Duty Pickup
- 27 F-350/F-450® DRW Super Duty Pickups
- 28 F-350/F-450/F-550®/F-600® Super Duty Chassis Cabs
- 30 Medium Duty Truck, Class A Motorhome Chassis, Commercial Stripped Chassis and E-Series Cutaway/Stripped Chassis
- 31 Transit Vans
- 32 Transit Cutaway/Chassis Cab
- 33 Ranger® and Maverick®
- 34 Bronco® and Bronco Sport
- 35 Expedition® and Explorer®
- 36 Edge®, Escape® and Mustang®

- 37 Know Before You Tow
- 38 Trailer Types/Classes
- 39 Hitch Styles
- 40 Factory-Installed Hitch Receivers
- 41 Calculate Weight Distribution
- 42 About Weights
- 43 Weight Limits and Axle Ratios
- 44 Towing Accessories
- 45 Towing Basics

The following vehicles are not recommended for trailer towing: E-Transit™ and Mustang Mach-E.

SAE Towing Standard

The Society of Automotive Engineers (SAE) testing standard J2807® defines procedures and requirements to determine gross combined weight ratings (GCWR) and to calculate the trailer weight rating (TWR) for any tow vehicle. This standard establishes minimum performance conditions to allow for consistent comparisons between similar class vehicles. Ford will apply the SAE standard to all vehicles.



F-150® – CONNECTED TOUGHNESS

Combining exceptional strength, capability and intelligent technology, the 2024 F-150 pickup can tow more than any truck in its class¹ while delivering impressive payload ratings² too! A high-strength steel frame and military-grade aluminum alloy body make F-150 Built Ford Tough®.



1. Max towing of 13,500 lbs. available on F-150® SuperCrew® 6.5' box 4x4 with available 3.5L V6 engine. Class is Full-Size Pickups under 8,500 lbs. GVWR. When properly equipped. Max towing varies and is based on accessories and vehicle configuration. 2. When properly equipped. Max payload varies and is based on accessories and vehicle configuration.

F-150 Platinum SuperCrew in Rapid Red Metallic Clearcoat

IMPRESSIVE POWER AND CAPABILITY

F-150 has earned the reputation of being composed while working the hardest due to the strength of its torque-rich powertrain lineup. With 6 different engine choices, F-150 offers you many options to meet diverse job applications. So you can confidently pick the engine that best fits your recreational vehicle or job-related towing needs.

All 2024 F-150 powertrains include an innovative 10-speed automatic transmission with optimized gear spacing, including 3 overdrive gears to help maximize shift points to optimize power, low-rpm torque and fuel efficiency. Selectable Drive Modes provide added functionality.

| Engine | HP @ rpm | Torque @ rpm | Available Max Towing (lbs.) | Available Max Payload (lbs.) |
|-------------------------------------|-------------|---------------------|-----------------------------|------------------------------|
| 2.7L EcoBoost® V6 | 325 @ 5,000 | 400 lb.-ft. @ 3,000 | 8,400 | 1,775 |
| 3.5L EcoBoost V6 | 400 @ 6,000 | 500 lb.-ft. @ 3,100 | 13,500 ³ | 2,445 |
| 3.5L PowerBoost™ Full Hybrid V6 | 430 @ 6,000 | 570 lb.-ft. @ 3,000 | 11,200 | 1,755 |
| 5.0L Ti-VCT V8 | 400 @ 6,000 | 410 lb.-ft. @ 4,250 | 12,000 ³ | 2,230 ⁴ |
| 3.5L EcoBoost H. O. V6 ⁵ | 450 @ 5,850 | 510 lb.-ft. @ 3,000 | 8,200 | 1,405 ⁶ |
| 5.2L Supercharged V8 ⁷ | 720 @ 6,650 | 640 lb.-ft. @ 4,300 | 8,700 | 1,410 |

3. Requires Tow/Haul Package (not shown). When properly equipped, max towing varies based on cargo, vehicle configuration, accessories and number of passengers. 4. Max payload of 2,230 lbs. on SuperCrew 4x2 with 5.0L gas engine and Tow/Haul Package (not shown). Max payload varies and is based on accessories and vehicle configuration. Always properly secure cargo. 5. Raptor only. 6. 37" tires. 7. Raptor R only.

Note: Horsepower, torque, payload and towing are independent attributes and may not be achieved simultaneously.

M Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in kilometers, multiply miles by 1.6; to obtain information in centimeters, multiply inches by 2.54.

F-150 TOWING FEATURES

Standard Tow/Haul Mode reduces gear hunting, improves power delivery. Especially useful with hauling or towing a heavy load.

Standard Trailer Sway Control works in conjunction with the AdvanceTrac® with RSC (Roll Stability Control™) system to expand the vehicle's dynamic stability control capabilities, adding an additional layer of confidence and control while towing a trailer.

Available Trailer Brake Controller uses braking input, vehicle speed and ABS logic to balance the performance of the truck brakes and electric trailer brakes.

Available On-Board Scales with Smart Hitch provides real-time weight estimates of the total vehicle weight and cargo weight of an F-150, including the Smart Hitch measuring the trailer tongue load weight. This system indicates how much weight has been loaded, letting you know if the truck is within the maximum ratings. Works with all trailer types.

Available Pro Trailer Backup Assist™ and Pro Trailer Hitch Assist improve driver confidence by letting the driver steer the trailer instinctively while controlling the accelerator and brakes – the truck takes care of the rest. Pro Trailer Hitch Assist controls throttle, braking and steering to automatically back truck up and align conventional hitch ball to trailer receiver.

Trailer Reverse Guidance uses high-definition cameras to provide multiple views along with helpful steering guidance graphics to assist in backing and maneuvering a conventional trailer. Included with 360-Degree Camera®. Included on XLT series and above.

Standard BLIS® (Blind Spot Information System) with cross traffic alert and available trailer tow monitoring alerts the driver if something is detected in the trailer's blind spot®.

8. Driver-assist features are supplemental and do not replace the driver's attention, judgement and need to control the vehicle. It does not replace safe driving. See Owner's Manual for details and limitations.

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. Maximum payload capabilities are for properly equipped vehicles with required equipment and vary based on vehicle configuration, accessories, and option content. Horsepower, torque, payload and towing are independent attributes and may not be achieved simultaneously. For additional information, see your Ford Dealer.

SUPER DUTY® PICKUPS – CAPABLE, DURABLE, PRODUCTIVE

The 2024 Super Duty Pickups expand their role as the pinnacle of BUILT FORD TOUGH® with rugged durability and improved capability and productivity. Impressive powertrains, improved camera technologies and innovative connected features and services meet the needs of a multitude of commercial vocations and personal use towing customers. Super Duty Pickups are designed to handle your rugged jobs with Regular Cab, SuperCab and Crew Cab choices in both 4x2 and 4x4 configurations for maximum flexibility.



Super Duty F-450 XL Crew Cab 4x4 in Race Red

NEXT LEVEL POWER

6.8L Gas V8 – Workhorse Power

This 6.8L gas V8 workhorse, standard on XL models, raises the bar for entry-level performance with **405 horsepower and 445 lb.-ft. of torque**.¹ Naturally aspirated with port injection, the engine uses a cam-in-block and overhead valve architecture with variable valve timing and leverages the latest technology to deliver impressive power and torque to get heavy loads up to speed more quickly.

7.3L Gas V8 – Most Powerful Gas Engine In Its Class²

The available 7.3L gas V8 engine provides impressive performance with maximum available best-in-class output of **430 horsepower** and maximum available best-in-class gas **torque of 485 lb.-ft.**^{1,2} for heavy-duty flexibility when towing or hauling. A port fuel-injection system offers fuel-efficiency and easy maintenance access.

6.7L Power Stroke® Diesel – A Proven Performer

This available 6.7L Power Stroke engine delivers **475 horsepower** and **1,050 lb.-ft. of torque**¹ and includes a 36,000-psi fuel injection system that helps optimize combustion and provide excellent pedal response. Forged-steel pistons provide high firing pressure capability and less friction for improved durability. A turbocharger with a fully electronic vane actuator helps cold-weather performance.


6.7L High Output Power Stroke Diesel – High-Performance Engine

This available High Output Diesel engine incorporates a turbocharger with a cooled compressor and stainless-steel exhaust manifolds helping it deliver best maximum available diesel **500 horsepower** in the class and best-in-class maximum available **1,200 lb.-ft. of torque**.^{1,3}

A 10-speed automatic transmission is standard on all models.

1. Horsepower and torque ratings determined based upon testing requirements prescribed in SAE J1349. Your results may vary. Horsepower and torque are independent attributes and may not be achieved simultaneously. 2. Max 430 horsepower and 485 lb.-ft. of torque based on 7.3L V8 gas engine. Class is Full-Size Pickups over 8,500 lbs. GVWR. 3. Max 500 horsepower and 1,200 lb.-ft. of torque based on 6.7L High Output Power Stroke V8 Turbo Diesel. Class is Full-Size Pickups over 8,500 lbs. GVWR.

SUPER DUTY® TOW TECHNOLOGY



5th-Wheel/Gooseneck Prep Package

Available on all models

Provides the necessary under-the-bed hardware to allow mounting of a 5th-wheel/gooseneck hitch in the pickup bed to put more of the trailer weight over the tow vehicle

Features five pickup bed attachment points with plugs, frame under-bed crossmember and integrated 7-pin connector

Standard Trailer Sway Control

Works in conjunction with AdvanceTrac® with RSC (Roll Stability Control™) to detect trailer sway and reduce it as necessary

Software measures the yaw motion of the vehicle to determine if the trailer is swaying and then responds to eliminate the sway condition¹

Standard Trailer Brake Controller (TBC)

Helps to ensure smooth and effective trailer braking by powering the trailer's brakes with an output proportional to the towing vehicle's brake pressure. Factory-installed and warranted by Ford Motor Company²

Smart Trailer Tow Connector

Provides trailer connection status, lighting and trailer battery alerts/warnings

Alerts/warnings are displayed within the instrument cluster

Available Onboard Scales with Smart Hitch

Estimates cargo weight in real-time and provides guidance on trailer tongue weight distribution directly on the center touchscreen and within the taillamps on Platinum and Limited models

Tow/Haul Mode with Integrated Engine-Exhaust Brake

Tow/haul mode and tow/haul mode with integrated engine-exhaust brake (6.7L V8 Power Stroke® turbo diesel only) with auto setting give drivers even greater control when traveling downhill

Helps eliminate unwanted frequency of gear shifting on steep uphill grades and allow engine braking to maintain or reduce vehicle speed and assist the driver in controlling the vehicle when descending a steep grade



Pro Trailer Backup Assist™ and Pro Trailer Hitch Assist

Pro Trailer Backup Assist makes parking your trailer as simple as turning a knob on the instrument panel left or right in the direction you want the trailer to go. Pro Trailer Hitch Assist controls throttle, braking and steering to automatically back the truck up and align the conventional hitch ball to the trailer receiver³



Trailer Reverse Guidance^{4,5}

Available feature utilizes 3 cameras to provide multiple views along with steering guidance graphics to assist in backing and maneuvering a trailer

Functions with all trailers, including gooseneck and 5th-wheel applications



360-Degree Camera Package

Available 360-Degree Camera Package allows you to see if you are free and clear on all sides of your truck^{5,6}

Includes BLIS® (Blind Spot Information System), with Cross Traffic Alert and Trailer Coverage, Rear Parking Sensors and Reverse Sensing System with Reverse Brake Assist⁵



Available BLIS with Trailer Coverage

Alerts you when a vehicle is spotted in your blind spots and when one is alongside the trailer. Helps ease lane-change anxiety—even with a conventional trailer (up to 33 feet long) in tow⁵

Turn Signal View with Trailer


Camera view displays on center touchscreen showing truck and trailer when turn signal is activated

Digital Instrument Cluster

Available 12-inch customizable digital instrument cluster delivers vital information in brilliant high-resolution clarity. Configurable to display information most important for normal, towing and off-road drive modes

Trailer Profiles

Allows driver to create a profile for each trailer to track key information such as mileage and fuel economy while trailering



Trailer Navigation

Available feature keeps the size of your trailer in mind and adapts the route based on height and width clearances to help avoid jam-ups like low bridges and tight corners

Power Tailgate

Available system provides ability to raise or lower tailgate from inside cab, from key fob or from button on tailgate. Includes Tailgate Down camera³ and reverse sensors in the top of tailgate that provide visual and audible alerts when the tailgate is down to make backing up to a dock or hitching a gooseneck or 5th-wheel trailer easier than ever before



Available Head-Up Display

Important information (speed limit, driver-assist details and more) is projected onto the windshield in line of sight without being intrusive, allowing eyes to remain fixed on the road. Information displayed and location on windshield is customizable⁷

Trailer Theft Security

Feature sends an alert, via the FordPass App, should anyone attempt to disconnect the trailer when the truck is locked

1. Remember that even advanced technology cannot overcome the laws of physics. It's always possible to lose control of a vehicle due to inappropriate driver input or improper trailer loading for the conditions. 2. See limited warranty for details. Ask your Ford Dealer for details. 3. Standard on XLT series and above. 4. Included with 360-Degree Camera on XL series and above. Not available on XL and XLT. 5. Driver-assist features are supplemental and do not replace the driver's attention, judgment and need to control the vehicle. It does not replace safe driving. See Owner's Manual for details and limitations. 6. Cameras only operate at speeds under 6 miles per hour. 7. Don't drive while distracted. See Owner's Manual for details and limitations.

SUPER DUTY® PICKUP/ CAMPER COMBINATION SELECTOR

Combined weight of vehicle, camper body, occupants and cargo must not exceed Gross Vehicle Weight Rating (GVWR).

Cargo Weight Rating shown in chart is maximum allowable, assuming weight of a base vehicle with required camper option content and a 150-lb. passenger at each available seating position.

Ratings also assume weight of engine and standard transmission. Cargo Weight Rating shown must be further reduced by weight of transmission upgrade and any other options. Option weights and center-of-gravity information are available on the Ford Pickup Truck Consumer Information Sheet.

CAMPER CENTER-OF-GRAVITY

All Styleside pickups that qualify for slide-in camper bodies have camper center-of-gravity included on the Consumer Information Sheet in the glovebox.

Data is calculated for each individual truck, based on vehicle options.

If vehicle does not qualify for camper use, the Consumer Information Sheet states that the vehicle is not recommended for camper use and no center-of-gravity data is shown.

SLIDE-IN CAMPER INSTALLATION

Consult your camper manufacturer/dealer for details regarding proper installation of your slide-in camper.

A dimensionally stable block spacer is recommended between the headboard of the pickup box and the forward edge of the camper floor. Resting the spacer on the pickup box bed helps prevent movement and contact of the fully-installed camper with the pickup box headboard or taillight rear pillars.

Note: Be sure to measure your slide-in camper before attempting to install it onto the bed of the truck. Some campers may require a platform in the bed of the truck to make sure there is adequate clearance for both the box rails and cab roof of the truck.

F-250®/F-350®/F-450® SUPER DUTY CAMPER PACKAGE (OPTION CODE 471)

Increased capacity front springs (2 Up [4x2] or 1 Up [4x4] upgrade over springs, computer-selected based on options ordered. Not included if maximum springs already selected.)

Rear stabilizer bar (SRW)

Rear auxiliary springs (F-250; standard on F-350)

Slide-in camper certification

Available on XL, XLT, LARIAT, King Ranch® (DRW only), and Platinum (DRW only)

If you intend to pull a trailer in addition to carrying your camper, see the Super Duty Pickup Trailer Towing Selector charts on pages 23, 25 and 27.

MAXIMUM CARGO WEIGHT WITH SLIDE-IN CAMPER

Note: This chart lists GVWRs and Maximum Cargo Weights (with minimum equipment) by engine for each approved pickup model: 6.8L V8, 7.3L V8, 6.7L Power Stroke® Turbo Diesel V8 and H.O. 6.7L Power Stroke Turbo Diesel V8.

| | Wheelbase | GVWR (lbs.) | | | | Maximum Cargo Weight Rating (lbs.) | | | |
|--|-----------|-------------|--------|---------------------|---------------------|------------------------------------|-----------------------------|-----------------------------|-----------------------------|
| | | 6.8L | 7.3L | 6.7L | 6.7L H.O. | 6.8L Std./Opt. ³ | 7.3L Std./Opt. ³ | 6.7L Std./Opt. ³ | 6.7L H.O./Opt. ³ |
| F-250 Super Duty¹ | | | | | | | | | |
| 4x2 Reg. Cab | 141.6" | 10,000 | 10,000 | 10,000 | 10,600 ² | 3,793/3,693 | 3,690/3,590 | 3,036/2,936 | 3,535/ - |
| 4x2 Reg. Cab | 141.6" | - | - | - | 10,600 ² | - / - | - / - | 3,550/ - | - / - |
| 4x2 Reg. Cab | 141.6" | - | - | - | 10,600 | - / - | - / - | 3,636/ - | - / - |
| 4x2 SuperCab | 148.0" | 10,000 | 10,000 | - | 10,700 ² | 3,046/2,946 | 2,962/2,862 | - / - | 2,898/ - |
| 4x2 SuperCab | 148.0" | 10,100 | 10,100 | - | - | 3,146/ - | 3,062/ - | - / - | - / - |
| 4x2 SuperCab | 164.2" | 10,000 | - | 10,000 | 11,000 ² | 2,937/2,837 | - / - | 2,170/2,070 | 3,069/ - |
| 4x2 SuperCab | 164.2" | - | - | 11,000 ² | - | - / - | - / - | 3,084/ - | - / - |
| 4x2 SuperCab | 164.2" | 10,400 | - | 10,600 | - | 3,337/ - | - / - | 2,770/ - | - / - |
| 4x2 Crew Cab | 159.8" | 10,000 | 10,000 | 10,000 | 10,800 ² | 3,000/2,900 | 2,916/2,816 | 2,206/2,106 | 2,905/ - |
| 4x2 Crew Cab | 159.8" | - | - | 10,800 ² | - | - / - | - / - | 2,920/ - | - / - |
| 4x2 Crew Cab | 159.8" | 10,100 | 10,200 | 10,600 | - | 3,100/ - | 3,116/ - | 2,806/ - | - / - |
| 4x2 Crew Cab | 176.0" | 10,000 | 10,000 | 10,000 | 11,100 ² | 2,777/2,677 | 2,693/2,593 | 1,959/1,859 | 2,958/ - |
| 4x2 Crew Cab | 176.0" | - | - | 11,100 ² | - | - / - | - / - | 2,973/ - | - / - |
| 4x2 Crew Cab | 176.0" | 10,400 | 10,500 | 10,600 | - | 3,177/ - | 3,193/ - | 2,559/ - | - / - |
| 4x4 Reg. Cab | 141.6" | 10,000 | 10,000 | 10,000 | 11,000 ² | 3,348/3,248 | 3,264/3,164 | 2,628/2,528 | 3,527/ - |
| 4x4 Reg. Cab | 141.6" | - | - | 11,000 ² | - | - / - | - / - | 3,542/ - | - / - |
| 4x4 Reg. Cab | 141.6" | 10,300 | 10,400 | 10,600 | - | 3,648/ - | 3,664/ - | 3,228/ - | - / - |
| 4x4 SuperCab | 148.0" | 10,000 | 10,000 | 10,000 | 11,000 ² | 2,631/2,531 | 2,548/2,448 | 1,906/1,806 | 2,805/ - |
| 4x4 SuperCab | 148.0" | - | - | 11,000 ² | - | - / - | - / - | 2,820/ - | - / - |
| 4x4 SuperCab | 148.0" | 10,400 | 10,400 | 10,600 | - | 3,031/ - | 2,948/ - | 2,506/ - | - / - |
| 4x4 SuperCab | 164.2" | 10,000 | 10,000 | 10,000 | 11,400 ² | 2,543/2,443 | 2,459/2,359 | 1,788/1,688 | 3,088/ - |
| 4x4 SuperCab | 164.2" | - | - | 11,200 ² | - | - / - | - / - | 2,903/ - | - / - |
| 4x4 SuperCab | 164.2" | 10,600 | 10,600 | 10,600 | - | 3,143/ - | 3,059/ - | 2,388/ - | - / - |
| 4x4 Crew Cab | 159.8" | 10,000 | 10,000 | 10,000 | 11,100 ² | 2,650/2,550 | 2,566/2,466 | 1,843/1,743 | 2,842/ - |
| 4x4 Crew Cab | 159.8" | - | - | 11,100 ² | - | - / - | - / - | 2,857/ - | - / - |
| 4x4 Crew Cab | 159.8" | 10,500 | 10,500 | 10,600 | - | 3,150/ - | 3,066/ - | 2,443/ - | - / - |
| 4x4 Crew Cab | 176.0" | 10,000 | 10,000 | 10,000 | 11,400 ² | 2,347/2,247 | 2,263/2,163 | 1,529/1,429 | 2,828/ - |
| 4x4 Crew Cab | 176.0" | - | - | 11,200 ² | - | - / - | - / - | 2,643/ - | - / - |
| 4x4 Crew Cab | 176.0" | 10,600 | 10,600 | 10,600 | - | 2,947/ - | 2,863/ - | 2,129/ - | - / - |
| F-350 SRW Super Duty¹ | | | | | | | | | |
| 17" Tires | | | | | | | | | |
| 4x2 Reg. Cab | 141.6" | - | - | 10,600 | 10,600 | - | - | 3,580 | 3,565 |
| 4x2 SuperCab | 148.0" | 10,100 | 10,100 | 10,700 | - | 3,116 | 2,933 | 3,011 | - |
| 4x2 SuperCab | 164.2" | 10,400 | - | 11,000 | 11,000 | 3,304 | - | 3,186 | 3,170 |
| 4x2 Crew Cab | 159.8" | 10,200 | 10,200 | 10,800 | 10,800 | 3,061 | 2,878 | 2,936 | 2,921 |
| 4x2 Crew Cab | 176.0" | 10,600 | 10,600 | 11,100 | 11,100 | 3,225 | 3,053 | 2,999 | 2,984 |
| 4x4 Reg. Cab | 141.6" | 10,400 | 10,400 | 11,000 | 11,000 | 3,688 | 3,506 | 3,566 | 3,551 |
| 4x4 SuperCab | 148.0" | 10,500 | 10,500 | 11,000 | 11,000 | 3,094 | 2,912 | 2,899 | 2,883 |
| 4x4 SuperCab | 164.2" | 10,800 | 10,800 | 11,300 | 11,300 | 3,287 | 3,104 | 3,073 | 3,058 |
| 4x4 Crew Cab | 159.8" | 10,600 | 10,600 | 11,200 | 11,200 | 3,050 | 2,868 | 2,917 | 2,901 |
| 4x4 Crew Cab | 176.0" | 10,900 | 10,900 | 11,499 | 11,499 | 3,235 | 3,053 | 2,939 | 2,923 |
| 18" All-Season Tires | | | | | | | | | |
| 4x2 Reg. Cab | 141.6" | 10,500 | 10,500 | 11,100 | 11,100 | 4,179 | 3,965 | 4,023 | 4,008 |
| 4x2 SuperCab | 148.0" | 10,600 | 10,600 | 11,200 | - | 3,586 | 3,373 | 3,454 | - |
| 4x2 SuperCab | 164.2" | 10,900 | - | 11,499 | 11,499 | 3,778 | - | 3,627 | 3,611 |
| 4x2 Crew Cab | 159.8" | 10,600 | 10,700 | 11,300 | 11,300 | 3,435 | 3,321 | 3,379 | 3,364 |
| 4x2 Crew Cab | 176.0" | 11,100 | 11,100 | 11,499 | 11,499 | 3,709 | 3,496 | 3,341 | 3,326 |
| 4x4 Reg. Cab | 141.6" | 10,900 | 10,900 | 11,499 | 11,499 | 4,162 | 3,949 | 4,008 | 3,993 |
| 4x4 SuperCab | 148.0" | 10,900 | 11,000 | 11,499 | 11,499 | 3,468 | 3,355 | 3,340 | 3,324 |
| 4x4 SuperCab | 164.2" | 11,300 | 11,300 | 11,499 | 11,499 | 3,761 | 3,547 | 3,215 | 3,200 |
| 4x4 Crew Cab | 159.8" | 11,000 | 11,100 | 11,499 | 11,499 | 3,424 | 3,311 | 3,159 | 3,143 |
| 4x4 Crew Cab | 176.0" | 11,300 | 11,300 | 12,000 | 12,000 | 3,608 | 3,395 | 3,355 | 3,339 |
| 18"/20" All-Terrain and 20" All-Season Tires | | | | | | | | | |
| 4x4 Reg. Cab | 141.6" | 11,400 | 11,400 | 12,000 | 12,000 | 4,657 | 4,444 | 4,504 | 4,489 |
| 4x4 SuperCab | 148.0" | 11,400 | 11,400 | 12,000 | 12,000 | 3,963 | 3,750 | 3,837 | 3,821 |
| 4x4 SuperCab | 164.2" | 11,800 | 11,800 | 12,300 | 12,300 | 4,256 | 4,042 | 4,011 | 3,996 |
| 4x4 Crew Cab | 159.8" | 11,499 | 11,499 | 12,000 | 12,000 | 3,918 | 3,705 | 3,655 | 3,639 |
| 4x4 Crew Cab | 176.0" | 11,900 | 11,900 | 12,400 | 12,400 | 4,203 | 3,990 | 3,792 | 3,776 |
| F-350 DRW Super Duty¹ | | | | | | | | | |
| 4x2 Reg. Cab | 141.6" | 14,000 | 14,000 | 14,000 | 14,000 | 7,344 | 7,236 | 6,558 | 6,542 |
| 4x2 SuperCab | 164.2" | - | - | 14,000 | 14,000 | - | - | 5,664 | 5,649 |
| 4x2 Crew Cab | 176.0" | - | - | 14,000 | 14,000 | - | - | 5,478 | 5,463 |
| 4x4 Reg. Cab | 141.6" | 14,000 | 14,000 | 14,000 | 14,000 | 6,903 | 6,807 | 6,129 | 6,114 |
| 4x4 SuperCab | 164.2" | 14,000 | 14,000 | 14,000 | 14,000 | 6,020 | 5,924 | 5,248 | 5,232 |
| 4x4 Crew Cab | 176.0" | 14,000 | 14,000 | 14,000 | 14,000 | 5,794 | 5,698 | 4,989 | 4,973 |
| F-450 DRW Super Duty¹ | | | | | | | | | |
| 4x2 Reg. Cab | 141.6" | - | - | 14,000 | 14,000 | - | - | 5,983 | 5,877 |
| 4x2 Crew Cab | 176.0" | - | - | 14,000 | 14,000 | - | - | 4,788 | 4,773 |
| 4x4 Reg. Cab | 141.6" | - | - | 14,000 | 14,000 | - | - | 5,497 | 5,482 |
| 4x4 Crew Cab | 176.0" | - | - | 14,000 | 14,000 | - | - | 4,488 | 4,473 |

1. Requires Camper Package option. 2. With Trailer Tow Package. 3. With available 9,900-lb. GVWR Package.

Maximum cargo weight capabilities requires Camper Package (471) and are exclusive of the weight of the occupants in the vehicle, computed as 150-lbs. times the number of designated seating positions, and vary based on cargo, vehicle configuration, accessories, and option content. See Truck Camper Loading document provided with the vehicle for carrying capacity of a specific vehicle. For additional information, see your Ford Dealer.

SUPER DUTY® CHASSIS CABS – WORK-READY

The 2024 Super Duty Chassis Cab models define the legendary work ethic and capability associated with being BUILT FORD TOUGH®. They meet the needs of a multitude of commercial applications.

Powerful engines, a heavy-duty 10-speed automatic transmission and available, innovative driver-assist technologies make F-350®/F-450®/F-550® and the F-600® Super Duty Chassis Cabs smart and capable. They are always ready to be upfit and designed to conquer the rugged jobs.

STANDARD, HEAVY-DUTY TORQSHIFT® 10-SPEED AUTOMATIC TRANSMISSION FEATURES

Live-Drive power takeoff (PTO) provision with mobile mode and up to 300 lb.-ft. of torque – standard on all Chassis Cab models

Selectable Drive Modes (Normal, Tow/Haul, Slippery, Eco and Deep Sand/Snow)

SelectShift® capability and Progressive Range Select



CNG/Propane Gaseous Engine Prep Package is available for 7.3L V8 engine.¹ Package includes hardened valves and valve seats to help ready your Super Duty for alternative-fuel upfits.

F-550 XL Chassis Cab in Antimatter Blue

¹. Available on XL and XLT F-450, F-550 and F-600 Chassis Cabs only.

FOR MORE INFORMATION ON ANY OF THESE FORD TRUCKS, SEE YOUR FORD DEALER OR VISIT WWW.FORD.COM.



CLASS A MOTORHOME CHASSIS

FEATURES

Six wheelbase choices:
178/190/208/228/242/252-inch

Six Gross Vehicle Weight Ratings (GVWRs): 16,000/18,000/20,500/22,000/24,000/26,000 lbs.

Three Gross Combination Weight Ratings (GCWRs): 23,000/26,000/30,000 lbs. for excellent towing capabilities (7,000 lbs. maximum trailer weight at 16,000-lb. GVWR)

7.3L OHV V8 gas engine (335 hp/468 lb.-ft. of torque¹)

6-speed automatic transmission with tow/haul mode

Power 4-wheel disc Anti-lock Brake System (ABS) for consistent, responsive braking performance

Standard traction control for better vehicle handling when braking

19.5-inch steel wheels and tires included with 16,000/18,000/20,500-lb. GVWR; 19.5-inch wheels and tires optional with 22,000-lb. GVWR

22.5-inch aluminum wheels and tires included with 22,000/24,000/26,000-lb. GVWR

81-inch front tread width (79-inch on 22,000/24,000/26,000-lb. GVWRs)

Large-diameter stabilizer bars, front and rear, for ride control

Heavy-duty front track bar enhances ride and handling on all models (optional on 16,000-lb. GVWR)

Designed to accommodate wide-body and slide-out type motorhomes

7-wire trailer wiring harness with relays, blunt cut and labeled

Hill start assist

Embedded modem

Standard Electronic stability control

High-capacity front axle system

80-gallon fuel tank, aft axle

Heavy-duty shock absorbers

Air Conditioning Prep Package

CNG/LPG Gaseous Fuel Prep Package available

Available Driver-Assist Technology Package



COMMERCIAL STRIPPED CHASSIS



FEATURES

Five wheelbase choices:
158/168²/178/190/208-inch

Three Gross Vehicle Weight Ratings (GVWRs): 16,000/19,500/22,000 lbs.

Four Gross Combination Weight Ratings (GCWRs): 23,000/26,000/27,200²/29,700² lbs.

7,700 lbs. maximum trailer weight with 19,500-lb. or 22,000-lb. GVWR with optional Parcel Delivery Package (7,000 lbs. maximum trailer weight at 16,000-lb. GVWR)

7.3L OHV V8 gas engine (335 hp/468 lb.-ft. of torque¹)

6-speed automatic transmission

Power 4-wheel disc Anti-lock Brake System (ABS) for consistent, responsive braking performance

Standard electronic stability control

19.5-inch steel wheels and tires

7-wire trailer wiring harness with relays, blunt cut and labeled

Fleet telematics modem

40-gallon fuel tank capacity, aft of axle

Front and rear stabilizer bars

Driver's steering column positioned for easy ingress and egress

Galvanized frame available on 208-inch wheelbase with 19,500-lb. or 22,000-lb. GVWR and included with Parcel Delivery Package

Low load floor height for ease of cargo loading

Heavy-duty Sachs shock absorbers

Traction control

Hill start assist

Fleet telematics modem

Air Conditioning Prep Packages available

Driver-Assist Technology Package available

CNG/LPG Gaseous Fuel Prep Package available

M Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in centimeters, multiply inches by 2.54; to obtain information in liters, multiply gallons by 3.8; to obtain information in kilometers, multiply miles by 1.6.

¹ Horsepower and torque ratings determined based upon testing requirements prescribed in SAE J1349. Your results may vary. Horsepower and torque are independent attributes and may not be achieved simultaneously. ² Only available with Parcel Delivery Package (59P).

Maximum towing capabilities require Parcel Delivery Package (59P) for Commercial Stripped Chassis. For additional information on Class A Motorhome Chassis and Commercial Stripped Chassis, see your Ford Dealer.

2025 E-SERIES® CLASS C MOTORHOME CHASSIS



MOTORHOME CUSTOMER CARE

Customer Assistance Center

This 24-hour, seven-days-a-week hotline was designed to serve both motorhome owners and RV dealers. By simply calling 1-800-444-3311, the caller has access to:

The nearest appropriate service location

Assistance in scheduling a service appointment

Service assistance for motorhome customers and RV dealers in resolving Ford chassis-related concerns

In-Dealership Service Support

Over 1,900 Ford dealerships in the U.S. and Canada provide Class C motorhome service support

Certified service technicians backed by computerized diagnostics and national technical hotline support

Verification of available owner notification and recall information affecting motorhomes

E-350 Cutaway DRW in Oxford White

FEATURES

Three wheelbase choices:
138/158/176-inch

Up to 14,500-lb. GVWR and
22,000-lb. GCWR¹

7.3L V8 engine

6-speed automatic
transmission

Twin-I-Beam independent
front suspension (with caster/
camber adjustment), front
stabilizer bar and gas-
pressurized shock absorbers
contribute to a smooth,
comfortable ride

Driver and front passenger
airbags²

Steel ladder-type truck frame
with seven cross members

Out-front engine design
provides spacious cab with
access to “living area” and ease
of ingress/egress

40-gallon fuel tank (E-350™;
optional on E-450™); 55-gallon
fuel tank (E-450; optional on
E-350 DRW with 11,500- or
12,500-lb. GVWR)

Standard electronic stability
control

Comfortable driver position
with updated ergonomic
instrument panel and controls

Available Driver-Assist
Technology Package

Fleet telematics modem

Traction control

Standard hill start assist

Available dual alternators –
240-amp/157-amp

CNG/Propane Gaseous Fuel
Prep Package available

1. 22,000-lb. GCWR requires electrical connector heat shield on all E-450 Cutaways. 2. Always wear your safety belt.

TRANSIT® CLASS C MOTORHOME CHASSIS



T-350HD AWD LWB-EL DRW in Oxford White

FEATURES

Three wheelbase choices: 138/156/178-inch
Up to 11,000-lb. GVWR¹ and 15,000-lb. GCWR¹
Two engine choices: 3.5L PFDI V6 gas and 3.5L EcoBoost® V6
10-speed automatic transmission with SelectShift®
Available All-Wheel-Drive (AWD)
Ford Co-Pilot360® Technologies²
Driver and front passenger airbags³
4-wheel disc Anti-lock Brake System (ABS)
AdvanceTrac® with Roll Stability Control™ (RSC®)
Independent MacPherson strut front suspension and stabilizer bar
Leaf spring rear suspension with heavy-duty shock absorbers
25-gallon fuel tank capacity; 31-gallon available
Frame rail extension adapters
Available Trailer Brake Controller (TBC)
Available Tow/Haul Mode with Trailer Wiring Provisions
Available dual alternators – 240-amp/157-amp



NOTE: Image shown on TV screen is simulated.

1. Only available with 3.5L EcoBoost. 2. Driver-assist features are supplemental and do not replace the driver's attention, judgment and need to control the vehicle. It does not replace safe driving. See Owner's Manual for details and limitations. 3. Always wear your safety belt.

FOUR-WHEEL-DOWN TOWING

Many motorhome owners prefer the practicality of having another vehicle along when they travel. In fact, towing another vehicle behind the motorhome has become more and more popular in recent years. Furthermore, many of those who want to tow another vehicle prefer one that can be easily towed without a dolly or trailer.



The chart on this page shows which car and truck models can be towed with all four wheels down. For safe operation, towed vehicles (or dollies or trailers carrying them) should be equipped with a separate functional brake system. See pages 37 and 45 for additional brake information.

Note: Some aftermarket camper centers offer kits which may allow vehicles with automatic transmissions to be flat-towed. Check your new vehicle Warranty Guide, as this could void the warranty of your vehicle.

INDIVIDUAL VEHICLES HAVE DIFFERENT RESTRICTIONS AND TOWING PROCEDURES. CONTACT YOUR FORD DEALER FOR COMPLETE DETAILS.

FOUR-WHEEL-DOWN AVAILABILITY

| | Automatic Transmission | Manual Transmission |
|--|------------------------|---------------------|
| 2024 FORD CARS | | |
| Mustang® – All Models | No | No |
| 2024 FORD ELECTRIC VEHICLES | | |
| Mustang Mach-E® | No | N/A |
| E-Transit™ | No | N/A |
| F-150® Lightning® | No | N/A |
| 2024 FORD CUVS/SUVS | | |
| Bronco® Sport | No | N/A |
| Escape® | No | N/A |
| Escape Hybrid | Yes ^{1,2,3} | N/A |
| Escape Plug-in Hybrid | Yes ^{1,2,3} | N/A |
| Edge® | No | N/A |
| Edge ST | Yes ^{4,5,6,7} | N/A |
| Bronco | Yes ⁹ | Yes ⁹ |
| Explorer® | No | N/A |
| Expedition®/Expedition MAX 4x2 | No | N/A |
| Expedition/Expedition MAX 4x4 | Yes ^{8,9} | N/A |
| 2024 FORD TRUCKS | | |
| Maverick® | No | N/A |
| Maverick Hybrid | Yes ^{1,2,3} | N/A |
| Ranger® 4x2 | No | N/A |
| Ranger 4x4 | No | N/A |
| F-150 Pickup 4x2 | No | N/A |
| F-150 Pickup 4x4 | Yes ⁹ | N/A |
| F-150 Raptor Pickup 4x4 | Yes ⁹ | N/A |
| F-250®/350®/450®/550®/600® Super Duty® 4x2 | No | N/A |
| F-250/350/450/550/600 Super Duty 4x4 | Yes ⁹ | N/A |
| Transit® | No | N/A |
| 2025 E-Series® Cutaway/Stripped Chassis | No | N/A |

1. Maximum speed with hybrid transmission is 70 mph. 2. Select "Neutral Tow" mode – refer to Owner's Manual transmission and towing sections to follow procedures. 3. Start the engine and allow it to run for one (1) minute at the beginning of each day and every six (6) hours thereafter. 4. Intelligent all-wheel-drive (AWD)/4WD vehicles cannot be towed on a dolly. 5. Maximum speed with automatic transmission is 65 mph. 6. Start the engine and allow it to run for five (5) minutes at the beginning of each day and every six (6) hours thereafter. 7. Activate Manual Park Release (MPR) – refer to Owner's Manual to follow procedures. 8. Requires 2-speed transfer case. 9. Place the transfer case in the neutral tow position to engage the four-wheel-down towing feature – refer to Owner's Manual to follow procedure.

N/A – Not Applicable.

TOW-DOLLY FLEXIBILITY

Tow-dollies allow you to tow your vehicle behind a RV or motorhome if you are unable to four-wheel-down your car, SUV or truck. Tow-dollies work by elevating the vehicle's front drive wheels and resting them securely on the dolly while the back two wheels stay on the ground. They are not as long as the traditional trailers, which helps make turning corners easier.

TOW-DOLLY AVAILABILITY

| 2024 FORD CARS | FWD | RWD | AWD/4WD ¹ |
|----------------|-----|-----|----------------------|
| Mustang® | N/A | No | N/A |

2024 FORD ELECTRIC VEHICLES

| | | | |
|-------------------|-----|-----|-----|
| Mustang Mach-E | N/A | No | No |
| E-Transit™ | N/A | No | N/A |
| F-150® Lightning® | N/A | N/A | No |

2024 FORD CUVS/SUVS

| | | | |
|-----------------------|-----|-----|-----|
| Bronco® Sport | N/A | N/A | No |
| Escape® | Yes | N/A | No |
| Escape Hybrid | Yes | N/A | No |
| Escape Plug-in Hybrid | Yes | N/A | N/A |
| Edge® | N/A | N/A | No |
| Bronco | N/A | N/A | No |
| Explorer® | N/A | No | No |
| Expedition® | N/A | No | No |

2024 FORD TRUCKS

| | | | |
|---|-----|-----|-----|
| Maverick® | Yes | N/A | No |
| Maverick Hybrid | Yes | N/A | N/A |
| Ranger® | N/A | No | No |
| F-150® Pickup | N/A | No | No |
| Super Duty® Pickup/Chassis Cab | N/A | No | No |
| Transit® | N/A | No | No |
| 2025 E-Series® Cutaway/Stripped Chassis | N/A | No | N/A |

¹. AWD/4WD vehicles cannot be towed with 2 wheels lifted off the ground.

N/A – Not Applicable.



Before using the tow-dolly, read the manufacturer's instructions that came with the tow-dolly before towing, loading or unloading the dolly.

- Attach the appropriate trailer hitch and drawbar hardware to the vehicle for the tow-dolly
- Attach the tow-dolly to the drawbar. The tow-dolly should be completely secure and on level ground before the vehicle to be towed is put on or taken off the tow-dolly
- Drive the vehicle onto the tow-dolly with its front wheels
- Secure the vehicle to the tow-dolly according to the manufacturer's instructions
- Follow the instructions for attaching and connecting the auxiliary lights to the back of the vehicle being towed
- Test the auxiliary lights to make sure that the turn signals, stop lamps and running lights work properly

TOWING EQUIPMENT

It is essential that your vehicle includes any optional equipment needed to best perform its expected towing tasks. This equipment falls into two categories: **Required and Recommended.**

REQUIRED EQUIPMENT

Includes items that must be installed.* Your New Vehicle Limited Warranty (see your Ford Dealer for a copy) may be voided if you tow without them.

**Check with your dealer for additional requirements, restrictions and limited warranty details.*

Edge®

For trailers over 1,500 lbs. – Class II Trailer Tow Package (53G) and AWD

Bronco® Sport

For trailers over 1,500 lbs. – Class II Trailer Tow Package (53B)

Escape®

For trailers over 2,000 lbs. – Class II Trailer Tow Package (536)

Bronco

For trailers over 2,000 lbs. – dealer-installed towing equipment

Explorer®

For trailers over 3,000 lbs. – Class IV Trailer Tow Package (52T)

Expedition®

For trailers over 6,000 lbs. – Class IV Heavy-Duty Trailer Tow Package (536)

Transit®

For trailers over 5,000 lbs. – Heavy-Duty Trailer Tow Package (53B)

Maverick®

For trailers over 2,000 lbs. – Trailer Tow Package (53Q)

Ranger®

For trailers over 3,500 lbs. – Trailer Tow Package (53R)

F-150 Lightning®

For trailers over 5,000 lbs. with standard-range battery or trailers over 7,700 lbs. with extended-range battery – Trailer Tow Package (53D)

F-150® Pickup

For trailers over 11,600 lbs. – Tow/Haul Package (53T)

F-250® Pickup

For conventional towing greater than 18,200 lbs. – High-Capacity Axle Upgrade Package (535) required with 18" All-Season or 20" All-Terrain Tires

F-450®/F-550® Chassis Cab

For 37,000/40,000-lb. GCWR on F-550; 35,000-lb. GCWR on F-450 – High-Capacity Trailer Tow Package (535)

RECOMMENDED EQUIPMENT

(where not required)

Includes items that can make towing easier, and are strongly recommended for strenuous towing conditions. A weight-carrying hitch is recommended for all vehicles towing trailers less than 5,000 pounds. See pages 39 and 40 for vehicles other than Super Duty and for weight-distributing hitch towing requirements.

A weight-distributing hitch is required for certain Class III and all Class IV trailer applications.

For a listing of all SUV, Pickup Truck and Commercial-Oriented Vehicles towing equipment and trailer towing packages, see charts on the next three pages.

FRONTAL AREA LIMITATIONS

Frontal Area is the total area in square feet that a moving vehicle and trailer exposes to air resistance. The chart shows the maximum trailer frontal area that must be considered for a vehicle/trailer combination. Exceeding these limitations may significantly reduce the performance of your towing vehicle.

| Vehicle | Trailer Frontal Area Limitations | With |
|---|----------------------------------|--|
| Mustang® | 12 sq. ft. | All Applications |
| | 20 sq. ft. | Without Class II Trailer Tow Package |
| Bronco Sport | 30 sq. ft. | With Class II Trailer Tow Package |
| | 20 sq. ft. | Without Class II Trailer Tow Package |
| Escape | 30 sq. ft. | With Class II Trailer Tow Package |
| | 20 sq. ft. | Without Class II Trailer Tow Package |
| Edge | 30 sq. ft. | With Class II Trailer Tow Package |
| | 20 sq. ft. | Without Class II Trailer Tow Package |
| Explorer | 30 sq. ft. | Without Class IV Trailer Tow Package |
| | 40 sq. ft. | With 3.3L HEV V6 engine and Class IV Trailer Tow Package ¹ |
| | 55 sq. ft. | With Class IV Trailer Tow Package |
| Expedition | 55 sq. ft. | Without Class IV Heavy-Duty Trailer Tow Package |
| | 60 sq. ft. | With Class IV Heavy-Duty Trailer Tow Package |
| Bronco | 30 sq. ft. | Without dealer-installed towing equipment |
| | 30 sq. ft. | With dealer-installed towing equipment, Tow Rating of 3,500 lbs. or less |
| | 40 sq. ft. | With Raptor Tow Package 2 |
| Maverick | 20 sq. ft. | Without Trailer Tow Package (53Q) |
| | 40 sq. ft. | With Trailer Tow Package (53Q) |
| Ranger | 30 sq. ft. | Without Trailer Tow Package |
| | 55 sq. ft. | With Trailer Tow Package |
| F-150 Lightning | 40 sq. ft. | With standard-range battery and without Trailer Tow Package (53D) |
| | 55 sq. ft. | With standard-range battery and Trailer Tow Package (53D) |
| | 60 sq. ft. | With extended-range battery |
| F-150 Pickup | 55 sq. ft. | Vehicles with Trailer Tow Rating of 7,700 lbs. or less |
| | 65 sq. ft. | Vehicles with Trailer Tow Rating of 7,701 lbs. and greater |
| | 75 sq. ft. | All 5th-Wheel and Gooseneck Applications |
| F-250/F-350®/F-450/F-550/F-600® Super Duty® | 75 sq. ft. | All 5th-Wheel and Gooseneck Applications |
| | 60 sq. ft. | All Other Applications |
| Transit Cargo Van/Passenger Van | 55 sq. ft. | All Applications |
| Transit Cutaway/Chassis Cab | 72 sq. ft.* | See Incomplete Vehicle Manual (IVM) for frontal area restriction details |
| 2025 E-Series® Cutaway | 82 sq. ft.* | All Applications |

1. Police Interceptor Utility only. *Base vehicle frontal area.

Note: All vehicles calculated with SAE J2807® method except Cutaway/Chassis Cab models.



Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in kilometers, multiply miles by 1.6; to obtain information in square meters, multiply square feet by .09; to obtain information in centimeters, multiply inches by 2.54.

SPORT UTILITY VEHICLES TOWING EQUIPMENT & TRAILER TOWING PACKAGES

| Vehicle (Option Code) | Escape ¹ (536) | Edge (536) ² | Explorer (52T) | Expedition (536) | Bronco Sport (53B) | Bronco (NOC) | Bronco Raptor ³ (NOC) |
|---------------------------------------|------------------------------|----------------------------|-------------------|---------------------|--------------------------|-----------------|--|
| 7-Wire Harness & 4-/7-Pin Connector | | | I | S | | I ⁴ | S |
| Trailer Wiring Harness (4-Pin) | I | I | | | I | | |
| Trailer Module | | | | | | I ⁴ | S |
| Hitch Receiver (See chart on page 40) | I | I | I | S | I | I ⁴ | S |
| Aux. Auto Trans. Oil Cooler | I | | | | | | S |
| Upgraded Rear Axle | | | | I | | | |
| Tow/Haul Mode | | | S | S | | | S |
| Tow Hooks Front | | | | I ⁵ | S ⁶ | S | S |
| 2-Speed Automatic 4WD | | | | I ⁵ | | | |
| Trailer Brake Controller | | | | I | | | |
| Trailer Sway Control | I | I | S | S | I | S | S |
| Trailer Reverse Guidance | | | | I ⁷ | | | |
| 360-Degree Camera | | | | I ⁷ | | | S |
| Lane Keeping Alert | S | S | S | S | S | I ⁸ | S |
| Pro Trailer Backup Assist™ | | | | I | | | |

1. Available with 2.0L EcoBoost® I4 or 2.5L I4 Hybrid/Plug-in Hybrid (Platinum, ST-Line Select, ST-Line Elite and PHEV) only. **2.** Available with 2.0L EcoBoost I4 only and AWD only. Standard on ST. **3.** Bronco Raptor includes Tow Package 2 as standard equipment. **4.** Dealer-installed equipment. **5.** 4x4 only. **6.** Standard only on Badlands™. **7.** Availability varies by model. See your Ford Dealer for details. **8.** Included in Package 222A on Big Bend™ and Black Diamond™ Series.

Note: Content may vary depending on model, trim and/or powertrain. See your Ford Dealer for specific content information for all light trucks that will be used for towing to help ensure easy, proper connection of trailer lights.

LEGEND

I = Equipment is included in the package
S = Equipment is standard on the vehicle
(NOC) = No "Option Code" assigned

MAXIMUM TRAILER WEIGHTS IN POUNDS FOR PROPERLY EQUIPPED VEHICLES WITH NO CARGO*

CONVENTIONAL

9,300 Expedition®
5,600 Explorer®
4,500 Bronco® Raptor®
3,500 Bronco
3,500 Edge®
3,500 Escape®
2,200 Bronco Sport
1,000 Mustang®

*Weights shown are for specific vehicle configurations. See pages 34–36 for maximum trailer weight ratings by vehicle configuration.

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer.



Explorer Timberline in Forged Green Metallic. Optional features shown with available Ford Accessories.

PICKUP TRUCKS TOWING EQUIPMENT & TRAILER TOWING PACKAGES

| Vehicle (Option Code) | Maverick (53Q) | Ranger (53R) | Ranger (67P) | Ranger (67S, 67E, 67X) | Ranger Raptor (NOC) | F-150 Lightning (53D) ¹ | F-150 Lightning (17V) ² | F-150 (53T) | F-150 Raptor (NOC) | F-250/F-350/F-450 Super Duty Pickup ³ (535) | F-350/F-450 Super Duty Pickup (NOC) |
|--|----------------|-----------------|-----------------|------------------------|---------------------|------------------------------------|------------------------------------|-----------------|--------------------|--|-------------------------------------|
| 7-Wire Harness & 4-/7-Pin Connector | I | I | I | I | S | S | S | S | S | S | S |
| Hitch Receiver (See chart on page 40) | I | I | I | I | S | S | S | S | S | S | S |
| Aux. Auto Trans. Oil Cooler | I | | | | | | | | S | S | S |
| Radiator Upgrade | I | | | | | | | | S | | |
| Smart Trailer Tow Connector | | | | | | S | S | S | S | S | S ⁴ |
| Trailer Brake Wiring/Feed Kit | | | | | | | | | | S | S ⁵ |
| Upgraded Rear Axle | | | | | | | | | S | I | S ⁴ |
| Increased GCW (6.7L) | | | | | | | | I | | I | S ⁴ |
| Upgraded Rear Bumper | | | | | | | | I | | | |
| Tow/Haul Mode | | S | S | S | S | S | S | S | S | S | S |
| Tow Hooks, Front | | S ⁶ | S ⁶ | S ⁶ | S ⁶ | | | | S | S | S |
| 2-Speed Automatic 4WD | | | | | | | | | S | | |
| Trailer Brake Controller | I | | I | I | S | I | | I | S | S | S ⁴ |
| Trailer Sway Control | | S | S | S | S | S | S | S | S | S | S |
| Trailer Reverse Guidance | | | | | | | I | S ⁷ | | S ⁸ | S ⁸ |
| 360-Degree Camera | | S ⁹ | S ⁹ | S ⁹ | S | S ² | I | S ⁸ | S | S ¹⁰ | S ¹⁰ |
| Lane Keeping Alert | | S ¹¹ | S ¹¹ | S ¹¹ | S | S | S | S | S | S ¹² | S ¹² |
| Pro Trailer Backup Assist™ | | | I | I | S | | I | S ¹³ | S | S ⁸ | S ⁸ |
| Pro Trailer Hitch Assist | | | | | | | I | S ¹³ | S | S ⁸ | S ⁸ |
| Onboard Scales with Smart Hitch | | | | | | | I | I ⁷ | | S ¹² | S ¹² |
| Reverse Park Aid with Trailer Guidance | | | | I | S | | | | | | |

1. Optional on Pro, XLT and LARIAT; standard on Platinum. **2.** Standard on (311A) and above. **3.** Requires 6.7L diesel engine. **4.** F-350 DRW/F-450 only. **5.** In-cab, no controller (SRW). **6.** 4-wheel drive only. Not available with 2-wheel drive. **7.** Included with 360-Degree Camera on XLT series and above. **8.** Standard on XLT and above. **9.** Standard on LARIAT. Optional on XLT. **10.** Available across all trims. **11.** Standard on XLT and LARIAT. **12.** Standard on King Ranch®, Platinum and Limited. Optional on XLT and LARIAT. **13.** XLT series and above.

Note: Content may vary depending on model, trim and/or powertrain. See your Ford Dealer for specific content information for all light trucks that will be used for towing to help ensure easy, proper connection of trailer lights.

LEGEND

I = Equipment is included in the package
S = Equipment is standard on the vehicle
(NOC) = No "Option Code" assigned

MAXIMUM TRAILER WEIGHTS IN POUNDS FOR PROPERLY EQUIPPED VEHICLES WITH NO CARGO*

GOOSENECK

40,000 Super Duty® Pickup
11,600 F-150® Pickup

5TH-WHEEL

35,000 Super Duty Pickup
11,400 F-150 Pickup

CONVENTIONAL

30,000 Super Duty Pickup
13,500 F-150 Pickup
10,000 F-150 Lightning®
7,500 Ranger®
4,000 Maverick®

*Weights shown are for specific vehicle configurations. See pages 18–27, 33 for maximum trailer weight ratings by vehicle configuration.



Super Duty F-350 LARIAT Crew Cab in Darkened Bronze Metallic

COMMERCIAL-ORIENTED VEHICLES TOWING EQUIPMENT & TRAILER TOWING PACKAGES

| Vehicle (Option Code) | Transit (53B) ¹ | Transit (53D) | F-350/F-450/F-550 Super Duty Chassis Cab (NOC) | F-450/F-550 Super Duty Chassis Cab (535) ² | F-600 Super Duty Chassis Cab (NOC) |
|--|-------------------------------|------------------|---|--|---|
| 7-Wire Harness & 4-/7-Pin Connector | I ³ | I | | | |
| 7-Wire Harness (Blunt Cut) with Relays | | | S | S | S |
| Trailer Wiring Harness (4-Pin) | | I | | | |
| Trailer Wiring Provision | I | I | | | |
| Hitch Receiver (See chart on page 40) | I | | | | |
| Trailer Brake Wiring/Feed Kit | | | | I | |
| Trailer Brake Controller | | | S | S | S |
| Upgraded Rear Axle | | | | I | |
| Increased GCW (6.7L) | | | | I | |
| Tow/Haul Mode | I | I | S | S | S |
| Tow Hooks, Front | | | S | S | S |
| Trailer Sway Control | | I | S | S | S |
| Lane Keeping Alert | S | S | S | S | S |

1. Not available on Cutaway or Chassis Cab models. 2. Requires 6.7L diesel engine. 3. Includes relay system for backup/B+/running lights.

Note: Content may vary depending on model, trim and/or powertrain. See your Ford Dealer for specific content information for all light trucks that will be used for towing to help ensure easy, proper connection of trailer lights.

LEGEND

I = Equipment is included in the package
S = Equipment is standard on the vehicle
(NOC) = No "Option Code" assigned

M Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in centimeters, multiply inches by 2.54.

MAXIMUM TRAILER WEIGHTS IN POUNDS FOR PROPERLY EQUIPPED VEHICLES WITH NO CARGO*

GOOSENECK

34,700 Super Duty® Chassis Cab

5TH-WHEEL

34,600 Super Duty Chassis Cab

CONVENTIONAL

18,500 Super Duty Chassis Cab

7,500 Transit® Cutaway/
Chassis Cab

6,900 Transit Cargo Van

4,500 Transit Passenger Van

*Weights shown are for specific vehicle configurations. See pages 28–29, 31–32 for maximum trailer weight ratings by vehicle configuration.

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer.



Super Duty F-550 XL Chassis Cab in Oxford White

TRAILER TOWING SELECTOR



F-SERIES® TRUCKS

- Select the F-Series cab design and drive system (4x2 or 4x4) you prefer. (See pages 18–29.)
- Read down the column to find the trailer weight that can be towed with engine/axle ratio combinations listed.
- GCWR column shows maximum allowable combined weight of vehicle, trailer and cargo (including passengers) for each engine/axle ratio combination.

Maximum Loaded Trailer Weight assumes a towing vehicle with any mandatory options, no cargo, tongue load of 10% (conventional trailer) or king pin weight of 15% (5th-wheel trailer) and driver and passenger (150 lbs. each). Weight of additional options, passengers, cargo and hitch must be deducted from this weight. Also check Required and Recommended Equipment on page 13.

TRAILER TOWING SELECTOR



F-150 Platinum Plus SuperCrew in Darkened Bronze Metallic

F-150® PICKUP CONVENTIONAL TOWING

Towing capability will vary based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference "eSourceBook" Job Aid "Spec'ing F-Series Trucks for Towing".

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

| Automatic Transmission | | | REGULAR CAB | | | | | | SUPERCAB | | SUPERCREW® | |
|------------------------|------------|-------------|---------------|---------------|---------------|---------------------|---------------|---------------------|---------------------|----------------------------|---------------|--|
| Engine | Axle Ratio | GCWR (lbs.) | 4x2 122.8" WB | 4x2 141.5" WB | 4x4 122.8" WB | 4x4 141.5" WB | 4x2 145.4" WB | 4x4 145.4" WB | 4x2 145.4" WB | 4x4 145.4" WB | 4x4 157.2" WB | |
| 5.0L 4-Valve V8 | 3.15 | 14,800 | | 9,600 | | | 9,600 | | 9,500 | | | |
| | | 13,200 | | | 8,000 | | | | | | | |
| | 3.73 | 14,800 | | 9,600 | | | 9,600 | | 9,500 | 9,300 | 9,200 | |
| | | 14,900 | | | | 9,600 | | 9,400 | | | | |
| | | 13,900 | 9,000 | | | | | | | | | |
| | | 15,300 | | 10,200 | | | | | | | | |
| | | 15,600 | | | | | 10,400 | | | | | |
| | | 15,700 | | | | 10,400 | | | 10,400 | | | |
| | | 15,800 | | | | | | | | 10,300/10,000 ¹ | 10,200 | |
| | | 17,700 | | | | | | 12,200 ² | | | | |
| 17,900 | | | | | | 12,700 ² | | | | | | |
| 18,100 | | | | | | | | 12,700 ² | | | | |
| 18,400 | | | | | | | | | 12,900 ² | 12,800 ² | | |

1. Tremor® Package. 2. Requires Tow/Haul Package (53T).

- Notes:**
- Do not exceed trailer weight of 5,000 lbs. when towing without a weight-distribution system.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Calculated with SAE J2807® method.

TRAILER TOWING SELECTOR



F-150 XLT SuperCrew in Atlas Blue Metallic

F-150® PICKUP CONVENTIONAL TOWING

Towing capability will vary based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference "eSourceBook" Job Aid "Spec'ing F-Series Trucks for Towing".

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

| Automatic Transmission | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | |
|-----------------------------------|------------|---------------------|--------------------------------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Engine | Axle Ratio | GCWR (lbs.) | REGULAR CAB | | SUPERCAB | | SUPERCREW® | | |
| | | | 4x2 141.5" WB | 4x4 141.5" WB | 4x2 145.4" WB | 4x4 145.4" WB | 4x2 145.4" WB | 4x4 145.4" WB | 4x4 157.2" WB |
| 2.7L GTDI V6 | 3.55 | 12,300 | 7,400 | | | | | | |
| | | 12,700 | | 7,500 | 7,500 | | | | |
| | | 12,800 | | | | 7,400 | 7,600 | | |
| | | 13,000 | | | | | | 7,500 | |
| | | 13,300 | 8,400 | | | | | | |
| 3.73 | | 13,400 | | 8,200 | 8,200 | 8,000 | 8,200 | | |
| | | 13,500 | | | | | | 8,000 | |
| | | 16,200 | 10,900 | | | | | | |
| 3.5L GTDI V6 | 3.31 | 16,300 | | | 10,800 | | | | |
| | | 16,500 | | 11,000 | | | 10,600 | | |
| | | 16,600 | | | | 10,600 | | | |
| | | 16,800 | | | | | | 10,400 | 10,800 |
| | | 16,800 | 10,900 | | | | | | |
| 3.55 | | 16,200 | 10,900 | | | | | | |
| | | 16,300 | | | 10,800 | | | | |
| | | 16,500 | | 11,000 | | | 10,600 | | |
| | | 16,600 | | | | 10,600 | | | |
| | | 16,800 | | | | | | 10,400 | 10,800 |
| | | 17,600 ³ | | | 10,900 | | | | |
| | | 17,700 ³ | | | | 10,600 | | | |
| 19,300 ³ | | | | | | 12,800 | | | |
| 19,400 ³ | | | | | | | 13,100 | 13,500 | |
| 3.73 | | 17,100 ⁴ | | | | | | 10,200 | |
| 3.5L GTDI V6 H.O. ¹ | 4.10 | 14,600 | | | | | | 8,200 | |
| | | 14,650 | | | | | | 8,200 | |
| 5.2L Supercharged V8 ² | 4.10 | 15,300 | | | | | | 8,700 | |

1. Raptor only. 2. Raptor R only. 3. Requires Tow/Haul Package (53T). 4. Tremor® Package.

- Notes:**
- Do not exceed trailer weight of 5,000 lbs. when towing without a weight-distribution system.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Calculated with SAE J2807® method.

M Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in kilometers, multiply miles by 1.6; to obtain information in centimeters, multiply feet by 30.48.

TRAILER TOWING SELECTOR

F-150® PICKUP HYBRID

CONVENTIONAL TOWING

| Automatic Transmission | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | |
|------------------------|------------|---------------------|--------------------------------------|------------------|
| Engine | Axle Ratio | GCWR (lbs.) | SUPERCREW® 4x4 145.4" WB | 4x4 157.2" WB |
| 3.5L Hybrid V6 | 3.73 | 17,100 | 10,800 | 10,800 |
| | | 18,400 ¹ | 11,200 | 11,000 |

5TH-WHEEL/ GOOSENECK TOWING

| Automatic Transmission | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | |
|------------------------|------------|---------------------|--------------------------------------|------------------|
| Engine | Axle Ratio | GCWR (lbs.) | SUPERCREW 4x4 145.4" WB | 4x4 157.2" WB |
| 3.5L Hybrid V6 | 3.73 | 17,100 | 7,100 | 7,000 |
| | | 18,400 ¹ | 7,100 | 7,000 |

1. Requires Tow/Haul Package (53T).

- Notes:**
- Do not exceed trailer weight of 5,000 lbs. when towing without a weight-distribution system.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Calculated with SAE J2807® method.



F-150 XLT SuperCrew 4x4 in Iconic Silver Metallic

F-150 LIGHTNING®

CONVENTIONAL TOWING

| Automatic Transmission | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | |
|-------------------------------|-----------------------|-------------------------|--------------------------------------|--|
| Engine | Axle Ratio | GCWR (lbs.) | SUPERCREW 4x4 145.4" WB | |
| Electric (F-150 Lightning) | 9.61 | 11,700 ² | 5,000 | |
| | | 12,200 ^{2,7} | 5,100/5,000 ⁶ | |
| | | 14,400 ^{2,3} | 7,700 | |
| | | 14,800 ³ | 7,700 | |
| | | 14,900 ³ | 7,700 ⁶ | |
| | | 15,000 ⁴ | 7,700 | |
| | | 15,900 ^{4,5} | 8,500 | |
| | | 16,700 ^{3,4,6} | 9,500 | |
| | 17,300 ^{3,4} | 10,000 | | |

2. Standard range battery. 3. Requires Max Trailer Tow Package (53D). 4. Extended range battery. 5. Platinum model. 6. Requires 20" All-Terrain tires. 7. LFP 4P battery, late availability.

- Notes:**
- Do not exceed trailer weight of 5,000 lbs. when towing without a weight-distribution system.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Calculated with SAE J2807® method.



F-150 Lightning LARIAT SuperCrew 4x4 in Rapid Red Metallic Tinted Clearcoat

TRAILER TOWING SELECTOR



F-150 LARIAT SuperCrew in Rapid Red Metallic Clearcoat

F-150® PICKUP 5TH-WHEEL/GOOSENECK TOWING

Towing capability will vary based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference "eSourceBook" Job Aid "Spec'ing F-Series Trucks for Towing".

| Automatic Transmission | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | | | | | | | |
|------------------------|------------|-------------|--------------------------------------|---------------|---------------|---------------|---------------|---------------|----------------------------|----------------------------|--------------------------|--------|--------|--------|--|
| Engine | Axle Ratio | GCWR (lbs.) | REGULAR CAB | | | | SUPERCAB | | SUPERCREW® | | | | | | |
| | | | 4x2 122.8" WB | 4x2 141.5" WB | 4x4 122.8" WB | 4x4 141.5" WB | 4x2 145.4" WB | 4x4 145.4" WB | 4x2 145.4" WB ¹ | 4x4 145.4" WB ¹ | 4x4 157.2" WB | | | | |
| 5.0L 4-Valve V8 | 3.15 | 14,800 | | | | | | 9,500 | | 9,500 | | | | | |
| | | 13,200 | | | | 8,000 | | | | | | | | | |
| | | 14,800 | | | | | | 9,500 | | 9,500 | | 9,200 | 9,100 | | |
| | 3.73 | 14,900 | | | | | 9,500 | | 9,400 | | | | | | |
| | | | 13,900 | 8,800 | | | | | | | | | | | |
| | | | 14,600 | | | 8,400 | | | | | | | | | |
| | | 15,300 | | | 10,100 | | | | | | | | | | |
| | | | 15,600 | | | | | 10,300 | | | | | | | |
| | | | 15,700 | | | | | 10,300 | | 9,900 | | | | | |
| | | | 15,800 | | | | | | | | 9,800/8,100 ² | | 10,000 | | |
| | | | 15,900 | | | | | | | | 10,000 | | | | |
| | | | 17,700 ³ | | | | | | | | 10,000 | | | | |
| | | | 17,900 ³ | | | | | | 10,300 | | | | | | |
| | | | 18,100 ³ | | | | | | | | 11,600 | | | | |
| | | | 18,400 ³ | | | | | | | | | 10,300 | | 10,300 | |

1. Vehicles equipped with a 5.5' box will accept a 5th-wheel hitch but most 5th-wheel trailer designs are not compatible with this model.
2. Tremor® Package. 3. Requires Tow/Haul Package (53T).

- Notes:**
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer king pin load weight should be 15% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer king pin load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Calculated with SAE J2807® method.

TAILGATE CLEARANCE

Considerations When Towing a 5th-Wheel or Gooseneck Trailer†

| Model | F-150 |
|---------------------------|-------------|
| Max. Tailgate Height 4x4* | 58.3 inches |

†5th-wheel towing is not recommended for Raptor or Lightning models.
*Distance from ground to top of closed tailgate lip at base curb weight.

Note: Maximum tailgate height will vary based upon vehicle configuration, option content and tire size.

M Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in kilometers, multiply miles by 1.6; to obtain information in centimeters, multiply feet by 30.48.

TRAILER TOWING SELECTOR



F-150 King Ranch® SuperCrew 4x4 with Chrome Appearance Package in Oxford White

F-150® PICKUP 5TH-WHEEL/GOOSENECK TOWING

Towing capability will vary based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference “eSourceBook” Job Aid “Spec’ing F-Series Trucks for Towing”.

| Automatic Transmission | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | | |
|------------------------|---------------------|-------------|--------------------------------------|---------------|---------------|---------------|----------------------------|----------------------------|---------------|--|
| Engine | Axle Ratio | GCWR (lbs.) | REGULAR CAB | | SUPERCAB | | SUPERCREW® | | | |
| | | | 4x2 141.5" WB | 4x4 141.5" WB | 4x2 145.4" WB | 4x4 145.4" WB | 4x2 145.4" WB ¹ | 4x4 145.4" WB ¹ | 4x4 157.2" WB | |
| 2.7L GTDI V6 | 3.55 | 12,300 | 7,300 | | | | | | | |
| | | 12,700 | | 7,400 | 7,500 | | | | | |
| | | 12,800 | | | | 7,300 | 7,400 | | | |
| | 3.73 | 13,000 | | | | | | 7,200 | | |
| | | 13,300 | 8,300 | | | | | | | |
| | | 13,400 | | 8,100 | 7,500 | 7,500 | 7,400 | | | |
| 3.5L GTDI V6 | 3.31 | 13,500 | | | | | 7,200 | | | |
| | | 16,200 | 10,900 | | | | | | | |
| | | 16,300 | | | 8,500 | | | | | |
| | | 16,500 | | 10,300 | | | 8,200 | | | |
| | | 16,600 | | | | 8,300 | | | | |
| | | 16,800 | | | | | | 8,100 | 8,300 | |
| | 3.55 | 16,200 | 10,900 | | | | | | | |
| | | 16,300 | | | 8,500 | | | | | |
| | | 16,500 | | 10,300 | | | 8,200 | | | |
| | | 16,600 | | | | 8,300 | | | | |
| | | 16,800 | | | | | | 8,100 | 8,300 | |
| | | 17,600 | | | 8,500 | | | | | |
| 3.73 | 17,700 ² | | | | | 8,300 | | | | |
| | 19,300 ² | | | | | | 10,100 | | | |
| | 19,400 ² | | | | | | | 8,800 | 9,200 | |
| | 17,100 ³ | | | | | | | 7,900 | | |

1. Vehicles equipped with a 5.5' box will accept a 5th-wheel hitch but most 5th-wheel trailer designs are not compatible with this model. 2. Requires Tow/Haul Package (53T). 3. Tremor® Package.

- Notes:**
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer king pin load weight should be 15% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer king pin load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Calculated with SAE J2807® method.

TRAILER TOWING SELECTOR



F-250 Tremor® Crew Cab in Darkened Bronze Metallic

F-250® SRW SUPER DUTY® PICKUP CONVENTIONAL TOWING

Towing capability will vary based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference “eSourceBook” Job Aid “Spec’ing F-Series Trucks for Towing”.

| Automatic Transmission | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | | | | |
|---------------------------|--------------------|---------------------|--------------------------------------|----------------------|--------------------------|----------------------|--------------------------|----------------------|--------------------------|----------------------|--------------------------|----------------------|
| Engine | Axle Ratio | GCWR (lbs.) | REGULAR CAB | | SUPERCAB | | | | CREW CAB | | | |
| | | | 4x2 141.6" WB 8' Box | 4x4 141.6" WB 8' Box | 4x2 148.0" WB 6-3/4' Box | 4x2 164.2" WB 8' Box | 4x4 148.0" WB 6-3/4' Box | 4x4 164.2" WB 8' Box | 4x2 159.8" WB 6-3/4' Box | 4x2 176.0" WB 8' Box | 4x4 159.8" WB 6-3/4' Box | 4x4 176.0" WB 8' Box |
| 6.7L V8 Turbo Diesel | 3.31 | 23,500 | 16,600 | 16,200 | | 16,200 | 15,900 | 15,800 | 16,200 | 15,900 | 15,800 | 15,500 |
| | | 30,000 ¹ | 18,200 | 20,000 | | | 20,000 | 22,000 | 19,500 | 19,500 | 22,000 | 21,900 |
| | 3.55 | 30,000 ¹ | 18,200 | 20,000 | 18,200 | 19,500 | 20,000 | 22,000 | 19,500 | 19,500 | 22,000 | 21,900 |
| 6.7L V8 H.O. Turbo Diesel | 3.55E ² | 28,300 ³ | | | | | | | | | 18,200 | |
| | 3.31 | 31,000 ¹ | 18,200 | 20,000 | | | 20,000 | 22,000 | 19,500 | 19,500 | 22,000 | 22,000 |
| | 3.55 | 31,000 ¹ | 18,200 | 20,000 | 18,200 | 19,500 | 20,000 | 22,000 | 19,500 | 19,500 | 22,000 | 22,000 |
| 6.8L V8 | 3.73 | 21,000 | 14,800 | 14,400 | 14,500 | 14,400 | 14,100 | 14,000 | 14,500 | 14,300 | 14,100 | 13,800 |
| | 4.30 | 23,500 | 17,300 | 16,900 | 17,000 | 16,900 | 16,600 | 16,500 | 17,000 | 16,800 | 16,600 | 16,300 |
| 7.3L V8 | 3.73 | 23,500 | | 16,800 | 17,000 | | 16,500 | 16,400 | | | 16,600 | 16,200 |
| | 3.73E ² | 24,600 | 18,200 | 17,900 | 18,100 | | 17,600 | 17,500 | 18,000 | 17,800 | 17,700 | 17,300 |
| | 4.30 | 26,000 | 18,200 | 18,200 | 18,200 | | 18,200 | 18,200 | 18,200 | 18,200 | 18,200 | 18,200 |

1. Requires F-250 High-Capacity Axle Upgrade Package (535). 2. 3.55E and 3.73E are electronic locking rear axles. 3. Tremor® Off-Road Package (17Y).

- Notes:**
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Conventional trailer tongue load weight should be 10% (15% for 5th-wheel and gooseneck towing) of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo must not cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Calculated with SAE J2807® method.
 - Trailer towing values are the same for weight-carrying and weight-distributing hitches.
 - If using load bars for weight distribution, Ford recommends 50% front axle load restoration (FALR).

TAILGATE CLEARANCE

Considerations When Towing a 5th-Wheel or Gooseneck Trailer

| Model | F-250 SRW | F-350® SRW | F-350® DRW | F-450® DRW | TREMOR |
|---------------------------|------------------|------------------|------------------|------------------|------------------|
| Max. Tailgate Height 4x4* | 57.8–60.0 inches | 56.7–59.7 inches | 58.1–58.9 inches | 58.8–59.3 inches | 59.7–61.3 inches |

*Distance from ground to top of closed tailgate lip at base curb weight.

Note: Maximum tailgate height will vary based upon vehicle configuration, option content and tire size.

TRAILER TOWING SELECTOR



F-250 LARIAT Crew Cab in Agate Black

F-250® SRW SUPER DUTY® PICKUP

5TH-WHEEL/GOOSENECK TOWING

Towing capability will vary based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference “eSourceBook” Job Aid “Spec’ing F-Series Trucks for Towing”.

| | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | | | | | | | | | | | | | | |
|---------------------------|------------|---------------------|--------------------------------------|------------|----------------------------|------------|--------------------------|------------|----------------------------|------------|---|---|---|---|--------------------------|------------|---|----------------------------|---|---|---|---|
| | | | REGULAR CAB | | | | SUPERCAB | | | | CREW CAB | | | | | | | | | | | |
| | | | 4x2 141.6" WB 8' Box | | 4x4 141.6" WB 8' Box | | 4x2 148.0" WB 6-3/4' Box | | 4x2 164.2" WB 8' Box | | 4x4 148.0" WB 6-3/4' Box | | 4x4 164.2" WB 8' Box | | 4x2 159.8" WB 6-3/4' Box | | 4x2 176.0" WB 8' Box | | 4x4 159.8" WB 6-3/4' Box | | 4x4 176.0" WB 8' Box | |
| Automatic Transmission | Axle Ratio | GCWR (lbs.) | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck |
| 6.7L V8 Turbo Diesel | 3.31 | 23,500 | 16,300 | 16,500 | 15,900/15,800 ⁴ | 16,100 | | | 15,900/15,800 ⁴ | 16,100 | 14,600/15,700 ³ /14,000 ⁴ | 15,700/15,800 ³ /15,000 ⁴ | 13,900/15,500 ³ /13,200 ⁴ | 14,900/15,700 ³ /14,200 ⁴ | 16,000 | 16,100 | 15,000/15,700 ³ /14,400 ⁴ | 15,900/15,400 ⁴ | 14,200/13,600 ⁴ /15,600 ³ | 15,300/14,600 ⁴ /15,700 ³ | 12,100/11,500 ⁴ /15,300 ³ | 13,200/12,500 ⁴ /15,400 ³ |
| | | 30,000 ¹ | 22,300 | 22,900 | 21,700 | 22,500 | | | | | 20,500 | 21,500 | 20,600 | 21,600 | 20,900 | 22,000 | 20,200 | 21,200 | 20,500 | 21,600 | 19,300 | 20,300 |
| | | 3.55 | 30,000 ¹ | 22,300 | 22,900 | 21,700 | 22,500 | 21,000 | 22,000 | 20,900 | 22,000 | 20,500 | 21,500 | 20,600 | 21,600 | 20,900 | 22,000 | 20,200 | 21,200 | 20,500 | 21,600 | 19,300 |
| 6.7L V8 H.O. Turbo Diesel | 3.55E | 28,300 ² | | | | | | | | | | | | | | | | | 19,500 | 20,000 | | |
| | 3.31 | 31,000 ¹ | 22,300 | 23,000 | 21,700 | 22,700 | | | | | 20,400 | 21,400 | 20,600 | 21,600 | 20,900 | 22,000 | 20,200 | 21,200 | 20,500 | 21,600 | 19,900 | 20,900 |
| | 3.55 | 31,000 ¹ | 22,300 | 23,000 | 21,700 | 22,700 | 21,000 | 22,000 | 20,900 | 22,000 | 20,400 | 21,400 | 20,600 | 21,600 | 20,900 | 22,000 | 20,200 | 21,200 | 20,500 | 21,600 | 19,900 | 20,900 |
| 6.8L V8 | 3.73 | 21,000 | 14,600 | 14,800 | 14,100 | 14,300 | 14,300 | 14,500 | 14,200 | 14,300 | 13,900 | 14,000 | 13,800 | 13,900 | 14,300 | 14,400 | 14,000 | 14,200 | 13,900 | 14,100 | 13,600 | 13,800 |
| | 4.30 | 23,500 | 17,100 | 17,300 | 16,600 | 16,800 | 16,800 | 17,000 | 16,700 | 16,800 | 16,400 | 16,500 | 16,300 | 16,400 | 16,800 | 16,900 | 16,500 | 16,700 | 16,400 | 16,600 | 16,100 | 16,300 |
| 7.3L V8 | 3.73 | 23,500 | | | 16,600 | 16,700 | 16,700 | 16,900 | | | 16,300 | 16,500 | 16,200 | 16,400 | | | | | 16,300 | 16,500 | 16,000 | 16,200 |
| | 3.73E | 24,600 | 18,100 | 18,300 | 17,700 | 17,800 | 17,800 | 18,000 | | | 17,400 | 17,600 | 17,300 | 17,500 | 17,800 | 17,900 | 17,500 | 17,700 | 17,400 | 17,600 | 17,000/17,100 ³ | 17,300 |
| | 4.30 | 26,000 | 19,500 | 19,500 | 19,100 | 19,200 | 19,200 | 19,400 | | | 18,800/18,300 ⁴ | 19,000 | 18,300/18,700 ³ | 18,900 | 19,200 | 19,300 | 18,900 | 19,100 | 18,800/18,500 ² | 19,000/18,500 ² | 17,000/18,500 ³ | 18,100/18,700 ³ |

1. Requires F-250 High-Capacity Axle Upgrade Package (535). 2. Tremor® Off-Road Package (17Y). 3. 10,000 plus GVWR. 4. Fixed 9,900 GVWR.

- Notes:**
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Conventional trailer tongue load weight should be 10% (15% for 5th-wheel and gooseneck towing) of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo must not cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Calculated with SAE J2807® method.
 - Trailer towing values are the same for weight-carrying and weight-distributing hitches.
 - If using load bars for weight distribution, Ford recommends 50% front axle load restoration (FALR).

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer.

TRAILER TOWING SELECTOR



F-350 LARIAT Sport Crew Cab in Oxford White

F-350® SRW SUPER DUTY® PICKUP

CONVENTIONAL TOWING

Towing capability will vary based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference "eSourceBook" Job Aid "Spec'ing F-Series Trucks for Towing".

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

| Automatic Transmission | | | REGULAR CAB | | SUPERCAB | | | | CREW CAB | | | |
|---------------------------|------------|---------------------|----------------------------|----------------------------|----------------------------|----------------------------|------------------------------|------------------------------|--------------------------|----------------------------|------------------------------|------------------------------|
| Engine | Axle Ratio | GCWR (lbs.) | 4x2 141.6" WB 8' Box | 4x4 141.6" WB 8' Box | 4x2 148.0" WB 6-3/4' Box | 4x2 164.2" WB 8' Box | 4x4 148.0" WB 6-3/4' Box | 4x4 164.2" WB 8' Box | 4x2 159.8" WB 6-3/4' Box | 4x2 176.0" WB 8' Box | 4x4 159.8" WB 6-3/4' Box | 4x4 176.0" WB 8' Box |
| 6.7L V8 Turbo Diesel | 3.31 | 31,000 | 20,000 | 20,000 | | | 20,000 | 23,200 | 23,000 | 23,000 | 23,200/23,100 ^{1,2} | 22,900/22,800 ^{1,2} |
| | 3.55 | 31,000 | 20,000 | 20,000 | 20,000 | | 20,000 | 23,200 | 23,000 | 23,000 | 23,200/23,100 ^{1,2} | 22,900/22,800 ^{1,2} |
| 6.7L V8 H.O. Turbo Diesel | 3.31 | 31,800 | 20,000 | 20,000 | | | | 24,000/23,900 ^{1,2} | 23,000 | 23,000 | | 23,700/23,600 ^{1,2} |
| | 3.55 | 31,200 ³ | | | | | | | | | 18,200 | |
| | | 35,200 | 20,000 | 20,000 | | | 23,000 | 20,000 | 24,000 | 23,000 | 24,000 | 24,800/25,000 ^{1,2} |
| 6.8L V8 | 3.73 | 21,000 | 14,500/14,700 ¹ | 14,300/14,200 ² | 14,500/14,400 ¹ | 14,400/14,300 ¹ | 14,100/14,000 ^{1,2} | 14,000/13,900 ^{1,2} | 14,300 | 14,100 | 13,900 | 13,800/13,700 ^{1,2} |
| | 4.30 | 24,400 | 17,900/18,100 ¹ | 17,700/17,600 ² | | | 17,500/17,400 ^{1,2} | 17,400/17,300 ^{1,2} | 17,700 | 17,500 | | 17,200/17,100 ^{1,2} |
| 7.3L V8 | 3.73 | 25,200 | 18,200 ¹ | 18,200 | 18,200 | | 18,100/18,000 ^{1,2} | 17,900 | 18,200 | 18,100/18,000 ¹ | 17,900/17,800 ² | 17,800/17,700 ^{1,2} |
| | 4.30 | 28,600 ³ | | | | | | | | | 18,200 | |
| | | 29,000 | 18,200 ¹ | 19,500 | 18,200 | | 19,500 | 19,500 | 19,500 | 19,500 | 19,500 | 19,500 |

1. 18" All-Season Tires. 2. 18" and 20" All-Terrain Tires. 3. Tremor® Off-Road Package (17Y).

Notes: • Combined weight of vehicle and trailer cannot exceed listed GCWR.

- Do not exceed the Maximum Loaded Trailer Weight listed.
- Conventional trailer tongue load weight should be 10% (15% for 5th-wheel and gooseneck towing) of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo must not cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
- Calculated with SAE J2807³ method.
- Trailer towing values are the same for weight-carrying and weight-distributing hitches.
- If using load bars for weight distribution, Ford recommends 50% front axle load restoration (FALR).

M Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in centimeters, multiply inches by 2.54.

TRAILER TOWING SELECTOR



F-350 XLT Crew Cab 4x4 in Antimatter Blue

F-350® SRW SUPER DUTY® PICKUP

5TH-WHEEL/GOOSENECK TOWING

Towing capability will vary based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference "eSourceBook" Job Aid "Spec'ing F-Series Trucks for Towing".

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

| | | | REGULAR CAB | | | | SUPERCAB | | | | CREW CAB | | | | | | | | | | | |
|---------------------------|------------|-------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| | | | 4x2 141.6" WB 8' Box | | 4x4 141.6" WB 8' Box | | 4x2 148.0" WB 6-3/4' Box | | 4x2 164.2" WB 8' Box | | 4x4 148.0" WB 6-3/4' Box | | 4x4 164.2" WB 8' Box | | 4x2 159.8" WB 6-3/4' Box | | 4x2 176.0" WB 8' Box | | 4x4 159.8" WB 6-3/4' Box | | 4x4 176.0" WB 8' Box | |
| Automatic Transmission | Axle Ratio | GCWR (lbs.) | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck |
| 6.7L V8 Turbo Diesel | 3.31 | 31,000 | 22,100 ¹ 23,700 ¹ | 23,100 ¹ 23,800 ¹ | 22,000 ¹ 23,300 ^{1,2} | 23,000 ¹ 23,400 ^{1,2} | | | | | 20,800 ¹ 23,000 ^{1,2} | 21,900 ¹ 23,200 ^{1,2} | 21,000 ¹ 22,900 ^{1,2} | 22,100 ¹ 23,100 ^{1,2} | 20,800 ¹ 23,300 ¹ | 21,900 ¹ 23,400 ¹ | 20,300 ¹ 23,100 ¹ | 21,300 ¹ 23,200 ¹ | 20,500 ¹ 22,700 ¹ | 21,600 ¹ 23,000 ^{1,2} | 20,100 ¹ 22,500 ¹ | 21,100 ¹ 22,700 ¹ |
| | 3.55 | 31,000 | 22,100 ¹ 23,700 ¹ | 23,100 ¹ 23,800 ¹ | 22,000 ¹ 23,300 ^{1,2} | 23,000 ¹ 23,400 ^{1,2} | 21,400 ¹ 23,500 ¹ | 22,500 ¹ 23,600 ¹ | 21,400 ¹ 23,300 ¹ | 22,500 ¹ 23,500 ¹ | 20,800 ¹ 23,000 ^{1,2} | 21,900 ¹ 23,200 ^{1,2} | 21,000 ¹ 22,900 ^{1,2} | 22,100 ¹ 23,100 ^{1,2} | 20,800 ¹ 23,300 ¹ | 21,900 ¹ 23,400 ¹ | 20,300 ¹ 23,100 ¹ | 21,300 ¹ 23,200 ¹ | 20,500 ¹ 22,700 ¹ | 21,600 ¹ 23,000 ^{1,2} | 20,100 ¹ 22,500 ¹ | 21,100 ¹ 22,700 ¹ |
| 6.7L V8 H.O. Turbo Diesel | 3.31 | 31,800 | 22,100 ¹ 24,500 ¹ | 23,100 ¹ 24,600 ¹ | 22,000 ¹ 24,100 ¹ | 23,000 ¹ 24,200 ^{1,2} | | | | | 20,800 ¹ 23,800 ^{1,2} | 21,900 ¹ 24,000 ^{1,2} | 21,000 ¹ 23,000 ¹ | 22,100 ¹ 23,900 ^{1,2} | 20,800 ¹ 23,600 ¹ | 21,900 ¹ 24,200 ¹ | 20,300 ¹ 23,200 ¹ | 21,300 ¹ 24,000 ¹ | 20,500 ¹ 22,600 ¹ | 21,600 ¹ 23,700 ¹ | 20,100 ¹ 22,500 ¹ | 21,100 ¹ 23,500 ^{1,2} |
| | 3.55 | 31,200 | | | | | | | | | | | | | | | | | 23,000 ³ | 23,000 ³ | | |
| | | 35,200 | 22,100 ¹ 25,200 ¹ | 23,100 ¹ 26,300 ¹ | 22,000 ¹ 25,000 ¹ | 23,000 ¹ 26,000 ¹ | | | 21,400 ¹ 24,000 ¹ | 22,500 ¹ 25,100 ¹ | 20,800 ¹ 23,800 ¹ | 21,900 ¹ 24,900 ¹ | 21,000 ¹ 23,000 ¹ | 22,100 ¹ 24,000 ¹ | | | 20,300 ¹ 23,200 ¹ | 21,300 ¹ 24,300 ¹ | 20,500 ¹ 22,600 ¹ | 21,600 ¹ 23,700 ¹ | 20,100 ¹ 22,500 ¹ | 21,100 ¹ 23,500 ¹ |
| 6.8L V8 | 3.73 | 21,000 | 14,400 ¹ | 14,600 ¹ | 14,100 ¹ 14,000 ^{1,2} | 14,200 ¹ 14,200 ^{1,2} | 14,300 ¹ 14,200 ¹ | 14,400 | 14,100 | 14,300 ¹ 14,200 ¹ | 13,800 | 14,000 ¹ 13,900 ^{1,2} | 13,700 | 13,900 ¹ 13,800 ^{1,2} | 14,100 ¹ 14,000 ¹ | 14,300 ¹ 14,200 ¹ | 13,900 ¹ 13,800 ¹ | 14,000 ¹ 14,000 ¹ | 13,700 ¹ 13,600 ^{1,2} | 13,800 | 13,600 ¹ 13,500 ^{1,2} | 13,700 |
| | 4.30 | 24,400 | 17,800 ¹ | 18,000 ¹ | 17,500 ¹ 17,400 ^{1,2} | 17,600 | | | | | 17,200 | 17,400 ¹ 17,300 ^{1,2} | 17,100 | 17,300 ¹ 17,200 ^{1,2} | 17,500 ¹ 17,400 ¹ | 17,700 ¹ 17,600 ¹ | 17,300 ¹ 17,200 ¹ | 17,400 | | | 17,000 ¹ 16,900 ^{1,2} | 17,100 |
| 7.3L V8 | 3.73 | 25,200 | 18,400 ¹ | 18,600 ¹ | 18,100 ¹ 18,000 ^{1,2} | 18,200 | 18,200 | 18,400 ¹ 18,300 ¹ | | | 17,800 | 18,000 ¹ 17,900 ^{1,2} | 17,700 ¹ 17,600 ¹ | 17,900 ¹ 17,800 ^{1,2} | 18,100 ¹ 18,000 ¹ | 18,200 | 17,900 ¹ 17,800 ¹ | 18,000 | 17,700 ¹ 17,600 ^{1,2} | 17,800 | 17,600 ¹ 17,500 ^{1,2} | 17,700 |
| | 4.30 | 28,600 | | | | | | | | | | | | | | | | | 21,000 ³ | 21,000 ³ | | |
| | | 29,000 | 22,200 ¹ | 22,400 ¹ | 21,800 | 22,000 | 21,300 ¹ 22,000 ¹ | 22,200 ¹ 22,100 ¹ | | | 21,000 ¹ 21,600 ^{1,2} | 21,800 ¹ 21,700 ^{1,2} | 21,100 ¹ 21,500 ¹ | 21,700 ¹ 21,600 ^{1,2} | 20,800 ¹ 21,800 ¹ | 21,900 ¹ 22,000 ¹ | 20,600 ¹ 21,600 ¹ | 21,600 ¹ 21,800 ¹ | 20,600 ¹ 21,400 ^{1,2} | 21,600 | 21,100 ¹ 21,300 ^{1,2} | 21,500 |

1. 18" All-Season Tires. 2. 18" and 20" All-Terrain Tires. 3. Tremor® Off-Road Package (17Y).

Notes: • Combined weight of vehicle and trailer cannot exceed listed GCWR.

- Do not exceed the Maximum Loaded Trailer Weight listed.
- Conventional trailer tongue load weight should be 10% (15% for 5th-wheel and gooseneck towing) of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo must not cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
- Calculated with SAE J2807⁹ method.
- Trailer towing values are the same for weight-carrying and weight-distributing hitches.
- If using load bars for weight distribution, Ford recommends 50% front axle load restoration (FALR).

M Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in centimeters, multiply inches by 2.54.

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer.

TRAILER TOWING SELECTOR



F-450 XL Regular Cab in Agate Black Metallic

F-350®/450® DRW SUPER DUTY® PICKUPS CONVENTIONAL TOWING

Towing capability will vary based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page. See dealer and reference "eSourceBook" Job Aid "Spec'ing F-Series Trucks for Towing".

| Automatic Transmission | | | REGULAR CAB | | | | SUPERCAB | | | | CREW CAB | | | |
|---------------------------|------------|---------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|--|--|
| Engine | Axle Ratio | GCWR (lbs.) | F-350 4x2 141.6" WB 8' Box | F-350 4x4 141.6" WB 8' Box | F-450 4x2 141.6" WB 8' Box | F-450 4x4 141.6" WB 8' Box | F-350 4x2 164.2" WB 8' Box | F-350 4x4 164.2" WB 8' Box | F-350 4x2 176.0" WB 8' Box | F-350 4x4 176.0" WB 8' Box | F-450 4x2 176.0" WB 8' Box | F-450 4x4 176.0" WB 8' Box | | |
| 6.7L V8 Turbo Diesel | 3.55 | 40,000 | 24,800/18,200 ¹ | 24,800 | | | 26,700 | 26,700 | 27,000 | 27,000 | | | | |
| | 4.10 | 43,900 | 24,800/18,200 ¹ | 24,800 | | | 26,700 | 26,700 | 27,000 | 27,000 | | | | |
| | 4.30 | 43,500 | | | | | | | | | 30,000 | 30,000 | | |
| | | 46,700 | | | 25,000 | 25,000 | | | | | | | | |
| 6.7L V8 H.O. Turbo Diesel | 3.55 | 40,500 | 24,800 | 24,800 | | | 26,700 | 26,700 | 27,000 | 27,000 | | | | |
| | 4.10 | 45,600 | 24,800 | 24,800 | | | 26,700 | 26,700 | 28,000 | 28,000 | | | | |
| | 4.30 | 43,500 | | | | | | | | | 30,000 | 30,000 | | |
| | | 46,700 | | | 25,000 | 25,000 | | | | | | | | |
| | | 48,000 ² | | | 18,000 | | | | | | | | | |
| 6.8L V8 | 4.30 | 25,400 | 18,700/18,200 ¹ | 18,300 | | | | | | 17,800 | 17,600 | | | |
| 7.3L V8 | 3.73 | 25,700 | 18,900 | 18,500 | | | | | | 18,100 | 17,800 | | | |
| | 4.30 | 29,500 | 22,000 | 22,000 | | | | | | 21,900 | 21,600 | | | |

5TH-WHEEL/GOOSENECK TOWING

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

| Automatic Transmission | | | REGULAR CAB | | | | SUPERCAB | | | | CREW CAB | | | | | | | | | | | | |
|---------------------------|------------|---------------------|----------------------------|----------------------------|----------------------------|------------|----------------------------|------------|----------------------------|------------|----------------------------|------------|----------------------------|------------|----------------------------|------------|----------------------------|------------|----------------------------|------------|----------------------------|------------|--------|
| Engine | Axle Ratio | GCWR (lbs.) | F-350 4x2 141.6" WB 8' Box | | F-350 4x4 141.6" WB 8' Box | | F-450 4x2 141.6" WB 8' Box | | F-450 4x4 141.6" WB 8' Box | | F-350 4x2 164.2" WB 8' Box | | F-350 4x4 164.2" WB 8' Box | | F-350 4x2 176.0" WB 8' Box | | F-350 4x4 176.0" WB 8' Box | | F-450 4x2 176.0" WB 8' Box | | F-450 4x4 176.0" WB 8' Box | | |
| | | | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | 5th-Wheel | Goose-neck | |
| 6.7L V8 | 3.55 | 40,000 | 32,300/32,400 ¹ | 32,500/32,600 ¹ | 31,900 | 32,000 | | | | | 31,800 | 32,000 | 31,400 | 31,600 | 31,700 | 31,800 | 31,200 | 31,300 | | | | | |
| | 4.10 | 43,900 | 35,000/35,000 ¹ | 36,400/36,500 ¹ | 35,000 | 35,900 | | | | | 35,000 | 35,900 | 35,000 | 35,500 | 35,000 | 35,700 | 34,800 | 35,200 | | | | | |
| | 4.30 | 43,500 | | | | | | | | | | | | | | | | | | 34,000 | 34,700 | 32,000 | 33,100 |
| | | 46,700 | | | | | 35,000 | 38,600 | 35,000 | 36,900 | | | | | | | | | | | | | |
| 6.7L V8 H.O. Turbo Diesel | 3.55 | 40,500 | 32,800 | 32,900 | 32,300 | 32,500 | | | | | 32,300 | 32,500 | 31,900 | 32,100 | 32,100 | 32,300 | 31,700 | 31,800 | | | | | |
| | 4.10 | 45,600 | 35,000 | 38,000 | 35,000 | 37,600 | | | | | 35,000 | 37,600 | 35,000 | 37,200 | 35,000 | 37,400 | 34,700 | 35,800 | | | | | |
| | 4.30 | 43,500 | | | | | | | | | | | | | | | | | | 33,900 | 34,700 | 31,900 | 33,000 |
| | | 46,700 | | | | | 35,000 | 38,600 | 35,000 | 36,800 | | | | | | | | | | | | | |
| | | 48,000 ² | | | | | 35,000 | 40,000 | | | | | | | | | | | | | | | |
| 6.8L V8 | 4.30 | 25,400 | 18,500/18,700 ¹ | 18,600/18,900 ¹ | 18,000 | 18,200 | | | | | | | | 17,600 | 17,800 | | 17,400 | 17,500 | | | | | |
| 7.3L V8 | 3.73 | 25,700 | 18,700 | 18,800 | 18,200 | 18,400 | | | | | | | | 17,800 | 18,000 | | 17,600 | 17,700 | | | | | |
| | 4.30 | 29,500 | 22,500 | 22,500 | 22,000 | 22,200 | | | | | | | | 21,600 | 21,800 | | 21,400 | 21,500 | | | | | |

1. Heavy Duty Payload Package (68F).
2. 40k Gooseneck Tow Package (535).

- Notes:**
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Conventional trailer tongue load weight should be 10% (15% for 5th-wheel and gooseneck towing) of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo must not cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Calculated with SAE J2807[®] method.
 - Trailer towing values are the same for weight-carrying and weight-distributing hitches.
 - If using load bars for weight distribution, Ford recommends 50% front axle load restoration (FALR).

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer.

TRAILER TOWING SELECTOR

F-350® SUPER DUTY® CHASSIS CAB

CONVENTIONAL TOWING¹

Trailer weights shown assume 715-lb.–1,115-lb. second-unit body weight.

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

| Automatic Transmission | | | REGULAR CAB CHASSIS | | | | SUPERCAB CHASSIS | | | | CREW CAB CHASSIS | | | | | |
|------------------------|--------------------|-------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| Engine | Axle Ratio | GCWR (lbs.) | 4x2 SRW 145.3" WB | 4x4 SRW 145.3" WB | 4x2 DRW 145.3" WB | 4x2 DRW 169.3" WB | 4x4 DRW 145.3" WB | 4x4 DRW 169.3" WB | 4x2 SRW 167.9" WB | 4x4 SRW 167.9" WB | 4x2 DRW 167.9" WB | 4x4 DRW 167.9" WB | 4x2 SRW 179.8" WB | 4x4 SRW 179.8" WB | 4x2 DRW 179.8" WB | 4x4 DRW 179.8" WB |
| 6.7L V8 Diesel | 3.73E ² | 31,000 | | 13,500 | | | | | | 13,500 | | | 13,500 | 13,500 | | |
| | 3.73 | 34,000 | | | 17,500 | 17,500 | 17,500 | 17,500 | | | | 17,500 | | | 17,500 | 17,500 |
| | 4.10 | 34,500 | | | 17,500 | 17,500 | 17,500 | 17,500 | | | | 17,500 | | | 17,500 | 17,500 |
| 7.3L V8 | 3.73 | 23,500 | | | 16,400 | 16,100 | 16,000 | 15,700 | | | 15,900 | 15,600 | | | 15,900 | 15,500 |
| | 4.30E ² | 27,200 | 13,500 | 13,500 | | | | | 13,500 | 13,500 | | | 13,500 | 13,500 | | |
| | 27,500 | | | | 17,500 | 17,500 | 17,500 | 17,500 | | | 17,500 | 17,500 | | | 17,500 | 17,500 |

5TH-WHEEL TOWING

| | | | | | | | | | | | | | | | | |
|----------------|--------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 6.7L V8 Diesel | 3.73E ² | 31,000 | | 22,700 | | | | | | 20,100 | | | 21,100 | 19,600 | | |
| | 3.73 | 34,000 | | | 26,000 | 25,800 | 25,600 | 25,400 | | | | 25,200 | | | 25,500 | 25,100 |
| | 4.10 | 34,500 | | | 26,500 | 26,300 | 26,100 | 25,900 | | | | 25,700 | | | 26,000 | 25,600 |
| 7.3L V8 | 3.73 | 23,500 | | | 16,200 | 16,000 | 15,900 | 15,600 | | | 15,800 | 15,400 | | | 15,700 | 15,300 |
| | 4.30E ² | 27,200 | 20,300 | 19,800 | | | | | 19,900 | 19,400 | | | 19,700 | 19,300 | | |
| | 27,500 | | | | 20,200 | 20,000 | 19,900 | 19,600 | | | 19,800 | 19,400 | | | 19,700 | 19,300 |

GOOSENECK TOWING

| | | | | | | | | | | | | | | | | |
|----------------|--------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 6.7L V8 Diesel | 3.73E ² | 31,000 | | 23,100 | | | | | | 20,900 | | | 21,900 | 20,500 | | |
| | 3.73 | 34,000 | | | 26,100 | 25,900 | 25,800 | 25,500 | | | | 25,300 | | | 25,600 | 25,200 |
| | 4.10 | 34,500 | | | 26,600 | 26,400 | 26,300 | 26,000 | | | | 25,800 | | | 26,100 | 25,700 |
| 7.3L V8 | 3.73 | 23,500 | | | 16,300 | 16,100 | 16,000 | 15,700 | | | 15,900 | 15,500 | | | 15,800 | 15,400 |
| | 4.30E ² | 27,200 | 20,400 | 20,000 | | | | | 20,000 | 19,600 | | | 19,900 | 19,400 | | |
| | 27,500 | | | | 20,300 | 20,100 | 20,000 | 19,700 | | | 19,900 | 19,500 | | | 19,800 | 19,400 |

1. Super Duty Chassis Cab does not offer a conventional hitch receiver as a factory-installed option. 2. E = Electronic Locking Rear Axle.

Notes: • Combined weight of vehicle and trailer cannot exceed listed GCWR.

- Do not exceed the Maximum Loaded Trailer Weight listed.
- Trailer tongue (trailer king pin for 5th-wheel towing) load weight should be 10% (15% for 5th-wheel and gooseneck towing) of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo must not cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
- Trailer towing values are the same for weight-carrying and weight-distributing hitches.
- If using load bars for weight distribution, Ford recommends 50% front axle load restoration (FALR).

F-450® SUPER DUTY CHASSIS CAB

CONVENTIONAL TOWING¹

Trailer weights shown assume 715-lb.–1,115-lb. second-unit body weight.

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

| Automatic Transmission | | | REGULAR CAB CHASSIS | | | | SUPERCAB CHASSIS | | | | CREW CAB CHASSIS | | | | | | | |
|------------------------|------------|---------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| Engine | Axle Ratio | GCWR (lbs.) | 4x2 DRW 145.3" WB | 4x2 DRW 169.3" WB | 4x2 DRW 193.3" WB | 4x2 DRW 205.3" WB | 4x4 DRW 145.3" WB | 4x4 DRW 169.3" WB | 4x4 DRW 193.3" WB | 4x4 DRW 205.3" WB | 4x2 DRW 167.9" WB | 4x2 DRW 192.0" WB | 4x4 DRW 167.9" WB | 4x4 DRW 192.0" WB | 4x2 DRW 179.8" WB | 4x2 DRW 203.8" WB | 4x4 DRW 179.8" WB | 4x4 DRW 203.8" WB |
| 6.7L V8 Diesel | 4.10 | 34,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 |
| | 4.30 | 39,000 ² | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 |
| 7.3L V8 | 4.88 | 30,000 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 | 17,500 |

5TH-WHEEL TOWING

| | | | | | | | | | | | | | | | | | | |
|----------------|------|---------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 6.7L V8 Diesel | 4.10 | 34,500 | 25,700 | 25,600 | 25,300 | 25,100 | 25,500 | 25,200 | 24,800 | 24,700 | | 25,100 | 25,100 | 24,800 | 25,300 | 24,900 | 24,900 | 24,700 |
| | 4.30 | 39,000 ² | 30,200 | 30,100 | 29,800 | 29,600 | 30,000 | 29,700 | 29,300 | 29,200 | | 29,600 | 29,600 | 29,300 | 29,800 | 29,400 | 29,400 | 29,200 |
| 7.3L V8 | 4.88 | 30,000 | 22,000 | 21,800 | 21,500 | 21,300 | 21,700 | 21,400 | 21,100 | 21,000 | 21,600 | | 21,300 | 21,000 | 21,500 | 21,200 | 21,200 | 20,900 |

GOOSENECK TOWING

| | | | | | | | | | | | | | | | | | | |
|----------------|------|---------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 6.7L V8 Diesel | 4.10 | 34,500 | 25,800 | 25,700 | 25,400 | 25,200 | 25,600 | 25,400 | 25,000 | 24,900 | | 25,200 | 25,200 | 24,900 | 25,400 | 25,000 | 25,100 | 24,900 |
| | 4.30 | 39,000 ² | 30,300 | 30,200 | 29,900 | 29,700 | 30,100 | 29,900 | 29,500 | 29,400 | | 29,700 | 29,700 | 29,400 | 29,900 | 29,500 | 29,600 | 29,400 |
| 7.3L V8 | 4.88 | 30,000 | 22,100 | 21,900 | 21,600 | 21,400 | 21,900 | 21,600 | 21,200 | 21,100 | 21,700 | | 21,400 | 21,200 | 21,600 | 21,400 | 21,300 | 21,100 |

1. Super Duty Chassis Cab does not offer a conventional hitch receiver as a factory-installed option. 2. Requires Trailer Tow Package – High Capacity (535).

Notes: • Combined weight of vehicle and trailer cannot exceed listed GCWR.

- Do not exceed the Maximum Loaded Trailer Weight listed.
- Trailer tongue (trailer king pin for 5th-wheel towing) load weight should be 10% (15% for 5th-wheel and gooseneck towing) of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo must not cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
- Trailer towing values are the same for weight-carrying and weight-distributing hitches.
- If using load bars for weight distribution, Ford recommends 50% front axle load restoration (FALR).

TRAILER TOWING SELECTOR

F-550® SUPER DUTY® CHASSIS CAB CONVENTIONAL TOWING¹

Trailer weights shown assume 715-lb.–1,115-lb. second-unit body weight.

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

| Automatic Transmission | | | REGULAR CAB CHASSIS | | | | | | | | SUPERCAB CHASSIS | | | | CREW CAB CHASSIS | | | |
|------------------------|------------|-----------------------|---------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Engine | Axle Ratio | GCWR (lbs.) | 4x2 DRW 145.3" WB | 4x2 DRW 169.3" WB | 4x2 DRW 193.3" WB | 4x2 DRW 205.3" WB | 4x4 DRW 145.3" WB | 4x4 DRW 169.3" WB | 4x4 DRW 193.3" WB | 4x4 DRW 205.3" WB | 4x2 DRW 167.9" WB | 4x2 DRW 192.0" WB | 4x4 DRW 167.9" WB | 4x4 DRW 192.0" WB | 4x2 DRW 179.8" WB | 4x2 DRW 203.8" WB | 4x4 DRW 179.8" WB | 4x4 DRW 203.8" WB |
| 6.7L V8 Diesel | 4.10 | 34,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 |
| | 4.30 | 39,000 ² | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 |
| | | 43,000 ^{2,4} | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 |
| 7.3L V8 Diesel | 4.88 | 30,000 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 |

5TH-WHEEL TOWING

| | | | | | | | | | | | | | | | | | | |
|----------------|------|-----------------------|--------------------------------|--------------------------------|--------------------------------|--------|--------|--------------------------------|--------------------------------|--------------------------------|--------|--------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------------------------------|
| 6.7L V8 Diesel | 4.10 | 34,500 | 25,700 | 25,600 | 25,300 | 25,100 | 25,500 | 25,200 | 24,800 | 24,700 | 25,400 | 25,100 | 25,100 | 24,800 | 25,300 | 24,900 | 24,900 | 24,700 |
| | 4.30 | 39,000 ² | 30,200 | 30,100 | 29,800 | 29,600 | 30,000 | 29,700 | 29,300 | 29,200 | 29,900 | 29,600 | 29,600 | 29,300 | 29,800 | 29,400 | 29,400 | 29,200 |
| | | 43,000 ^{2,4} | 34,200 | 34,000 | 33,600 | 33,500 | 34,000 | 33,700 | 33,300 | 33,200 | 33,800 | 33,500 | 33,500 | 33,200 | 33,700 | 33,500 | 33,400 | 33,100 |
| 7.3L V8 Diesel | 4.88 | 30,000 | 22,000/ 21,900 ³ | 21,800/ 21,700 ⁴ | 21,500/ 21,400 ⁴ | 21,300 | 21,700 | 21,400/ 21,300 ⁴ | 21,100/ 21,000 ⁴ | 21,000/ 20,900 ⁴ | 21,600 | | 21,300/ 21,200 ⁴ | 21,000 | 21,500/ 21,400 ⁴ | 21,200 | 21,200/ 21,100 ⁴ | 20,900/ 20,800 ⁴ |

GOOSENECK TOWING

| | | | | | | | | | | | | | | | | | | |
|----------------|------|-----------------------|--------|--------------------------------|--------------------------------|--------|--------------------------------|--------------------------------|--------|--------------------------------|--------|--------|--------|--------------------------------|--------|--------------------------------|--------|--------------------------------|
| 6.7L V8 Diesel | 4.10 | 34,500 | 25,800 | 25,700 | 25,400 | 25,200 | 25,600 | 25,400 | 25,000 | 24,900 | | 25,200 | 25,200 | 24,900 | 25,400 | 25,000 | 25,100 | 24,900 |
| | 4.30 | 39,000 ² | 30,300 | 30,200 | 29,900 | 29,700 | 30,100 | 29,900 | 29,500 | 29,400 | | 29,700 | 29,700 | 29,400 | 29,900 | 29,500 | 29,600 | 29,400 |
| | | 43,000 ^{2,4} | 34,300 | 34,100 | 33,800 | 33,700 | 34,200 | 33,800 | 33,500 | 33,300 | | 33,700 | 33,600 | 33,400 | 33,800 | 33,600 | 33,500 | 33,300 |
| 7.3L V8 Diesel | 4.88 | 30,000 | 22,100 | 21,900/ 21,800 ⁴ | 21,600/ 21,500 ⁴ | 21,400 | 21,900/ 21,800 ³ | 21,600/ 21,500 ⁴ | 21,200 | 21,100/ 21,000 ⁴ | 21,700 | | 21,400 | 21,200/ 21,100 ⁴ | 21,600 | 21,400/ 21,300 ³ | 21,300 | 21,100/ 21,000 ⁴ |

1. Super Duty Chassis Cab does not offer a conventional hitch receiver as a factory-installed option. 2. Requires Trailer Tow Package – High Capacity (535). 3. Payload Upgrade Package (68U). 4. Payload Plus Upgrade Package (68M).

- Notes:**
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer tongue (trailer king pin for 5th-wheel towing) load weight should be 10% (15% for 5th-wheel and gooseneck towing) of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo must not cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Trailer towing values are the same for weight-carrying and weight-distributing hitches.
 - If using load bars for weight distribution, Ford recommends 50% front axle load restoration (FALR).

M Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in square meters, multiply square feet by .09; to obtain information in centimeters, multiply inches by 2.54; to obtain information in kilometers, multiply miles by 1.6.

F-600® SUPER DUTY® CHASSIS CAB CONVENTIONAL TOWING¹

Trailer weights shown assume 715-lb.–1,115-lb. second-unit body weight.

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

| Automatic Transmission | | | REGULAR CAB CHASSIS | | | | | | | |
|------------------------|------------|-------------|---------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Engine | Axle Ratio | GCWR (lbs.) | 4x2 DRW 145.3" WB | 4x2 DRW 169.3" WB | 4x2 DRW 193.3" WB | 4x2 DRW 205.3" WB | 4x4 DRW 145.3" WB | 4x4 DRW 169.3" WB | 4x4 DRW 193.3" WB | 4x4 DRW 205.3" WB |
| 6.7L V8 Diesel | 4.30 | 43,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 |
| 7.3L V8 Diesel | 4.88 | 31,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 | 18,500 |

5TH-WHEEL TOWING

| | | | | | | | | | | |
|----------------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 6.7L V8 Diesel | 4.30 | 43,500 | 34,600 | 34,300 | 34,100 | 33,800 | 34,300 | 34,000 | 33,700 | 33,600 |
| 7.3L V8 Diesel | 4.88 | 31,500 | 23,300 | 23,000 | 22,800 | 22,600 | 23,000 | 22,700 | 22,500 | 22,300 |

GOOSENECK TOWING

| | | | | | | | | | | |
|----------------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 6.7L V8 Diesel | 4.30 | 43,500 | 34,700 | 34,400 | 34,300 | 33,900 | 34,400 | 34,200 | 33,900 | 33,800 |
| 7.3L V8 Diesel | 4.88 | 31,500 | 23,400 | 23,100 | 23,000 | 22,700 | 23,100 | 22,800 | 22,600 | 22,400 |

1. Super Duty Chassis Cab does not offer a conventional hitch receiver as a factory-installed option.

- Notes:**
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer tongue (trailer king pin for 5th-wheel towing) load weight should be 10% (15% for 5th-wheel and gooseneck towing) of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo must not cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Trailer towing values are the same for weight-carrying and weight-distributing hitches.
 - If using load bars for weight distribution, Ford recommends 50% front axle load restoration (FALR).

TRAILER TOWING SELECTOR



F-750 Regular Cab in Agate Black

SUPER DUTY® CLASS A MOTORHOME CHASSIS



| GVWR | GCWR | Trailer Weight |
|-------------|-------------|----------------|
| 16,000 lbs. | 23,000 lbs. | 7,000 lbs. |
| 18,000 lbs. | 23,000 lbs. | 5,000 lbs. |
| 20,500 lbs. | 26,000 lbs. | 5,500 lbs. |
| 22,000 lbs. | 26,000 lbs. | 4,000 lbs. |
| 24,000 lbs. | 30,000 lbs. | 6,000 lbs. |
| 26,000 lbs. | 30,000 lbs. | 4,000 lbs. |

- Notes:**
- Towing vehicle's braking system is rated for operation at GVWR – NOT GCWR. See page 37 for more details.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.

2025 MEDIUM DUTY TRUCK

DIESEL ENGINE

| Model | GVWR | GCWR |
|------------------------|--------------------|-------------|
| F-650 (Straight Frame) | 25,600-29,000 lbs. | 50,000 lbs. |
| F-750 (Straight Frame) | 30,200-37,000 lbs. | 50,000 lbs. |

GAS ENGINE

| Model | GVWR | GCWR |
|------------------------|--------------------|-------------|
| F-650 (Straight Frame) | 25,600-29,000 lbs. | 37,000 lbs. |
| F-750 (Straight Frame) | 30,200-33,000 lbs. | 37,000 lbs. |

Note: Combined weight of vehicle and trailer cannot exceed listed GCWR.

SUPER DUTY STRIPPED CHASSIS



| GVWR | GCWR | Trailer Weight |
|-------------|-------------|-------------------------|
| 16,000 lbs. | 23,000 lbs. | 7,000 lbs. |
| 19,500 lbs. | 26,000 lbs. | 6,500 lbs. |
| 19,500 lbs. | 27,200 lbs. | 7,700 lbs. ¹ |
| 22,000 lbs. | 26,000 lbs. | 4,000 lbs. |
| 22,000 lbs. | 29,700 lbs. | 7,700 lbs. ¹ |

- 1.** Requires Parcel Delivery Package option.
- Notes:**
- Towing vehicle's braking system is rated for operation at GVWR – NOT GCWR. See page 37 for more details.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.

2025 E-SERIES® CUTAWAY AND STRIPPED CHASSIS



E-350 Cutaway DRW in Oxford White

MAXIMUM TRAILER WEIGHT = GCWR (lbs.) – Vehicle GVW or 10,000 pounds, whichever is less

Automatic Transmission

| Engine | Axle | GVWR (lbs.) | CUTAWAY | | | | STRIPPED CHASSIS | | | | | | | |
|-----------------|------|-------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| | | | E-350 SRW 138.0" WB | E-350 SRW 158.0" WB | E-350 DRW 138.0" WB | E-350 DRW 158.0" WB | E-350 DRW 176.0" WB | E-450 DRW 158.0" WB | E-450 DRW 176.0" WB | E-350 DRW 138.0" WB | E-350 DRW 158.0" WB | E-350 DRW 176.0" WB | E-450 DRW 158.0" WB | E-450 DRW 176.0" WB |
| 7.3L V8 Premium | 4.10 | 10,050 | 18,500 | 18,500 | | | | | | | | | | |
| | | 11,500 | | | 18,500 | 18,500 | | | 18,500 | | | | | |
| | | 12,500 | | | 18,500 | 18,500 | | | 18,500 | 18,500 | | | | |
| | 4.56 | 10,050 | 18,500 | 18,500 | | | | | | | | | | |
| | | 11,500 | | | 18,500 | | | | | 18,500 | | | | |
| | | 12,500 | | | 18,500 | 18,500 | | | | 18,500 | 18,500 | | | |
| | | 14,000 | | | | | | 22,000 | 22,000 | | | 22,000 | 22,000 | |
| | | 14,500 | | | | | | 22,000 | 22,000 | | | 22,000 | 22,000 | |

- Notes:**
- Do not exceed trailer weight of 5,000 lbs. when towing with bumper only.
 - Do not exceed the Maximum Loaded Trailer Weight.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer.

TRAILER TOWING SELECTOR



T-150 Cargo Van Medium Roof in Oxford White

TRANSIT® PASSENGER VAN

| | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | | | |
|------------------------|--------------|--------------------------------------|-------------|-----------|--------------------|-----------------|--------------------------|-----------|-----------|--------------------|
| | | REAR-WHEEL DRIVE | | | | ALL-WHEEL DRIVE | | | | |
| Automatic Transmission | | 350 | 350 | 350 | 350 | 350 | 350 | 350 | 350 | 350 |
| Axle GCWR | | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB |
| Engine | Ratio (lbs.) | Low Roof | Medium Roof | High Roof | Extended High Roof | Low Roof | Medium Roof | High Roof | High Roof | Extended High Roof |
| 3.5L PFDI V6 | 3.73 10,800 | 4,200 | 4,100 | 3,900 | | 4,000 | 3,900/3,800 ¹ | 3,700 | | |
| | 4.10 11,200 | 4,500 | 4,400 | 4,200 | 3,700 | 4,300 | 4,200/4,100 ¹ | 4,000 | | |
| 3.5L EcoBoost® V6 | 3.73 11,200 | 4,400 | 4,300 | 4,200 | 3,600 | 4,200 | 4,100 | 3,900 | | 3,400 |

1. 15-passenger van.

CARGO VAN

| | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | | | | |
|------------------------|--------------|--------------------------------------|-------------|----------|-------------|-------------|-----------|-----------------|-----------|-----------|-----------|
| | | REAR-WHEEL DRIVE | | | | | | ALL-WHEEL DRIVE | | | |
| Automatic Transmission | | 150/250/350 | 150/250/350 | 350HD | 150/250/350 | 350HD | 250/350 | 350HD | 250/350 | 350HD | 350HD DRW |
| Axle GCWR | | 130" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB |
| Engine | Ratio (lbs.) | Low Roof | Low Roof | Low Roof | Medium Roof | Medium Roof | High Roof | High Roof | High Roof | High Roof | High Roof |
| 3.5L PFDI V6 | 3.73 10,800 | 5,200 | 5,100 | | 5,000 | | 4,900 | | | | |
| | 4.10 12,000 | 6,300 | 6,200 | 6,200 | 6,100 | 6,100 | 6,000 | 6,000 | 5,800 | 5,700 | 5,600 |
| 3.5L EcoBoost V6 | 3.73 12,600 | 6,900 | 6,800 | 6,800 | 6,600 | 6,600 | 6,500 | 6,500 | 6,300 | | |
| | 4.10 13,000 | | | | | | | | | 6,700 | 6,500 |

| | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | | | | |
|------------------------|--------------|--------------------------------------|-------------|----------|-------------|-------------|-----------|-----------------|-----------|-----------|-----------|
| | | REAR-WHEEL DRIVE | | | | | | ALL-WHEEL DRIVE | | | |
| Automatic Transmission | | 150/250/350 | 150/250/350 | 350HD | 150/250/350 | 350HD | 250/350 | 350HD | 250/350 | 350HD | 350HD DRW |
| Axle GCWR | | 130" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB | 148" WB |
| Engine | Ratio (lbs.) | Low Roof | Low Roof | Low Roof | Medium Roof | Medium Roof | High Roof | High Roof | High Roof | High Roof | High Roof |
| 3.5L PFDI V6 | 3.73 10,800 | 5,000 | 4,900 | | 4,800 | | 4,700 | | | | |
| | 4.10 12,000 | 6,100 | 6,000 | 6,000 | 5,900 | 5,900 | 5,800 | 5,800 | 5,600 | 5,500 | 5,300 |
| 3.5L EcoBoost V6 | 3.73 12,600 | 6,700 | 6,600 | 6,600 | 6,400 | 6,400 | 6,300 | 6,300 | 6,100 | | |
| | 4.10 13,000 | | | | | | | | | 6,500 | 6,200 |

- Notes:**
- Do not exceed trailer weight of 5,000 lbs. when towing without a weight-distribution system.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Transit calculated with SAE J2807® method.

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer.

TRAILER TOWING SELECTOR



T-350HD Cutaway AWD in Race Red

TRANSIT®

CUTAWAY

Automatic Transmission

| Engine | Axle Ratio | GCWR (lbs.) | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | | | | | | | | | | |
|-------------------|------------|-------------|--------------------------------------|-------------------|-----------------|---------------|-------------------|-------------|-----------------|-------------------|-----------------|-------------------|-----------------|---------------|-------------------|-------------|---------------|-------------------|
| | | | REAR-WHEEL DRIVE | | | | | | ALL-WHEEL DRIVE | | | | | | | | | |
| | | | 250/350 138" WB | 350HD DRW 138" WB | 250/350 156" WB | 350HD 156" WB | 350HD DRW 156" WB | 350 178" WB | 350HD 178" WB | 350HD DRW 178" WB | 250/350 138" WB | 350HD DRW 138" WB | 250/350 156" WB | 350HD 156" WB | 350HD DRW 156" WB | 350 178" WB | 350HD 178" WB | 350HD DRW 178" WB |
| 3.5L PFDI V6 | 4.10 | 12,000 | 6,500 | 6,400 | 6,400 | 6,400 | 6,200 | 6,100 | 6,100 | 6,000 | 6,300 | 6,100 | 6,200 | 6,200 | 6,000 | 5,900 | 5,900 | 5,800 |
| 3.5L EcoBoost® V6 | 3.73 | 12,600 | 7,100 | | 6,900 | | | | | | 6,900 | | 6,700 | | | | | |
| | | 13,000 | | 7,300 | | 7,300 | 7,100 | 7,100 | 7,100 | 6,900 | | 7,100 | | 7,100 | 6,900 | 6,800 | 6,800 | 6,700 |
| | | 15,000 | | 7,500 | | | 7,500 | | | 7,500 | | 7,500 | | | 7,500 | | | 7,500 |

CHASSIS CAB

Automatic Transmission

| Engine | Axle Ratio | GCWR (lbs.) | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | | | | | | | | | | | | | | |
|-------------------|------------|-------------|--------------------------------------|-------------------|-----------------|---------------|-------------------|-------------|-----------------|-------------------|-----------------|-------------------|-----------------|---------------|-------------------|-------------|---------------|-------------------|
| | | | REAR-WHEEL DRIVE | | | | | | ALL-WHEEL DRIVE | | | | | | | | | |
| | | | 250/350 138" WB | 350HD DRW 138" WB | 250/350 156" WB | 350HD 156" WB | 350HD DRW 156" WB | 350 178" WB | 350HD 178" WB | 350HD DRW 178" WB | 250/350 138" WB | 350HD DRW 138" WB | 250/350 156" WB | 350HD 156" WB | 350HD DRW 156" WB | 350 178" WB | 350HD 178" WB | 350HD DRW 178" WB |
| 3.5L PFDI V6 | 4.10 | 12,000 | 6,500 | 6,300 | 6,400 | 6,400 | 6,200 | 6,100 | 6,100 | 5,900 | 6,300 | 6,100 | 6,200 | 6,200 | 6,000 | 5,900 | 5,900 | 5,700 |
| 3.5L EcoBoost® V6 | 3.73 | 12,600 | 7,000 | | 6,900 | | | | | | 6,800 | | 6,700 | | | | | |
| | | 13,000 | | 7,300 | | 7,300 | 7,100 | 7,000 | 7,000 | 6,900 | | 7,000 | | 7,100 | 6,900 | 6,800 | 6,800 | 6,600 |
| | | 15,000 | | 7,500 | | | 7,500 | | | 7,500 | | 7,500 | | | 7,500 | | | 7,500 |

Notes: • Combined weight of vehicle and trailer cannot exceed listed GCWR.

• Do not exceed the Maximum Loaded Trailer Weight listed.

• Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.



Metric Conversion – To obtain information in kilograms, multiply pounds by .45; to obtain information in kilometers, multiply miles by 1.6; to obtain information in centimeters, multiply feet by 30.48.

TRAILER TOWING SELECTOR



Ranger LARIAT SuperCrew 4x4 in Iconic Silver Metallic

RANGER®

| Automatic Transmission | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | |
|-------------------------------|------------|-------------|--------------------------------------|--------------------|--------------------|
| Engine | Axle Ratio | GCWR (lbs.) | SUPERCREW® | | |
| | | | 4x2 | 4x4 | AWD |
| 2.3L EcoBoost® I4 | 3.73 | 12,370 | 7,500 ¹ | | |
| | | 12,590 | | 7,500 ¹ | |
| 2.7L EcoBoost V6 ³ | 3.73 | 12,745 | | 7,500 ¹ | |
| 3.0L EcoBoost V6 ² | 4.27 | 11,465 | | | 5,510 ¹ |

M Metric Conversion – To obtain information in kilograms, multiply pounds by .45.

1. Requires available Trailer Tow Package (53R); standard on Raptor®. When properly equipped, maximum towing varies based on cargo, vehicle configuration, accessories and number of passengers. **2.** Raptor only. **3.** Optional 2.7L engine, available Spring 2024.

- Notes:**
- Do not exceed trailer weight of 3,500 lbs. when towing with bumper only.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Ranger calculated with SAE J2807® method.

MAVERICK®

| Automatic Transmission | | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) | | |
|------------------------|------------|-------------|--------------------------------------|--------------------|--------------------|
| Engine | Axle Ratio | GCWR (lbs.) | SUPERCREW | | |
| | | | FWD | | AWD |
| 2.5L I4 Hybrid | 2.91 | 6,045 | 2,000 | | |
| 2.0L EcoBoost I4 | 3.63 | 5,935 | 2,000 | | |
| | | 6,085 | | 2,000 | |
| | | 6,175 | | 2,000 ¹ | |
| | | 8,085 | | | 4,000 ² |

1. Tremor® Package. **2.** Available 4,000-lb. towing with available 2.0L EcoBoost engine and available 4,000-lb. Tow Package (53Q). Max towing varies based on cargo, vehicle configuration, accessories and number of passengers.

- Notes:**
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Maverick calculated with SAE J2807® method.



Maverick LARIAT SuperCrew in Hot Pepper Red Metallic Tinted Clearcoat

TRAILER TOWING SELECTOR



Bronco Wildtrak with available equipment in Hot Pepper Red Metallic Tinted Clearcoat

BRONCO®

10-Speed Automatic Transmission

| Engine | Axle Ratio | GCWR (lbs.) | | BIG BEND™ | | BLACK DIAMOND™ | | OUTER BANKS™ | BADLANDS™ | | WILDTRAK™ | | EVERGLADES™ | RAPTOR™ | HERITAGE™ | |
|-------------------|------------|-------------|--------|-----------|--------|----------------|--|--------------|-----------|--------|-----------|--------|-------------|--------------------|--------------------|--------------------------|
| | | 2-Door | 4-Door | 2-Door | 4-Door | 2-Door | 4-Door | 4-Door | 2-Door | 4-Door | 2-Door | 4-Door | 4-Door | 4-Door | 2-Door | 4-Door |
| 2.3L EcoBoost® I4 | 3.73 | 8,480 | 8,480 | 3,500 | 3,500 | | | 3,500 | | | | | | | | |
| | 4.27 | 8,480 | 8,480 | 3,500 | 3,500 | | | 3,500 | | | | | | | | |
| | 4.46 | 8,780 | 8,780 | | | 3,500 | 3,500 | | | | | | | | | |
| | 4.70 | 8,780 | 8,780 | 3,500 | 3,500 | 3,500 | 3,460 ² /3,500 ³ | 3,500 | | | | 3,080 | | | 3,500 | |
| 2.7L EcoBoost V6 | 3.73 | 8,740 | 8,480 | | | | | 3,500 | | | | | | | | |
| | | | 8,740 | | | | | 3,360 | 3,500 | | | | | | | |
| | 4.27 | | 8,740 | | | | | 3,360 | 3,500 | | | | | | | |
| | 4.46 | 8,840 | 8,840 | | | 3,500 | 3,440 ² /3,460 ³ | | 3,500 | 3,320 | | | | | | |
| 3.0L EcoBoost V6 | 4.70 | 8,840 | 8,780 | 3,500 | 3,500 | 3,500 | 3,500 | 3,400 | 3,500 | 3,260 | 3,500 | 3,400 | | 4,500 ⁵ | 3,260 ⁵ | 3,400/3,280 ⁵ |

7-Speed Manual Transmission

| | | | | | | | | | | | | | | | | |
|------------------|------|-------|-------|--------------------|--------------------|--------------------|--------------------|--|-------|-------|--|--|--|--|-------|-------|
| 2.3L EcoBoost I4 | 4.27 | 8,480 | | | | | | | 3,420 | | | | | | | |
| | 4.46 | 8,780 | 8,780 | 3,500 | 3,500 | 3,500 | 3,500 | | | | | | | | | |
| | 4.70 | 8,780 | 8,780 | 3,500 ⁴ | 3,500 ⁴ | 3,500 ⁴ | 3,500 ⁴ | | 3,500 | 3,440 | | | | | 3,500 | 3,500 |

1. Trailer Tow Prep Package included on all models, excluding Raptor. Available towing equipment is dealer installed. (See chart on page 14) **2.** Equipped with Electromechanical Transfer Case (EMTC). **3.** Equipped with Electronic Shift On-the-Fly (ESOF). **4.** Sasquatch™ Package (765). **5.** Heritage Limited model only. **6.** Raptor model includes Tow Package 2 as standard equipment.

Notes: • Do not exceed the Maximum Loaded Trailer Weight listed.
• Combined weight of vehicle and trailer cannot exceed listed GCWR.
• Bronco calculated with SAE J2807® method.

BRONCO SPORT

Automatic Transmission

| Engine | Final Drive Ratio | GCWR (lbs.) 4x4 | MAXIMUM LOADED TRAILER WEIGHT (lbs.) |
|------------------|-------------------|-----------------|--------------------------------------|
| 1.5L EcoBoost I3 | 3.81 | 5,860 | 2,000 ^{1,2} |
| 2.0L EcoBoost I4 | 3.81 | 6,260 | 2,200 ^{2,3} |

1. Big Bend, Outer Banks and Heritage models only. **2.** Requires available Class II Trailer Tow Package (53B). **3.** Badlands model only.

Notes: • Certain states require electric trailer brakes for trailers over a specified weight. Be sure to check state regulations for this specified weight.
WARNING: Do not tow a trailer fitted with electric trailer brakes unless your vehicle is fitted with a compatible aftermarket electronic trailer brake controller. Failure to follow this instruction could result in the loss of control of your vehicle, personal injury or death. For additional information and assistance, we recommend that you contact an authorized dealer.
• Combined weight of vehicle and trailer cannot exceed listed GCWR.
• Do not exceed the Maximum Loaded Trailer Weight listed.
• Bronco Sport calculated with SAE J2807® method.



Bronco Sport Badlands with available equipment in Eruption Green Metallic

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer.

TRAILER TOWING SELECTOR



Expedition Platinum in Stone Blue Metallic. Optional features shown with available Ford Accessories.

EXPEDITION®

| Automatic Transmission | | GCWR (lbs.) | MAXIMUM LOADED TRAILER WEIGHT (lbs.) ¹ | | | |
|------------------------|------------|---------------------|---|-------|----------------------|-------|
| Engine | Axle Ratio | | EXPEDITION (SWB) | | EXPEDITION MAX (LWB) | |
| | | | 4x2 | 4x4 | 4x2 | 4x4 |
| 3.5L EcoBoost® V6 | 3.31 | 12,000 | 6,000 | | | |
| | | 12,300 | | 6,000 | | |
| | | 12,400 | | | | 6,000 |
| | | 12,500 | | | 6,300 ³ | |
| | 3.73 | 12,300 ² | | 6,000 | | |
| | | 12,400 ² | | | | 6,000 |
| | | 15,200 ³ | | | 9,000 | |
| | | 15,300 ³ | 9,300 | | | |
| | | 15,500 ³ | | 9,200 | | 9,000 |

1. Max loaded trailer weight ratings over 6,000 lbs. require weight-distributing hitch (see page 40 for additional information) for Expedition SWB and LWB models. When properly equipped, max towing varies based on cargo, vehicle configuration, accessories and number of passengers.
2. Included in Electronic Limited Slip rear axle. **3.** Requires available Class IV Heavy-Duty Trailer Tow Package (536).

Notes:

- Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduced by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.**
- Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
- Do not exceed the Maximum Loaded Trailer Weight listed.
- Expedition calculated with SAE J2807[®] method.

EXPLORER®

| Automatic Transmission | | GCWR (lbs.) | MAXIMUM LOADED TRAILER WEIGHT (lbs.) ¹ | | |
|-------------------------------|-------------------|--------------|---|--------------------------|--------------------------|
| Engine | Axle Ratio | | RWD | 4WD | 4WD |
| 2.3L EcoBoost I4 | 3.58 | 7,700 | 7,800 | 3,000 ¹ | 3,000 ¹ |
| | | 10,000 | 10,100 | 5,300 ² | 5,300 ² |
| | | | 10,300 | | 5,300 ³ |
| | | | | | |
| 3.0L EcoBoost V6 ⁴ | 3.31 ⁵ | 10,800 | 10,800 | 5,600 | 5,600 |
| | 3.58 ⁶ | | 10,800 | 5,600 | 5,600 |
| 3.3L Ti-VCT V6 ⁷ | 3.58 | 8,000/10,600 | | | 3,000/5,600 ² |
| 3.3L HEV V6 ⁸ | 3.58 | 8,500/10,500 | | 3,000/5,000 ² | |
| | 3.73 | 8,600/10,600 | | 3,000/5,000 ² | |

1. Explorer does not offer factory-installed towing equipment for this application; only available as dealer accessory. **2.** Requires available Class IV Trailer Tow Package (52T). **3.** Class IV Trailer Tow Package standard on Timberline model. **4.** Class IV Trailer Tow Package (52T) standard on ST model. **5.** King Ranch[®] and Platinum models only. **6.** ST model only. **7.** Fleet only. **8.** Police Interceptor Utility only.

Notes:

- Certain states require electric trailer brakes for trailers over a specified weight. Be sure to check state regulations for this specified weight. **WARNING:** Do not tow a trailer fitted with electric trailer brakes unless your vehicle is fitted with a compatible aftermarket electronic trailer brake controller. Failure to follow this instruction could result in the loss of control of your vehicle, personal injury or death. For additional information and assistance, we recommend that you contact an authorized dealer.
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
- Do not exceed the Maximum Loaded Trailer Weight listed.
- Explorer calculated with SAE J2807[®] method.



Explorer King Ranch in Star White Metallic Tri-Coat

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer.

TRAILER TOWING SELECTOR



Edge ST in Stone Blue Metallic

EDGE®

Automatic Transmission

| Engine | Axle Configuration | GCWR (lbs.) | MAXIMUM LOADED TRAILER WEIGHT (lbs.) |
|-------------------|--------------------|-------------|--------------------------------------|
| 2.0L EcoBoost® I4 | AWD | 6,300 | 1,500 ¹ |
| | AWD | 8,300 | 3,500 ² |
| 2.7L EcoBoost V6 | AWD | 8,500 | 3,500 ³ |

1. Edge does not offer factory-installed towing equipment for this application; only available as dealer accessory. 2. Requires Class II Trailer Tow Package (53G). 3. Edge ST includes Class II Trailer Tow Package (53G) standard.

Notes:

- Certain states require electric trailer brakes for trailers over a specified weight. Be sure to check state regulations for this specified weight. **WARNING:** Do not tow a trailer fitted with electric trailer brakes unless your vehicle is fitted with a compatible aftermarket electronic trailer brake controller. Failure to follow this instruction could result in the loss of control of your vehicle, personal injury or death. For additional information and assistance, we recommend that you contact an authorized dealer.
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
- Do not exceed the Maximum Loaded Trailer Weight listed.
- Edge calculated with SAE J2807® method.



Escape Platinum in Iconic Silver Metallic

ESCAPE®

Automatic Transmission

| Engine | Final Drive Ratio | GCWR (lbs.) | | MAXIMUM LOADED TRAILER WEIGHT (lbs.) |
|------------------------|-------------------|-------------|-------|--|
| | | FWD | AWD | |
| 2.5L I4 Hybrid | 2.91 | 5,373 | 5,507 | 1,500 ¹ |
| 2.5L I4 Plug-in Hybrid | 2.91 | 5,706 | | 1,500 ¹ |
| 1.5L EcoBoost I3 | 3.81 | 5,639 | | 2,000 ² |
| | | | | 5,811 |
| 2.0L EcoBoost I4 | 3.47 | 7,402 | | 2,000 ² /3,500 ³ |

1. Requires Class II Trailer Tow Package (536) available on ST-Line Select, ST-Line Elite and Platinum Hybrid or Plug-in Hybrid series. 2. Escape does not offer factory-installed towing equipment for this application; only available as dealer accessory. 3. Requires Class II Trailer Tow Package (536).

Notes:

- Certain states require electric trailer brakes for trailers over a specified weight. Be sure to check state regulations for this specified weight. **WARNING:** Do not tow a trailer fitted with electric trailer brakes unless your vehicle is fitted with a compatible aftermarket electronic trailer brake controller. Failure to follow this instruction could result in the loss of control of your vehicle, personal injury or death. For additional information and assistance, we recommend that you contact an authorized dealer.
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
- Do not exceed the Maximum Loaded Trailer Weight listed.
- Escape calculated with SAE J2807® method.



Mustang EcoBoost Premium with Bronze Appearance Package in Vapor Blue Metallic

MUSTANG®^{1,2}

Automatic Transmission

| Engine | Axle Configuration | MAXIMUM LOADED TRAILER WEIGHT (lbs.) |
|------------------|--------------------|--------------------------------------|
| 2.3L EcoBoost I4 | RWD | 1,000 |
| 5.0L V8 GT | RWD | 1,000 |

Manual Transmission

| | | |
|------------|-----|-------|
| 5.0L V8 GT | RWD | 1,000 |
|------------|-----|-------|

1. Mustang does not offer factory-installed towing equipment for this application; only available as aftermarket accessory. 2. Mustang Dark Horse is not rated to tow a trailer.

Notes:

- Do not exceed the Maximum Loaded Trailer Weight listed.
- Mustang calculated with SAE J2807® method.

KNOW BEFORE YOU TOW

BEFORE YOU BUY

If you are selecting a vehicle that will be used for towing, you should determine the approximate weight of the trailer you intend to tow, including the weight of any additional cargo and fluids that you will be carrying in the trailer. Also, be sure the vehicle has the proper optional equipment (see page 13). Keep in mind that performance can be severely affected in hilly terrain when the minimum acceptable powertrain combination is selected. Consider purchasing a vehicle with a more powerful engine.

AFTER YOU BUY

Before heading out on a trip, check your vehicle Owner's Manual for break in and severe duty maintenance schedules (do not tow a trailer until your vehicle has been driven at least 1,000 miles). Be sure to have your fully loaded vehicle (including passengers) and trailer weighed so as not to exceed critical weight limits (see page 42). If any of these limits are exceeded, cargo should be removed from the vehicle and/or trailer until all weights are within the specified limits.



BRAKES

Many states require a separate braking system on trailers with a loaded weight of more than 1,500 pounds. For your safety, Ford Motor Company recommends that a separate functional brake system be used on any towed vehicle, including those dolly-towed or towbar-towed. There are several basic types of brake systems designed to activate trailer brakes:

Electronically Controlled Brakes usually provide automatic and manual control of trailer brakes. They require that the tow vehicle be equipped with a controlling device and additional wiring for electrical power. These brakes typically have a control box installed within reach of the driver and can be applied manually or automatically.

Electric-Over-Hydraulic (EOH) Trailer Brakes are operated by an electrically powered pump that pressurizes a hydraulic fluid reservoir built into the trailer's brake system. Many of the available EOH trailer brake models are compatible with the Ford factory installed, dash-integrated Trailer Brake Controller (TBC).

Surge Brakes are independent hydraulic brakes activated by a master cylinder at the junction of the hitch and trailer tongue. They are not controlled by the hydraulic fluid in the tow vehicle's brake system and the tow vehicle's hydraulic system should never be connected directly to the trailer's hydraulic system.

Be sure your trailer brakes conform to all applicable state regulations. *See Towing Basics on the last page for additional braking information.*

TRAILER LAMPS

Make sure the trailer is equipped with lights that conform to all applicable government regulations. The trailer lighting system should not be connected directly to the lighting system of the vehicle. See a local recreational vehicle dealer or rental trailer agency for correct wiring and relays for the trailer and heavy-duty flashers.

SAFETY CHAINS

- Always use safety chains when towing. Safety chains are used to retain connection between the towing and towed vehicle in the event of separation of the trailer coupling or ball.
- Cross chains under the trailer tongue to prevent the tongue from contacting the ground if a separation occurs. Allow only enough slack to permit full turning – be sure they do not drag on the pavement.
- When using a frame-mounted trailer hitch, attach the safety chains to the frame-mounted hitch using the recommendations supplied by the hitch manufacturer.
- See your vehicle Owner's Manual for safety chain attachment information.
- For rental trailers, follow rental agency instructions for hookup of safety chains.

TRAILER WIRING HARNESS

- Some vehicles equipped with a factory-installed Trailer Tow Package include a trailer wiring harness and a wiring kit.
- This kit includes one or more jumper harnesses (to connect to your trailer wiring connector) and installation instructions.

Refer to charts on pages 14 – 16 for standard and optional wiring harness usage.

TRAILER TYPES

FOLDING CAMPING TRAILER

These are very cost effective units providing campers with a comfortable, dry, mobile shelter, plus these added benefits:

- Lightweight for easy towing
- Simple conventional weight-carrying hitch is usually sufficient for towing
- Compact, low-profile traveling package
- Easily maneuverable – generally 8 to 16 feet long



CONVENTIONAL TRAVEL TRAILER

Generally larger, rigid construction units offering more of the conveniences of home, including such features as kitchen sink, dinette, shower, refrigerator and flush toilet. Additional benefits include:

- Widely varied levels of roominess, comfort and luxury – depending on the towing capacity of your vehicle and your budget
- Sizes usually range from 12 to 35 feet long
- Normally towed with a conventional weight-distributing hitch, depending on weight



5TH-WHEEL TRAILER

Provides the same types of accommodations as a conventional travel trailer but with these unique characteristics:

- The forward raised portion is designed to extend over the box of a pickup truck
- Attaches to the truck via a 5th-wheel hitch mounted in the pickup bed
- Offers the advantages of improved weight distribution and towing dynamics, since some trailer weight is directly over the towing vehicle



TRAILER CLASSES

CLASS I LIGHT-DUTY

- 2,000-lb. maximum weight (trailer and cargo combined)
- Small folding camping trailers and trailers for small boats, motorcycles and snowmobiles
- Many Ford vehicles can handle easily
- Conventional weight-carrying hitch

CLASS II MEDIUM-DUTY

- 2,001–3,500-lb. gross trailer weight
- Large folding camping trailers, single-axle, small- to medium-length (up to 18-ft.) trailers
- Ford trucks and compact SUVs can be equipped to tow these trailers¹
- Conventional weight-distributing hitch not required unless specified for a particular vehicle

CLASS III HEAVY-DUTY

- 3,501–5,000-lb. gross trailer weight
- Dual-axle or large single-axle travel trailers
- Most properly equipped Ford trucks and SUVs can tow them¹
- Conventional weight-distributing hitch not required unless specified for a particular vehicle

CLASS IV EXTRA-HEAVY-DUTY²

- Over 5,000-lb. gross trailer weight²
- Largest travel and 5th-wheel trailers made for recreation
- Most Ford trucks and some SUVs can be equipped to handle trailer weights in this class¹
- Most applications require a conventional weight-distributing or 5th-wheel hitch

¹. Refer to page 13 for Required Equipment. ². Some industry sources refer to trailers over 10,000 pounds as Class V Trailers. Ford F-150®, Super Duty® Pickups and Chassis Cabs can be equipped to handle these trailers.

HITCH STYLES

WEIGHT-CARRYING (NON-WEIGHT-DISTRIBUTING)

A weight-carrying (non-weight-distributing) hitch is commonly used to tow small- and medium-sized trailers. Choose a proper hitch and ball and make sure its location is compatible with that of the trailer. Use a good weight-carrying hitch that uniformly distributes the trailer tongue loads through the bumper and frame (through the body with Escape®; bumper hitch not available with Escape® or Explorer®). Ford hitch receivers provide weight-carrying capacities as shown in the chart on the following page. (A label affixed to the hitch receiver provides both the weight-carrying and weight-distributing capacities for each receiver.) You are responsible for obtaining the proper hitch ball, ball mounting and other appropriate equipment to tow both the trailer and load that will be towed.



WEIGHT-DISTRIBUTING

A weight-distributing hitch is used in conjunction with a hitch platform (receiver) to distribute tongue load to all towing vehicle and trailer wheels. Required for certain Class III and all Class IV applications (see the chart on the next page).

- Weight-distributing hitch platforms are welded or bolted to the vehicle frame. Bolt-on types are recommended because they can be removed.
- A properly installed bolt-on weight-distributing hitch platform should not weaken the vehicle or underbody as heat of welding might.
- Equalizing arms are connected from the hitch to the trailer's A-frame. They can be adjusted for best towing performance. Lengths of chain are pulled up and tightened to bend spring bars upward, which lifts some of the weight from the rear wheels and transfers weight to the other wheels of the vehicle and trailer.



GOOSENECK

A gooseneck hitch attaches in the truck bed using custom or universal rails. This hitch style provides great stability and is suitable for heavier loads, since the weight of the tongue rests directly on the truck bed over the rear axles. Goosenecks are commonly used for horse and other agricultural trailers. Other features include:

- Tight turning radius
- “Fold down” and “install under bed” models provide unobstructed bed area for carrying cargo
- Attachment rails require no welding (sold separately)



5TH-WHEEL

A 5th-wheel hitch is mounted in the pickup bed to put more of the trailer weight directly over the towing vehicle. The receiver center line of the hitch should be mounted at least two inches forward from the rear axle of the truck chassis. This mounting location will distribute the king pin weight of the trailer for optimum load-carrying and sway-control performance. 5th-wheel hitches are commonly used for RV trailers.



FACTORY-INSTALLED TRAILER HITCH RECEIVER OPTIONS AND CAPACITIES

Bronco® Sport

Included with Trailer Tow Package – Option Code 53B

Escape®

Included with Class II Trailer Tow Package – Option Code 536

Edge®

Included with Class II Trailer Tow Package – Option Code 53G

Bronco Raptor®

Standard

Bronco

Included with dealer-installed towing equipment

Explorer®

Included with Class IV Trailer Tow Package – Option Code 52T

Expedition®

Standard

Transit®

Included with Trailer Tow Package – Option Code 53B

Maverick®

Included with Trailer Tow Package – Option Code 53Q

Ranger®

Included with Trailer Tow Package – Option Code 53R

F-150® Lightning®

Standard

F-150 Raptor® Pickup

Standard

F-150 Pickup

A 2" hitch receiver rated at 11,600 lbs. is standard. Tow/Haul Package (53T) includes 2" reinforced receiver rated at 14,000 lbs.

F-250®/F-350®/F-450® Super Duty® Pickups

A 2.5" hitch receiver is standard on all models except for the following configurations which get a 3" hitch receiver:

- F-350 DRW Crew Cab with 6.7L H.O. Diesel engine with 4.10 FDR (Final Drive Ratio)
- F-450 Crew Cab with 6.7L and 6.7L H.O. Diesel engines

Note: The chart below shows the weight-carrying and weight-distributing capacities of these hitch receivers. (These capacities also are shown on a label affixed to each receiver.)

You are responsible for obtaining the proper hitch ball, ball mounting, weight-distributing equipment (i.e., equalizing arms and snap-up brackets, sway control system) and other appropriate equipment to tow both the trailer and its cargo load.

REAR STEP BUMPER/HITCH RECEIVER WEIGHT CAPACITY

The maximum weight capacities for the hitch receivers shown below may exceed the maximum loaded trailer weight for the vehicle specified. Refer to the Trailer Towing Selector charts on pages 18–36 for Maximum Loaded Trailer Weights for each vehicle.

| Vehicle | Weight-Carrying Max. Trailer Capacity (lbs.) ¹ | Max. Tongue Load (lbs.) | Weight-Distributing Max. Trailer Capacity (lbs.) ¹ | Max. Tongue Load (lbs.) |
|------------------------------|---|-------------------------|---|-------------------------|
| REAR STEP BUMPER | | | | |
| Ranger | 3,500 | 350 | | |
| HITCH RECEIVER | | | | |
| Bronco Sport | 2,200 | 220 | | |
| Escape Hybrid/Plug-in Hybrid | 1,500 ² | 150 ² | | |
| Escape | 3,500 | 350 | | |
| Edge | 3,500 | 350 | | |
| Bronco | 3,500 | 350 | | |
| Bronco Raptor | 4,500 | 450 | | |
| Maverick | 4,000 | 400 | | |
| Explorer Hybrid | 5,000 | 500 | | |
| Explorer | 5,600 | 560 | | |
| Expedition | 6,000 | 600 | 9,300 | 930 |
| Expedition MAX | 6,300 | 630 | 9,000 | 900 |
| Transit Passenger Van | 4,500 | 450 | | |
| Transit Cargo Van | 6,900 | 690 | | |
| Ranger | 7,500 ² | 750 ² | | |
| Ranger Raptor | 5,510 ² | 550 ² | | |
| F-150 Pickup | 5,000 | 500 | 13,500 | 1,350 |
| F-150 Lightning | 5,000 | 500 | 10,000 | 1,000 |
| F-150 Raptor Pickup | 5,000 | 500 | 8,200 | 820 |
| F-150 Raptor R | 5,000 | 500 | 8,700 | 870 |
| F-250 | 22,000 | 2,200 | 22,000 | 2,200 |
| F-350 SRW | 25,000 | 2,500 | 25,000 | 2,500 |
| F-250/F-350 Tremor® | 18,200 | 1,820 | 18,200 | 1,820 |
| F-350 DRW | 28,000 | 2,800 | 28,000 | 2,800 |
| F-450 DRW | 30,000 | 3,000 | 30,000 | 3,000 |

1. Ford rear step bumpers and hitch receivers do not include a hitch ball or ball mounting. You are responsible for obtaining the proper hitch ball, ball mounting, weight-distributing equipment (i.e., equalizing arms and snap-up brackets, sway control system) and other appropriate equipment to tow both the trailer and its cargo load. 2. When properly equipped.

5TH-WHEEL AND GOOSENECK HITCH RECOMMENDATION

Shorter pickup boxes (e.g. 5.5'/6.5' F-150, 6.75' F-250/350) provide less clearance between the cab and 5th-wheel/gooseneck trailer compared to "long box" pickups. When selecting a trailer and tow vehicle, it's critical that this combination provide clearance between the cab and tow vehicle for turns up to and including 90 degrees. Failure to follow this recommendation could result in the trailer contacting the cab of the tow vehicle during tight turns that are typical during low speed parking and turning maneuvers. This contact could result in damage to the trailer and tow vehicle.

Ford Motor Company offers a factory-installed 5th-wheel hitch prep package option for Super Duty only. Optional 5th-wheel hitch and gooseneck ball are also available. Go to accessories.ford.com for more information.

CALCULATE WEIGHT DISTRIBUTION

CALCULATION EXAMPLE


| | |
|---------------------|---------------------------------|
| Vehicle = | F-150 |
| H1 = | 37 inches |
| H2 = | 38 inches |
| Correction Factor = | 50% |
| Height Change = | 38" - 37" = 1 inch |
| Reduction Amount = | 1" x 50% = .50 inch |
| Height Change = | 38" - .50" = 37.5 inches |
| Target Height = | 37.5 inches |

- < (H2) **minus** (H1)
- < (Height Change) **times** (Correction Factor)
- < (H2) **minus** (Reduction Amount)


WEIGHT DISTRIBUTION HITCH SETUP

| Vehicle | Weight Distribution Correction Factor |
|----------------------------------|---------------------------------------|
| Mustang® | Not Required |
| Bronco® Sport | Not Required |
| Edge® | Not Required |
| Escape® | Not Required |
| Bronco | Not Required |
| Explorer® | Not Required |
| Expedition® | 50% |
| Transit® | Use Not Recommended |
| Maverick® | Not Required |
| Ranger® | Not Required |
| F-150® Pickup | 50% |
| F-150 Lightning® | 50% |
| F-150 Raptor® Pickup | 50% |
| F-250®/F-350® Super Duty® Pickup | 50% |
| F-450® Super Duty Pickup | 25% Regular Cab 50% Crew Cab |
| Super Duty Chassis Cab (All) | 50% |


- 1 Load trailer similar to the way it will be loaded for the trip with 10% tongue load and park on level ground
- 2 Adjust trailer tongue jack to get trailer level or just slightly nose down
- 3 Load tow vehicle similar to the way it will be used for the trip and park vehicle on level ground
- 4 Adjust and secure weight distribution ball mount height per manufacturer's instructions so tow ball is the same height as trailer coupler when trailer is not connected to tow vehicle
- 5 Measure top of front fender lip above the center of the wheel to ground
- 6 Record this value as "H1"



- 7 Connect trailer to tow ball with no weight distribution bars attached (make sure tongue jack is fully retracted)
- 8 Measure top of front fender lip above the center of the wheel to ground
- 9 Record this value as "H2"



- 10 Adjust weight distribution bars per manufacturer's instructions to get tow vehicle top front of fender lip to "Target Height" and make sure trailer is level to slightly nose down
- 11 Complete coupler latching, electrical connections, safety chains and emergency braking system attachments



ABOUT WEIGHTS

Base Curb Weight is the weight of the vehicle including a full tank of fuel and all standard equipment. It does not include passengers, cargo or any optional equipment. Your dealership sales consultant can give you this number for the vehicle(s) you are considering.

Cargo Weight includes all weight added to the Base Curb Weight, including cargo and optional equipment (check with your sales consultant). When towing, trailer tongue load or king pin weight is also part of the Cargo Weight.

Payload is the combined maximum allowable weight of cargo and passengers that the vehicle is designed to carry. It is the Gross Vehicle Weight Rating minus the Base Curb Weight.



BASE CURB WEIGHT

plus

CARGO WEIGHT

plus

PASSENGER WEIGHT

equals

GROSS VEHICLE WEIGHT (GVW)

GVW must not exceed GVWR (obtain from Safety Compliance Certification Label on the left front door lock facing or the door latch post pillar).

GROSS VEHICLE WEIGHT

plus

LOADED TRAILER WEIGHT

equals

GROSS COMBINATION WEIGHT (GCW)

GCW must not exceed GCWR (obtain from Towing Selector charts on pages 18–36 or your vehicle Owner's Manual).

Gross Vehicle Weight (GVW) is the Base Curb Weight plus actual Cargo Weight plus passengers. It is important to remember that GVW is not a limit or specification – it is the actual weight that is obtained when the fully-loaded vehicle is driven onto a scale.

Gross Vehicle Weight Rating (GVWR) is the maximum allowable weight of the fully-loaded vehicle (including passengers and cargo). This number – along with other weight limits, as well as tire, rim size and inflation pressure data – is shown on the vehicle's Safety Compliance Certification Label, located on the left front door lock facing or the door latch post pillar (sample label on next page). **The GVW must never exceed the GVWR.**

Gross Axle Weight (GAW) is the total weight placed on each axle (front and rear). To determine the Gross Axle Weights for your vehicle and trailer combination, take your loaded vehicle and trailer to a scale. With the trailer attached, place the front wheels of the vehicle on the scale to get the front GAW. For rear GAW, weigh the towing vehicle with trailer attached, but with just the four wheels of the vehicle on the scale. Subtracting front GAW from that amount gives you rear GAW.

Gross Axle Weight Rating (GAWR) is the maximum weight to be carried by a single axle (front or rear). These numbers are also shown on the Safety Compliance Certification Label. **The total load on each axle must never exceed its GAWR.**

MEASURING TONGUE LOAD WITH COMMERCIAL SCALE

To measure actual tongue load or king pin weight, disconnect the trailer and place only the tongue (king pin) on a scale (at hitch ball or 5th-wheel king pin receiver height). If the tongue load/king pin weight exceeds the upper weight limit, move more of the trailer contents rearward to achieve the recommended tongue load/king pin weight. If the tongue load or king pin weight is less than the lower limit, shift the load forward.

WEIGHT LIMITS

Gross Combination Weight (GCW) is the weight of the loaded vehicle (GVW) plus the weight of the fully loaded trailer. It is the actual weight obtained when the vehicle and trailer are weighed together on a scale.

Gross Combination Weight Rating (GCWR) is the maximum allowable weight of the towing vehicle and the loaded trailer – including all cargo and passengers – that the vehicle can handle without risking damage. (Important: The towing vehicle's brake system is rated for operation at the GVWR – NOT GCWR. Separate functional brake systems should be used for safe control of towed vehicles and for trailers weighing more than 1,500 lbs. when loaded.) The measured GCW must never exceed the GCWR.

Maximum Loaded Trailer Weight (as shown in the Trailer Towing Selector charts on pages 18–36) is the highest possible weight of a fully loaded trailer the vehicle can tow, based on a minimum towing vehicle GVW. It assumes a towing vehicle with any mandatory options, no cargo, tongue load of 10% (conventional trailer) or king pin weight of 15% (5th-wheel trailer), and driver and passenger (150 lbs. each). F-Series Super Duty® Chassis Cab models also assume a second-unit body weight based on 80 lbs. per foot cab-to-axle (CA). Weight of additional options, passengers, cargo and hitch must be deducted from this weight.

Tongue Load or 5th-Wheel King Pin Weight is another critical measurement that must be made before towing. It refers to the amount of the trailer's weight that presses down on the trailer hitch. Too much tongue load or king pin weight can cause suspension/drivetrain damage and can press the vehicle down in back causing the front wheels to lift to the point where traction, steering response and braking can be severely decreased. Too little tongue load or king pin weight can reduce rear-wheel traction and cause instability, which may result in tail wagging or jackknifing.

Tongue load or king pin weights must meet the following requirements:*

For trailers up to 2,000 lbs., tongue load not to exceed 200 lbs.

For conventional trailers over 2,000 lbs., tongue load is 10% of loaded trailer weight.

For 5th-wheel trailers, king pin weight is 15% of loaded trailer weight.

Examples:

For a 5,000-lb. conventional trailer, multiply 5,000 by .10 to obtain a proper tongue load of 500 lbs.

For an 11,500-lb. 5th-wheel trailer, multiplying 11,500 by .15 yields a king pin weight of 1,725 lbs.

Note: Be sure the addition of tongue load or king pin weight does not cause the key towing vehicle weight limits (GVWR and Rear GAWR) to be exceeded. Remember, GVWR and GAWR are found on the vehicle's Safety Compliance Certification Label. If either of these limits is exceeded, you should go with a larger vehicle or a smaller trailer.

*Refer to the chart on page 40 for tongue load recommendations with Ford factory-installed trailer hitch receivers.

HOW TO FIND THE TRUCK'S AXLE RATIO

If you do not know the axle ratio of your vehicle, check its Truck Safety Compliance Certification Label (located on the left front door lock facing or the door latch post pillar). Below the bar code, you will see the word AXLE and a two-digit code. Use the chart below to find the axle ratio that corresponds to that code.

REAR AXLE RATIO CODES

| Vehicle | Rear Axle Ratio | Non-Limited Slip | Limited Slip | Electronic Locking |
|-----------------------------|-------------------|------------------|--------------------|--------------------|
| Super Duty® (F-250/600) | 3.31 | 31 | Not Available | 3H |
| | 3.55 | 35 | 3K | 3J |
| | 3.73 | 37 | 3L | 3E |
| | 4.10 | 41 | 4N/4W ¹ | Not Available |
| | 4.30 | Not Available | 4L/4X ² | 4M |
| | 4.88 | 48 | 8L | Not Available |
| F-150® Pickup | 3.15 | 15 | Not Available | Not Available |
| | 3.31 | 27 | Not Available | L3 |
| | 3.55 | 19 | Not Available | L9 |
| | 3.73 | 26 | Not Available | L6 |
| | 4.10 | Not Available | Not Available | L4 |
| F-150 Lightning® | 9.61 | Not Available | Not Available | Std. |
| Explorer® | 3.31 | 3A | Not Available | Not Available |
| | 3.58 | 3B | 3B ³ | Not Available |
| | 3.73 | 3C | Not Available | Not Available |
| Expedition® | 3.31 | 15 | Not Available | Not Available |
| | 3.73 | 2L | 2E ⁴ | Not Available |
| Transit® | 3.73 | 73 | 7L | Not Available |
| | 4.10 | 41 | 4L | Not Available |
| Ranger® | 3.73 | 71 | Not Available | 73 |
| | 4.27 ⁵ | Not Available | Not Available | 73 |
| Bronco® | 3.73 | 73 | Not Available | Not Available |
| | 4.27 | Not Available | Not Available | 2L |
| | 4.46 | 46 | Not Available | 4L |
| | 4.70 | Not Available | Not Available | 7L |
| E-Series® Cutaway | 4.10 ⁶ | 52/56 | E2/E6 | Not Available |
| | 4.56 | 58/83/85 | E8/F3/F5 | Not Available |
| Motorhome | 4.88 | 48 | Not Available | Not Available |
| | 5.86 | 58 | Not Available | Not Available |
| | 6.14 | 61 | Not Available | Not Available |
| Commercial Stripped Chassis | 4.30 | 43 | Not Available | Not Available |
| | 4.88 | 48 | Not Available | Not Available |
| | 5.38 | 53 | Not Available | Not Available |

1. Wide rear axle on F-350 DRW Chassis Cab with Ambulance Package and 6.7L diesel engine.
2. Wide rear axle on F-350 DRW Chassis Cab with Ambulance Package and 7.3L gas engine.
3. TORSEN® Rear Axle. 4. Electronic Limited Slip axle. 5. Raptor only. 6. DRW models only.

Sample Truck Safety Compliance Certification Label

(Refer to actual label on your vehicle)

Front GAWR

FRONT GAWR: 2540 KG (5600 LB)

Rear GAWR

REAR GAWR: 2876 KG (6340 LB)

GVWR

GVWR: 4536 KG (10000 LB)

DATE: 03/22

WITH: LT275/65R18E 123/120S 18x8.0J

TIRES RIMS

AT 480 kPa/ 70 PSI COLD

AT 520 kPa/ 75 PSI COLD

THIS VEHICLE CONFORMS TO ALL APPLICABLE FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN: 1FT7X2B66NEE15874 TYPE: Truck

EXT PNT: HX RC: 48 DSD

| | | | | | | | |
|-----|--------|-------|---|------|----|------|-------------|
| WB | INT TR | TP/PS | R | AXLE | TR | SPR | |
| 148 | 35 | | 5 | 3E | 5 | LLKK | F1266 T1612 |

ULC SUSA-3520472-AA

↑
Axle Code

TOWING ACCESSORIES



FORD ACCESSORIES

Ford Accessories offer a great selection of towing items to enhance function and comfort.

For current price and warranty information, please contact your Ford Dealer or visit our website at: accessories.ford.com.



Trailer Hitch Wiring Harnesses – 4-Pin

This 4-pin wiring harness assembly is made to plug into the factory electrical system. The 4-pin design does not allow the use of trailers with electric brakes. Dealer installation recommended.

Base Part No. 15A416

The 7-pin design allows the use of trailers with electric brakes. Includes bracket for convenient attachment. Available for vehicles with or without reverse camera system option. Dealer installation recommended.

Base Part No. 15A416



Trailer Hitch Assemblies

CLASS II, III and IV:

Original equipment hitch bolts directly into existing holes – no drilling or welding required. Rear fascia may require trimming for installation.

NOTE: Towing capacity could be limited by vehicle powertrain. See your Ford Dealer or Owner's Manual for details.

Base Part No. 19D520



Trailer Hitch Ball Mounts – Square Shank

Can be used in the raised or dropped position to match trailer coupler height. Available in durable black powdercoat. See your Ford Dealer or Owner's Manual for towing limitations.

Base Part No. 19A282



Trailer Hitch Ball

Forged, stainless steel construction for maximum strength and corrosion resistance. Available in three sizes – 1-7/8", 2" and 2-5/16". See your Ford Dealer for towing limitations.

Base Part No. 19F503



Locking Hitch Pin

This hitch lock allows you to lock the ball mount into the trailer hitch, deterring theft and helping prevent anyone from detaching your trailer at the ball mount. For 2" receivers.

Part No. VML3Z-19A326-A




5th-Wheel Hitch Kits

The 5th-Wheel Hitch Kits have a Gross Trailer Weight Rating of 20,000 and 35,000 lbs. Other features include a forged jaw; a high-capacity head support structure; 10° front-to-back pivot and 6° side-to-side pivot for easy hook-ups; 15-inch to 18-inch vertical height adjustment; and an extended-length handle.

NOTE: Requires 5th-Wheel and Gooseneck Hitch Prep Package. Other restrictions: only compatible with 8-foot beds – cannot be used with drop-in bedliners or bed mats. See Owner's Manual for specific vehicle tow ratings.

Base Part No. 19D520



Gooseneck Hitch Kit

This Gooseneck Hitch Ball has a Gross Trailer Weight Rating of 27,500 lbs. on a 2-5/16" ball and 40,000 lbs. with a 3" ball. The kit also includes two steel safety chain tie-down attachments and a durable plastic case.

NOTE: This kit is only for use with the 5th-Wheel and Gooseneck Hitch Prep Package. Other restrictions: cannot be used with drop-in bedliners or bed mats. See Owner's Manual for specific vehicle tow ratings.

Base Part No. 19F503

5th-Wheel/Gooseneck Hitch Prep Package

Required Prep Package for 5th-Wheel and Gooseneck Hitch Kits. 2017 and newer Super Duty® kits include in-bed wiring harness.

Base Part No. 5F057



Neutral Tow Kit

This handy kit allows you to tow your vehicle behind your motorhome – with all four wheels on the ground. Available for 4WD and an automatic transmission. Dealer installation recommended. Not available for AWD vehicles.

Base Part No. 7H332



Telescoping Trailer Tow Mirrors

Manual: When towing, the mirror telescopes out to help increase your range of vision. When not towing, the mirror slides in for normal range. Mirrors also include a rearward folding feature that allows them to be folded against the vehicle for tight spaces. (Black housing.)

Power: Provides the same features as manual trailer tow mirrors, but the mirror glass features a power adjust. Mirror glass is also electrically heated to minimize snow and ice buildup. The mirror telescoping feature is still manual. (Black or chrome housing cap.)

NOTE: Power trailer tow mirrors are for vehicles equipped with power mirrors only and turn signal/marker light feature is only functional on vehicles originally equipped with those features.

Base Part No. 17682 Passenger Side

Base Part No. 17683 Driver Side

Base Part No. 17696 Kit (Driver and Passenger Side)



Trailer Brake Kit

Vehicles must be equipped with Trailer Tow Package or Max Trailer Tow Package (wiring) for kit to be functional.

Base Part No. 19H332*

Base Part No. 2C006 (Bronco and Ranger)

**Expected availability 12/31/23*

Trailer-Mounted Camera

Attach this helpful weatherproof camera to the rear of the trailer to show you what's behind when in reverse gear; image can be accessed on the 8" color LCD screen in the center stack.

Part No. LC3Z-1A189-A COMBO KIT - CAM/TPMS* (w/ Pro Trailer Backup Assist™)

Part No. LC3Z-1A189-B TPMS ONLY (w/Pro Trailer Backup Assist)

Part No. LC3Z-1A189-C CAM ONLY (w/Pro Trailer Backup Assist)

Part No. LC3Z-1A189-D COMBO KIT - CAM/TPMS* (Less Pro Trailer Backup Assist)

Part No. LC3Z-1A189-E TPMS ONLY (Less Pro Trailer Backup Assist)

Part No. LC3Z-1A189-F CAM ONLY (Less Pro Trailer Backup Assist)

**Not for use 2023/24 Super Duty models.*

Trailer Tire Pressure Monitoring System (TPMS)

Displays the air pressure of a connected trailer's tires individually; alerts you if any tire is low or losing pressure – a numerical value will tell you how low.

Base Part No. 1A189 (Tire Pressure Monitoring System)

TOWING BASICS

Towing a trailer is demanding on your vehicle, your trailer and your personal driving skills. Follow some basic rules that will help you tow safely and have a lot more fun.

For the latest RV & Trailer Towing information, check out [Ford Pro | Manuals & Certificates](#).

Cargo And Weight Distribution

For optimum handling and braking, the load must be properly distributed

Keep center of gravity low for best handling

Cargo and load capacity limited by weight and weight distribution

Approximately 60% of the allowable cargo weight should be in the front half of the trailer and 40% in the rear (within limits of tongue load or king pin weight)

Load should be balanced from side-to-side to optimize handling and tire wear

Load must be firmly secured to prevent shifting during cornering or braking, which could result in a sudden loss of control

Before Starting

Before setting out on a trip, practice turning, stopping and backing up your trailer in an area away from heavy traffic

Know clearance required for trailer roof

Check equipment (make a checklist)

Backing Up

Back up slowly, with someone spotting near the rear of the trailer to guide you

Place one hand at bottom of steering wheel and move it in the direction you want the trailer to go

Make small steering inputs – slight movement of steering wheel results in much greater movement in rear of trailer

Braking

Allow considerably more distance for stopping with trailer attached

Remember, the braking system of the tow vehicle is rated for operation at the Gross Vehicle Weight Rating (GVWR), not Gross Combination Weight Rating (GCWR)

If your tow vehicle is an F-150®, F-Series Super Duty®, Transit® or Expedition® and your trailer has electric brakes, the optional Integrated Trailer Brake Controller (TBC) assists in smooth and effective trailer braking by powering the trailer's electric or electric-over-hydraulic brakes with proportional output based on the towing vehicle's brake pressure

If you are experiencing trailer sway and your vehicle is equipped with electric brakes and a brake controller, activate the trailer brakes with the brake controller by hand. Do not apply the tow vehicle brakes as this can result in increased sway

Turning

When turning, be sure to swing wide enough to allow trailer to avoid curbs and other obstructions

Towing On Hills

Downshift the transmission to assist braking on steep downgrades and to increase power (reduce lugging) when climbing hills

With TorqShift® transmission, select tow/haul mode to automatically eliminate unwanted gear search when going uphill and help control vehicle speed when going downhill

Parking With A Trailer

Whenever possible, vehicles with trailers should not be parked on a grade. However, if it is necessary, place wheel chocks under the trailer's wheels, following the instructions below

Apply the foot service brakes and hold

Have another person place the wheel chocks under the trailer wheels on the downgrade side

Once the chocks are in place, release brake pedal, making sure the chocks will hold the vehicle and trailer

Apply the parking brake

Shift automatic transmission into park, or manual transmission into reverse

With 4-wheel drive, make sure the transfer case is not in neutral (if applicable)

Starting Out Parked On A Grade

Apply the foot service brake and hold

Start the engine with transmission in park (automatic) or neutral (manual)

Shift the transmission into gear and release the parking brake

Release the brake pedal and move the vehicle uphill to free the chocks

Apply the brake pedal while another person retrieves the chocks

Acceleration And Passing

The added weight of the trailer can dramatically decrease the acceleration of the towing vehicle – exercise caution

When passing a slower vehicle, be sure to allow extra distance. Remember, the added length of the trailer must clear the other vehicle before you can pull back in

Signal and make your pass on level terrain with plenty of clearance

If necessary, downshift for improved acceleration

Driving With An Automatic Overdrive Transmission

With certain automatic overdrive transmissions, towing – especially in hilly areas – may cause excessive shifting between overdrive and the next lower gear

To eliminate this condition and achieve steadier performance, overdrive can be locked out (see vehicle Owner's Manual)

If excessive shifting does not occur, use overdrive to help enhance performance

Overdrive may also be locked out to obtain engine braking on downgrades

When available, select tow/haul mode to automatically eliminate unwanted gear search and help control vehicle speed when going downhill

Driving With Cruise Control¹

Turn off the cruise control with heavy loads or in hilly terrain. The cruise control may turn off automatically when you are towing on long, steep grades. Use caution while driving on wet roads and avoid using cruise control in rainy or winter weather conditions

¹ Driver-assist features are supplemental and do not replace the driver's attention, judgement and need to control the vehicle. It does not replace safe driving. See Owner's Manual for details and limitations.

Tire Pressure

Underinflated tires get hot and may fail, leading to possible loss of vehicle control

Overinflated tires may wear unevenly and compromise traction and stopping capability

Tires should be checked often for conformance to recommended cold inflation pressures

Spare Tire Use

A conventional, identical full-size spare tire is required for trailer towing (mini, compact and dissimilar full-size spare tires should not be used; always replace the spare tire with a new road tire as soon as possible)

On The Road

After about 50 miles, stop in a protected location and double-check:

Trailer hitch attachment

Lights and electrical connections

Trailer wheel lug nuts for tightness

Engine oil – check regularly throughout your trip

High Altitude Operation

Your vehicle may have reduced performance when operating at high altitudes and when heavily loaded or towing a trailer. While driving at elevation, in order to match driving performance as perceived at sea level, reduce Gross Vehicle Weight (GVW) and Gross Combination Weight (GCW) by 2% per 1,000 ft. elevation

Powertrain/Frontal Area Considerations

The charts in this Guide show the minimum powertrain needed to achieve an acceptable towing performance for the listed GCW of tow vehicle and trailer

Under certain conditions, however, (e.g., when the trailer has a large frontal area that adds substantial air drag or when trailering in hilly or mountainous terrain) it is wise to choose a vehicle with a higher rating

Towing performance is maximized with a low-drag, rounded front design trailer

Selecting A Trim Series

Your specific vehicle's tow capability could be reduced based on weight of selected trim series and option content

Note: For additional trailering information pertaining to your vehicle, refer to the vehicle Owner's Manual.

Photography, illustrations and information presented herein were correct when approved for publishing. Ford Motor Company reserves the right to discontinue or change at any time the specifications or designs without incurring obligation. Some features shown or described are optional at extra cost. Some options are required in combination with other options. Consult your Ford Dealer for the latest, most complete information on models, features, prices and availability.

Many of the recreational vehicles shown in this brochure are modified or manufactured by companies other than Ford Motor Company. Ford assumes no responsibility for such modifications or manufacturing.

© 2023 Ford Motor Company. All rights reserved.