

OPTIONS The chart below lists the range of equipment available at extra cost, to enhance the appearance and performance of your new Falcon.

	LUXURY EQUIPMENT		
	AM/FM mono push-button radio	Opt	Opt
Ī	Variable ratio power steering	Opt	Opt
Ī	Integrated Air-conditioning (a)	Opt	Opt
Ī	Loop-pile carpeting	Opt	Std
Ī	Bench seat with folding centre armrest	Std	NCO
Ī	Rubber floor mat	Std	O/R

Relax . . . what better way than in deeply cushioned reclining bucket seats with pull-down centre armrest. Fan-boosted ventilation, 3-speed heater demister. Interior prismatic rear vision mirror reduces reflected glare at night.

Falcon 500 Utility

where you're at after dark-quartz halogen

headlights.

anywhere. The worker with strength, power and reliability. Test ... Falcon 500 Utility's strength for Work . . . the 3.3 litre emissionised cross flow carrying loads up to 750 kg (15 cwt). A torque-box engine works hard. It delivers power with the chassis construction. All steel load floor, Twoeconomy of standard grade fuel. Front power disc stage, seven-leaf rear suspension. brakes help you stop smooth and sure. And to see

### **Falcon Utility**

The tried and tested workmate. Takes the rough with the smooth and provides the style, comfort and performance you'd expect from Falcon Utility.

Admire . . . low sleek lines, bold grille, smart

tail design, colour matched interior ... impressive

Standard equipment highlights common to Falcon 500 and Falcon Utilities • 3.3 litre (200 CID) Cross-flow head 6-cvl. engine • All-synchro 3-speed columnmounted transmission • 285 mm (11¼") power-assisted front disc brakes, 254 mm (10T) diam, self-adjusting rear drum brakes • 7.75 x 14 BSW 4-ply tyres on 6JJ "safety-rim" wheels (750 kg (15 cwt) rating) . Power-boosted ventilation with 3-sneed fan + Prismatic Interior rear-view mirror + Left and right hand side exterior rear-view mirrors • Inertia reel seat belts • Padded door pull armrests incorporating door handles \* Lockable glove box \* Steering and ignition lock 
\* 3-apped "Blendaire" heater/demister \* Steering column stalk control for turn indicators lane-channe hi-lo beam headlight flasher and horn button • Roof Insulation • 750 kg (15 cwl) carrying capacity • 60 amp/hr battery.

Additional Falcon 500 Utility highlights Reclining bucket seats with folding centre armrest • Loop pile carpet • Interior courtesy light cograted by both doors • Cigarette lighter • Interior paint in load area • Side protection mouldings • Tonneau cover • Quartz halogen headlights.

Additional Falcon Utility highlights High-backed bench seat with folding centre armrest • Heavy-duty rubber floor mat.

Illustrated below: Falcon 500 Utility with

optional 4.1 litre engine (available at extra cost).



treatment: styled steel road



wheels with trim rings; bonnet scoops; driving lights; comprehensive instrumentation options available at extra cost including tachometer, oil pressure temperature and fuel more personal, more outstand- gauges; speedometer with odometer, plus electric clock:

"soft-feel" sports steering

wheel and map reading light. \*All options are available at extra cost unless otherwise stated.









tional 4 on the floor manual shift (500 only) Optional 4.9 litre V8 engine



Falcon 500 Utility with optional GS Rally Pack and 4.1 litre engine (available at extra cost).



PERFORMANCE FOUIPMENT 152.4 mm (6") Alloy sports road wheels 500 kg (10 cwt) 'Sedan Ride

Limited-slip differential (f) Quartz halogen driving lights (incorporated in grille) Outback Package: Heavy-duty Shock absorbers with protection plates: engine stone guard: Heavy-duty aircleaner Opt Opt

EXTERIOR/APPEARANCE ITEMS Grand Sport Rally Pack: special paint treatment: styled steel wheels: sports steering wheel; comprehensive instrumentation: 'NASA' hood scoops: driving lights Front rubber bumper over-riders Protection strips Styled full wheel covers Remote-control styled exterior mirror (driver's side)

Tinted band laminated windshield Tonneau cover Opt Std POWER-TRAIN COMBINATIONS All synchro 3 speed manual (column) Std Std

Select Shift Cruisomatic (column) Opt Opt 4.1 litre (250 CID) 'Six' with: Opt Opt All synchro 3 speed manual (column) All synchro 4 on the floor manual (b) Opt Opt Select Shift Cruisomatic (column) Select Shift Cruisomatic T-Bar (b) NA Opt 4.9 litre (302 CID) V8 with: NA Opt All synchro 4 on the floor manual (b) Opt Opt

GT POWER PAK 5.8 litre (351 CID) V8 All synchro 4 on floor manual (b)

Select Shift Cruisomatic (column)

Select Shift Cruisomatic T-Bar (b)

Select Shift Cruisomatic (column


Select Shift Cruisomatic (T-Bar) (b)

Mandatory equipment with this engine • Limited-slip differential • 4-wheel power disc brakes • FR70 H14 steel-belted radial ply tyres

### WHEELS AND TYRES (Some tyre options are required in combination

with other options! 7.75 L14 BSW 4 Ply 6JJ Std Std 185 SR14 BSW 4 Ply 6JJ Radials (c) Opt Opt ER78 S14 BSW 4 Ply 6JJ Steel-Belted Radials (d) Opt Opt FR78 S14 BSW 4 Ply 6JJ Steel-Belted Radials (e) Opt Opt FR70 H14 BSW 6 Ply 6JJ Steel-Belted Radials (f

Note: (a) Air-conditioning suitable only with A: Time (180 CID) 1" and V8 regions: (b) Sports sould be considered to the condition of the cond



Illustrated left: Falcon Utility interior with optional carpet and push-button radio (available at extra cost), clock illustrated available with GS only.

Printed April 1977

NA Opt NA Opt

# Specifications:

ENGINES	3.3 litre	4.1 litre	4.9 litre	5.8 litre
	(200 CID)	(250 CID)	(302 CID)	(351 CID)
	Six	Six	V8	V8
Carburettion	Single Barrel	Single Barrel	4 Barrel	4 Barrel
Displacement	3280	4100	4950	5750
Cubic Cap.	(200 in <sup>3</sup> )	(250 in <sup>3</sup> )	(302 in <sup>3</sup> )	(351 in <sup>3</sup> )
Bore	93 mm	93 mm	102 mm	102 mm
	(3.68")	(3.68")	(4.0")	(4.0")
Stroke	x 80 mm	x 99 mm	x 76 mm	x 89 mm
	(3.13")	(3.91")	(3.0")	(3.5")
Compression	7.9:1	8.9:1	9.2:1	8.9:1

ENGINE FEATURES: Up to 10,000 kilometres oil changes; 12-volt electrical system; 54 plate 60 amp/hour battery; 35 amp heavy-duty alternator; corrosion resistant muffler.

CLUTCH: (Manual Transmission): Diaphragm spring type, single cushion disc, dry plate, hydraulically operated. 3.3 litre (200 CID) and 4.1 litre (250 CID) 6 cylinder engine: Diam. 241 mm (9.5"), Friction area 503 mm (78 in<sup>2</sup>). 4.9 litre (302 CID) 8 cylinder engine and 5.8 litre (351 CID) 8 cylinder engine: Diam. 241 mm (9.5"), Twin Plate. Friction area 1110 mm2 (170.4 in2).

MANUAL TRANSMISSION - Column Shift: 3 forward speeds all-synchro - 1 reverse. Ratios: 6 cylinder; 1st-2.95; 2nd-1.69; 3rd-1.00; reverse-3.67.

FOUR ON THE FLOOR MANUAL: 4.1 litre (250 CID) 6 cylinder and 4.9 litre (302 CID) V8 engines. All synchro. Ratios: 1st-3.06; 2nd-1.84; 3rd-1.32; 4th-1.00; reverse-3.04. 5.8 litre (351 CID) V8. All synchro. Ratios: 1st-2.46; 2nd-1.78; 3rd-1.27; 4th-1.00; reverse-2.47.

AUTOMATIC TRANSMISSION: 3.3 litre (200 CID) and 4.1 litre (250 CID) 6 cylinder engines with Cruisomatic. Ratios: 1st-2.46; 2nd-1.45; 3rd-1.00; reverse-2.09. 4.9 litre (302 CID) V8. Ratios: 1st-2.46; 2nd-1.46; 3rd-1.00; reverse-2.20. 5.8 litre (351 CID) V8. Ratios: 1st-2.40; 2nd-1.47; 3rd-1.00; reverse-2.00.

FRONT SUSPENSION: Angle-poised ball-joint type. Heavy-duty coil springs with hyd. shock absorbers. Torsion bar ride stabilizer.

REAR SUSPENSION: Semi-elliptic asymmetrical 2-stage 7-leaf variable rate leaf springs. Diagonally mounted hydraulic shock absorbers. Rubber bushed shackles. 500 kg (10 cwt) option has 6-leaf springs.

BRAKES: Dual line system with inbuilt warning light on instrument panel and brake proportioning valve. Floating caliper-type disc front brakes, turbo cooled and ventilated, 285.75 mm (11.25") diam. Self adjusting hydraulic 254 mm (10") x 44.45 mm (1.75") rear drums with bonded linings.

STEERING: Recirculating ball type. Steering gear ratio - 20:1. Optional power steering - variable ratio 17.5:1 - 11.5:1 at lock. Steering wheel - 406 mm (16") diam. Turning circle 12.5 m (41.2 ft).

WHEELS: 14" x 6JJ, pressed steel, safety rims, 5-stud mounting type.

Wheelbase	2946 mm (116") 1536 mm (60.5") 1524 mm (60.0")	
Track — front — rear		
Ground clearance		162 mm (6.4")
Max. load length (tailga Max. load length (tailga Max. loading height (ur	2640 mm (103.9") 2134 mm (84.0") 593 mm (23.3")	
GVM 6 cylinder engine V8 engine	500 kg (10 cwt) 1939 kg (4265 lbs) 2035 kg (4486 lbs)	750 kg (15 cwt) 2208 kg (4869 lbs) 2309 kg (5090 lbs)
Fuel Tank capacity		67 litres (14.8 gall)
Turning circle		12.5 m (41.2 ft)

### DRIVER AND PASSENGER PROTECTION:

The following items are built-in to all Falcon models to minimise the likelihood of an accident occurring-and personal injury in the event of an accident . Outboard inertia reel seat belts . Front power disc brakes • High-backed seats • Deeply-recessed, padded instrument panel • Windshield-mounted breakaway, anti-glare interior rear view mirror • 3-speed 'Blendaire' heater/demister • 3-speed power ventilation • Collapsible steering column • Impact-absorbing steering wheel with full width padded hub • Controlled collapsible front end • Padded sun-visors • Padded door-pull armrests • 2-speed electric windscreen wipers • "Non-lift", non-reflective wiper blades with driver's\_side anti-lift vane • Push-button electric windscreen washers • Thick "safety-plate" glass windscreen with "zone toughened" area in front of driver, and "safety glass" other windows • Dual hydraulic brake system with brake proportioning valve, warning light . Exterior rearvision mirrors • "Safety rim" wheels • High-intensity quartz halogen headlights (500 only) . Reversing lights . Front and rear side marker lamps • Flush-mounted exterior door handles.

#### PLEASE NOTE:

The illustrations, information and specifications presented and referred to herein were correct at the time this publication was approved for printing. However, Ford Motor Company of Australia Limited and/or Ford Sales Comnowever, Ford Motor Company of Australia Limited and/or Ford Sales Company of Australia Limited reserve(s) the right, subject to the laws of Australia and/or any applicable State or Territory thereof and/or the regulations of any competent authority which may apply from time to time, at their or its discretion, and without notice, to discontinue or change the specifications or design of the products referred to herein and any options therefor at any time without incurring any liability whatsoever to any purchaser thereof.

Some options may be required in combination with other options.

Always consult your Ford Dealer for the latest information on models. specifications, features, prices, options and availability.

FORD MOTOR COMPANY OF AUSTRALIA LIMITED. FORD SALES COMPANY OF AUSTRALIA LIMITED. 1735 Sydney Road, Campbellfield, Victoria.

## FORD FALCON UTILITY (3)



Printed April 1977

Illustrated below: Falcon 500 Utility with optional 4.1 litre engine (available at extra cost).

