FORD TRADER DIESEL

2.5 TO 4.1 TONNES (COMBINATION BODY AND PAYLOAD).



* AVAILABLE ON THE 0509 AND 0711 CHASSIS CAB MODELS.

** AVAILABLE ON THE 0409, 0509 AND 0711 CHASSIS CAB MODELS.

Ford



Ituatrated: Ford Trader 0409 SWB in a potential operating function. The tray body filled is not available from Ford Motor Company of Australia Limited.



Trader is broad. Aggressive even. With a wide front track for stability. A wide comfor able dab that tits for fast service on the 0409, 0509 and 0711 chassis cab models. And power/economy shift on all forward gears on both the 0509 and 0711 chassis cab modes. Ford Trader's all dieselline-up spans 2.5 to 4.1 tonnes (combination body and payload). This line-up includes four cylinder chassis cabs and a crew cab, plus a big six-cylinder chassis cab at the top of the range.

FORD TRADER. Broad as it's strong.

perforated

facings for surface

air circulation. Trim is prown

viny). The driver's seat tits for

access to jack lever and spare tyre winch handle.

Seat adjustment fore and aft is 1200mm (434").

Wide track for peace of mind When you've got alload on, you need everything going for you. Trade's front track is a tyre width wider than many two to four tonners sold today. It provides a sure-footed stance especially around corners and helps you straddle bumps or ruts.

The wide one that tilts


These days wide cabs are not that uncommon. but wide cabs that tit for service are. And a tit cab means clearer engine access for efficient servicing. The Trader cab is counter-balanced for easy one-man operation. While the cab lock-down has a triple security caton.

Wide cab for three across

Trader's wide track and broad squared-up cab means tons of room for three across, even if they're all broad shouldered. Or you can stretch out for a lunchtime nap in real comfort.

This is Trader control

The instrument panel is designed around the criver. Instruments are easy to read, controls are easy to reach. They include engine idle adjustment knob. intermittent wiper mode and hydraulic fluid evel indicator. Seats are thick foam over deep padding with



All Trader models are equipped with an energyefficient five-speed transmission with synchromesh on all forward gears up to overdrive fifth. The gear lever is

an orward gear up to overdrive inn. The gear eyer's foor-mounted for direct, easy operation. Trader chassis cab models 0509 and 0711 are filed with powerforcommy in his providing the option of staying in direct power drive (1.1 ratio) or switching to overdrive economy (0.731.1 ratio) on all five forward gears. This sub-transmission also provides the penerts of intermediate gear selection for dimbing critical



Clutch reliability - built in

For stop and go traffic or stop-and-start deliveries, Trader's dutch is designed for heavy-duty use. It combines a hard-wearing single dry disc assembly with robust dutch cover, pressure plate and dutch release mechanism.

Ventilation and heating systems

The most obvious standard vent lation feature on all models is the wind-up roof vents. These provide ram-fresh air for additional ventilation as required. Fresh air intakes are fitted into the grille above the headlamps while vents for the extraction of stale air are in the doors.

Trader has an integral heating system with its capacity boosted by a powerful three-stage fan. The system includes a side window demist facility.




FORD TRADER. 2.5 tonnes (combined body, payload)

With two Trader models in this category, you have the choice of a three-seater cab or a seven-seater crew cab configuration. Short specifications are as follows:

Trader Model No.	Type	Gross Vehicle Mass			
0409	Chases Cab	4405 kg -			

High-torque 3-litre diesel engine Designed for rugged durability and high torque output at low engine revs. Features of the engine are: Engine block has curved outer walls to: reduced. noise

- Cil oca er buit into black for improvedioil. consumption.
- Auto-thermatic pistons for quieter running, longer life. · Special of jets to lucricate pistons and keep
- temperatures down. Ring carriers cast into the top ring chambers improve durablity
- . 'Ricardo' type flow 'swirt combustion champers with



Combined body Wheelbase & payload 2515 mm 3335 mm 2.5 tonnes 2.5 tonnes

single injection nozzles reduce ignition lag, improve power and economy, and reduce combustion noise. Rotary injection pump meters the amount of fuel

required over the engine speed range and allows higher RPM.

• Separate crankcase and counter-weight for reduced.

- · Requiator built into alternator no adjustment

corrosion protection.

. Warning ght and buzzer alert driver to cloqued filter. Sy-passiol filter protects engine from running dry.

• Diesel fuel sedimenter removes impurities for

The engine has a pre-engaged starter, plus "rader's "3-second" quick-start system (OSS).

Roomy 7-seater crew-cab

Now you can take the work team and their gear in the one vehicle - three in the front, four in the rear. By taking one vehicle, you'll save fuel and all arrive on the obtogether.

Tough

Torsion Guard Chassis

Where normal chassisside members tend to twist on rough roads, Trader's Torsion Guard Chassis provides a platform of great structural strength which restricts flexing. This neighbor protect cab, body and mountings so safeguarding your nvestment. In the Trader chassis, the heavy double 'U' side members are looked together by tubular cross members. For example in the long wheelbase models, six out of the eight cross members are tubular, the other two being stamped. The tubular cross members extend through the double "U" side sections and are double-rosette welded into position.

LSGV means surer braking, especially unladen

The Tracer model 0409 is equipped with an hydraulic Load Sensing Gravity Valve' to reduce braking time, promote more even brake lining wear, and assist in extending tyre life. It works by automatically regulating rear brake fluid pressure.

The LSGV helps prevent rear wheel look-up, especially during an emergency stop when unladen. An LSG Valve is not required on the longer wheelbase models due to different weight distribution





Trader braking system
Front and rear brakes are of the fast-acting. internal expanding drum type with vacuum power

via a cual ine system. The assistance delivered

parking brake on all models slofthe mechanical. ntoma expanding design and operates on the driveshaft. The Trader model 0/11 is also littled with an exhaust brake as standard.



FORD TRADER. 3.5 and 4.1 tonnes (combined body, payload)

The two Tracer chassis cab models in this heaver tonnage caregory are born equipped with Power/Foorony Shift to give you a choice of direct drive or overdrive on all five forward gears. Short specifications are as follows:

ype

ChacooCah

Gross Vehicle Mass

5560 kg

Model No.

0711	Chass s Cab	6405 kg		
		12		
	HOLL S	1		
1				

Combined body Wheelhouse & payload 3235 mm 3.5 tonnes 4.1 tonnes 3335 mm

Power/Economy Shift

When you're running empty or light on, you've got the option of staying in direct ocwer drive (1:1 ratio) or switching to overdrive economy (0.731:1 ratio) which operates on all forward gears. It's a great way to stretch your fuel dollar, available on the Trader 3.5 and 4.1 forme models (combination body and payload).


Trader's Big Six Top of the Trader range is the 0711 model. It lips

the scales at just over 6 connes gross vehicle mass. And its powered by a 4.1 litre 6 cylinder diesel putting. out around 110 grosslengine horsective: Trace is big axis broad-shouldered in more than cab width. With a powerplant of this size, it offers you good route times and arrefficien, turn around.

A combination body and payload of 4.1 tonnes

This maximum combination affords flexibility in the choice of body style and payload capacity.

Power steering standard on the 0711 With additional engine mass and a heavier truck overall, power steering is a standard feature designed to make the driver's job easier, especially where tight mandeuvring at slow speeds is called for



Nest start. Ford Tractor 5009 equipodd with Power Foonomy Shift in a potential operating situation. The topen hody is not avallable from Ford Moor Company of Australia. Independent reserves with road are non-standard and have been timed by the coverage.

Exhaust brake standard
Any truck in the 6 to nie GVM area provides a solid work-out for normal service brakes. To help save brakelinings, while at the same time increasing slopping power and efficiency the model 3711 is fitted with an exhaust brake as standard.

Big 6-cylinder, 4.1 litre diesel

This engine powers the model 0711. It incorporates many of the features of the 4-cylinder engine and is designed for long I to and reliability while delivering economy of performance.

Casings, not the axle shafts, carry the weight


he fully-floating rear axle has dual rear wheels mounted on the outcoard side of the axle hub flange. Weight is carried by the axie casing through externally mounted double opposed taper roller wheel bearings. In this way, a fully floating rear axier akes the weight off the inner axie shaft bearings and helps extend ther life

Suspension - a balance between rugged load and soft-ride

Tracer suspension from and rear is by way of semi-eliptic leaf springs with heavy-duty rubber

bushes. They strike a balance between load carrying capacity and comfortable ride for driver and passengers. Front - springs have large bump stops for protection against pottoming on roughroads


For better pitch control, the double acting hydraulic shock absorbers are mounted close into the front




Rear - two-stage springs for combination load and ride benefits. With around two-thirds of the load being taken by the rear of the truck, the springs have been designed for heavy-duty operation

FORD TRADER

Dimensions





Ford Trader-Specifications Features	0409	0509 (crew) 0)509 O	711	Features	0409	0509 (crew)	0509	0711
Wide Cab	×	×	x	×	5-speed transmission				
TiltCab	×	177	x	×	inc. overdrive	×	×	×	X
Seats	3	7	3	3	Power/Economy shift	-	\$ <u>22</u> .5	×	×
Gross vehicle Mass (kg)	4405	4900	5560	6405	Power steering	-	-	2	X
Kerb Mass (kg)	1830	2015	1910	2240	Exhaust Brake	-	-		×
Combination body and	\$ 2.555	365705FB			Load Sensing Gravity Valve	е х		-	-
payload (tonnes)	25 .	28	3.6	4.1	75 litre fuel tank	X	×	×	X
Wheelbase (mm)	2515	3335	3335	3335	Battery 12V, 120 amp H	×	×	×	
Twin roof vents	×	×	x	×	Battery 24V, 70 amp H		-	-	×
Toughened glass all round	×	×	x	×	Starter 2.7kW	×	×	×	2
Engine 3.0L, 4-cvl	×	x	X	H	Starter 5.0kW	-		1.	×
4.1L.6-cvl	-	19 4 0	-	x	Alternator 40 amp	x	X	×	100
Power (JIS) @ 3600 RPM	61.9kW(83 BH	P) 61 9kW(83 BHP)	61.9kW(83 BHP)	79.8kW(107.BHP)	Alternator 25 amp	-	_	43	X
Torque (SAE Gross) @ 2000 RPM		21.1 kgf-m	21.1 kgf-m	25.4 kgf-m	Radiator coolant reservoir	×	×	×	×
"3-second" Quick Start System	X	×	x	X			x = Standard	-= Not available	

Take the wheel, you'll like the feel

Trader's robust variable ratio recirculating balland-nut design gives light yet positive feel even under heavy loads. The turning action of the wide-track front wheels is easy and responsive. Power steering is standard on the Trader 0711.

Colour range

Interior trim on all models is a hard-wearing brown vinyl. Seat facings are perforated for all-weather comfort. The paint colour range is as follows:

Corrosion resistance

Rust protection is applied in a bath using a cathodic electro-coating process prior to undercoat. This provides excellent protection against rust and improves the adhesion of the paint.



Backed by Ford Service

Trader is sold and serviced throughout Australia by around 400 Authorised Ford Dealers. You can buy and work a Ford Trader in most parts of Australia secure in the knowledge that your investment is backed by Ford Service.

Printed July 1982.

About this brochure. This brochure is designed to provide you with a general introduction to the Ford Products (including available optional equipment) referred to. Because of changes in conditions and circumstances Ford* reserves the right, subject to all applicable laws, at any time, at their discretion, and without notice to discontinue or change the features, designs, materials, colours and other specifications and the prices of their products, and to either permanently or temporarily withdraw any such products from the market without incurring any liability to any prospective purchaser or purchaser. Because of variations which occur in manufactured products, all capacities, measurements,

dimensions and weights quoted in this brochure should be taken as approximate only. Always consult an Authorised Ford Dealer for the latest information with respect to the features, specifications, prices, optional equipment and availability before deciding to place an order.

*FORD MOTOR COMPANY OF AUSTRALIA LIMITED FORD SALES COMPANY OF AUSTRALIA LIMITED 1735 Sydney Road, Campbellfield, Victoria, 3061.

