

1978 PLYMOUTH Sapporo

The sophisticated new small car



ECONOMICAL . . . AND MORE

Sapporo's exterior and interior appointments reflect more than just an economy car's "miles per gallon". The reverse

side (specifications) will tell you more about this superb car and a test drive will prove its value.

Plymouth Sapporo

Standard Equipment Features

ASH RECEIVER—Front, with light
 APPLIQUE—Bright Landau roof with opera lamps
 BRAKES—Power disc front, 22.9 mm (9") rear
 BUMPER GUARDS—Front and rear
 BUMPERS—Energy-absorbing
 CARPETING
 CHIMES—For seat belt and ignition key warning
 CONSOLE—Floor. Overhead with electronic digital clock
 CONSOLE—Floor. Overhead with electronic digital clock, warning lights for washer fluid level and "door ajar". Reading and interior Dome light with switches
 DECK LID RELEASE—Inside
 ELECTRIC HEATED REAR WINDOW DEFROSTER
 GLASS—Tinted all windows
 HEATER/DEFROSTER—With forced air ventilation

HOOD RELEASE—Inside
 HORNS—Dual
 INSTRUMENT PANEL AND CONTROLS—Padded, recessed controls variable intensity lights, master cylinder and park brake warning indicator, glove box lock, cigarette lighter, engine temperature, oil pressure, ammeter and fuel level gauges
 LIGHTS—Dual rectangular headlamps, side by side, backup, courtesy dome, door key cylinder, trunk, side marker, ash receiver, opera
 MIRRORS—Interior prismatic. Outside, dual, power adjustable
 ODOMETER—Trip (calibrated in km)
 RADIO—AM/FM
 SEATS—Front, bucket with recliners, multi-position cushions, lumbar supports and walk-in adjuster with memory for the front passenger seat
 STEERING COLUMN—Tilt, impact-absorbing

STEERING WHEEL—Sports type
 SPEEDOMETER—Dual calibrated (km/h and MPH) with metric predominant. Distance recorder (odometer) reads in kilometres
 TACHOMETER
 TIRES—195/70 HR x 14" radial white sidewalls
 TRANSMISSION—5-speed manual
 VINYL ROOF—Canopy
 WHEEL COVERS
 WINDSHIELD WASHERS—Electric
 WINDSHIELD WIPERS—2-speed electric

Selected Optional Equipment

AUTOMATIC TRANSMISSION—3-speed
 PERFORMANCE PACKAGE WHICH INCLUDES—2.6 litre "silent-shaft" engine, 5-speed manual transmission, 195/70 HR14 R.W.L. tires, power steering, 4 wheel power disc brakes and power windows

Plymouth Sapporo — Basic Specifications

Exterior Dimensions

	MILLIMETRES	INCHES
Wheelbase	2515	99.0
Overall Length	4651	183.1
Overall Width	1669	65.7
Overall Height	1326	52.2
Track — Front	1369	53.9
— Rear	1395	54.9
Road Clearance	145	5.7
Approximate Shipping Weight		
— Kilograms	1179	
— Pounds		2600

Interior Dimensions

	MILLIMETRES	INCHES
Effective Headroom — Front	925	36.4
— Rear	890	35.0
Effective Legroom — Front	1067	42.0
— Rear	825	32.5
Shoulder Room — Front	1300	51.2
— Rear	1295	51.0
Hiproom — Front	1340	52.7
— Rear	1330	52.4
Trunk Capacity (dm ³)	294	
(cu. ft.)		10.4

Engine and Transmission Specifications

Displacement (litres)	2.0	2.6 (a)
Application	"Silent-Shaft"	"Silent-Shaft"
Installed Net Horsepower (kW @ R.P.M.)	Standard	Optional
(H.P. @ R.P.M.)	72 @ 5500	81 @ 5000
Installed Net Torque (N.m @ R.P.M.)	96 @ 5500	108 @ 5000
(Pd./ft. @ R.P.M.)	148 @ 3500	190 @ 2500
Compression Ratio	109 @ 3500	140 @ 2500
Air Cleaner	8.5:1	8.2:1
Carburetor	Dry Type, Replaceable Element	
Cooling System	2-Barrel Downdraft	
Alternator — 12-Volt	Forced Circulation (Includes Coolant Overflow Bottle)	
Battery — 12-Volt	45 amp.	
Fan (Blades)	345 amp.	380 amp.
Oil Capacity Without Filter (litres)	6	6
(quarts)	3.8	4.5
Oil Filter — 0.5 litre Capacity	3.3	4.0
Transmission — Standard	Full Flow-Through Throw-Away	
— Optional	5-Speed Overdrive Manual	
	Automatic	

(a) Available with "Performance Package" (Sales Code A23) only.



All product illustrations and specifications are based on authorized information. Although descriptions are believed correct at publication approval, accuracy cannot be guaranteed. Some of the equipment shown on product illustrations is optional, at extra cost. Chrysler Canada Ltd. reserves the right to make changes from time to time, without notice or obligation, in prices, specifications, standard and optional equipment listed, colours and materials, and to change or discontinue models.

