



*If you gotta go to and fro
you need a Holden Shuttle.*



Introducing Holden Shuttle. The best way to go to and fro!

If you have to go back and forth, across town, into the suburbs, back again, up the country, into the city, short trips, traffic jams, in and out, load fast, deliver on time, park in tight places, please the accountant, do it every day and enjoy it. Then we've got the perfect van for you.

Holden Shuttle comes in four configurations.

Standard wheelbase panel van. Petrol engine.
Standard wheelbase panel van. Diesel engine.
Standard wheelbase window van. Petrol engine.
Long wheelbase window van. Petrol engine.


The petrol engine is a zappy 1.8 litre powerhouse that churns out 65kw at 5,000 rpm. That's equal to the power most vans get from larger thirstier engines. Our diesel is a powerful two litre, overhead cam engine.

Holden Shuttle has a 5 speed overdrive transmission on all models. A big 60 litre fuel tank for longer hauls between refills. An enormous cargo volume. Full height and full width rear loading and side loading doors. A turning circle smaller than any other one tonne van with a comparable wheelbase.

Everything about the new Holden Shuttle is good for your business.

Exterior Dimensions

	Std. W.B.	Long W.B.
Overall Length	4350mm	4690mm
Overall Width	1690mm	1690mm
Overall Height	1950mm	2185mm
Wheelbase	2350mm	2690mm
Ground Clearance	200mm	200mm
Turning Radius	4.8m	5.4m



Large cargo volume.




High, wide rear access with rear step, for really tall cargo.



5 speed overdrive for extra highway economy.



60 litre fuel tank. Longer hauls between refills.



The smallest turning circle of any 1 tonne van. (SWB).



Petrol or diesel. Take your pick.

MAJOR SPECIFICATIONS

Front Suspension. Independent wishbone arms with coil spring stabilizer bar and double-acting hydraulic telescopic shock absorbers. Capacity 1,250kg.

Rear Axle. Banjo semi-floating. Axle capacity 1,588kg.

Final Gear Ratio. 41/9 (4.555).

Rear Suspension. Semi-elliptical alloy steel leaf springs with double-acting hydraulic telescopic shock absorbers.

BRAKES

Service - Front. Hydraulic ventilated disc.

Rear. Leading/Trailing.

Parking. Mechanical, expanding on rear wheels.

Master cylinder. Tandem with vacuum servo.

ENGINE PETROL

4ZB1, Petrol 4-cyl., 1817cc SOHC, 65 kW/5,000 rpm (DIN), 135 Nm/3,000 rpm (DIN).

Choke Control. Automatic.

Alternator. 12V-50A.

Starter. 12V-0.8kW.

ENGINE DIESEL

4FC1, Diesel, 4-cyl., 1995cc SOHC, with oil cooler, 44kW/4,500 rpm (DIN), 118 Nm/2,500 rpm (DIN).

Starting System. "QSSI" Quick Start and quiet idling.

Engine Stop. Automatic.

Alternator. 12V-50A.

Starter. 12V-2kW.

Radiator. Heavy duty type with reserve tank.

Clutch. Dry single plate with cushioning springs.

Transmission. Column shift. MSG, 5 speed overdrive.

Steering. Recirculating ball.

Steering Lock. Anti-theft system on steering column.

Panel Van. Tyres 6.00 - 14 - 8PR

Window Van. Disc Wheels 4 1/2 - Jx14

185R - 14 - 8PR 5 - Jx14

Steel Radial

Battery. PETROL, 12V - 40AH.

DIESEL 12V - 65AH.

Fuel Tank. 60 lit.

CAB INTERIOR

Ventilation. Boosted ventilation, centre and side.

FRONT SEAT

Driver. High-back bucket, vinyl, with seat slide.

High-back bucket, vinyl.

Assistant. Steering column mounted incorporating head lamps, dimmer, passing signal, turn signal, wiper and washer.

Combination Controls.

Courtesy Switches. All doors.

Instrument Cluster. Combination meter, fuel, water temperature. Indicator for parking brake, brake warning, charging, oil pressure, turn signal, head lamp beam. Pre-heat indicator - Diesel. Fuel sedimentor warning - Diesel.

Speedometer. Km/h with odometer and trip-meter.

EXTERIOR GLASS

Front Windshield. Laminated.

Front Door. Tempered.

Side Window. Tempered - (Window Van model).

Rear Door Window. Tempered.

Head Lamps. Rectangular, sealed beam.

Shield Wiper. 2-speed with electric washer.

Rear Step. Located between rear bumpers.

Rear Door. Lift-back door.

WEIGHTS

Gross Vehicle Mass. 2,500kg.

Gross Comb. Mass. 3,500kg with trailer brakes.

Payload. 1 to 1.2 tonnes nominal, depending on specification.

Standard Equipment. (Window Van Model). Rear window washer, Rear window hot wire defogger, AM push-button radio.

PLEASE NOTE: As the policy of General Motors-Holden's is one of continual product improvement, all specifications and equipment are subject to change without notice.

No GMH dealer or other person is authorised or permitted to give or make any statement assertion or undertaking in relation to the quality performance characteristics descriptions or fitness for any purpose of any GMH product or in connection with the supply of any GMH product, which is at variance with any written statement assertion or undertaking on any of these subjects given or made by General Motors-Holden's Limited or General Motors-Holden's Sales Pty. Ltd. in its published sales literature, and neither company accepts any liability for any such unauthorised action.

General Motors-Holden's Limited and General Motors-Holden's Sales Pty. Ltd. have franchised dealers in many parts of Australia for the sale of service parts and the provision of service to owners of GMH's products. Every endeavour is made to ensure that such dealers carry adequate stocks of service parts, and are equipped to provide satisfactory service, but neither General Motors-Holden's Ltd. nor General Motors-Holden's Sales Pty. Ltd. makes any promise, other than that contained in the New Vehicle Warranty given by General Motors-Holden's Sales Pty. Ltd., that such parts or service facilities will be available, or available at any specific location or any particular time.

Warranty 12 months, 20,000kms.



General Motors-Holden's Sales Pty. Ltd.