

**NEW '84  
HOLDEN RODEO  
A TOUGH  
CHOICE**

**Rodeo**



# RODEO- BRED FOR ACTION!



*Rodeo LS 4x4 with 4-speed transmission  
and 2-speed transfer case.*

The supertough Holden Rodeo range of 4x2 and 4x4 pick-up trucks has earned an unrivalled reputation for ruggedness, dynamic performance and smooth-flowing sophistication.

And for '84 it's bigger and better with high performing 2 litre OHC petrol and 2.2 litre diesel engines.

To complement this sort of go-anywhere power, this line delivers head turning styling outside and inviting passenger car comforts inside.



Sports cab boasts body-hugging contoured bucket seats.



Standard cab featuring spacious bench seat.

So if you're after a pick-up truck that's got what it takes, there's a Holden Rodeo to suit your needs and your lifestyle in this big range.

**LS 4x4** The trail tough 4x4 is designed for those who want action all the way.

Standard equipment includes a 2 litre powerplant, auto-locking, free-wheeling front hubs, 4-speed transmission, 2-speed transfer case, independent front suspension, white spoked steel wheels and ground grabbing all-terrain radials.

Inside, it's big on space and luxury — push-button AM radio, soft feel sports steering wheel, 3-speed heater/demister, bucket seats, full carpeting, you name it — this Rodeo's probably got it!

**LS 4x2** The moment you take off in this Rodeo you'll feel its 2 litre power come alive.

Then experience its smooth, sedan-like ride and feature-packed interior. Because like the LS 4x4, it is loaded with creature comforts.

ratios in the 4x4 mode plus auto-locking free-wheeling front hubs.


**Cab Chassis** If you want a no-nonsense workhorse that gets the job done right, these hefty haulers aren't afraid of the roughest farm roads or the longest freeways. Why? Because they're built tough.

You'll also find their handsome styling and comfortable 3-seat interiors unbeatable.

**Pick-ups** Toughness and power give these Rodeos the guts to handle the toughest tasks while their city smart styling makes them winners wherever they go.

And when it comes to ride and comfort, the man-sized cabs and easy riding suspensions deliver firm load support and absorb bumps and potholes with ease.

Also, the pick-up boxes are the longest in the business.



Comprehensive LS instrumentation and multi-function controls.

# PICKUPS

2 models: LWB 4x2 with 2 litre petrol engine and 4-speed transmission.  
LWB 4x2 with 2.2 litre diesel engine and 5-speed overdrive transmission.



# LS PICKUPS

2 models: LWB 4x2 with 2 litre petrol engine and 5-speed overdrive transmission.  
SWB 4x4 with 2 litre petrol engine and 4-speed transmission with 2-speed transfer case.



# CREW CABS

3 models: LWB 4x2 with 2 litre petrol engine and 4-speed trans. LWB 4x2, 2.2 litre diesel, 5-speed o'drive trans. LWB 4x4, 2 litre petrol, 4-speed trans., 2-speed transfer case.



# CAB CHASSIS

4 models: LWB 4x2, 2 litre petrol, 4-speed trans. LWB 4x2, 2.2 litre diesel, 5-speed o'drive trans. SWB 4x4, 2l. petrol, 4-sp. trans., 2-sp. transfer case. SWB 4x4, 2.2l. diesel, 4-sp. trans., 2-sp. transfer case.



Aluminium tray shown optional extra.

# TOUGH TRUCKIN' FEATURES

Here's what makes the 4x4 Holden Rodeos tough in the rough, yet easy on you.



- 1 Smooth riding double wishbone independent front suspension.
- 2 Split disc shaft to rear drive train.
- 3 Water resistant ventilated front disc brakes.
- 4 Leading/trailing rear drum brakes.
- 5 Tandem master brake cylinder with 203 mm (8") vacuum booster.
- 6 Automatic locking, free-wheeling front hubs.
- 7 Progressive rate rear suspension.
- 8 4-speed all-synchromesh transmission and 2 speed transfer case.

- 9 Steel chassis frame with box section side members to resist twisting and bending stresses.
- 10 Bias mounted shock absorbers to resist axle hop.
- 11 Rear leaf springs provide long wheel travel and high lateral wheel stability.
- 12 Underbody rust-proofing measures help resist corrosion.
- 13 Re-circulating ball steering for easy handling.
- 14 Steel-belted on/off-road radial tyres on 6-stud wheels with 127 mm (5") rims.
- 15 139.7 mm (5½") rims on LS models.
- 16 50 litre fuel tank.

- 16 On cab chassis your choice of 2 advanced engines – 2 litre OHC petrol or 2.2 litre diesel.
- 17 Heavy-duty battery for both petrol and diesel engines.
- 18 Protection guards.
- 19 Towing hook.

## 2 LITRE PETROL ENGINE

Power and performance are what you get from this pushy 1949cc 4-cylinder OHC petrol engine. It produces 65 kW at 4600 rpm and 140 Nm of torque at 3000 rpm. The specially engineered combustion chambers and ports give Rodeo power to spare while maintaining low fuel consumption.

## 2.2 LITRE DIESEL ENGINE

This durable and fuel efficient engine with oil cooler generates an impressive 45 kW at 4000 rpm and 130 Nm of torque at 2200 rpm. That's more than enough power to satisfy your needs – on or off the road.

## RODEO SPECIFICATIONS

	2 litre Petrol Models								2.2 litre Diesel Models			
	Cab Chassis 202 LWB 2 litre petrol	Cab Chassis 219 LWB 2 litre petrol	Pick-up 402 LWB 2 litre petrol	LS Pick-up 462 LWB 2 litre petrol	LS Pick-up 464 SWB 2 litre petrol	Crew Cab 464 LWB 2 litre petrol	Crew Cab 464 LWB 2 litre petrol	Cab Chassis 219 LWB 2.2 litre diesel	Cab Chassis 22.2 litre diesel	Pick-up 462 LWB 2.2 litre diesel	Crew Cab 462 LWB 2.2 litre diesel	
<b>Dimensions &amp; Weights:</b>												
GVM	kg	2350	2350*	2350	1800	1800	2250*	2250	2350*	2350	2350	2250
GCW (on-road with trailer brakes - installed by driver)	kg	2750	2750	2750	2750	2750	2750	2750	2750	2750	2750	2750
Wheel base	mm	2995	2650	2995	2995	2650	2995	2995	2650	2995	2995	2995
Overall length	mm	4625	4190	4860	4860	4425	4860	4860	4190	4625	4860	4860
Overall width	mm	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600
Overall height	mm	1550	1605	1550	1550	1605	1620	1565	1605	1550	1550	1565
Cargo bed interior length	mm	—	—	2290	2290	1855	1550	1550	—	—	2290	1550
Cargo bed interior width	mm	—	—	1415	1415	1415	1415	1415	—	—	1415	1415
Cargo bed interior height	mm	—	—	415	415	415	415	415	—	—	415	415
Min. ground clearance	mm	200	210	200	200	210	210	200	210	200	200	200
Front track	mm	1365	1340	1365	1365	1340	1340	1365	1340	1365	1365	1365
Rear track	mm	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300
<b>Engines:</b>	Type	4-cylinder, in-line, water-cooled, cross flow, SOHC								4-cylinder, in-line, water-cooled with oil-cooler, 4-stroke OHV with swirl chamber		
Bore x stroke	mm	87 x 82								88 x 92		
Displacement	cc	1949								2238		
Power – kW DIN @ rpm		65/4600								45/4000		
Torque – Nm @ rpm		140/3000								130/2200		
Compression Ratio		8.4:1								21:1		
<b>Electrical System:</b>												
Battery		12 volt-50amp hrs.								12 volt-70amp hrs.		
Generator		12 volt-40amp								12 volt-40amp		
Starter motor		12 volt-1.2kW								12 volt-2.0kW		
<b>Fuel System:</b>		Single, down-draft 2-barrel carburettor								"VE" distributor-type fuel injection with fuel-enrich device		
<b>Drive Train:</b> shift type (manual)		4-speed column	4-speed floor	4-speed column	5-speed floor	4-speed floor	4-speed floor	4-speed floor	4-speed floor	5-speed floor	5-speed floor	5-speed floor
Clutch		Diaphragm pressure spring and dry single plate with cushioning springs										
Gear Ratio (to 1)	1st	4.122	4.122	4.122	4.122	4.122	4.122	4.122	4.122	4.122	4.122	4.122
	2nd	2.493	2.493	2.493	2.493	2.493	2.493	2.493	2.493	2.493	2.493	2.493
	3rd	1.504	1.504	1.504	1.504	1.504	1.504	1.504	1.504	1.504	1.504	1.504
	4th	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
	5th	—	—	—	0.855	—	—	—	—	0.855	0.855	0.855
Reverse		3.820	3.720	3.820	3.820	3.720	3.720	3.820	3.720	3.820	3.820	3.820
Transfer Ratio	High	—	1000	—	—	1000	1000	—	1000	—	—	—
	Low	—	1870	—	—	1870	1870	—	1870	—	—	—
<b>Steering:</b>	Type	Recirculating ball and nut, variable ratio 26-30:1										
<b>Suspension:</b>	Front	Independent, wishbone, torsion bar springs with stabilizer bar										
	Rear	Semi-elliptical alloy leaf springs										
<b>Shock absorbers:</b>	Front	Hydraulic double-acting telescopic										
	Rear	Hydraulic double-acting telescopic (4 x 4 models with protector)										
<b>Brakes:</b>	Type	Front: Ventilated discs; Rear: Drum, leading/trailing										
	Apply System	Vacuum servo-assisted hydraulic										
<b>Tyres</b>	(Steel radials)	185R x 14	195R x 14 <sup>†</sup>	185R x 14	195R x 14	195R x 14	195R x 14	195R x 14	185R x 14	195R x 14 <sup>†</sup>	185R x 14	185R x 14

\*2100kg in rough terrain use. †On/off road pattern

Standard colours: Champignon Beige, Cameo White, Claret Red, Primrose Yellow, Alpine Blue. LS models: Bordeaux Red Metallic, Marquis Blue Metallic, Cannon Metallic, Gothic Brown Metallic, Cameo White. 2-tone option on LS models: Bordeaux Red/Matterhorn Silver, Marquis Blue/Matterhorn Silver, Gothic Brown/Matterhorn Silver, Cannon Metallic/Matterhorn Silver.

# BRAND IT YOUR WAY




There is an extensive range of quality accessories available from your Holden dealer that'll make the already well-equipped Rodeo even more so.

Here are just a few. Other popular accessories not illustrated can be selected from - heavy-duty front mud flaps, tough and durable tray protector, AM/FM radio stereo cassette player, sports body stripes, carpet or rubber floor mats and radiator insect screen.

## NEW '84 RODEO

Holden: Australia's Driving Future. 



Handsome yet durable tonneau cover.




Headlamp protector guards.



Bull bar, winch and driving lights.



Sunshade and weathershields.



Rear tow bar and tongue. Wiring harness also available.



Highly efficient air-conditioning.

**PLEASE NOTE:** As the policy of General Motors-Holden's is one of continual product improvement, all specifications and equipment are subject to change without notice. No GMH dealer or other person is authorised or permitted to give or make any statement, assertion or undertaking in relation to the quality performance characteristics, descriptions or fitness for any purpose of any GMH product or in connection with the supply of any GMH product, which is at variance with any written statement, assertion or undertaking on any of these subjects given or made by General Motors-Holden's Limited or General Motors-Holden's Sales Pty Ltd in its published sales literature and neither company accepts any liability for any such unauthorised action. General Motors-Holden's Limited and General Motors-Holden's Sales Pty Ltd have franchised dealers in many parts of Australia for the sale of service parts and the provision of service to owners of GMH's products. Every endeavour is made to ensure that such dealers carry adequate stocks of service parts, and are equipped to provide satisfactory service, but neither General Motors-Holden's Pty Ltd nor General Motors-Holden's Sales Pty Ltd makes any promise, other than that contained in the New Vehicle Warranty given by General Motors-Holden's Sales Pty Ltd that such parts or service facilities will be available at any specific location at any particular time. Warranty 12 months, 20,000 km.